

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NTPA7160LB1A0 from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-eu/products/productdetail?partno=NTPA7160LB1AC

NTPA7160LB1A0



Appearance & Shape





(in mm)

Applications

| | | Switching power supplies, CRT monitors, Color televisions, VCR-Power supplies, Other power circuits |
|--|--|---|
|--|--|---|

Packaging Information

| Packaging | Specifications | Minimum Order Quantity |
|-----------|----------------|---------------------------|
| A0 | Ammo Pack | 1000 |



 Lead is not contained in the ceramic element, the terminations, the solder for inner connection and the coating resin.
Most suitable for power supplies of less than 100W
Excellent recovery characteristics due to resin coating with excellent heat characteristics

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of NTPA7160LB1A0 from the official website of Murata Manufacturing Co.,

Ltd. https://www.murata.com/en-eu/products/productdetail?partno=NTPA7160LB1AC

NTPA7160LB1A0

Specifications

| Resistance (25°C) | 16Ω |
|--|----------------|
| Resistance Value Tolerance (at 25°C) | ±15% |
| Permissible Max. Current (25°C) | 1.2A |
| Permissible Max. Current (55°C) | 1A |
| Thermal Time Constant | 40s |
| Typical Dissipation Constant (25°C) | 9.9mW/°C |
| Permissible Electrolytic Capacitor | 400µF |
| Measure Condition of Permissible Electrolytic Capacitor | at 100V |
| Operating Temperature Range | -20℃ to 160℃ |
| Lead Shape | Lead Wire type |
| Shape | Lead |
| Mass | 0.81g |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet

Note: This datasheet may be out of date.


Please download the latest datasheet of NTPA7160LB1A0 from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-eu/products/productdetail?partno=NTPA7160LB1AC

NTPA7160LB1A0

Product Data


INNOVATOR IN ELECTRON





Permissible Maximum Current Derating Curve

Current-R ratio(Rt/R25), Current-Temperature Characteristics



Permissible Electrolytic Capacitor

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.