

MATERIAL:

- 1. INSULATORS = TEFLON, VIRGIN WHITE PER ASTM D1710, GRADE I, TYPE I, CLASS A.
- CONTACT & SPRING = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.
- 3. CRIMP SLEEVE = SEAMLESS COPPER TUBE PER ASTM B75, TYPE C12000, TEMPER: LIGHT ANNEAL O50.
- 4. ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

FINISHES:

- 1. CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.
- 2. ALL OTHER METAL PARTS = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C OVER .00010 TO .00020 COPPER STRIKE PER MIL-C-14550.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	D.N.	DATE 12-9-96	APPLIED ENGINEERING PRODUCTS 104 John W. Murphy Drive, P.O. Box 510 New Haven, CT 06513				
TOLERANCES ON FRAC. DECIMAL ANGLES 1/64 ± 2°	CHECKED DATE VPS 12-9-96		SMB RIGHT ANGLE FEMALE CABLE PLUG FOR USE WITH RG-174,179,188 & 316 CABLE				
MATERIAL:	APPROVED DATE /2/9/96 FINISH: SEE NOTES						
SEE NOTES			SIZE	1950	NT NO.	2105-1521-003	
			SCALE	NTS	RE	V.B	SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Radiall:

2105-1521-003