
Spec Sheet

Radial Leaded Inductors[LHL]

LHL10TB390K



Features

- Item Summary
 39uH±10%, 1.8A, φ11.0x14.0mm Radial
- Lifecycle Stage
 Non-preferred
- Standard packaging quantity (minimum)
 Taping 500pcs

Products characteristics table

Inductance	39 uH ± 10 %
Case Size (mm)	11.0x14.0
Rated Current (max)	1.8 A
DC Resistance (max)	85 mΩ
Q (min)	60
LQ Measuring Frequency	2.52 MHz
Self Resonant Frequency (min)	6.7 MHz
Operating Temp. Range	-25 to +105 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	±7%
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (181 subst.)	Yes
Soldering	Wave

■ External Dimensions

Dimension D	Max φ11.0 mm
Dimension H2	Max 14.0 mm
Dimension d	φ 0.6 ±0.05 mm
Dimension F	5.0 ±1.0 mm
Dimension I	5.0 ±1.0 mm

The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the data at any time without notice.

Before making final selection, please check product specification.

Please read this notice before using the TAIYO YUDEN products.



REMINDERS

- Please conduct validation and verification of our products in actual condition of mounting and operating environment before using our products.
- The product listed in this spec sheet is intended for use in general electronic equipment (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and medical equipment classified as Class I or II by IMDRF. Please be sure to contact TAIYO YUDEN for further information before using the products for any equipment which may directly cause loss of human life or bodily injury (e.g., transportation equipment including, without limitation, automotive powertrain control system, train control system, and ship control system, traffic signal equipment, disaster prevention equipment, medical equipment classified as Class III by IMDRF, highly public information network equipment including, without limitation, telephone exchange, and base station).

Please do not incorporate our products into any equipment requiring high levels of safety and/or reliability (e.g., aerospace equipment, aviation equipment*, medical equipment classified as Class IV by IMDRF, nuclear control equipment, undersea equipment, military equipment).

*Note: There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

When our products are used even for high safety and/or reliability-required devices or circuits of general electronic equipment, it is strongly recommended to perform a thorough safety evaluation prior to use of our products and to install a protection circuit as necessary.

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the product listed in this spec sheet for any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

- Information contained in this spec sheet is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.
- Please note that the scope of warranty for our products is limited to the delivered our products themselves and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a fault or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement.
- The contents of this spec sheet are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this spec sheet are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.
- Caution for Export
 - The product listed in this spec sheet may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiyo Yuden:

 LHL08NB100K
 LHL08NB101K
 LHL08NB102J
 LHL08NB103J
 LHL08NB120K
 LHL08NB121K
 LHL08NB122J

 LHL08NB123J
 LHL08NB150K
 LHL08NB151K
 LHL08NB152J
 LHL08NB153J
 LHL08NB180K
 LHL08NB181K

 LHL08NB182J
 LHL08NB183J
 LHL08NB1R0N
 LHL08NB1R5M
 LHL08NB220K
 LHL08NB221K
 LHL08NB222J

 LHL08NB23J
 LHL08NB270K
 LHL08NB271K
 LHL08NB272J
 LHL08NB273J
 LHL08NB2R2M
 LHL08NB2R7M

 LHL08NB330K
 LHL08NB331K
 LHL08NB332J
 LHL08NB333J
 LHL08NB390K
 LHL08NB391K
 LHL08NB392J

 LHL08NB3R3M
 LHL08NB3R9M
 LHL08NB470K
 LHL08NB471K
 LHL08NB472J
 LHL08NB472M
 LHL08NB560K

 LHL08NB561K
 LHL08NB562J
 LHL08NB566M
 LHL08NB680K
 LHL08NB681K
 LHL08NB682J
 LHL08NB688M

 LHL08NB820K
 LHL08NB821K
 LHL08NB822J
 LHL08TB120K
 LHL08TB120J
 LHL08TB150K
 LHL08TB151K

 LHL08TB153J
 LHL08TB180K
 LHL08TB181K
 LHL08TB182J
 LHL08TB183J
 LHL08TB270K
 LHL08TB273J
 LHL08TB273J
 LHL08TB330K