

Crystal Units Surface Mount Type CX3225CA





3.2×2.5mm for Automotive



Features

- Crystal unit for automotive electronics
- Small and low profile (3.2×2.5×0.80mm)
- Ceramic package
- Reflow compatible

Applications

- ECU
- High-Speed Automotive Network

How to Order

CX3225CA 16000 D0 P S V CC

①Series ©Frequency 3Load Capacitance D0 8 pF Р ±50×10⁻⁶

Operating Temp. Range OFrequency Temp. Stability

-40 to +125°C ±150×10⁻⁶

OIndividual Specification (STD Standard is "CC".)

Packaging (Tape & Reel 3000 pcs./ reel)

Specifications

Item	Symbol	Specification	Unit	Remarks
Frequency Range	f_nom	12000 to 54000	kHz	
Overtone Order	ОТ	Fundamental	_	
Load Capacitance	CL	8	pF	Please contact us for other CL requirements.
Frequency Tolerance	f_tol	±50	×10 ⁻⁶	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T_use	-40 to +125	°C	
Storage Temp. Range	T_stg	-40 to +150	°C	
Frequency Temp. Characteristics	f_tem	±150	×10 ⁻⁶	Freq. deviation from the value at 25°C

Please contact us for other specifications.


Table 1 Motional Series Resistance

Frequency Range	Motional Series Resistance		
12000≤f_nom<13560kHz	200 Ω max.		
13560≤f_nom<16000kHz	120 Ω max.		
16000≤f_nom≤54000kHz	100 Ω max.		


Table 2 Level of Drive

Frequency Range	Level of Drive		
12000≤f_nom≤54000kHz	10μW (200μW max.)		

Dimensions



Recommended Land Pattern



(Unit: mm)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kyocera:

CX3225CA20000D0PSWZ	1 CX3225CA09843D0HSSZ	CX3225CA10000D0HSSZ1	CX3225CA12000D0HSSZ1
CX3225CA13560D0HSSZ1	CX3225CA16000D0HSSZ1	CX3225CA16000H0HSSZ1	CX3225CA20000D0HSSZ1
CX3225CA24000D0HSSZ1	CX3225CA25000D0HSSZ1	CX3225CA26000D0HSSZ1	CX3225CA27000D0HSSZ1
CX3225CA28636D0HSSZ1	CX3225CA30000D0HSSZ1	CX3225CA32000D0HSSZ1	CX3225CA40000D0HSSZ1
CX3225CA20000D0HSSCC	CX3225CA09843D0HSSTT	CX3225CA10000D0HSSTT	CX3225CA13560D0HSSCC
CX3225CA28636D0HSSCC	CX3225CA24000D0HSSCC	CX3225CA30000D0HSSCC	CX3225CA25000D0HSSCC
CX3225CA12000D0HSSCC	CX3225CA40000D0HSSCC	CX3225CA16000D0HSSCC	CX3225CA27000D0HSSCC
CX3225CA32000D0HSSCC	CX3225CA12000P0HSTC1	CX3225CA25000P0HPQCC	CX3225CA12000P0HPQCC
CX3225CA48000P0HPQCC	CX3225CA12000F0KFQCC	CX3225CA16000P0HPQCC	