

Cable feed-through sleeve - HC-KDT 14-15 - 1644148

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable feed-through sleeves, for conductor diameters of 14-15 mm, starting at 10 mm, a cable binder can be used as strain relief



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	3.67 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-40 °C 125 °C

General

Material	Thermoplastic rubber	
Flammability rating according to UL 94	НВ	
Color	black	

Standards and Regulations

Flammability rating according to UL 94	НВ

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209



Cable feed-through sleeve - HC-KDT 14-15 - 1644148

Classifications

eCl@ss

eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27069220

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000451

UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

Approvals

Approvals			

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details


EAC

Drawings



Cable feed-through sleeve - HC-KDT 14-15 - 1644148

Dimensional drawing



Dimensional drawing

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: