

## Specification Sheet

Part Number: TSR3FW-6A



One Piece Surface Raceway, 1-3/4", 6.0 ft Long, PVC, Office White, 120ft/Carton

**Article Number** 250-03600

**Type** TSR3-6A

**Color** Office White (OEWH)

**Features & Benefits**

- Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.
- PVC construction is lightweight, durable and more affordable than metallic raceway systems.
- Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.
- Foam tape backing with rubber based adhesive conforms to any flat surface to assist with temporary positioning and mounting.
- Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.
- Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.

**Quantity Per** carton

|                            |   |
|----------------------------|---|
| <b>Product Description</b> | HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. |
| <b>Short Description</b>   | One Piece Surface Raceway, 1-3/4", 6.0 ft Long, PVC, Office White, 120ft/Carton   |
| <b>Global Part Name</b>    | TSR3-6A-PVC-WH  |
| <b>Length L (Imperial)</b> | 6.0   |
| <b>Length L (Metric)</b>   | 1.83  |
| <b>Width W (Imperial)</b>  | 1.75  |
| <b>Width W (Metric)</b>    | 44.45   |
| <b>Height H (Imperial)</b> | 1.0   |
| <b>Height H (Metric)</b>   | 25.40   |
| <b>Material</b>            | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>   | PVC   |

|                                       |                |
|---------------------------------------|----------------|
| <b>Flammability</b>                   | UL 94 V0       |
| <b>Halogen free</b>                   | No             |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C) |
| <b>Reach Complaint(Article 33)</b>    | No             |
| <b>ROHS Complaint</b>                 | Yes            |
| <b>Package Quantity(Imperial)</b>     | 120            |
| <b>Package Quantity (Metric)</b>      | 36.58          |
| <b>Customs Number</b>                 | 3925900000     |