


RAY-90 Issue 3 17th April 2007 Page 1 of 2

Page 2 is for internal use only

## RAYBRAID® PLATED COPPER BRAID

The complete requirements for procuring the wire described herein shall consist of this document.



Part	Braid Detail				
Number	Strand	Number of		Minimum	Nom.
	size			Coverage	Weight #
	AWG/ mm	Carriers	Ends	%	(kg/ km)
RAY-90-3.0	36/ 0.13	16	5	90.0	13
RAY-90-4.0	36/ 0.13	16	7	90.0	17
RAY-90-5.0	36/ 0.13	24	6	90.0	21
RAY-90-6.0	36/ 0.13	24	7	90.0	25
RAY-90-10.0	34/ 0.16	24	9	90.0	52
RAY-90-12.5	34/ 0.16	24	10	90.0	65
RAY-90-15.0	32/ 0.20	24	11	90.0	100
RAY-90-20.0	30/ 0.25	36	7	90.0	165
RAY-90-25.0	30/ 0.25	36	9	90.0	207
RAY-90-30.0	28/ 0.32	36	9	90.0	310

NOTE:

The last number of the part depicts the nominal internal diameter of the braid, e.g. RAY-90-5.0 Tin Plated Copper Braid with 5.00 mm nominal internal diameter.

'#' The nominal weight value excludes weight of former

PERFORMANCE REQUIREMENTS:

To be tested to and meet the requirements of the issue in effect of WSD 1922.

APPROVAL:

Electronic sign off - no signatures will appear.

RAYBRAID<sup>®</sup> is a registered trademark of Tyco Electronics Corporation.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: