


# QR/P4 SERIES

## Small Rectangular Multi-electrode Solderless Connectors for Racks and Panels

### General

QR/P4 Series is a series of small connectors for rack and panel application. This is a smaller-size version of the QR/P and QR/P1 Series, whose rectangular multi-electrode plug in connectors for racks and panels have been well received in the market.

Six models with different numbers of contacts are available: 8, 12, 16, 24 32 and 40. Wires are connected to the connectors without solder for easier connection and higher reliability.



### Features

- (1) The pins can be smoothly inserted into the receptacle, and give stable contact pressure because of their point contact with the receptacle blades. Furthermore, they have a larger allowance for the variation of connection length - a characteristic of plug-in connections.
- (2) The connector size has been made smaller by separating the terminals for signals from those for voltage supply.
- (3) The pitch of the signal terminals inside the housing is 2.54mm. Two pairs of diametrically opposed electrodes (four electrodes in total) on the two sides are arranged with a pitch of 5.08mm so that they can withstand high voltage, and can be used for power supply. In addition, a nonflammable material (UL94V-0) is used as the insulating housing of the connectors.
- (4) Guide pins and the housing body are molded as one piece to achieve a smaller connector size.
- (5) Since the connectors are mounted on racks or panels with stepped screws, connection and disconnection can be done easily.
- (6) The contact for female terminals in the housing is deeper than the fitting surface of the housing which conforms to the finger test (UL Standard 1950).
- (7) The connectors of this series have passed UL, CSA and TÜV standard.

### Application

PPC, Transmission and reception equipment, Data Communication, Vending Machine, Measuring Instruments, Automatic Equipment, Switchboards, etc.

## Specification

Item	Specifications	
Contact Resistance	Power	Max. 15mΩ at DC1A
	Signal	Max. 15mΩ at DC1A
Insulation Resistance		Min. 5000MΩ at DC500V
Withstand Voltage (for 1 minute)	Power	AC 2000V
	Signal	AC 500V
Rated Current	Power	3A
	Signal	1A
Rated Voltage	Power	AC 300V
	Signal	AC 250V

Item	Material	Finish
Insulator	PBT resin *:UL94V-0	Black
Contact	Phosphor Bronze	Selective Gold plating over Nickel

Ratings authorized by QR/P4 safety standards			
Safety standard	UL, CSA, TÜV		
Operating temperature	-10~ +60°C		
Rated Voltage	Power supply	AC 30V	AC380V, DC450V
	Signal unit	AC 250V	AC120V, DC150V
Rated current	AWG#20	3A	2.5A
	AWG#22		1A
	AWG#24	2A	
	AWG#26	1A	
	AWG#28		

## Ordering Information

### ▲ Connector Unit

QR / P4 — 12 P — C — (01)

(1) (2)(3) (4) (10)

### ▲ Contact


QR / P1 — PC 2 A — 1 1 1

(1) (5) (6) (7)(8)(9)


- (1) Series name
- (2) No.of contacts (8, 12, 16, 24, 32, 40)
- (3) Type of Housing
  - P: Plug Housing
  - S: Socket Housing
- (4) Type of termination
  - C: Crimping
- (5) Type of Contact
  - PC: Pin Contact
  - SC: Socket Contact
- (6) Size of Barrel
  - 2A: Thin Wire (UL1007 Type)
  - 2B: Thin Wire (UL1007 Type) . . . For 4 contact holes at both ends
- (7) Contact Type
  - 1: Loose Contact
  - 2: Chain Contact
- (8) Applicable wire
  - 1: Thin Wire AWG #24 - #28
  - 2: Thick Wire AWG #20 - #24
- (9) Finish
  - 1: Selective Gold plated over Nickel
- (10) UL, CSA, TÜV
  - Approved Spec

## Housing

Male Housing



Female Housing




Unit: mm						
HRS No.	No. of Pin	Part No.	A	B	C	RoHS
CL221-0159-5-01	8	QR/P4- 8P-C (01)	34.68	26.68	17.68	○
CL221-0139-8-01	12	QR/P4-12P-C (01)	39.8	31.8	22.8	
CL221-0155-4-01	16	QR/P4-16P-C (01)	44.84	36.84	27.84	
CL221-0141-0-01	24	QR/P4-24P-C (01)	55	47	38	
CL221-0153-9-01	32	QR/P4-32P-C (01)	67.7	59.7	50.7	
CL221-0211-3-01	40	QR/P4-40P-C (01)	77.86	69.86	60.86	

Unit: mm						
HRS No.	No. of Pin	Part No.	A	B	C	RoHS
CL221-0160-4-01	8	QR/P4- 8S-C (01)	34.68	26.68	17.68	○
CL221-0140-7-01	12	QR/P4-12S-C (01)	39.8	31.8	22.8	
CL221-0156-7-01	16	QR/P4-16S-C (01)	44.84	36.84	27.84	
CL221-0142-2-01	24	QR/P4-24S-C (01)	55	47	38	
CL221-0154-1-01	32	QR/P4-32S-C (01)	67.7	59.7	50.7	
CL221-0212-6-01	40	QR/P4-40S-C (01)	77.86	69.86	60.86	


Note: Determine the combinations with the panel so that the mating clearance between the P side and S side is 1.5mm or less.

## Contact

Power Male Contact



Power Female Contact



Selective gold plated with nickel under plating


Applicable Wire	HRS No.	Part No.	Type	Packing	RoHS
AWG#20~24	CL221-0115-0-12	QR/P1-PC2B-121 (12)	Loose contact	100pin	○
	CL221-0119-0-12	QR/P1-PC2B-221 (12)	Chain contact	5,000pin	

Selective gold plated with nickel under plating

Applicable Wire	HRS No.	Part No.	Type	Packing	RoHS
AWG#20~24	CL221-0117-2-12	QR/P1-SC2B-121 (12)	Loose contact	100pin	○
	CL221-0121-2-12	QR/P1-SC2B-221 (12)	Chain contact	5,000pin	

## Contact


### Signal Male Contact



Partly gold plated over nickel plating

Applicable Wire	HRS No.	Part No.	Type	Packing	RoHS
AWG#20~24	CL221-0103-0-12	QR/P1-PC2A-111 (12)	Loose contact	100pin	○
	CL221-0107-1-12	QR/P1-PC2A-211 (12)	Chain contact	5,000pin	○

### Signal Female Contact




Partly gold plated over nickel plating

Applicable Wire	HRS No.	Part No.	Type	Packing	RoHS
AWG#24~28	CL221-0105-6-12	QR/P1-SC2A-111 (12)	Loose contact	100pin	○
	CL221-0109-7-12	QR/P1-SC2A-211 (12)	Chain contact	5,000pin	○


## Panel Cutout

### QR/P4-※P-C




No. of pin	8pin	12pin	16pin	24pin	32pin	40pin
Rear Mounting	A 15.87	18.45	20.97	26.05	32.4	37.48
	B 19.18	24.3	29.34	39.5	52.2	62.36
	C 20.18	25.3	30.34	40.5	53.2	63.36
	D 26.68	31.8	36.84	47	59.7	69.86
Front Mounting	E 18.18	23.3	28.34	38.5	51.2	61.36
	F 21.68	26.8	31.84	42	54.7	64.86
	G 26.68	31.8	36.84	47	59.7	69.86

### QR/P4-※S-C



No. of pin	8pin	12pin	16pin	24pin	32pin	40pin
Rear Mounting	A 16.87	18.95	21.49	26.57	32.9	37.98
	B 19.68	24.8	29.84	40	52.7	62.86
	C 20.18	25.3	30.34	40.5	53.2	63.36
	D 26.68	31.8	36.84	47	59.7	69.86
Front Mounting	E 26.68	31.8	38.84	47	59.7	69.86
	F 19.18	24.3	29.34	39.5	52.2	62.36
	G 22.68	27.8	32.84	43	55.7	65.68

## Tooling



Hand Crimp Tool


Auto Crimp Machine  
CM-105  
CL901-0005-4

Kind	HRS No.	Part No.	Applicator Contact
Hand Crimp Tool	CL250-0021-3	TC-QR/P1-PC2B	QR/P1-PC2A-111
	CL250-0016-3	TC-QR/P1-PC2A	QR/P1-PC2A-111
	CL250-0023-9	TC-QR/P1-SC2B	QR/P1-SC2A-121
	CL250-0018-9	TC-QR/P1-SC2A	QR/P1-SC2A-111
Auto Crimp Machine Applicator	CL901-2530-5	AP105-QR/P1-2B-2	QR/P1-PC2B-221 QR/P1-SC2B-221
	CL901-2528-3	AP105-QR/P1-2A-1	QR/P1-PC2A-211 QR/P1-SC2A-211
Extraction Tool	CL250-0029-5	TC-QR/P4-21	QR/P1-SC2, PC2


## Contacts for thick wire Contact Configuration

Male Housing (Viewed from Wiring Side)

■: indicates a contact hole for thick wire



QR/P4-8P-C (01)




QR/P4-12P-C (01)



QR/P4-16P-C (01)



QR/P4-24P-C (01)



QR/P4-32P-C (01)



QR/P4-40P-C (01)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Hirose Electric:

[TC-QR/P4-21](#) [QR/P4-12P-C\(01\)](#) [QR/P4-12S-C\(01\)](#) [QR/P4-12S-C\(02\)](#) [QR/P4-24P-C\(01\)](#) [QR/P4-24P-C\(06\)](#) [QR/P4-24S-C\(01\)](#) [QR/P4-32P-C\(01\)](#) [QR/P4-32P-C\(06\)](#) [QR/P4-32S-C\(01\)](#) [QR/P4-32S-C\(02\)](#) [QR/P4-32S-C\(06\)](#) [QR/P4-16P-C\(01\)](#) [QR/P4-16S-C\(01\)](#) [QR/P4-16S-C\(02\)](#) [QR/P4-16S-C\(06\)](#) [QR/P4-8P-C\(01\)](#) [QR/P4-8S-C\(01\)](#) [QR/P4-8S-C\(02\)](#)  
[QR/P4-SCREW](#) [QR/P4-SCREW\(01\)](#) [QR/P4-40P-C\(01\)](#) [QR/P4-40S-C\(01\)](#) [QR/P4-40S-C\(02\)](#)