

THIS DRAWING IS UNPUBLISHED. DIFFUSION RESTREINTE. RELEASED FOR PUBLICATION LIBRE A LA DIFFUSION. ALL RIGHTS RESERVED. TOUS DROITS RESERVES.

FILS ADMISSIBLES (ACCEPTABLES WIRES)

LOC F DIST 7

REVISIONS

P	LTR	DESCRIPTION MODIFICATIONS	DATE	DWN DESS.	APVD APP.
D1		REVISED PER ECO-11-005150	27APR11	RK	HMR

JAUGE (AWG) SECTION / 7 BRINS (7 STRANDS) 24 0.22mm²

ISOLANT: Ø MAX / MATIERE (INSUL.: Ø MAX / MAT'L) Ø 1.2 / PVC

VOIE N°1 (FIRST POSITION)

REPERE VOIE N°1 (MARK POSITION NUMBER 1)

"C" 0 -0.8

"B" +0.12 0

COUPE C-C

1 CES CONNECTEURS SONT PREVUS POUR ETRE ACCOUPLES AVEC LES EMBASES 'HE1402' SIMPLE RANGEE (THESE CONNECTORS ARE DESIGNED TO BE MATED WITH 'HE1402' HEADERS SINGLE ROW)

2 LES REFERENCES SUIVIES D'UN ' * ' SONT LES VERSIONS NORMALISEES SELON LA 'CEI 603-8' (THE PART-N° FOLLOWED BY ' * ' ARE COVERED BY THE INTERNATIONAL STANDARD 'IEC603-8')

3 REVETEMENT DES CONTACTS: ETAME (THE CONTACTS ARE TIN PLATED)

4 CONNECTEURS CONDITIONNES SOUS TUBE PVC (THESE CONNECTORS ARE PACKAGED IN TUBE)

5 ' X ' EST REMPLACÉ PAR LE DEUXIEME CHIFFRE DES JAUGES AWG (' X ' REPLACED BY THE SECOND DIGIT OF AWG AS DEFINED IN TABLE)

6 MATIERES - BOITIER: PBT UL94V0 - CONTACTS: BRONZE PHOSPHOREUX. (MATERIALS - CASE: PBT UL94V0 - CONTACTS: PHOSPHOR BRONZE)

Obsolete Part No.	Length (mm)	Width (mm)	Height (mm)	Part No.	Part No.
9	64.38	60.96	25	2-201700-5	2-144270-5
9	61.76	58.42	24	2-201700-4	2-144270-4
10	59.22	55.88	23	2-201700-3	2-144270-3
10	56.68	53.34	22	2-201700-2	2-144270-2
10	54.14	50.80	21	2-201700-1	2-144270-1
11	51.60	48.26	20	2-201700-0	2-144270-0
12	49.06	45.72	19	1-201700-9	1-144270-9
12	46.52	43.18	18	1-281708-8 *	1-144270-8 *
13	43.98	40.64	17	1-201700-7	1-144270-7
14	41.44	38.10	16	1-201700-6	1-144270-6
15	38.90	35.56	15	1-281708-5 *	1-144270-5 *
16	36.36	33.02	14	1-201700-4	1-144270-4
17	33.82	30.48	13	1-201700-3	1-144270-3
18	31.28	27.94	12	1-281708-2 *	1-144270-2 *
20	28.74	25.40	11	1-201700-1	1-144270-1
20	26.20	22.86	10	1-281708-0 *	1-144270-0 *
25	23.66	20.32	9	0-201700-9	0-144270-9
25	21.12	17.78	8	0-281708-8 *	0-144270-8 *
30	18.58	15.24	7	0-281708-7	0-144270-7
35	16.04	12.70	6	0-281708-6 *	0-144270-6 *
40	13.50	10.16	5	0-281708-5 *	0-144270-5 *
50	10.96	7.62	4	0-281708-4 *	0-144270-4 *
70	8.42	5.08	3	0-281708-3 *	0-144270-3 *
100	5.88	2.54	2	0-281708-2	0-144270-2

Dimensions	Tolerances	Material	Finish	Weight	Customer Drawing
mm	0 PLC/DEC: ±0.3 1 PLC/DEC: ±0.3 2 PLC/DEC: ±0.3 3 PLC/DEC: ±0.3 4 PLC/DEC: ±0.3 ANGLES: ±5°				

Material	Finish	Weight	Customer Drawing

References	Part No.

Size	Format	Cage Code	Drawing No	Restricted To
A2	00779	C=281708		

CUSTOMER DRAWING /PLAN CLIENT

UNIQUEMENT POUR REFERENCE

SCALE

SHEET

OF

REV

D1

D

C

B

A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[144270-4](#)