









RECOMMENDED HOLE PATTERN



BASIC DIMENSIONS FOR EVEN NO OF SPACES (SEE TABLE) BASIC DIMENSIONS FOR ODD NO OF SPACES (SEE TABLE)

DETAIL R

- CONTACT AREA PLATED WITH .000030 GOLD; SOLDER TAILS PLATED WITH .000150 TIN-LEAD, ALL OVER .000050 NICKEL
- POINT OF MEASUREMENT FOR PLATING THICKNESS
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- CONTACT AREA PLATED WITH .000030 GOLD; SOLDER TAILS PLATED WITH .000150 TIN, ALL OVER .000050 NICKEL.
- FINISH: .000001 MIN. GOLD ON GOLD PLATED AREA, .000150-.000250 MATTE TIN LEAD ON TIN PLATE AREA, UNDER PLATING SHOULD BE .000050-.000100 NICKEL ON ENTIRE CONTACT.
- FINISH: .000001 MIN GOLD ON GOLD PLATED AREA, .000150-.000250 MATTE TIN ON TIN PLATED AREA. UNDER PLATING TO BE .000050-.000100 NICKEL ON ENTIRE CONTACT
- PRELIMINARY - NOT FOR PRODUCTION
- SUPERSEDED
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

6	2.450	49	2.644	100	7-104076-8
	1.200	24	1.394	50	7-104076-7
	.700	14	.894	30	7-104076-6
	.200	4	.394	10	7-104076-5
	1.950	39	2.144	80	7-104076-4
	.950	19	1.144	40	7-104076-3
	1.450	29	1.644	60	7-104076-2
	.450	9	.644	20	7-104076-1
	2.450	49	2.644	100	5-104076-8
	1.200	24	1.394	50	5-104076-7
4	.700	14	.894	30	5-104076-6
	.200	4	.394	10	5-104076-5
	1.950	39	2.144	80	5-104076-4
	.950	19	1.144	40	5-104076-3
	1.450	29	1.644	60	5-104076-2
	.450	9	.644	20	5-104076-1
	2.450	49	2.644	100	NO OF POS
	1.200	24	1.394	50	PART NUMBER
	.700	14	.894	30	
	.200	4	.394	10	

5	2.450	49	2.644	100	2-104076-8
	1.200	24	1.394	50	2-104076-7
	.700	14	.894	30	2-104076-6
	.200	4	.394	10	2-104076-5
	1.950	39	2.144	80	2-104076-4
	.950	19	1.144	40	2-104076-3
	1.450	29	1.644	60	2-104076-2
	.450	9	.644	20	2-104076-1
	2.450	49	2.644	100	8-104076-8
	1.200	24	1.394	50	104076-7
1	.700	14	.894	30	104076-6
	.200	4	.394	10	104076-5
	1.950	39	2.144	80	104076-4
	.950	19	1.144	40	104076-3
	1.450	29	1.644	60	104076-2
	.450	9	.644	20	104076-1
	2.450	49	2.644	100	NO OF POS
	1.200	24	1.394	50	PART NUMBER
	.700	14	.894	30	
	.200	4	.394	10	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .005

4 PLC ± -

ANGLES ± -

MATERIAL: HOUSING; THERMOPLASTIC COLOR-BLACK POST; COPPER ALLOY

DWN K. HELM 12-19-88

CHK H. MOLL 12-19-88

APVD R. DURBIN 12-19-88

PRODUCT SPEC 108-1093

APPLICATION SPEC 114-25031

WEIGHT -

CUSTOMER DRAWING

NAME

SIZE CAGE CODE DRAWING NO

RESTRICTED TO

TE Connectivity

HEADER ASSEMBLY, VERTICAL SHROUDED, WITH SLOT, AMPMODU System 50

100779C=104076

SCALE 4:1 SHEET 1 OF 1 REV U

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[104076-6](#)