

### Wall Plug - Ins

## WDU75-100

#### Electrical Specifications (@25C)

- 1. Primary Rating: 120V 60Hz 6W
- 2. Primary Excitation Current: 40mA Max
- 3. Secondary Rating: 7.5VDC ± 5%, 100mADC
- 4. Secondary No-Load Rating: 10.1VDC Ref.
- 5. Output Ripple Voltage: 800mV Max
- 6. Operating Temperature Range: -10 Deg C to +40 Deg C
- 7. Temperature Rise: 70 Deg C Max at rated load

50 Deg C Max on enclosure surface

#### Mechanical Parameters:

Case Type: Thermoplastic molded enclosure. Output Cord: 24 AWG, 6 Ft. Long Min.

Agency File:

UL/CUL: File E104603, UL 1310


CSA: LR67888

#### A. Dimensions:

Н	W	D
56	43	37

\*Units: In Millimeter

#### B. Schematic:



Technical Note: 1. Inside (tip)-positive (+), outside-negative (-)

U.S. DOE Compliance per Sec. 301 of EISA 2007: As of July 1, 2008, this product is intended for use as follows:

- 1. Requires Federal Food and Drug Administration listing and approval as a medical device in accordance with section 513 of the Federal Food, Drug, and Cosmetic Act (21 U.S.C. 360c)
- 2. Powers the charger of a detachable battery pack or charges the battery of a product that is fully or primarily motor operated.
- As a service part or a spare part for an end-use product manufactured before July 1, 2008, that constitutes the primary load of this power supply.

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

D



# AC ADAPTOR

MODEL: WDU75-100 INPUT: 120V 60Hz 6W OUTPUT: 7.5VDC 100mA **CLASS 2 TRANSFORMER** 







MADE IN CHINA

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Triad Magnetics: WDU75-100