


**Product: [39126](#)**
**Lead Wire, #26 Str TC, PPO Ins, AWM 11028 600V 105C VW-1**
[Request Sample](#)
**Product Description**

Low Temp Plastic Lead Wire, 26AWG (7x34) Tinned Copper, PPO Insulation, AWM 11028 600V 105C VW-1

**Technical Specifications**
**Product Overview**

Suitable Applications:	Electrical panel builders, Electrical/electronic manufacturers, Appliance manufacturers, Furniture, Computer manufacturers, Automotive companies and their sub-suppliers
------------------------	--

**Physical Characteristics (Overall)**
**Conductor**

AWG	Stranding	Material	No. of Conductors
26	7x34	TC - Tinned Copper	1

Conductor Count: 1

**Insulation**

Material	Nominal Diameter	Nominal Wall Thickness
PPO - Polyphenylene Oxide	0.043 in	0.012 in

**Outer Jacket Material**

Material
No Jacket

**Electrical Characteristics**
**Conductor DCR**

Nominal Conductor DCR
37.3 Ohm/1000ft

**Current**

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	6.5 A

**Voltage**

UL Voltage Rating
600 V

**Temperature Range**

UL Temp Rating:	105°C
Operating Temp Range:	-40°C To +105°C Dry

**Mechanical Characteristics**

Bulk Cable Weight:	1.4 lbs/1000ft
--------------------	----------------

**Standards**

UL AWM Style:	AWM 11028
---------------	-----------

Military Specification:	N/A
-------------------------	-----

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2011-04-01
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	UPC	Length	Footnote
39126 010100	Black	612825150671	100 ft	C
39126 0101000	Black	612825150688	1,000 ft	C
39126 0105000	Black	612825150695	5,000 ft	C Z
39126 013100	Blue, Dark	612825150701	100 ft	C
39126 0131000	Blue, Dark	612825150718	1,000 ft	C
39126 0135000	Blue, Dark	612825150725	5,000 ft	C Z
39126 0035000	Blue, Light	612825150510	5,000 ft	C Z
39126 001100	Brown	612825150435	100 ft	C
39126 0011000	Brown	612825150442	1,000 ft	C
39126 0015000	Brown	612825150459	5,000 ft	C Z
39126 008100	Gray	612825150619	100 ft	C
39126 0081000	Gray	612825150626	1,000 ft	C
39126 0085000	Gray	612825150633	5,000 ft	C Z
39126 005100	Green, Dark	612825150558	100 ft	C
39126 0051000	Green, Dark	612825150565	1,000 ft	C
39126 0055000	Green, Dark	612825150572	5,000 ft	C Z
39126 0031000	Orange	612825150503	1,000 ft	C
39126 002100	Red	612825150466	100 ft	C
39126 0021000	Red	612825150473	1,000 ft	C
39126 0025000	Red	612825150480	5,000 ft	C Z
39126 007100	Violet	612825150589	100 ft	C
39126 0071000	Violet	612825150596	1,000 ft	C
39126 0075000	Violet	612825150602	5,000 ft	C Z
39126 009100	White	612825150640	100 ft	C
39126 0091000	White	612825150657	1,000 ft	C
39126 0095000	White	612825150664	5,000 ft	C Z
39126 004100	Yellow	612825150527	100 ft	C
39126 0041000	Yellow	612825150534	1,000 ft	C
39126 0045000	Yellow	612825150541	5,000 ft	C Z

Footnote: C - CRATE REEL PUT-UP.

Footnote: Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

## Product Notes

Notes:	Halogen-free.
--------	---------------

## History

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.