



- 1 MOLDED PARTS: FLAME RETARDANT, 94V-0 RATED, GLASS FILLED NYLON OR POLYESTER, BLACK
CONTACTS: BRASS
HARDWARE: ZINC
- 2 CONTACTS: SEE TABLE
HARDWARE: CLEAR CHROMATE
- 3 GOLD FLASH ON THE MATING SURFACES, .000100 MIN TIN OR TIN-LEAD PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
- 4 .000030 MIN GOLD PLATE ON THE MATING SURFACES, .000100 MIN TIN OR TIN-LEAD PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
-OR-
GOLD FLASH OVER PALLADIUM-NICKEL PLATE, .000030 MIN TOTAL ON THE MATING SURFACES, .000100 MIN TIN OR TIN-LEAD PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
- 5 REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.

SUPSD BY 747467-4	WITH SCREWLOCKS	4	747467-6
OBSOLETE	WITH SCREWLOCKS	3	747467-5
	WITH INSERTS	4	747467-4
SUPSD BY 747467-4	WITH INSERTS	3	747467-3
	WITH .120 DIA HOLE	4	747467-2
	WITH .120 DIA HOLE	3	747467-1
REMARKS		FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C RICHARD 7-29-87	TE Connectivity	
DIMENSIONS: INCHES		CHK S WELDON 8-3-87	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD B TAYLOR 8-3-87	PRODUCT SPEC	
0 PLC ± -		108-40005		
1 PLC ± -		APPLICATION SPEC		
2 PLC ± -		114-40015		
3 PLC ± .005		SIZE CAGE CODE DRAWING NO		
4 PLC ± -		A1 00779 C=747467		
ANGLES ± ± °		RESTRICTED TO		
MATERIAL	FINISH	WEIGHT	CUSTOMER DRAWING	
1	2		SCALE 4:1	SHEET 1 OF 1 REV H

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[747467-2](#)