

## Between Series Adaptor 33\_N-716-50-1/---\_U

### Description

Adaptor plug/jack  
N plug (male) / 7/16 jack (female)



Interface standards  
Series N - IEC 61169-16\_MIL-STD-348A/304\_CECC 22210  
Series 7/16 - IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250

### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
VSWR	DC - 7.5 GHz ≤ 1.03 + 0.02 f (GHz)

#### Mechanical Data

Number of matings	500
Weight	0.1015 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - 7/16 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

### Related Documents

Catalogue drawing DCA-00014333

### Ordering Information

Single package 33\_N-716-50-1/---\_UE

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[33\\_N-716-50-1/---\\_UE](#)