



LOC	DIST	REVISIONS					
AD	39	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A1	REVISED PER ECO-11-004820	11MAR11	RK	HMR



RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
3. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
4. HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
5. FINISH: 0.00254-0.00508 [.000100-.000200] BRIGHT TIN-LEAD OVER 0.00127 [.000050] NICKEL ENTIRE POST.
6. FINISH: 0.00254-0.00508 [.000100-.000200] MATTE TIN OVER 0.00127 [.000050] NICKEL ENTIRE POST.

△ ₆	101.19 [3.984]	99.06 [3.900]	39	40	9-146480-0
△ ₆	98.65 [3.884]	96.52 [3.800]	38	39	8-146480-9
△ ₆	96.11 [3.784]	93.98 [3.700]	37	38	8-146480-8
△ ₆	93.57 [3.684]	91.44 [3.600]	36	37	8-146480-7
△ ₆	91.03 [3.584]	88.90 [3.500]	35	36	8-146480-6
△ ₆	88.49 [3.484]	86.36 [3.400]	34	35	8-146480-5
△ ₆	85.95 [3.384]	83.82 [3.300]	33	34	8-146480-4
△ ₆	83.41 [3.284]	81.28 [3.200]	32	33	8-146480-3
△ ₆	80.87 [3.184]	78.74 [3.100]	31	32	8-146480-2
△ ₆	78.33 [3.084]	76.20 [3.000]	30	31	8-146480-1
△ ₆	75.79 [2.984]	73.66 [2.900]	29	30	8-146480-0
△ ₆	73.25 [2.884]	71.12 [2.800]	28	29	7-146480-9
△ ₆	70.71 [2.784]	68.58 [2.700]	27	28	7-146480-8
△ ₆	68.17 [2.684]	66.04 [2.600]	26	27	7-146480-7
△ ₆	65.63 [2.584]	63.50 [2.500]	25	26	7-146480-6
△ ₆	63.09 [2.484]	60.96 [2.400]	24	25	7-146480-5
△ ₆	60.55 [2.384]	58.42 [2.300]	23	24	7-146480-4
△ ₆	58.01 [2.284]	55.88 [2.200]	22	23	7-146480-3
△ ₆	55.47 [2.184]	53.34 [2.100]	21	22	7-146480-2
△ ₆	52.93 [2.084]	50.80 [2.000]	20	21	7-146480-1
△ ₆	50.39 [1.984]	48.26 [1.900]	19	20	7-146480-0
△ ₆	47.85 [1.884]	45.72 [1.800]	18	19	6-146480-9
△ ₆	45.31 [1.784]	43.18 [1.700]	17	18	6-146480-8
△ ₆	42.77 [1.684]	40.64 [1.600]	16	17	6-146480-7
△ ₆	40.23 [1.584]	38.10 [1.500]	15	16	6-146480-6
△ ₆	37.69 [1.484]	35.56 [1.400]	14	15	6-146480-5
△ ₆	35.15 [1.384]	33.02 [1.300]	13	14	6-146480-4
△ ₆	32.61 [1.284]	30.48 [1.200]	12	13	6-146480-3
△ ₆	30.07 [1.184]	27.94 [1.100]	11	12	6-146480-2
△ ₆	27.53 [1.084]	25.40 [1.000]	10	11	6-146480-1
△ ₆	24.99 [.984]	22.86 [.900]	9	10	6-146480-0
△ ₆	22.45 [.884]	20.32 [.800]	8	9	5-146480-9
△ ₆	19.91 [.784]	17.78 [.700]	7	8	5-146480-8
△ ₆	17.37 [.684]	15.24 [.600]	6	7	5-146480-7
△ ₆	14.83 [.584]	12.70 [.500]	5	6	5-146480-6
△ ₆	12.29 [.484]	10.16 [.400]	4	5	5-146480-5
△ ₆	9.75 [.384]	7.62 [.300]	3	4	5-146480-4
△ ₆	7.21 [.284]	5.08 [.200]	2	3	5-146480-3
△ ₆	4.67 [.184]	2.54 [.100]	1	2	5-146480-2
△ ₆	2.13 [.084]	-	-	1	5-146480-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

5	101.19 [3.984]	99.06 [3.900]	39	40	4-146480-0
5	98.65 [3.884]	96.52 [3.800]	38	39	3-146480-9
5	96.11 [3.784]	93.98 [3.700]	37	38	3-146480-8
5	93.57 [3.684]	91.44 [3.600]	36	37	3-146480-7
5	91.03 [3.584]	88.90 [3.500]	35	36	3-146480-6
5	88.49 [3.484]	86.36 [3.400]	34	35	3-146480-5
5	85.95 [3.384]	83.82 [3.300]	33	34	3-146480-4
5	83.41 [3.284]	81.28 [3.200]	32	33	3-146480-3
5	80.87 [3.184]	78.74 [3.100]	31	32	3-146480-2
5	78.33 [3.084]	76.20 [3.000]	30	31	3-146480-1
5	75.79 [2.984]	73.66 [2.900]	29	30	3-146480-0
5	73.25 [2.884]	71.12 [2.800]	28	29	2-146480-9
5	70.71 [2.784]	68.58 [2.700]	27	28	2-146480-8
5	68.17 [2.684]	66.04 [2.600]	26	27	2-146480-7
5	65.63 [2.584]	63.50 [2.500]	25	26	2-146480-6
5	63.09 [2.484]	60.96 [2.400]	24	25	2-146480-5
5	60.55 [2.384]	58.42 [2.300]	23	24	2-146480-4
5	58.01 [2.284]	55.88 [2.200]	22	23	2-146480-3
5	55.47 [2.184]	53.34 [2.100]	21	22	2-146480-2
5	52.93 [2.084]	50.80 [2.000]	20	21	2-146480-1
5	50.39 [1.984]	48.26 [1.900]	19	20	2-146480-0
5	47.85 [1.884]	45.72 [1.800]	18	19	1-146480-9
5	45.31 [1.784]	43.18 [1.700]	17	18	1-146480-8
5	42.77 [1.684]	40.64 [1.600]	16	17	1-146480-7
5	40.23 [1.584]	38.10 [1.500]	15	16	1-146480-6
5	37.69 [1.484]	35.56 [1.400]	14	15	1-146480-5
5	35.15 [1.384]	33.02 [1.300]	13	14	1-146480-4
5	32.61 [1.284]	30.48 [1.200]	12	13	1-146480-3
5	30.07 [1.184]	27.94 [1.100]	11	12	1-146480-2
5	27.53 [1.084]	25.40 [1.000]	10	11	1-146480-1
5	24.99 [.984]	22.86 [.900]	9	10	1-146480-0
5	22.45 [.884]	20.32 [.800]	8	9	146480-9
5	19.91 [.784]	17.78 [.700]	7	8	146480-8
5	17.37 [.684]	15.24 [.600]	6	7	146480-7
5	14.83 [.584]	12.70 [.500]	5	6	146480-6
5	12.29 [.484]	10.16 [.400]	4	5	146480-5
5	9.75 [.384]	7.62 [.300]	3	4	146480-4
5	7.21 [.284]	5.08 [.200]	2	3	146480-3
5	4.67 [.184]	2.54 [.100]	1	2	146480-2
5	2.13 [.084]	-	-	1	146480-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[7-146480-1](#)