



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

1200W 120V Line Conditioner - Automatic Voltage Regulator (AVR), AC Surge Protection, 4 Outlets

MODEL NUMBER: LC1200



Maintains usable 120V nominal output to sensitive electronics during severe brownouts and overvoltages. Prevents surges and spikes from damaging circuitry. Filters out potentially disruptive line noise.

Description

The LC1200 1200W 120V Line Conditioner - Automatic Voltage Regulator adjusts under- and overvoltages to provide safe, computer-grade AC power that meets ANSI C84.1 specifications. The automatic voltage regulation (AVR) offers three levels of voltage stabilization that corrects undervoltages as low as 89V and overvoltages as high as 147V back to regulated 120V nominal power. Providing optimum voltage conditions not only extends the life of your equipment, but also keeps your equipment working through brownouts and prolonged overvoltage conditions.

A network-grade 1200-joule surge suppression rating exceeds the IEEE-587 standard for surge suppression (both categories A and B) and prevents even the strongest spikes from inflicting damage, data loss or corruption and audio/video performance problems on your connected equipment. EMI/RFI noise filtering protects your AC line from disruptive electromagnetic and radio interference.

Just connect the space-saving NEMA 5-15P right-angle plug with 7-foot cord to an AC power source, and plug up to four devices into the NEMA 5-15R outlets. You can monitor AC power, incoming voltage level and AC line status using the seven diagnostic LEDs on the front panel. The compact LC1200 fits comfortably into your computer or home theater setup.

Features

Protects Valuable ElectronicsRated at 120V/1200W/10AIdeal for computers, routers, modems, printers, home theater components and point-of-sale equipmentConnect up to 4 electronic devices to the rear NEMA 5-15R outlets7 ft. cord with NEMA 5-15P right-angle plug for easier connection in tight spacesCompact unit (7.25 in. high) fits comfortably into your computer or home theater setup

Automatic Voltage Regulation (AVR)Monitors incoming AC power and keeps equipment working through brownouts and prolonged overvoltage conditionsCorrects undervoltages as low as 89V and overvoltages up to 147V

AC Line Surge Suppression1200 joules of surge suppression protects against potentially harmful power surges and spikesIncludes full normal (H-N) and common (N-G/H-G) line surge suppression

EMI/RFI Line Noise FilteringRemoves electromagnetic and radio frequency interference that can disrupt or damage your equipment's performance

Built-In DiagnosticsFront-panel LEDs indicate AC power, incoming voltage level and line statusRear on/off switch provides one-touch power control over all components

Highlights

- Ideal for computers, routers, modems and home theater components
- Corrects under- and overvoltages in 89V–147V range
- Protects against spikes with 1200 joules of surge suppression
- Monitors power status with front-panel diagnostic LEDs
- Features 4 NEMA 5-15R rear outlets

Package Includes

- LC1200 1200W 120V Power Conditioner
- Owner's Manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Specifications

OVERVIEW	
UPC Code	037332040022
INPUT	
Plug Type	Right-angle NEMA 5-15P input plug
Input Cord Length (ft.)	7
Input Cord Length (m)	2.13
OUTPUT	
Output (VA)	1200
Output (Watts)	1200
Nominal Output Voltage(s) Supported	120V
Output Receptacles	(4) 5-15R
VOLTAGE REGULATION	
Voltage Regulation Description	Maintains usable 120V nominal voltage during brownouts as low as 89VAC and over-voltages as high as 147VAC. Input voltages between 114V~127V are passed through unchanged.
Overvoltage Correction	Input voltages over 128V (+/-3V) are reduced by 10%
Brownout Correction	Input voltages between 113V (+/-3V) and 103V (+/-3V) are boosted by 9%.
Severe Brownout Correction	Input voltages below 102V (+/-3V) are boosted by 19%.
USER INTERFACE, ALERTS & CONTROLS	
Front Panel LEDs	7 LEDs show incoming voltage status, protection present and line fault conditions
SURGE / NOISE SUPPRESSION	
UPS AC Suppression Joule Rating	1200
EMI / RFI AC Noise Suppression	75 dB
PHYSICAL	
Form Factors Supported	Small Tower
Material of Construction	Plastic
Shipping Dimensions (hwd / cm)	19.56 x 25.65 x 22.10
Shipping Dimensions (hwd / in.)	7.70 x 10.10 x 8.70
Shipping Weight (kg)	4.04



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Shipping Weight (lbs.)	8.90
Unit Dimensions (hwd / cm)	18.4 x 15.2 x 17.8
Unit Dimensions (hwd / in.)	7.25 x 6 x 7
STANDARDS & COMPLIANCE	
Certifications	Tested to UL1012 (USA), cUL1012 (Canada), NOM (Mexico)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>