

# Housing - HC-B 10-TMQ-52/O1PG16S - 1673627

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows versions for double locking latch and single locking latch and with double locking latch

Sleeve housing, for double locking latch, height 52 mm, without screw connection, 1x Pg16, lateral cable entry



### **Key Commercial Data**

Packing unit	10 pc
GTIN	4 017918 152734
GTIN	4017918152734

### Technical data

#### **Dimensions**

Height	52 mm
Width	43 mm
Length	73 mm
Wrench size, union nut	22 mm
External cable diameter	7.5 mm 15 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C 125 °C

#### General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Size	B10
Housing type	Sleeve housing
Locking type	with double locking latch
No. of cable outlets	1



# Housing - HC-B 10-TMQ-52/O1PG16S - 1673627

## Technical data

### General


Cable outlet	lateral
Screw connection	none
Type of the screw connection	1x Pg16
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray
Material lock	Stainless steel, handle: PA
Material grip body interlock	PA


#### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# **Drawings**

#### Dimensional drawing





Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1673627