

# Single Phase Silicon Bridge Rectifier


 $V_{RRM} = 600\text{ V} - 1000\text{ V}$ 
 $I_O = 6\text{ A}$ 

## Features

- Ideal for printed circuit board
- Low forward voltage drop
- Low leakage current
- Types from 600 V up to 1000 V  $V_{RRM}$
- Not ESD Sensitive

## Mechanical Data

Case: Molded plastic body  
 Mounting: Hole thru for #6 screw  
 Mounting position: Any  
 Lead: As marked

**BR-6 Package**


## Maximum ratings at $T_c = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	BR66	BR68	BR610	Unit
Repetitive peak reverse voltage	$V_{RRM}$		600	800	1000	V
RMS reverse voltage	$V_{RMS}$		420	560	700	V
DC blocking voltage	$V_{DC}$		600	800	1000	V
Operating temperature	$T_j$		-65 to 125	-65 to 125	-65 to 125	$^\circ\text{C}$
Storage temperature	$T_{stg}$		-65 to 150	-65 to 150	-65 to 150	$^\circ\text{C}$

## Electrical characteristics at $T_c = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Single phase, half sine wave, 60 Hz, resistive or inductive load  
 For capacitive load derate current by 20%

Parameter	Symbol	Conditions	BR66	BR68	BR610	Unit
Maximum average forward rectified current	$I_O$	$T_c = 75\text{ }^\circ\text{C}$	6.0	6.0	6.0	A
Peak forward surge current	$I_{FSM}$	$t_p = 8.3\text{ ms}$ , half sine	200	200	200	A
Maximum instantaneous forward voltage drop per bridge element	$V_F$	$I_F = 3.0\text{ A}$	1.0	1.0	1.0	V
Maximum DC reverse current at rated DC blocking voltage	$I_R$	$T_a = 25\text{ }^\circ\text{C}$	10	10	10	$\mu\text{A}$
		$T_a = 100\text{ }^\circ\text{C}$	200	200	200	

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS







FIG.4-TYPICAL REVERSE CHARACTERISTICS



**Package dimensions and terminal configuration**

Product is marked with part number and terminal configuration.

BR-6



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[GeneSiC Semiconductor:](#)

[BR610](#) [BR66](#) [BR68](#)