						REV.	DATE	DESCRIPTION
						NC	07/31/07	INITIAL RELEASE
	5.	/8-24UNEF	-2A		[1.411]			- 12.7 HEX
				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.	APPROVALS	DATE		Amphenol Connex
				unless otherwise specified tolerances for millimeters are: $0.5-8$ mm $\pm~0.20$ mm	G.R.S.	07/31/0		
				8 – 30mm ± 0.40mm			PART DESCRIP	
GASKET	SILICONE	BLACK	1	30 – 120mm ± 0.50mm	ISSUED		N	FEMALE TO F MALE W/WATERPROOF ADAPTER 75ohm
CONTACT PIN	PHOS. BRONZE	GOLD	1	TOLERANCES FOR INCHES ARE:	SHEET 1 OF 1			/50hm
INSULATOR	TEFLON	NATURAL	1	$.020315 = \pm 0.007"$ $.315 - 1.180 = \pm 0.015"$			PART NO.	242152-75
BODY	BRASS	NICKEL	1	$1.180 - 4.724 = \pm 0.020"$				
DESCRIPTION	MATERIAL	FINISH	QTY	DO NOT SCALE DRAWING	C:/242/2421	52-75.DW	G DWG. NO.	242152-75.DWG REV. NC SIZE A SCALE N

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: 242152-75