



# PS-670 6 Volt 7.0 AH

## Rechargeable Sealed Lead Acid Battery




**We've Got The Power.™**





### Terminals: (mm)

- F1 - Quick disconnect tabs, 0.187" x 0.032". Mate with AMP. INC. FASTON "187" series



### Physical Dimensions: in (mm)



L: 5.95 (151) W: 1.34 (34) H: 3.70 (94) HT: 3.94 (100)

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

### Features

- Absorbent Glass Mat (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Power/volume ratio yielding unrivaled energy density
- Rugged impact resistant ABS case and cover (UL94-HB)
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- U.L. recognized under file number MH 20845

### Performance Specifications

**Nominal Voltage** ..... 6 volts (3 cells)

#### Nominal Capacity

|                                     |         |
|-------------------------------------|---------|
| 20-hr. (350mA to 5.25 volts) .....  | 7.00 AH |
| 10-hr. (630mA to 5.25 volts) .....  | 6.30 AH |
| 5-hr. (1.19A to 5.10 volts) .....   | 5.95 AH |
| 1-hr. (4.34A to 4.50 volts) .....   | 4.34 AH |
| 15-min. (13.5A to 4.50 volts) ..... | 3.38 AH |

**Approximate Weight** ..... 2.42 lbs. (1.10 kg)

**Energy Density (20-hr. rate)** ..... 1.42 W-h/in<sup>3</sup> (86.88 W-h/l)

**Specific Energy (20-hr. rate)** ..... 17.36 W-h/lb (38.26 W-h/kg)

**Internal Resistance (approx.)** ..... 15 milliohms

**Max Discharge Current (7 Min.)** ..... 21.0 amperes

**Max Short-Duration Discharge Current (10 Sec.)** .... 70.0 amperes

#### Shelf Life (% of nominal capacity at 68°F (20°C))

|                |     |
|----------------|-----|
| 1 Month .....  | 97% |
| 3 Months ..... | 91% |
| 6 Months ..... | 83% |

#### Operating Temperature Range


Charge ..... -4°F (-20°C) to 122°F (50°C)

Discharge ..... -40°F (-40°C) to 140°F (60°C)


**Case** ..... ABS Plastic

**Power-Sonic Chargers**.....PSC-61000A, 61000A-C

### Shelf Life & Storage



### Discharge Time vs. Discharge Current



### Charging

**Cycle Applications:** Limit initial current to 2.1A. Charge until battery voltage (under charge) reaches 7.20 to 7.35 volts at 68°F (20°C). Hold at 7.20 to 7.35 volts until current drops to under 70mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to "float" voltage.

**"Float" or "Stand-By" Service:** Hold battery across constant voltage source of 6.75 to 6.90 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

**Note:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

### Chargers

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for "C-Series Switch Mode Chargers" and "Transformer Type A and F Series". Please contact our Technical department for advice if you have difficulty in locating suitable models.

### Contact Information

**DOMESTIC SALES**  
Tel: +1-619-661-2020  
Fax: +1-619-661-3650  
national-sales@power-sonic.com

**CUSTOMER SERVICE**  
Tel: +1-619-661-2030  
Fax: +1-619-661-3648  
customer-service@power-sonic.com


**TECHNICAL SUPPORT**  
Tel: +1-619-661-2020  
Fax: +1-619-661-3648  
support@power-sonic.com

**INTERNATIONAL SALES**  
Tel: +1-650-364-5001  
Fax: +1-650-366-3662  
international-sales@power-sonic.com


CORPORATE OFFICE • 7550 Panasonic Way • San Diego, CA 92154 • USA • Tel: +1-619-661-2020 • Fax: +1-619-661-3650

0814 1M


### Discharge Characteristics



### Life Characteristics in Stand-By Use



### Life Characteristics in Cyclic Use



### Further Information

Please refer to our website [www.power-sonic.com](http://www.power-sonic.com) for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc..

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Power-Sonic:](#)

[PS-670](#)