



TMM SERIES

LOW-PROFILE SMT HEADER



Specify
2SN-BK-G
for 2 mm
shunt with
Gold plating.



- Pick & place pads
- Alignment pins
- Tape & reel packaging

(2.77 mm)
.109" Low Profile

Diagram illustrating a 16-bit bus system with 8 modules. The bus is labeled 02 at the top and 01 at the bottom. A bracket indicates a 16-bit width. The modules are numbered 80, 79, and 01. A value of (3.94, .155) is shown on the right.

Technical drawing of a 10-pin connector. The drawing shows a side view of the connector with dimensions in inches. The dimensions are: (0.50) .020 SQ (top), (1.50) .059 (top right), (2.00) .0787 (bottom), and .0787 (bottom right). The drawing also shows a cross-section of the connector with a .0787 dimension.

LEAD STYLE	A	MATES WITH
-01	(3.20) .126	SQT, SQW, ESQT, TLE, SMM, MMS, TCSD
-04	(1.91) .075	CLT
-05	(1.65) .065	
-06	(4.27) .168	CLT-BE

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications.

Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[TMM-117-03-L-D](#)