### R Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : 202D1XX-XX-07 Description : Boot, Straight, With Lips

\_

ь**—** Р —

#### NOTES

- 1. All dimensions are in  $\frac{\text{inches}}{[\text{millimeters}]}$
- 2. Dimensions appearing in table are as follows:
  - a As Supplied
- b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- Part numbers 202D163-X-07 thru 202D196-X-07 will have two lips.

COATING (SEE NOTE 3)							AFTER UNRESTRICTED RECOVERY				
TABLE OF DI	MENSIC	NS									
PART NUMBER	н		J Min Min			Р	R	s	т	JO	w
	Min a	Max b	-3,-4 -25 g	-12	Max b	±10%	Ref b	Ref b	Ref b	±10%	±20%
202D121-XX-07	.92	<u>.41</u>	.92	. <u>49</u>	.22	1.03	. <u>36</u>	<u>.12</u>	.04	. <u>40</u>	<u>.07</u>
	[23,3]	[10,5]	[23,3]	[12,4]	[5,6]	[26,1]	[9,1]	[3,1]	[1,0]	[10,2]	[1,8]
202D132-XX-07	1.12	.56	1.12	.58	.26	1.69	<u>.62</u>	<u>.12</u>	.04	<u>.65</u>	<u>.07</u>
	[28,4]	[14,2]	[28,4]	[14,7]	[6,6]	[42,9]	[15,7]	[3,1]	[1,0]	[16,6]	[1,8]
202D142-XX-07	1.22	<u>.70</u>	1.22	<u>.63</u>	.28	1.83	<u>.59</u>	<u>.12</u>	.04	<u>.70</u>	<u>.08</u>
	[31,0]	[17 <b>,</b> 8]	[31,0]	[16,0]	[7,2]	[46,5]	[15,0]	[3,1]	[1,0]	[17 <b>,8</b> ]	[2,0]
202D153-XX-07	1.42	.88	1.42	<u>.73</u>	. <u>33</u>	2.35	<u>.83</u>	.12	.04	.82	.08
	[36,1]	[22,3]	[36,1]	[18,5]	[8,4]	[59,7]	[21,1]	[3,0]	[1,0]	[20,8]	[2,0]
202D163-XX-07	1.68	<u>1.11</u>	1.68	<u>.87</u>	. <u>39</u>	3.28	1.42	<u>.12</u>	. <u>065</u>	<u>.97</u>	<u>.09</u>
	[42,7]	[28,2]	[42,7]	[22,0]	[9,9]	[83,3]	[36,0]	[3,1]	[1,65]	[24,6]	[2,3]
202D174-XX-07	2.04	1.38	2.04	1.39	<u>.62</u>	4.33	1.74	.12	. <u>065</u>	1 <u>.56</u>	<u>.13</u>
	[51 <b>,8</b> ]	[35,1]	[51,8]	[35,3]	[15,8]	[109,9]	[44,2]	[3,1]	[1,65]	[39,6]	[3,3]
202D185-XX-07	2.60	1.75	2.60	1.80	. <u>80</u>	5.70	2.51	.12	.08	1 <u>.90</u>	<u>.16</u>
	[66,0]	[44,5]	[66,0]	[45,7]	[20,4]	[144,7]	[63,7]	[3,1]	[2,0]	[48,3]	[4,06]
202D196-XX-07	3.22	2.27	3.22	2.25	1.00	5.53	2.28	<u>.12</u>	.08	1.88	<u>.16</u>
	[81,7]	[57,6]	[81,7]	[57,1]	[25,4]	[140,4]	[57,9]	[3,0]	[2,0]	[47,8]	[4,06]
		evision ate :	: G 2/12/	⁄97			art Nui escript				-XX—07 aight, V

### Raychem

YCHEM CORPORATION 10 CONSTITUTION DRIVE 2NLO PARK, CALIFORNIA 94025


## Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : Description :

202D1XX-XX-07 Boot, Straight, With Lips

COMPATABILITY CHART									
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION				
-3	Polyolefin, Semi-rigid	RT-301	/42,/86	S-1017,S-1048	Adhesive				
-4	Polyolefin, Flexible	RT-1304	/42,/86	S-1017,S-1048	Adhesive				
-12	*VITON, Flexible	RT-1312	N/A						
-25	Elastomer, Fluid Resistant	RT-1325	N/A						

\*VITON is a Registered Trademark of Dupont



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

### Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

If this document is printed it becomes uncontrolled. Check for the latest revision.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 202D132-25-07-0