|   |                    |                                   |                                  |  | THIS DRAWING IS A CONTROLLED DOCUMENT.             |            |             |  |   |             |                 |         |      |                |      |     |             |  |  |
|---|--------------------|-----------------------------------|----------------------------------|--|--|------------|-------------|--|---|-------------|-----------------|---------|------|----------------|------|-----|-------------|--|--|
|   |                    |                                   | LOC                              | DIST                                       | REVISIONS<br>変更<br>P LTR DESCRIPTION DATE DWN APVD |            |             |  |   |             |                 |         |      |                |      |     |             |  |  |
|   |                    |                                   | J                                |  | Ρ  | ltr<br>F   | REVI        | SED  | PER ECR-  |             |                 |         |      | 21AF           |      | DWN | apvd<br>T.M |  |  |
|   |                    |                                   |                                  |  |  |            | <br>Λ       |  | 16  | 40          | 7-              | M<br>−6 | -7   |                |      | 6-  |             |  |  |
|   |                    |                                   |                                  |  |  | 72         | 0999-5      | 12   | 50  | 7-          | -2              | 7-      |      | _              | 2    |     |             |  |  |
|   |                    |                                   |                                  | S<br>S                                     |  |            | Λ.          |  | 24  | 25          | 5-              | -4      | 5-   |                | _    | 4   |             |  |  |
| RELEASED FOR PUBLICATION , .  |                    |                                   |                                  | -TO-B)<br>TH BOSS                          |  |            |             |  | 22  | 30          | 5-              | -2      | 5-   |                | _    | 2   |             |  |  |
|   |                    |                                   | 基板対基板接続用)<br>ッセンブリ               | :め用ボス付<br>CTOR(BーT<br>TYPE WITH            |  |            |             |  | 20  | 30          | 5-              | -0      | 5-   |                | _    | 0   |             |  |  |
|   |                    |                                   | く基板対基板†<br>アッ センブリ               | 基板位置決め用ポス付<br>CONNECTOR (E<br>Y SMT TYPE W |  |            |             |  | 18  | 35          | 4-              | -8      | 4-   |                |      | 8   |             |  |  |
|   |                    |                                   | コネクタ<br>ッ ダ -                    | ъсŃ  |  |            |             |  | 16  | 40          | 4-              | -6      | 4-   |                | _    | 6   |             |  |  |
|   |                    |                                   | л т<br>Ч – Р<br>Х – Р            | · · · · ·                                  |  |            |             |  | 14  | 45          | 4-              | -4      | 4-   |                | _    | 4   |             |  |  |
|   | RIGHIS RESERVED.   |                                   | - ス詰 1.25 F-<br>2列仕様 ポスト         |  |  |            |             |  | 12  | 50          | 4-              | -2      | 4-   |                |      | 2   |             |  |  |
|   | all rights         |                                   | 崎<br>ビイ<br>し                     | + - 7<br>PACK/<br>ROW                      |  |            |             |  | 10  | 60          | 4-              | -0      | 4-   |                | _    | 0   |             |  |  |
|   | A                  |                                   |                                  | TUBE F<br>DOUBLE                           |  | 72         | 0999-       | -4   | 6   | 90          | 3-              | -6      | 3-   |                |      | 6-  |             |  |  |
|   |                    |                                   |                                  | ' ŭ  |  |            | Λ           |  | 20  | 30          | 2-              | -0      | 2-   |                | _    | 0   |             |  |  |
| ED.   |                    |                                   |                                  |  |  |            |             |  | 16  | 40          | 1-              | -6      | 1—   |                | — (  | 5   |             |  |  |
|   |                    |                                   |                                  |  | 2  | 2-912050-0 |             |  | 14  | 45          | 1-174           | 821-4   | 1-   | -1756          | 643- | 4   |             |  |  |
| UNPUBLISH   | By -               |                                   | 1                                | 塩ビケース<br>型 番<br>TUBE P/N                   |  |            | V           | 極数 数量 コネクタ型番 塩ビケー   (ケ) (パラ状) コネクタ   Pos. QTY'S CONN P/N (L/P) IN TUBE |   |             |                 |         |      | タ型番            | N    |     |             |  |  |
| 'HIS DRAWING IS UNPUBLISHED.  | COPYRIGHT          | 注記<br>1. 包装规格:107—5123—2<br>NOTES |                                  |  |  |            |             |  |   |             |                 |         |      |                |      |     |             |  |  |
| THIS [  | $\odot$            |                                   |                                  |  |  |            |             |  | J1ZJ-Z  |             |                 |         |      |                |      |     |             |  |  |
|   | -                  | ppp                               |                                  |  |  |            |             |  | MATERIAL FINISH<br>材料 住上  |             |                 |         |      |                |      |     |             |  |  |
| CHK 30MAY88<br>TOLERANCES UNLESS S.KIKUCHI<br>OTHERWISE SPECIFIED: APVD 30MAY88<br>一般公差 N.ONOUE |                    |                                   |                                  |  |  |            |             |  | TE Connectivity   |             |                 |         |      |                |      |     |             |  |  |
| 1—1<br>2—1  |                    | - 10を超え 30.<br>土 30を超え100.        | u下:±0.2<br>以下:±0.25<br>以下:±0.3 _ | PRODUCT SPE<br>製品規格                        |  |            |             |  | NAME<br>名称 TUBE PACKAGING 1.25 F—P CONNECTOR (B—TO—B)<br>DOUBLE ROW POST HDR ASS'Y SMT TYPE WITH BOSS |             |                 |         |      |                |      |     |             |  |  |
| 4   | PLC<br>PLC<br>GLES |                                   |                                  |  | SPEC   |            |             |  | SIZE CAGE CODE DRAWING NO RESTRICTED TO 조국  |             |                 |         |      |                |      |     |             |  |  |
|   |                    | $\oplus \subset$                  |                                  | weight<br>CUSTOME                          | <br>R  |            | WING        |  | 4 007   | /9 <b>G</b> | = 1756<br> \$€# |         | SHEE | <sup>г</sup> 1 | 0F 1 | RE  | -<br>^ F    |  |  |
|   |                    |                                   |                                  |  | - 12   |            | · · · · · · |  |   |             | 尺易              | z       |      | 1              | ~    |     | I.          |  |  |

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 7-175643-2