PHŒNIX CONTACT

Components of electronic housing - UM-PRO PCB C-LOCK L3 BK - 2200166

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Locking element for locking the PCB onto UM-PRO housing at level 3

The figure shows the versions for PCB level 1

Why buy this product

- ☑ Item is from the UM-BASIC/UM-PRO product range
- ☑ PVC press-drawn section (UM-BASIC) or PA (UM-PRO)
- ☑ Available in individual lengths
- ☑ Available in the overall widths of 72 mm, 108 mm, and 122 mm
- ☑ Variety of connection technologies
- ☑ Can be mounted on the DIN rail

RoHS

Key Commercial Data

Packing unit	50 pc
GTIN	4 046356 547604
GTIN	4046356547604

Technical data

General

Housing type	Panel mounting base
Housing material	Polyamide
Color (RAL)	black

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)

Standards and Regulations

Flammability rating according to UL 94	V0

Components of electronic housing - UM-PRO PCB C-LOCK L3 BK - 2200166

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information: