

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0746972503

Status:

Active

Overview:

VHDM-HSD™ Backplane Connectors

Description:

VHDM-HSD™ Backplane Header, 2.00mm Pitch, 5-Row, Guide Pin Signal Module, Shield End Version, 100 Circuits, Pin Length 4.25mm. Series:74702 Enables designers to create custom loaded connectors utilizing standard pin lengths 4.25, 4.75, 5.15 and 6.25mm

Documents:

Drawing (PDF)

Packaging Specification PK-74696-003 (PDF)

Product Specification PS-74031-999 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

General

Product Family

Backplane Connectors

Series

74697

Application

Backplane

Application Tooling Documents

TM-622010999

Comments

No Keying Orientation

Component Type

PCB Header

Overview

VHDM-HSD™ Backplane Connectors

Product Name

VHDM-HSD™

UPC

756054241806

Physical

Circuits (Loaded)

100

Circuits (maximum)

100

Color - Resin

Black

Durability (mating cycles max)

200

First Mate / Last Break

No

Flammability

94V-0

Guide to Mating Part

Yes

Keying to Mating Part

None

Material - Metal

High Performance Alloy (HPA), Stainless Steel

Material - Plating Mating

Gold

Material - Plating Termination

Matte Tin

Material - Resin

High Temperature Thermoplastic

Net Weight

11.243/g

Number of Columns

25

Number of Pairs

Open Pin Field

Number of Rows

5

Orientation

Vertical

PC Tail Length

2.50mm

PCB Locator

No

PCB Retention

None

PCB Thickness - Recommended

1.80mm

Packaging Type

Tube

Pitch - Mating Interface

2.00mm

Plating min - Mating

0.762µm

Plating min - Termination

0.762µm

Polarized to PCB

Yes

Surface Mount Compatible (SMC)


Yes

Temperature Range - Operating

-55°C to +105°C

Termination Interface: Style

Through Hole - Compliant Pin



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Not Contained Per -

ED/21/2016 (20 June

2016)

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

74697 Series

Mates With

74670 VHDM-HSD™ Daughtercard

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Signal Header, 5-Row by 25-Wide, 50.00mm	0622020202
Signal Pin Inserter Repair Tool	0622015700
5-Row Pin and Shield Repair Tool	0622015810

Electrical		5-Row Shield	<u>0622016010</u>
Current - Maximum per Contact	1.0A	Extraction Tool	
Data Rate	5.0 Gbps		
Voltage - Maximum	120V AC (RMS)/DC		
Solder Process Data			
Lead-freeProcess Capability	N/A		
Material Info			
Reference - Drawing Numbers			
Packaging Specification	PK-74696-003		
Product Specification	PS-74031-999		
Sales Drawing	SD-74697-002		
Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.			

This document was generated on 09/29/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

74697-2503