


REV. 2  
DCO 143371

COIL: @ 25°C  
 RESISTANCE 1560 OHMS ±10%  
 NOMINAL VOLTAGE 26.5 VDC  
 MUST OPERATE 14.2 VDC  
 MUST RELEASE 8.0 VDC MAX, 1.37 VDC MIN.

ENVIRONMENT:  
 VIBRATION 10 CPS TO 3000 CPS @ 30 g's  
 SHOCK 75 g's 6 MS. DURATION  
 TEMPERATURE -65 °C TO +125 °C

NOTES: OPERATE TIME 2.0 MS MAX  
RELEASE TIME 4.0 MS MAX  
CONTACT BOUNCE 1.5 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO  
1A 28 VDC RESISTIVE 100,000 OPERATIONS

DR. ASB 11/30/01 *CR. ERP 12/19/01*

**CII Technologies**  
 advanced control electronic solutions

CUST. OPL  
 CUST. NO. M39016/9-076L REV.     

"JMAC" RELAY

JMAC-26XLS

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMAC-26XLS](#)