








Surface Mount Ceramic Capacitor Products



IMPORTANT INFORMATION/DISCLAIMER

All product specifications, statements, information and data (collectively, the "Information") in this datasheet or made available on the website are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on AVX's knowledge of typical operating conditions for such applications, but are not intended to constitute and AVX specifically disclaims any warranty concerning suitability for a specific customer application or use.

ANY USE OF PRODUCT OUTSIDE OF SPECIFICATIONS OR ANY STORAGE OR INSTALLATION INCONSISTENT WITH PRODUCT GUIDANCE VOIDS ANY WARRANTY.

The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by AVX with reference to the use of AVX's products is given without regard, and AVX assumes no obligation or liability for the advice given or results obtained.

Although AVX designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Unless specifically agreed to in writing, AVX has not tested or certified its products, services or deliverables for use in high risk applications including medical life support, medical device, direct physical patient contact, water treatment, nuclear facilities, weapon systems, mass and air transportation control, flammable environments, or any other potentially life critical uses. Customer understands and agrees that AVX makes no assurances that the products, services or deliverables are suitable for any high-risk uses. Under no circumstances does AVX warrant or guarantee suitability for any customer design or manufacturing process.

Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.

Surface Mount Ceramic Capacitor Products



Table of Contents

How to Order

Part Number Explanation..... 1

COG (NP0) Dielectric

General Specifications 3

Specifications and Test Methods 4

Capacitance Range 5

U Dielectric

RF/Microwave COG (NP0) Capacitors (RoHS)

General Information 7

Capacitance Range 8

RF/Microwave COG (NP0) Capacitors (Sn/Pb)

General Information 10

Capacitance Range 11

RF/Microwave Automotive COG (NP0) Capacitors (RoHS)

AEC Q200 Qualified Ultra Low ESR 12

Designer Kits 14

X8R/X8L Dielectric

General Specifications 15

Specifications and Test Methods 17

X7R Dielectric

General Specifications 18

Specifications and Test Methods 19

Capacitance Range 20

X7S Dielectric

General Specifications 22

Specifications and Test Methods 23

Capacitance Range 24

X5R Dielectric

General Specifications 25

Specifications and Test Methods 26

Capacitance Range 27

Y5V Dielectric

General Specifications 29

Specifications and Test Methods 30

Capacitance Range 31

MLCC Gold Termination – AU Series

General Specifications 32

Capacitance Range 33

MLCC Tin/Lead Termination "B" (LD Series)

COG (NP0) – General Specifications 39

Specifications and Test Methods 40

Capacitance Range 41

X8R General Specifications 43

Specifications and Test Methods 44

Capacitance Range 45

X7R General Specifications 46

Specifications and Test Methods 47

Capacitance Range 48

X5R General Specifications 50

Specifications and Test Methods 51

Capacitance Range 52

Automotive MLCC

General Specifications 53

Capacitance Range 55

APS for COTS+ High Reliability Applications

General Specifications 58

Capacitance Range 59

MLCC with FLEXITERM®

General Specifications 62

Specifications and Test Methods 63

Capacitance Range 65

FLEXISAFE MLC Chips

General Specifications and Capacitance Range 67

Capacitor Array

Capacitor Array (IPC) 68

Automotive Capacitor Array (IPC) 72

Part & Pad Layout Dimensions 73

Low Inductance Capacitors

Introduction 74

LICC (Low Inductance Chip Capacitors) 76

IDC (InterDigitated Capacitors) 80

LGA Low Inductance Capacitors 84

High Temperature MLCCs

AT Series – 200°C & 250°C Rated 87

High Voltage MLC Chips

For 600V to 5000V Applications 93

Tin/Lead Termination "B" - 600V to 5000V Applications 98

FLEXITERM® - 600V to 5000V Applications 100

For 600V to 3000V Automotive Applications - AEC-Q200 105

MIL-PRF-55681/Chips

CDR01 thru CDR06 107

CDR31 thru CDR35 109

MLCC Medical Applications

MM Series 113

Packaging of Chip Components

..... 118

Embossed Carrier Configuration

..... 119

Paper Carrier Configuration

..... 120

Basic Capacitor Formulas

..... 121

General Description

..... 122

Surface Mounting Guide

..... 127



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

How to Order

Part Number Explanation



Commercial Surface Mount Chips

EXAMPLE: 0805A101JAT2A

0805	5	A	101	J*	A	T	2	A**
Size (L" x W")	Voltage	Dielectric	Capacitance	Tolerance	Failure Rate	Terminations	Packaging	Special Code
0101*	4 = 4V	A = NPO(COG)	2 Sig. Fig + No. of Zeros	B = ± 10 pF	A = N/A	T = Plated Ni and Sn	Available	A = Std
0201	6 = 6.3V	C = X7R	Examples: 100 = 10 pF	C = ± 25 pF	4 = Automotive	7 = Gold Plated	2 = 7" Reel	K = 30K (0603 2mm pitch)
0402	Z = 10V	D = X5R	101 = 100 pF	D = ± 50 pF		U = Conductive	4 = 13" Reel	22K (0805/1206 <0.030" / 0.76mm)
0603	Y = 16V	F = X8R	102 = 1000 pF	F = $\pm 1\%$ (≥ 10 pF)	J = $\pm 5\%$	Epoxy for Hybrid	U = 4mm TR	H = 18K (0603/0805/1206 <0.037" / 0.94mm)
0805	3 = 25V	G = Y5V	223 = 22000 pF	G = $\pm 2\%$ (≥ 10 pF)	K = $\pm 10\%$	Applications	(01005)	J = 15K (0805/1206 <0.050" / 1.27mm)
1206	D = 35V	U = U Series	224 = 220000 pF	M = $\pm 20\%$	Z = FLEXITERM®	*X = FLEXITERM®	1 = 12K (0805/1206 <0.055 / 1.4mm)	
1210	5 = 50V	W = X6S	105 = 1 μ F	Z = $+80\%$, -20%	with 5% min lead	(X7R & X8R only)		
1812	1 = 100V	Z = X7S	106 = 10 μ F	P = $+100\%$, -0%				
1825	2 = 200V		107 = 100 μ F					
2220	7 = 500V							
2225								
Contact Factory for Special Voltages								
*EIA 01005								
F = 63V 9 = 300V * = 75V X = 350V E = 150V 8 = 400V V = 250V								
Contact Factory For Multiples								
1 = Pd/Ag Term								

For values below
10 pF, use "R"
in place of
Decimal point, e.g.,
9.1 pF = 9R1.

Contact Factory For Multiples

* B, C & D tolerance for ≤ 10 pF values.

Standard Tape and Reel material (Paper/Embossed) depends upon chip size and thickness.

See individual part tables for tape material type for each capacitance value.

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

For Tin/Lead Terminations, please refer to LD Series

High Voltage MLC Chips

EXAMPLE: 1808AA271KA11A

1808	A	A	271	K	A	T	2	A
AVX Style	Voltage	Temperature Coefficient	Capacitance Code	Capacitance Tolerance	Failure Rate	Termination	Packaging/ Marking	Special Code
0805	C = 600V/630V	A = 1000V	A = COG	(2 significant digits + no. of zeros) COG: J = $\pm 5\%$	A=Not Applicable	1 = Pd/Ag	2 = 7" Reel	A = Standard
1206	S = 1500V	C = 1500V	C = X7R	Examples: 10 pF = 100		T = Plated Ni and Sn	4 = 13" Reel	
1210	G = 2000V			100 pF = 101		B = 5% Min Pb		
1808	W = 2500V			1,000 pF = 102		Z = FLEXITERM®		
1812	H = 3000V			22,000 pF = 223		*X = FLEXITERM®		
1825	J = 4000V			220,000 pF = 224		with 5% min lead		
2220	K = 5000V			1 μ F = 105		(X7R only)		
2225								
3640								

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

For Tin/Lead Terminations, please refer to LD Series

* Not RoHS Compliant



For RoHS compliant products,
please select correct termination style.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

How to Order

Part Number Explanation



Capacitor Array

EXAMPLE: W2A43C103MAT2A

W	2	A	4	3	C	103	M	A	T	2A
Style W = RoHS L = SnPb	Case Size 1 = 0405 2 = 0508 3 = 0612	Array A = X7R	Number of Caps 4 = NP0 5 = X5R	Voltage Z = 10V Y = 16V 3 = 25V 5 = 50V 1 = 100V	Dielectric A = NP0 C = X7R D = X5R	Capacitance Code (In pF) 2 Sig Digits + Number of Zeros	Capacitance Tolerance J = ±5% K = ±10% M = ±20%	Failure Rate A = Commercial 4 = Automotive	Termination Code T = Plated Ni and Sn *B = 5% min lead *X = FLEXITERM® with 5% min lead	Packaging & Quantity Code 2A = 7" Reel (4000) 4A = 13" Reel (10000) 2F = 7" Reel (1000)

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

Low Inductance Capacitors (LICC)

EXAMPLE: 0612ZD105MAT2A

0612	Z	D	105	M	A	T	2	A
Size 0306 0508 0612 *LD16 *LD17 *LD18	Voltage 6 = 6.3V Z = 10V Y = 16V 3 = 25V 5 = 50V	Dielectric C = X7R D = X5R	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance K = ±10% M = ±20%	Failure Rate A = N/A	Terminations T = Plated Ni and Sn *B = 5% min lead	Packaging Available 2 = 7" Reel 4 = 13" Reel	Thickness See Page 97 for Codes

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

Interdigitated Capacitors (IDC)

EXAMPLE: W3L16D225MAT3A

W	3	L	1	6	D	225	M	A	T	3	A
Style W = RoHS L = SnPb	Case Size 2 = 0508 3 = 0612	Low Inductance ESL = 50pH ESL = 60pH	Number of Terminals 1 = 8 Terminals	Voltage 4 = 4V 6 = 6.3V Z = 10V Y = 16V	Dielectric C = X7R D = X5R	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance M = ±20%	Failure Rate A = N/A	Termination T = Plated Ni and Sn *B = 5% min lead	Packaging Available 1 = 7" Reel 3 = 13" Reel	Thickness Max. Thickness mm (in) A = 0.95 (0.037) S = 0.55 (0.022)

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

Low Inductance Decoupling Capacitor Arrays (LICA)

EXAMPLE: LICA3T183M3FC4AA

LICA	3	T	102	M	3	F	C	4	A	A
Style & Size W = RoHS L = SnPb	Voltage 5V = 9 10V = Z 25V = 3	Dielectric D = X5R T = T55T S = High K T55T	Cap/Section (EIA Code) 102 = 1000 pF 103 = 10 nF 104 = 100 nF	Capacitance Tolerance M = ±20% P = GMV	Height Code 6 = 0.500mm 3 = 0.650mm 1 = 0.875mm 5 = 1.100mm 7 = 1.600mm X = None	Termination *F = C4 Solder H = C4 Solder P = Cr-Cu-Au N = Cr-Ni-Au X = None	Reel Packaging M = 7" Reel Balls-97Pb/3Sn R = 13" Reel 6 = 2"x2" Waffle Pack 8 = 2"x2" Black Waffle Pack 7 = 2"x2" Waffle Pack w/termination facing up A = 2"x2" Black Waffle Pack w/termination facing up C = 4"x4" Waffle Pack w/ clear lid	# of Caps/Part 1 = one 2 = two 4 = four	Inspection Code A = Standard B = Established Reliability Testing	Code Face A = Bar B = No Bar C = Dot, S55S Dielectrics D = Triangle


* Not RoHS Compliant



NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

COG (NP0) Dielectric

General Specifications



COG (NP0) is the most popular formulation of the "temperature-compensating," EIA Class I ceramic materials. Modern COG (NP0) formulations contain neodymium, samarium and other rare earth oxides.

COG (NP0) ceramics offer one of the most stable capacitor dielectrics available. Capacitance change with temperature is $0 \pm 30\text{ppm}/^\circ\text{C}$ which is less than $\pm 0.3\% \text{ C}$ from -55°C to $+125^\circ\text{C}$. Capacitance drift or hysteresis for COG (NP0) ceramics is negligible at less than $\pm 0.05\%$ versus up to $\pm 2\%$ for films. Typical capacitance change with life is less than $\pm 0.1\%$ for COG (NP0), one-fifth that shown by most other dielectrics. COG (NP0) formulations show no aging characteristics.







PART NUMBER (see page 4 for complete part number explanation)



RoHS
COMPLIANT


0805	5	A	101	J	A	T	2	A
Size (L" x W")	Voltage 6.3V = 6 10V = Z 16V = Y 25V = 3 50V = 5 100V = 1 200V = 2 250V = V 500V = 7	Dielectric COG (NP0) = A	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance B = $\pm 10\text{ pF}$ ($< 10\text{ pF}$) C = $\pm 25\text{ pF}$ ($< 10\text{ pF}$) D = $\pm 50\text{ pF}$ ($< 10\text{ pF}$) F = $\pm 1\%$ ($\geq 10\text{ pF}$) G = $\pm 2\%$ ($\geq 10\text{ pF}$) J = $\pm 5\%$ K = $\pm 10\%$	Failure Rate A = Not Applicable	Terminations T = Plated Ni and Sn	Packaging 2 = 7" Reel 4 = 13" Reel U = 4mm TR (01005)	Special Code A = Std. Product
						Contact Factory For 1 = Pd/Ag Term 7 = Gold Plated NOT RoHS COMPLIANT		
								Contact Factory For Multiples

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers. Contact factory for non-specified capacitance values.



COG (NP0) Dielectric

Specifications and Test Methods

Parameter/Test	NPO Specification Limits		Measuring Conditions		
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance <30 pF: $Q \geq 400 + 20 \times \text{Cap Value}$ ≥30 pF: $Q \geq 1000$		Freq.: 1.0 MHz ± 10% for cap ≤ 1000 pF 1.0 kHz ± 10% for cap > 1000 pF Voltage: 1.0Vrms ± .2V		
Insulation Resistance	100,000MΩ or 1000MΩ - μF, whichever is less		Charge device with rated voltage for 60 ± 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	±5% or ±.5 pF, whichever is greater			
	Q	Meets Initial Values (As Above)			
	Insulation Resistance	≥ Initial Value x 0.3			
Solderability	≥ 95% of each terminal should be covered with fresh solder		Dip device in eutectic solder at 230 ± 5°C for 5.0 ± 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal		Dip device in eutectic solder at 260°C for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	≤ ±2.5% or ±.25 pF, whichever is greater			
	Q	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: -55°C ± 2°	
	Capacitance Variation	≤ ±2.5% or ±.25 pF, whichever is greater		Step 2: Room Temp	
	Q	Meets Initial Values (As Above)		Step 3: +125°C ± 2°	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with twice rated voltage in test chamber set at 125°C ± 2°C for 1000 hours (+48, -0).	
	Capacitance Variation	≤ ±3.0% or ± .3 pF, whichever is greater			
	Q (C=Nominal Cap)	≥ 30 pF: $Q \geq 350$ ≥ 10 pF, <30 pF: $Q \geq 275 + 5C/2$ <10 pF: $Q \geq 200 + 10C$			
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Store in a test chamber set at 85°C ± 2°C/ 85% ± 5% relative humidity for 1000 hours (+48, -0) with rated voltage applied.	
	Capacitance Variation	≤ ±5.0% or ± .5 pF, whichever is greater			
	Q	≥ 30 pF: $Q \geq 350$ ≥ 10 pF, <30 pF: $Q \geq 275 + 5C/2$ <10 pF: $Q \geq 200 + 10C$			
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			

COG (NP0) Dielectric

Capacitance Range

PREFERRED SIZES ARE SHADED

SIZE	0101*	0201	0402	0603	0805	1206
Soldering	Reflow Only	Reflow Only	Reflow/Wave	Reflow/Wave	Reflow/Wave	Reflow/Wave
Packaging	All Paper	All Paper	All Paper	All Paper	Paper/Embossed	Paper/Embossed
(L) Length (in.)	0.40 ± 0.02 (0.016 ± 0.008)	0.60 ± 0.09 (0.024 ± 0.004)	1.00 ± 0.10 (0.040 ± 0.004)	1.60 ± 0.15 (0.063 ± 0.006)	2.01 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)
(W) Width (in.)	0.20 ± 0.02 (0.008 ± 0.008)	0.30 ± 0.09 (0.011 ± 0.004)	0.50 ± 0.10 (0.020 ± 0.004)	0.81 ± 0.15 (0.032 ± 0.006)	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)
(t) Terminal (in.)	0.10 ± 0.04 (0.004 ± 0.0016)	0.15 ± 0.05 (0.006 ± 0.002)	0.25 ± 0.15 (0.010 ± 0.006)	0.35 ± 0.15 (0.014 ± 0.006)	0.50 ± 0.25 (0.020 ± 0.010)	0.50 ± 0.25 (0.020 ± 0.010)
WVDC	16	25	50	16 25 50	16 25 50 100 200	16 25 50 100 200 250
Cap (pF)	0.5	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
1.0	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
1.2	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
1.5	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
1.8	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
2.2	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
2.7	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
3.3	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
3.9	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
4.7	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
5.6	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
6.8	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
8.2	B	A	A C C C G G G	J J J J J J J	J J J J J J J	J J J J J J J
10	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
12	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
15	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
18	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
22	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
27	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
33	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
39	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
47	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
56	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
68	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
82	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
100	B	A	A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
120			A C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
150			C C C G G G	G G J J J J J	J J J J J J J	J J J J J J J
180			C C C G G G	G G J J J J J	J J N N J J J	J J J J J J J
220			C C C G G G	G G J J J J J	J J N N J J J	J J J J J J J
270			C C C G G G	G G J J J J J	J J N N J J J	J J J J J J J
330			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
390			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
470			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
560			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
680			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
750			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
820			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
1000			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
1200			C C C G G G	G G J J J J J	N N N J J J	J J J J J J J
1500			C C C G G G	G G J J J J J	N N N J J J	M Q P P
1800			C C C G G G	G G J J J J J	P P J J J J	M P Q P
2200			C C C G G G	G G J J J J J	P P J J J J	M P Q P
2700			C C C G G G	G G J J J J J	P P J J J J	M P Q P
3300			C C C G G G	G G J J J J J	P P J J J J	M P Q X
3900			C C C G G G	G G J J J J J	P P J J J J	M P X X
4700			C C C G G G	G G J J J J J	P P J J J J	M P X X
5600						
6800						
8200						
Cap (μF)	0.010				P P P P	P P P P
0.012					P P P P	P P P P
0.015					P P P P	P P P P
0.018					X X X X	X X X X
0.022					X X X X	X X X X
0.027					X X X X	X X X X
0.033					X X X X	X X X X
0.039					X X X X	X X X X
0.047					X X X X	X X X X
0.068					X X X X	X X X X
0.082					X X X X	X X X X
0.1					X X X X	X X X X
WVDC	16	25	50	16 25 50	16 25 50 100 200	16 25 50 100 200 250
SIZE	0101*	0201	0402	0603	0805	1206



Letter	A	B	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.22 (0.009)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER							EMBOSS							

COG (NP0) Dielectric Capacitance Range



PREFERRED SIZES ARE SHADED



SIZE	1210					1812					1825					2220					2225								
	Reflow Only					Reflow Only					Reflow Only					Reflow Only					Reflow Only								
Soldering	Reflow Only					All Embossed					All Embossed					All Embossed					All Embossed								
Packaging	Paper/Embossed					All Embossed					All Embossed					All Embossed					All Embossed								
(L) Length mm (in.)	3.20 ± 0.20 (0.126 ± 0.008)					4.50 ± 0.30 (0.177 ± 0.012)					4.50 ± 0.30 (0.177 ± 0.012)					5.70 ± 0.40 (0.225 ± 0.016)					5.72 ± 0.25 (0.225 ± 0.010)								
W) Width mm (in.)	2.50 ± 0.20 (0.098 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)					6.40 ± 0.40 (0.252 ± 0.016)					5.00 ± 0.40 (0.197 ± 0.016)					6.35 ± 0.25 (0.250 ± 0.010)								
(t) Terminal mm (in.)	0.50 ± 0.25 (0.020 ± 0.010)					0.61 ± 0.36 (0.024 ± 0.014)					0.61 ± 0.36 (0.024 ± 0.014)					0.64 ± 0.39 (0.025 ± 0.015)					0.64 ± 0.39 (0.025 ± 0.015)								
WVDC	25	50	100	200	500	25	50	100	200	500	50	100	200	50	100	200	50	100	200	50	100	200	50	100	200				
Cap (pF)	3.9																												
	4.7																												
	5.6																												
	6.8																												
	8.2																												
10	M	M	M	M	M	P	P	P	P	P																			
12	M	M	M	M	M	P	P	P	P	P																			
15	M	M	M	M	M	P	P	P	P	P																			
18	M	M	M	M	M	P	P	P	P	P																			
22	M	M	M	M	M	P	P	P	P	P																			
27	M	M	M	M	M	P	P	P	P	P																			
33	M	M	M	M	M	P	P	P	P	P																			
39	M	M	M	M	M	P	P	P	P	P																			
47	P					P	P	P	P	P																			
56	P	P	P	P	P	P	P	P	P	P																			
68	P	P	P	P	P	P	P	P	P	P																			
82	P	P	P	P	P	P	P	P	P	P																			
100	P	P	P	P	P	P	P	P	P	P																			
120	P	P	P	P	P	P	P	P	P	P																			
150	P	P	P	P	P	P	P	P	P	P																			
180	P	P	P	P	P	P	P	P	P	P																			
220	P	P	P	P	P	P	P	P	P	P																			
270	P	P	P	P	P	P	P	P	P	P																			
330	P	P	P	P	P	P	P	P	P	P																			
390	P	P	P	P	P	P	P	P	P	P																			
470	P	P	P	P	P	P	P	P	P	P																			
560	P	P	P	P	P	P	P	P	P	P																			
680	P	P	P	P	P	P	P	P	P	P																			
820	P	P	P	P	P	P	P	P	P	P																			
1000	P	P	P	P	P	P	P	P	P	P						M	M	M					M	M	P				
1200	P	P	P	P	P	P	P	P	P	P						M	M	M					M	M	P				
1500	P	P	P	P	P	P	P	P	P	P						M	M	M					M	M	P				
1800	P	P	P	P	P	P	P	P	P	P						M	M	M					M	M	P				
2200	P	P	P	P	P	P	P	P	P	P						X	X	X					M	M	P				
2700	P	P	P	P	P	P	P	P	P	P						X	X	X					M	M	P				
3300	P	P	P	P	P	P	P	P	P	P						X	X	X					X	M	P				
3900	P	P	P	P	P	P	P	P	P	P						X	X	X					X	M	P				
4700	P	P	P	P	P	P	P	P	P	P						X	X	X					X	M	P				
5600	P	P	P	P	P	P	P	P	P	P						X	X	X					X	M	P				
6800	P	P	P	P	P	P	P	P	P	P						X	X	X					X	M	P				
8200	P	P	P	P	P	P	P	P	P	P						X	X	X					X	M	P				
Cap (pF)	0.010	P	P	X	X	P	P	Q	Q	Y		X	X	X	X	X	X	X	X	X	X	X	M	M	P				
	0.012	X	X	X	X	P	P	Q	Q	Y		X	X	X	X	X	X	X	X	X	X	X	M	M	P				
	0.015	X	X	X	Z	P	P	Q	X	Y		X	X	X	X	X	X	X	X	X	X	X	M	M	Y				
	0.018	X	X	Z	Z	P	P	X	X	Y		X	X	X	X	X	X	X	X	X	X	X	M	M	Y				
	0.022	X	X	Z	Z	P	P	X	X	Y		X	X	X	X	X	X	X	X	X	X	X	M	Y	Y				
	0.027	X	Z	Z	Z	Q	X	X	Z	X		X	X	X	Y	X	X	X	X	X	X	X	P	Y	Y				
	0.033	X	Z	Z	Z	Q	X	X	Z	Z		X	X	X	X	X	X	X	X	X	X	X	X	Y	Y				
	0.039	Z	Z	Z	Z	X	X	Z	Z	Z		X	X	X	X	X	X	X	X	X	X	X	X	Y	Y				
	0.047	Z	Z	Z	Z	X	X	Z	Z	Z		X	X	X	X	X	X	X	X	X	X	X	X	Z	Z				
	0.068					Z	Z	Z	Z	Z													Z		X	Z			
	0.082					Z	Z	Z	Z	Z													Z		X	Z			
	0.1					Z	Z	Z	Z	Z													Z		X	Z			
WVDC	25	50	100	200	500	25	50	100	200	500	50	100	200	50	100	200	50	100	200	50	100	200	50	100	200				
SIZE	1210					1812					1825					2220					2225								

Letter
Max.
Thickness

PAPER

The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or
available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

U Dielectric

RF/Microwave COG (NP0) Capacitors (RoHS)


Ultra Low ESR, "U" Series, COG (NP0) Chip Capacitors



GENERAL INFORMATION


"U" Series capacitors are COG (NP0) chip capacitors specially designed for "Ultra" low ESR for applications in the communications market. Max ESR and effective capacitance are met on each value producing lot to lot uniformity. Sizes available are EIA chip sizes 0402, 0603, 0805, and 1210.

DIMENSIONS: INCHES (MILLIMETERS)



Size	A	B	C	D	E
0402	0.039±0.004 (1.00±0.1)	0.020±0.004 (0.50±0.1)	0.022 (0.55mm) max	N/A	N/A
0603	0.060±0.010 (1.52±0.25)	0.030±0.010 (0.76±0.25)	0.036 (0.91mm) max	0.010±0.005 (0.25±0.13)	0.030 (0.76) min
0805	0.079±0.008 (2.01±0.2)	0.049±0.008 (1.25±0.2)	0.040±0.005 (1.02±0.127)	0.020±0.010 (0.51±0.255)	0.020 (0.51) min
1210	0.126±0.008 (3.2±0.2)	0.098±0.008 (2.49±0.2)	0.050±0.005 (1.27±0.127)	0.025±0.015 (0.635±0.381)	0.040 (1.02) min

HOW TO ORDER



ELECTRICAL CHARACTERISTICS

Capacitance Values and Tolerances:

Size 0402 - 0.2 pF to 30 pF @ 1 MHz

Size 0603 - 1.0 pF to 100 pF @ 1 MHz

Size 0805 - 1.6 pF to 160 pF @ 1 MHz

Size 1210 - 2.4 pF to 1000 pF @ 1 MHz

Temperature Coefficient of Capacitance (TC):

0±30 ppm/°C (-55° to +125°C)

Insulation Resistance (IR):

10¹² Ω min. @ 25°C and rated WVDC

10¹¹ Ω min. @ 125°C and rated WVDC

Working Voltage (WVDC):

Size Working Voltage

0402 - 100, 50, 25 WVDC

1210 - 200, 100 WVDC

0603 - 200, 100, 50 WVDC

Dielectric Working

0805 - 200, 100 WVDC

Voltage (DWV):

250% of rated WVDC

Equivalent Series Resistance Typical (ESR):

0402 - See Performance Curve, page 13

0603 - See Performance Curve, page 13

0805 - See Performance Curve, page 13

1210 - See Performance Curve, page 13

Marking:

Laser marking EIA J marking standard (except 0603) (capacitance code and tolerance upon request).

Military Specifications

Meets or exceeds the requirements of MIL-C-55681



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

U Dielectric

RF/Microwave C0G (NP0) Capacitors (RoHS)

Ultra Low ESR, "U" Series, C0G (NP0) Chip Capacitors



CAPACITANCE RANGE

Cap (pF)	Available Tolerance	Size			
		0402	0603	0805	1210
0.2	B,C	100V	N/A	N/A	N/A
0.3					
0.4	B,C				
0.5	B,C,D				
0.6					
0.7					
0.8	B,C,D				
0.9					

Cap (pF)	Available Tolerance	Size			
		0402	0603	0805	1210
1.0	B,C,D	100V	200V	200V	200V
1.1					
1.2					
1.3					
1.4					
1.5					
1.6					
1.7					
1.8					
1.9					
2.0					
2.1					
2.2					
2.4					
2.7					
3.0					
3.3					
3.6					
3.9					
4.3					
4.7					
5.1					
5.6					
6.2	B,C,D				
6.8	B,C,J,K,M				


Cap (pF)	Available Tolerance	Size			
		0402	0603	0805	1210
7.5	B,C,J,K,M	100V	200V	200V	200V
8.2					
9.1	B,C,J,K,M				
10	FG,J,K,M	100V	50V		
11					
12					
13					
15					
18					
20					
22					
24					
27					
30					
33					
36					
39					
43					
47					
51					
56					
68					
75					
82					
91					

Cap (pF)	Available Tolerance	Size			
		0402	0603	0805	1210
100	F,G,J,K,M	N/A	100V	50V	
110			50V	N/A	
120			200V	200V	
130					
140					
150					
160					
180					
200					
220					
270					
300					
330					
360					
390					
430					
470					
510					
560					
620					
680					
750					
820					
910					
1000	F,G,J,K,M				




ULTRA LOW ESR, "U" SERIES


TYPICAL ESR vs. FREQUENCY
0402 "U" SERIES




TYPICAL ESR vs. FREQUENCY
0603 "U" SERIES



TYPICAL ESR vs. FREQUENCY
0805 "U" SERIES




TYPICAL ESR vs. FREQUENCY
1210 "U" SERIES



ESR Measured on the Boonton 34A

TYPICAL SERIES RESONANT FREQUENCY "U" SERIES CHIP



U Dielectric

RF/Microwave COG (NP0) Capacitors (Sn/Pb)

Ultra Low ESR, "U" Series, COG (NP0) Chip Capacitors




GENERAL INFORMATION


"U" Series capacitors are COG (NP0) chip capacitors specially designed for "Ultra" low ESR for applications in the communications market. Max ESR and effective capacitance are met on each value producing lot to lot uniformity. Sizes available are EIA chip sizes 0402, 0603, 0805, and 1210.

DIMENSIONS: INCHES (MILLIMETERS)


0402




0603



0805



1210



inches (mm)

Size	A	B	C	D	E
0402	0.039±0.004 (1.00±0.1)	0.020±0.004 (0.50±0.1)	0.022 (0.55mm) max	N/A	N/A
0603	0.060±0.010 (1.52±0.25)	0.030±0.010 (0.76±0.25)	0.036 (0.91mm) max	0.010±0.005 (0.25±0.13)	0.030 (0.76) min
0805	0.079±0.008 (2.01±0.2)	0.049±0.008 (1.25±0.2)	0.040±0.005 (1.02±0.127)	0.020±0.010 (0.51±0.254)	0.020 (0.51) min
1210	0.126±0.008 (3.2±0.2)	0.098±0.008 (2.49±0.2)	0.050±0.005 (1.27±0.127)	0.025±0.015 (0.635±0.381)	0.040 (1.02) min

HOW TO ORDER

LD05

Case Size
LD02 = 0402
LD03 = 0603
LD05 = 0805
LD10 = 1210

1

Voltage Code
3 = 25V
5 = 50V
1 = 100V
2 = 200V

U
Dielectric = Ultra Low ESR

100

Capacitance
EIA Capacitance Code in pF.
First two digits = significant figures or "R" for decimal place.
Third digit = number of zeros or after "R" significant figures.

J
Capacitance Tolerance Code
B = ±0.1pF
C = ±0.25pF
D = ±0.5pF
F = ±1%
G = ±2%
J = ±5%
K = ±10%
M = ±20%

Failure Rate Code
A = Not Applicable

A

Termination
*B = 5% min lead

2

Packaging Code
2 = 7" Reel
4 = 13" Reel

A
Special Code
A = Standard

* Not RoHS Compliant

ELECTRICAL CHARACTERISTICS

Capacitance Values and Tolerances:

Size 0402 - 0.2 pF to 22 pF @ 1 MHz

Size 0603 - 1.0 pF to 100 pF @ 1 MHz

Size 0805 - 1.6 pF to 160 pF @ 1 MHz

Size 1210 - 2.4 pF to 1000 pF @ 1 MHz

Temperature Coefficient of Capacitance (TC):

0±30 ppm/°C (-55° to +125°C)

Insulation Resistance (IR):

10¹² Ω min. @ 25°C and rated WVDC

10¹¹ Ω min. @ 125°C and rated WVDC

Working Voltage (WVDC):

Size Working Voltage

0402 - 50, 25 WVDC

0603 - 200, 100, 50 WVDC

0805 - 200, 100 WVDC

1210 - 200, 100 WVDC

Dielectric Working Voltage (DWV):

250% of rated WVDC

Equivalent Series Resistance Typical (ESR):

0402 - See Performance Curve, page 16

0603 - See Performance Curve, page 16

0805 - See Performance Curve, page 16

1210 - See Performance Curve, page 16

Marking:

Laser marking EIA J marking standard (except 0603) (capacitance code and tolerance upon request).

Military Specifications

Meets or exceeds the requirements of MIL-C-55681

U Dielectric

RF/Microwave C0G (NP0) Capacitors (Sn/Pb)

Ultra Low ESR, "U" Series, C0G (NP0) Chip Capacitors



CAPACITANCE RANGE

Cap (pF)	Available Tolerance	Size			
		LD02	LD03	LD05	LD10
0.2	B,C	50V	N/A	N/A	N/A
0.3					
0.4	B,C				
0.5	B,C,D				
0.6					
0.7					
0.8	B,C,D				
0.9					

Cap (pF)	Available Tolerance	Size			
		LD02	LD03	LD05	LD10
1.0	B,C,D	50V	200V	200V	200V
1.1					
1.2					
1.3					
1.4					
1.5					
1.6					
1.7					
1.8					
1.9					
2.0					
2.1					
2.2					
2.4					
2.7					
3.0					
3.3					
3.6					
3.9					
4.3					
4.7					
5.1					
5.6					
6.2	B,C,D				
6.8	B,C,J,K,M				


Cap (pF)	Available Tolerance	Size			
		LD02	LD03	LD05	LD10
7.5	B,C,J,K,M	50V	200V	200V	200V
8.2					
9.1	B,C,J,K,M				
10	F,G,J,K,M				
11					
12					
13					
15					
18					
20					
22					
24					
27					
30					
33					
36					
39					
43					
47					
51					
56					
68					
75					
82					
91					
910					
1000	F,G,J,K,M				

Cap (pF)	Available Tolerance	Size			
		LD02	LD03	LD05	LD10
100	F,G,J,K,M	N/A	100V	50V	200V
110			50V	N/A	200V
120			100V		200V
130					
140					
150					
160					
180					
200					
220					
270					
300					
330					
360					
390					
430					
470					
510					
560					
620					
680					
750					
820					
910					
1000	F,G,J,K,M				




ULTRA LOW ESR, "U" SERIES


TYPICAL ESR vs. FREQUENCY
0402 "U" SERIES




TYPICAL ESR vs. FREQUENCY
0603 "U" SERIES



TYPICAL ESR vs. FREQUENCY
0805 "U" SERIES



TYPICAL ESR vs. FREQUENCY
1210 "U" SERIES



ESR Measured on the Boonton 34A



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer/ by reference and should be reviewed in full before placing any order.

U Dielectric

RF/Microwave Automotive COG (NP0) Capacitors (RoHS)


AEC Q200 Qualified Ultra Low ESR, "U" Series, COG (NP0) Chip Capacitors



GENERAL INFORMATION


Automotive "U" Series capacitors are COG (NP0) chip capacitors specially designed for "Ultra" low ESR for applications in the automotive market. Max ESR and effective capacitance are met on each value producing lot to lot uniformity. Sizes available are EIA chip sizes 0402 and 0603.

DIMENSIONS: INCHES (MILLIMETERS)



Size	A	B	C	D	E
0402	1.00 \pm 0.1 (0.039 \pm 0.004)	0.50 \pm 0.1 (0.020 \pm 0.004)	0.60 max (0.024)	N/A	N/A
0603	1.52 \pm 0.25 (0.060 \pm 0.010)	0.76 \pm 0.25 (0.030 \pm 0.010)	0.91 max (0.036)	0.25 \pm 0.13 (0.010 \pm 0.005)	0.76 min (0.030)

HOW TO ORDER



ELECTRICAL CHARACTERISTICS

Capacitance Values and Tolerances:

Size 0402 - 0.2 pF to 22 pF @ 1 MHz

Size 0603 - 1.0 pF to 100 pF @ 1 MHz

Temperature Coefficient of Capacitance (TC):

0 \pm 30 ppm/ $^{\circ}$ C (-55 $^{\circ}$ to +125 $^{\circ}$ C)

Insulation Resistance (IR):

10¹² Ω min. @ 25 $^{\circ}$ C and rated WVDC
10¹¹ Ω min. @ 125 $^{\circ}$ C and rated WVDC

Working Voltage (WVDC):

Size Working Voltage
0402 - 50, 25 WVDC
0603 - 200, 100, 50 WVDC

Dielectric Working Voltage (DWV):

250% of rated WVDC

Equivalent Series Resistance Typical (ESR):

0402 - See Performance Curve
0603 - See Performance Curve

Automotive Specifications

Meets or exceeds the requirements of AEC Q200

U Dielectric

RF/Microwave Automotive C0G (NP0) Capacitors (RoHS)

AEC Q200 Qualified, Ultra Low ESR, "U" Series, C0G (NP0) Chip Capacitors



CAPACITANCE RANGE

Cap (pF)	Available Tolerance	Size	
		0402	0603
0.2	B,C	100V	N/A
0.3			
0.4			
0.5	B,C		
0.6	B,C,D		
0.7			
0.8			
0.9	B,C,D		


Cap (pF)	Available Tolerance	Size	
		0402	0603
1.0	B,C,D	100V	200V
1.1			
1.2			
1.3			
1.4			
1.5			
1.6			
1.7			
1.8			
1.9			
2.0			
2.1			
2.2			
2.4			
2.7			
3.0			
3.3			
3.6			
3.9			
4.3			
4.7			
5.1			
5.6			
6.2	B,C,D		
6.8	B,C,J,K,M		

Cap (pF)	Available Tolerance	Size	
		0402	0603
7.5	B,C,J,K,M	100V	200V
8.2			
9.1	B,C,J,K,M		
10	F,G,J,K,M		
11			
12			
13			
15			
18			
20			
22			
24			
27			
30		50V	N/A
33			
36			
39			
43			
47			
51			
56			
68			
75			
82			
91			


Cap (pF)	Available Tolerance	Size	
		0402	0603
100	F,G,J,K,M	N/A	100V
110			50V
120			50V
130			N/A
140			
150			
160			
180			
200			
220			
270			
300			
330			
360			
390			
430			
470			
510			
560			
620			
680			
750			
820			
910			
1000	F,G,J,K,M		

ULTRA LOW ESR, "U" SERIES


**TYPICAL ESR vs. FREQUENCY
0402 "U" SERIES**



**TYPICAL ESR vs. FREQUENCY
0603 "U" SERIES**



**TYPICAL SERIES RESONANT FREQUENCY
"U" SERIES CHIP**



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

U Dielectric Designer Kits

Communication Kits "U" Series



"U" SERIES KITS

0402

Kit 5000 UZ			
Cap. Value pF	Tolerance	Cap. Value pF	Tolerance
0.5	B ($\pm 0.1\text{pF}$)	4.7	B ($\pm 0.1\text{pF}$)
1.0		5.6	
1.5		6.8	
1.8		8.2	
2.2		10.0	
2.4		12.0	
3.0		15.0	
3.6			($\pm 5\%$)

***25 each of 15 values

0603

Kit 4000 UZ			
Cap. Value pF	Tolerance	Cap. Value pF	Tolerance
1.0	B ($\pm 0.1\text{pF}$)	6.8	B ($\pm 0.1\text{pF}$)
1.2		7.5	
1.5		8.2	
1.8		10.0	
2.0		12.0	
2.4		15.0	
2.7		18.0	
3.0		22.0	
3.3		27.0	
3.9		33.0	
4.7		39.0	
5.6		47.0	

***25 each of 24 values

0805

Kit 3000 UZ			
Cap. Value pF	Tolerance	Cap. Value pF	Tolerance
1.0	B ($\pm 0.1\text{pF}$)	15.0	J ($\pm 5\%$)
1.5		18.0	
2.2		22.0	
2.4		24.0	
2.7		27.0	
3.0		33.0	
3.3		36.0	
3.9		39.0	
4.7		47.0	
5.6		56.0	
7.5		68.0	
8.2		82.0	
9.1		100.0	
10.0	J ($\pm 5\%$)	130.0	
12.0		160.0	

***25 each of 30 values

1210

Kit 3500 UZ			
Cap. Value pF	Tolerance	Cap. Value pF	Tolerance
2.2	B ($\pm 0.1\text{pF}$)	36.0	J ($\pm 5\%$)
2.7		39.0	
4.7		47.0	
5.1		51.0	
6.8		56.0	
8.2		68.0	
9.1		82.0	
10.0		100.0	
13.0		120.0	
15.0		130.0	
18.0		240.0	
20.0		300.0	
24.0		390.0	
27.0		470.0	
30.0		680.0	

***25 each of 30 values

X8R/X8L Dielectric

General Specifications



AVX has developed a range of multilayer ceramic capacitors designed for use in applications up to 150°C. These capacitors are manufactured with an X8R and an X8L dielectric material. X8R material has capacitance variation of $\pm 15\%$ between -55°C and +150°C. The X8L material has capacitance variation of $\pm 15\%$ between -55°C to 125°C to 125°C and +15/40% from +125°C to +150°C.

The need for X8R and X8L performance has been driven by customer requirements for parts that operate at elevated temperatures. They provide a highly reliable capacitor with low loss and stable capacitance over temperature.

They are ideal for automotive under the hood sensors, and various industrial applications. Typical industrial application would be drilling monitoring system. They can also be used as bulk capacitors for high temperature camera modules.

Both X8R and X8L dielectric capacitors are automotive AEC-Q200 qualified. Optional termination systems, tin, FLEXITERM® and conductive epoxy for hybrid applications are available. Providing this series with our FLEXITERM® termination system provides further advantage to customers by way of enhanced resistance to both, temperature cycling and mechanical damage.

0805	5	A	104	K	4	T	2	A
Size	Voltage	Dielectric	Capacitance Code (in pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
0402	10V = Z	X8R = F		J = $\pm 5\%$	4=Automotive	T = Plated Ni and Sn	2 = 7" Reel	A = Std. Product
0603	16V = Y	X8L = L	2 Sig. Digits + Number of Zeros	K = $\pm 10\%$	A = Not Applicable	Z = FLEXITERM®**	4 = 13" Reel	
0805	25V = 3		e.g. 10 F = 106	M = $\pm 20\%$				
1206	50V = 5							
	100V = 1							

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

X8R

Size	0603		0805		1206		
	Soldering		Reflow/Wave	Reflow/Wave	Reflow/Wave	Reflow/Wave	
	WVDC	25V	50V	25V	50V	25V	50V
271	Cap	G	G				
331	(pF)	G	G	J	J		
471		G	G	J	J		
681		G	G	J	J		
102		G	G	J	J	J	J
152		G	G	J	J	J	J
222		G	G	J	J	J	J
332		G	G	J	J	J	J
472		G	G	J	J	J	J
682		G	G	J	J	J	J
103	Cap	G	G	J	J	J	J
153	(μ F)	G	G	J	J	J	J
223		G	G	J	J	J	J
333		G	G	J	J	J	J
473		G	G	J	J	J	J
683		G	G	J	J	J	J
104	0.01	G	G	N	M	M	M
154	0.15		N	N	M	M	M
224	0.22		N		M	M	M
334	0.33				M	M	M
474	0.47				M	M	M
684	0.68						
105	1						
155	1.5						
225	2.2						
	WVDC	25V	50V	25V	50V	25V	50V
	SIZE	0603	0805	1206			

Size	0603			0805			1206			1210		
	Soldering			Reflow/Wave			Reflow/Wave			Reflow/Wave		
	WVDC	25V	50V	100V	25V	50V	100V	16V	25V	50V	100V	10V
271	Cap	G	G									
331	(pF)	G	G	J	J	J						
471		G	G	J	J	J						
681		G	G	J	J	J						
102		G	G	J	J	J	J	J	J	J	J	J
152		G	G	J	J	J	J	J	J	J	J	J
182		G	G	J	J	J	J	J	J	J	J	J
222		G	G	J	J	J	J	J	J	J	J	J
272		G	G	J	J	J	J	J	J	J	J	J
332		G	G	J	J	J	J	J	J	J	J	J
392		G	G	J	J	J	J	J	J	J	J	J
472		G	G	J	J	J	J	J	J	J	J	J
562		G	G	J	J	J	J	J	J	J	J	J
682		G	G	J	J	J	J	J	J	J	J	J
822		G	G	J	J	J	J	J	J	J	J	J
103	Cap	G	G	J	J	J	J	J	J	J	J	J
123	(μ F)	0.012	G	G	J	J	J	J	J	J	J	J
153	0.015	G	G	J	J	J	J	J	J	J	J	J
183	0.018	G	G	J	J	J	J	J	J	J	J	J
223	0.022	G	G	J	J	J	J	J	J	J	J	J
273	0.027	G	G	J	J	J	J	J	J	J	J	J
333	0.033	G	G	J	J	N	J	J	J	J	J	J
393	0.039	G	G	J	J	N	J	J	J	J	J	J
473	0.047	G	G	J	J	N	J	J	J	J	J	J
563	0.056	G	G	J	J	N	J	J	J	J	J	J
683	0.068	G	G	J	J	N	J	J	J	J	J	J
823	0.082	G	G	J	J	N	J	J	J	J	J	J
104	0.1	G	G	J	J	N	J	J	M	J	J	M
124	0.12									J	J	M
154	0.15									J	J	Q
184	0.18									J	J	Q
224	0.22									J	J	Q
274	0.27									J	M	M
334	0.33									J	M	M
394	0.39									M	M	P
474	0.47									M	M	P
684	0.68									M	M	P
824	0.82									M	M	P
105	1									M	M	P
155	1.5									M	M	Z
225	2.2									M	M	Z
475										Z	Z	
106												
	WVDC	25V	50V	100V	25V	50V	100V	16V	25V	50V	100V	10V
	SIZE	0603	0805	1206								1210

= AEC-Q200 Qualified

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33	0.56	0.71	0.9	0.94	1.02	1.27	1.4	1.52	1.78	2.29	2.54	2.79
	(-0.013)	(-0.022)	(-0.028)	(-0.035)	(-0.037)	(-0.04)	(-0.05)	(-0.055)	(-0.06)	(-0.07)	(-0.09)	(-0.1)	(-0.11)
	PAPER												
	EMBOSSDED												




The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

X8R/X8L Dielectric

General Specifications

APPLICATIONS FOR X8R AND X8L CAPACITORS

- All market sectors with a 150°C requirement
- Automotive on engine applications
- Oil exploration applications
- Hybrid automotive applications
 - Battery control
 - Inverter / converter circuits
 - Motor control applications
 - Water pump
- Hybrid commercial applications
 - Emergency circuits
 - Sensors
 - Temperature regulation




ADVANTAGES OF X8R AND X8L MLC CAPACITORS

- Both ranges are qualified to the highest automotive AEC-Q200 standards
- Excellent reliability compared to other capacitor technologies
- RoHS compliant
- Low ESR / ESL compared to other technologies
- Tin solder finish
- FLEXITERM® available
- Epoxy termination for hybrid available
- 100V range available


ENGINEERING TOOLS FOR HIGH VOLTAGE MLC CAPACITORS

- Samples
- Technical Articles
- Application Engineering
- Application Support




X8R/X8L Dielectric

Specifications and Test Methods

Parameter/Test	X8R/X8L Specification Limits		Measuring Conditions	
Operating Temperature Range	-55°C to +150°C		Temperature Cycle Chamber	
Capacitance	Within specified tolerance		Freq.: 1.0 kHz ± 10% Voltage: 1.0Vrms ± .2V	
Dissipation Factor	≤ 2.5% for ≥ 50V DC rating ≤ 3.5% for 25V DC and 16V DC rating			
Insulation Resistance	100,000MΩ or 1000MΩ - µF, whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity	
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.	
Resistance to Flexure Stresses	Appearance	No defects	Deflection: 2mm Test Time: 30 seconds 1mm/sec 	
	Capacitance Variation	≤ ±12%		
	Dissipation Factor	Meets Initial Values (As Above)		
	Insulation Resistance	≥ Initial Value x 0.3		
Solderability	≥ 95% of each terminal should be covered with fresh solder		Dip device in eutectic solder at 230 ± 5°C for 5.0 ± 0.5 seconds	
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal	Dip device in eutectic solder at 260°C for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	≤ ±7.5%		
	Dissipation Factor	Meets Initial Values (As Above)		
	Insulation Resistance	Meets Initial Values (As Above)		
	Dielectric Strength	Meets Initial Values (As Above)		
Thermal Shock	Appearance	No visual defects	Step 1: -55°C ± 2°	30 ± 3 minutes
	Capacitance Variation	≤ ±7.5%	Step 2: Room Temp	≤ 3 minutes
	Dissipation Factor	Meets Initial Values (As Above)	Step 3: +125°C ± 2°	30 ± 3 minutes
	Insulation Resistance	Meets Initial Values (As Above)	Step 4: Room Temp	≤ 3 minutes
	Dielectric Strength	Meets Initial Values (As Above)	Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects	Charge device with 1.5 rated voltage (≤ 10V) in test chamber set at 150°C ± 2°C for 1000 hours (+48, -0) Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.	
	Capacitance Variation	≤ ±12.5%		
	Dissipation Factor	≤ Initial Value x 2.0 (See Above)		
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)		
	Dielectric Strength	Meets Initial Values (As Above)		
Load Humidity	Appearance	No visual defects	Store in a test chamber set at 85°C ± 2°C/ 85% ± 5% relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature and humidity for 24 ± 2 hours before measuring..	
	Capacitance Variation	≤ ±12.5%		
	Dissipation Factor	≤ Initial Value x 2.0 (See Above)		
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)		
	Dielectric Strength	Meets Initial Values (As Above)		

X7R Dielectric

General Specifications



X7R formulations are called "temperature stable" ceramics and fall into EIA Class II materials. X7R is the most popular of these intermediate dielectric constant materials. Its temperature variation of capacitance is within $\pm 15\%$ from -55°C to $+125^\circ\text{C}$. This capacitance change is non-linear.

Capacitance for X7R varies under the influence of electrical operating conditions such as voltage and frequency.







X7R dielectric chip usage covers the broad spectrum of industrial applications where known changes in capacitance due to applied voltages are acceptable.



PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)

0805	5	C	103	M	A	T	2	A
Size (L" x W")	Voltage 4V = 4 6.3V = 6 10V = Z 16V = Y 25V = 3 50V = 5 100V = 1 200V = 2 500V = 7	Dielectric X7R = C	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance J = $\pm 5\%$ * K = $\pm 10\%$ M = $\pm 20\%$	Failure Rate A = Not Applicable	Terminations T = Plated Ni and Sn Z = FLEXITERM®**	Packaging 2 = 7" Reel 4 = 13" Reel	Special Code A = Std. Product
				* $\leq 1\mu\text{F}$ only, contact factory for additional values		**See FLEXITERM® X7R section		Contact Factory For Multiples

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.
Contact factory for non-specified capacitance values.



X7R Dielectric



Specifications and Test Methods

Parameter/Test	X7R Specification Limits		Measuring Conditions	
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber	
Capacitance	Within specified tolerance			
Dissipation Factor	$\leq 10\%$ for $\geq 50V$ DC rating $\leq 12.5\%$ for 25V and 16V DC rating $\leq 12.5\%$ for $\leq 10V$ DC rating Contact Factory for DF by PN		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm .2V$ For Cap $> 10\mu F$, 0.5Vrm @ 120Hz	
Insulation Resistance	100,000MΩ or 1000MΩ - μF , whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity	
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.	
Resistance to Flexure Stresses	Appearance	No defects	Deflection: 2mm Test Time: 30 seconds	
	Capacitance Variation	$\leq \pm 12\%$		
	Dissipation Factor	Meets Initial Values (As Above)		
	Insulation Resistance	\geq Initial Value $\times 0.3$		
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at $230 \pm 5^\circ C$ for 5.0 ± 0.5 seconds	
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal	Dip device in eutectic solder at $260^\circ C$ for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	$\leq \pm 7.5\%$		
	Dissipation Factor	Meets Initial Values (As Above)		
	Insulation Resistance	Meets Initial Values (As Above)		
	Dielectric Strength	Meets Initial Values (As Above)		
Thermal Shock	Appearance	No visual defects	Step 1: $-55^\circ C \pm 2^\circ$	30 ± 3 minutes
	Capacitance Variation	$\leq \pm 7.5\%$	Step 2: Room Temp	≤ 3 minutes
	Dissipation Factor	Meets Initial Values (As Above)	Step 3: $+125^\circ C \pm 2^\circ$	30 ± 3 minutes
	Insulation Resistance	Meets Initial Values (As Above)	Step 4: Room Temp	≤ 3 minutes
	Dielectric Strength	Meets Initial Values (As Above)	Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects	Charge device with 1.5 rated voltage ($\leq 10V$) in test chamber set at $125^\circ C \pm 2^\circ C$ for 1000 hours (+48, -0) If $RV > 10V$ then Life Test voltage will be $2 \times RV$ but there are exceptions (please contact AVX for further details on exceptions)	
	Capacitance Variation	$\leq \pm 12.5\%$		
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)		
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)		
	Dielectric Strength	Meets Initial Values (As Above)		
Load Humidity	Appearance	No visual defects	Store in a test chamber set at $85^\circ C \pm 2^\circ C / 85\% \pm 5\%$ relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature and humidity for 24 ± 2 hours before measuring.	
	Capacitance Variation	$\leq \pm 12.5\%$		
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)		
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)		
	Dielectric Strength	Meets Initial Values (As Above)		



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

X7R Dielectric

Capacitance Range



PREFERRED SIZES ARE SHADED

SIZE		0101*		0201		0402		0603		0805		1206	
Soldering		Reflow Only		Reflow Only		Reflow/Wave		Reflow/Wave		Reflow/Wave		Reflow/Wave	
Packaging		Paper/Embossed		All Paper		All Paper		All Paper		Paper/Embossed		Paper/Embossed	
(L) Length (in.)	mm (in.)	0.40 ± 0.02 (0.016 ± 0.0008)	0.60 ± 0.09 (0.024 ± 0.004)	1.00 ± 0.10 (0.040 ± 0.004)	1.60 ± 0.15 (0.063 ± 0.006)	2.01 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.30 (0.126 ± 0.012)						
W) Width (in.)	mm (in.)	0.20 ± 0.02 (0.008 ± 0.0008)	0.30 ± 0.09 (0.011 ± 0.004)	0.50 ± 0.10 (0.020 ± 0.006)	0.81 ± 0.15 (0.032 ± 0.006)	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.30 (0.063 ± 0.012)						
(t) Terminal (in.)	mm (in.)	0.10 ± 0.04 (0.004 ± 0.0016)	0.15 ± 0.05 (0.006 ± 0.002)	0.25 ± 0.15 (0.010 ± 0.006)	0.35 ± 0.15 (0.014 ± 0.006)	0.50 ± 0.25 (0.020 ± 0.010)	0.50 ± 0.25 (0.020 ± 0.010)						
WVDC		16	6.3 10 16 25 50	6.3 10 16 25 50 100	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	500
Cap 100 101 (pF)	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N N
150 151	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N N
220 221	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N P
330 331	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N P
470 471	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N P
680 681	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N P
1000 102	B	A A A A	A C C C	C C C C	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	G G G G	N N N P
1500 152	A A A A	C C C C C C	C G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N P
2200 222	A A A A	C C C C C C	C G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N P
3300 332	A A A A	C C C C C C	C G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N P
3900 392	A A A A												
4700 472	A A A A	C C C C C C	C G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N P
5600 562	A A A A												
6800 682	A A A A	C C C C C C	C G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N P
Cap 0.01 103 (μF)	A A A A	C C C C C C	C G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N P
0.012 123													
0.015 153		C C C C E	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	N N N Q
0.018 183													
0.022 223	A A A	C C C C E	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	P P P Q
0.027 273													
0.033 333		C C C C E	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	Q Q Q
0.039 393													
0.047 473		C C C C E	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	Q Q Q
0.068 683		C C C C E	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	P Q Q
0.082 823													
0.1 104	A	C C C C E	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	G G G G G G	P Q Q
0.12 124													
0.15 154													
0.22 224		C C C C C	G G J J J	G G J J J	G G J J J	G G J J J	G G J J J	G G J J J	G G J J J	G G J J J	G G J J J	G G J J J	K K K K K Q Q Q
0.33 334													
0.47 474		C C	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	M M M M M X X
0.68 684													
1.0 105		C	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	J J J J J	M M M M M X X
2.2 225													
4.7 475					K								
10 106													
22 226													
47 476													
100 107													
WVDC	16	6.3 10 16 25 50	6.3 10 16 25 50 100	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	6.3 10 16 25 50 100 200 250	500
SIZE	0101*	0201	0402	0603	0805	0805	0805	0805	0805	0805	0805	0805	1206

Letter	A	B	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.22 (0.009)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER													EMBOSSED	

NOTE: Contact factory for non-specified capacitance values

*EIA 01005


**Contact Factory for Specifications

X7R Dielectric Capacitance Range



PREFERRED SIZES ARE SHAPED


SIZE	1210					1812					1825			2220					2225					
Soldering	Reflow Only					Reflow Only					Reflow Only			Reflow Only					Reflow Only					
Packaging	Paper/Embossed					All Embossed					All Embossed			All Embossed					All Embossed					
(L) Length	mm (in.)	3.30 ± 0.4 (0.130 ± 0.016)					4.50 ± 0.40 (0.177 ± 0.016)					4.50 ± 0.40 (0.177 ± 0.016)			5.70 ± 0.50 (0.224 ± 0.020)					5.70 ± 0.40 (0.224 ± 0.016)				
W) Width	mm (in.)	2.50 ± 0.30 (0.098 ± 0.012)					3.20 ± 0.40 (0.126 ± 0.016)					6.40 ± 0.40 (0.252 ± 0.016)			5.00 ± 0.40 (0.197 ± 0.016)					6.30 ± 0.40 (0.248 ± 0.016)				
(t) Terminal	mm (in.)	0.50 ± 0.25 (0.020 ± 0.010)					0.61 ± 0.36 (0.024 ± 0.014)					0.61 ± 0.36 (0.024 ± 0.014)			0.64 ± 0.39 (0.025 ± 0.015)					0.64 ± 0.39 (0.025 ± 0.015)				
WVDC	10	16	25	50	100	200	500	16	25	50	100	200	500	50	100	200	25	50	100	200	500	50	100	200
Cap	100	101																						
(pF)	150	151																						
	220	221		K	K	K	M																	
	330	331		K	K	K	M			N	N	N	N											
	470	471		K	K	K	M			N	N	N	N											
	680	681		K	K	K	M			N	N	N	N											
	1000	102	K	K	K	K	M	N	N	N	N	N	N	X	X	X	X	X	X	X	X	X	X	
	1500	152	K	K	K	K	M	N	N	N	N	N	N	X	X	X	X	X	X	X	X	X	X	
	2200	222	K	K	K	K	M	N	N	N	N	N	N	X	X	X	X	X	X	X	X	X	X	
	3300	332	K	K	K	K	P	N	N	N	N	N	N	X	X	X	X	X	X	X	X	X	X	
	4700	472	K	K	K	K	P	N	N	N	N	N	P	X	X	X	X	X	X	X	X	X	X	
	6800	682	K	K	K	K	P	N	N	N	N	N	P	X	X	X	X	X	X	X	X	X	X	
Cap	0.01	103	K	K	K	K	P	N	N	N	N	N	P	X	X	X	X	X	X	X	X	X	X	
(μF)	0.015	153	K	K	K	K	P	N	N	N	N	N	P	X	X	X	X	X	X	X	X	X	X	
	0.022	223	K	K	K	K	P	Q	N	N	N	N	N	P	X	X	X	X	X	X	X	X	X	
	0.033	333	K	K	K	K	P	X	N	N	N	N	N	X	X	X	X	X	X	X	X	X	X	
	0.047	473	K	K	K	K	P	X	N	N	N	N	P	X	X	X	X	X	X	X	X	X	X	
	0.068	683	K	K	K	K	P	X	N	N	N	N	P	X	X	X	X	X	X	X	X	X	X	
	0.1	104	K	K	K	K	P	X	N	N	N	N	P	P	X	X	X	X	X	X	X	X	X	
	0.15	154	K	K	K	M	P	Z	Z	N	N	N	P	P	Z	X	X	X	X	X	X	X	X	
	0.22	224	K	K	K	M	P	Z		N	N	N	P	Q	Z	X	X	X	X	X	X	X	X	
	0.33	334	K	K	K	M	Q	Z		N	N	N	P	X	Z	X	X	X	X	X	X	X	X	
	0.47	474	M	M	M	P	Q	Z		N	N	N	Q	X	Z	X	X	X	X	X	X	X	X	
	0.68	684	M	M	P	X	X	Z		Q	Q	Q	Q	Z		X	X	X	X	X	X	X	X	
	1.0	105	P	P	P	X	Z		Q	Q	Q	Q	X	Z		X	X	X	X	X	X	X	X	
	1.5	155	N	N	Z	Z	Z			Z	Z	Z				X	X	Z	X	X	Z	X	Z	
	2.2	225	X	X	Z	Z	Z			Z	Z	Z				X	X	Z	X	X	Z	X	Z	
	3.3	335	X	X	Z	Z	Z			Z	Z	Z				X	X		X	Z		X	X	
	4.7	475	Z	Z	Z	Z	Z			Z	Z	Z				X	X		Z	Z		X	X	
	10	106	Z	Z	Z	Z				Z	Z	Z				Z	Z		Z	Z		Z	Z	
	22	226	Z	Z	Z											Z								
	47	476	Z																					
	100	107																						
WVDC	10	16	25	50	100	200	500	16	25	50	100	200	500	50	100	200	25	50	100	200	500	50	100	200
SIZE	1210					1812					1825			2220					2225			2225		



NOTE: Contact factory for non-specified capacitance values.

X7S Dielectric

General Specifications



GENERAL DESCRIPTION

X7S formulations are called "temperature stable" ceramics and fall into EIA Class II materials. Its temperature variation of capacitances within $\pm 22\%$ from -55°C to $+125^\circ\text{C}$. This capacitance change is non-linear.

Capacitance for X7S varies under the influence of electrical operating conditions such as voltage and frequency.

X7S dielectric chip usage covers the broad spectrum of industrial applications where known changes in capacitance due to applied voltages are acceptable.







PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)

1206	Z	Z	105	M	A	T	2	A
Size (L" x W")	Voltage 4 = 4V 6 = 6.3V Z = 10V Y = 16V 3 = 25V 5 = 50V 1 = 100V 2 = 200V	Dielectric Z = X7S	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance K = $\pm 10\%$ M = $\pm 20\%$	Failure Rate A = N/A	Terminations T = Plated Ni and Sn	Packaging 2 = 7" Reel 4 = 13" Reel	Special Code A = Std. Product

NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers.




TYPICAL ELECTRICAL CHARACTERISTICS



X7S Dielectric

Specifications and Test Methods

Parameter/Test	X7S Specification Limits		Measuring Conditions		
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance				
Dissipation Factor	$\leq 5.0\%$ for $\geq 100V$ DC rating $\leq 5.0\%$ for $\geq 25V$ DC rating $\leq 10.0\%$ for $\geq 10V$ DC rating $\leq 10.0\%$ for $\leq 10V$ DC rating Contact Factory for DF by PN		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm .2V$ For Cap $> 10 \mu F$, 0.5Vrms @ 120Hz		
Insulation Resistance	100,000MΩ or 1000MΩ - μF , whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max)		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	$\leq \pm 12\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$			
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at 230 $\pm 5^\circ C$ for 5.0 ± 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal		Dip device in eutectic solder at 260°C for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	$\leq \pm 7.5\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: -55°C $\pm 2^\circ$	
	Capacitance Variation	$\leq \pm 7.5\%$		Step 2: Room Temp	
	Dissipation Factor	Meets Initial Values (As Above)		Step 3: +125°C $\pm 2^\circ$	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with 1.5 rated voltage ($\leq 10V$) in test chamber set at 125°C $\pm 2^\circ C$ for 1000 hours (+48, -0)	
	Capacitance Variation	$\leq \pm 12.5\%$			
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.	
	Capacitance Variation	$\leq \pm 12.5\%$			
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			


X7S Dielectric

Capacitance Range



PREFERRED SIZES ARE SHADED

SIZE	0402	0603	0805	1206	1210
Soldering	Reflow/Wave		Reflow/Wave	Reflow/Wave	Reflow Only
Packaging	All Paper		All Paper	Paper/Embossed	Paper/Embossed
(L) Length (in.)	1.00 ± 0.10 (0.040 ± 0.004)	1.60 ± 0.15 (0.063 ± 0.006)	2.01 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)
W) Width (in.)	0.50 ± 0.10 (0.020 ± 0.004)	0.81 ± 0.15 (0.032 ± 0.006)	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	2.50 ± 0.20 (0.098 ± 0.008)
(t) Terminal (in.)	0.25 ± 0.15 (0.010 ± 0.006)	0.35 ± 0.15 (0.014 ± 0.006)	0.50 ± 0.25 (0.020 ± 0.010)	0.50 ± 0.25 (0.020 ± 0.010)	0.50 ± 0.25 (0.020 ± 0.010)
WVDC	4	6.3	6.3	4	10 50 100 6.3
Cap (pF)	100				
	150				
	220				
	330				
	470				
	680				
	1000				
	1500				
	2200				
	3300				
	4700				
	6800				
Cap (μF)	0.010				
	0.015				
	0.022				
	0.033	C			
	0.047	C			
	0.068	C			
	0.10	C			
	0.15				
	0.22				
	0.33		G		
	0.47		G		
	0.68		G		
	1.0		G		
	1.5			N	
	2.2	E		N	
	3.3			N	
	4.7			N	Q
	10				Q*
	22				
	47				
	100				
WVDC		6.3	6.3	4	10 50 100 6.3
SIZE	0402	0603	0805	1206	1210




Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.90 (0.075)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER					EMBOSSED								

*Contact Factory for Specifications

X5R Dielectric

General Specifications



GENERAL DESCRIPTION

- General Purpose Dielectric for Ceramic Capacitors
- EIA Class II Dielectric
- Temperature variation of capacitance is within $\pm 15\%$ from -55°C to $+85^{\circ}\text{C}$
- Well suited for decoupling and filtering applications
- Available in High Capacitance values (up to $100\mu\text{F}$)

PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)



1210	4	D	107	M	A	T	2	A
Size (L" x W")	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
0101**	4 = 4V	D = X5R	2 Sig. Digits + Number of Zeros	K = $\pm 10\%$ M = $\pm 20\%$	A = N/A	T = Plated Ni and Sn	2 = 7" Reel 4 = 13" Reel U = 4mm TR (01005)	A = Std.
0201	6 = 6.3V							
0402	Z = 10V							
0603	Y = 16V							
0805	3 = 25V							
1206	D = 35V							
1210	5 = 50V							
1812	1 = 100V							

**EIA 01005




NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers.
Contact factory for non-specified capacitance values.

TYPICAL ELECTRICAL CHARACTERISTICS



X5R Dielectric

Specifications and Test Methods

Parameter/Test	X5R Specification Limits		Measuring Conditions		
Operating Temperature Range	-55°C to +85°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance				
Dissipation Factor	$\leq 2.5\%$ for $\geq 50V$ DC rating $\leq 12.5\%$ for 25V, 35V DC rating $\leq 12.5\%$ Max. for 16V DC rating and lower Contact Factory for DF by PN		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm 2V$ For Cap $> 10 \mu F$, 0.5Vrms @ 120Hz		
Insulation Resistance	10,000MΩ or 500MΩ - μF , whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max)		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	$\leq \pm 12\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$			
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at $230 \pm 5^\circ C$ for 5.0 ± 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal		Dip device in eutectic solder at $260^\circ C$ for 60seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	$\leq \pm 7.5\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: $-55^\circ C \pm 2^\circ$ 30 ± 3 minutes	
	Capacitance Variation	$\leq \pm 7.5\%$		Step 2: Room Temp ≤ 3 minutes	
	Dissipation Factor	Meets Initial Values (As Above)		Step 3: $+85^\circ C \pm 2^\circ$ 30 ± 3 minutes	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp ≤ 3 minutes	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with 1.5X rated voltage in test chamber set at $85^\circ C \pm 2^\circ C$ for 1000 hours (+48, -0). Note: Contact factory for *optional specification part numbers that are tested at < 1.5X rated voltage. Remove from test chamber and stabilize at room temperature for 24 ± 2 hours	
	Capacitance Variation	$\leq \pm 12.5\%$			
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Store in a test chamber set at $85^\circ C \pm 2^\circ C / 85\% \pm 5\%$ relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature and humidity for 24 ± 2 hours before measuring.	
	Capacitance Variation	$\leq \pm 12.5\%$			
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			

X5R Dielectric

Capacitance Range



PREFERRED SIZES ARE SHADED

Case Size	0101*			0201				0402					0603					0805									
Soldering	Reflow Only			Reflow Only				Reflow/Wave					Reflow/Wfeve					Reflow/Wfeve									
Packaging	Paper/Embossed			All Paper				All Paper					All Paper					Paper/Embossed									
(L) Length (in.)	mm 0.40 ± 0.02 (0.016 ± 0.0008)			mm 0.60 ± 0.09 (0.024 ± 0.004)				mm 1.00 ± 0.20 (0.040 ± 0.008)					mm 1.60 ± 0.15 (0.063 ± 0.006)					mm 2.01 ± 0.20 (0.079 ± 0.008)									
(W) Width (in.)	mm 0.20 ± 0.02 (0.008 ± 0.0008)			mm 0.30 ± 0.09 (0.011 ± 0.004)				mm 0.50 ± 0.20 (0.020 ± 0.008)					mm 0.81 ± 0.15 (0.032 ± 0.006)					mm 1.25 ± 0.20 (0.049 ± 0.008)									
(t) Terminal (in.)	mm 0.10 ± 0.04 (0.004 ± 0.0016)			mm 0.15 ± 0.05 (0.006 ± 0.002)				mm 0.25 ± 0.15 (0.010 ± 0.006)					mm 0.35 ± 0.15 (0.014 ± 0.006)					mm 0.50 ± 0.25 (0.020 ± 0.010)									
Voltage:	6.3	10	4	6.3	10	16	25	4	6.3	10	16	25	50	4	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50
Cap (pF)	100	101		B				A																			
	150	151		B				A																			
	220	221		B				A								C											
	330	331		B				A								C											
	470	471		B				A								C											
	680	681		B				A								C											
	1000	102		B				A	A							C											
	1500	152	B	B				A	A	A						C											
	2200	222	B	B				A	A	A						C											
	3300	332	B	B				A	A	A						C											
	4700	472	B	B				A	A	A						C											
	6800	682	B	B				A	A	A						C											
Cap (μF)	0.01	103	B	B				A	A	A						C											
	0.015	150	B													C											
	0.022	223	B					A	A	A	A					C	C									N	
	0.033	333	B													C											N
	0.047	473	B					A	A	A	A					C	C									N	
	0.068	689	B													C										N	
	0.1	104	B					A	A	A	A					C	C	C	C							N N N	
	0.15	154																									N N
	0.22	224	B					A	A	A						C	C	C	C							N N N	
	0.33	334																									N
	0.47	474	B					A	A							C	C	C	C	E						P P	
	0.68	684																									N
	1.0	105						A	A	C	C					C	C	C	C	C						P P	
	1.5	155																									
	2.2	225						C	C	C						C	C	C	C	C						P P	
	3.3	335																									N N P P
	4.7	475						C	C							E	E	E	E							N P J N N P P	
	10	106														E	E	E									P P P P P P
	22	226														E	G										P P P P P P
	47	476																									
	100	107																									
Voltage:	6.3	10	4	6.3	10	16	25	4	6.3	10	16	25	50	4	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50
Case Size	0101*			0201				0402					0603					0805									

Letter	A	B	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.22 (0.009)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
	PAPER													

PAPER and EMBOSSED available for 01005

NOTE: Contact factory for non-specified capacitance values

*EIA 01005



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

X5R Dielectric

Capacitance Range



PREFERRED SIZES ARE SHADED

Case Size	1206							1210							1812							
Soldering	Reflow/Wave							Reflow Only							Reflow Only							
Packaging	Paper/Embossed							Paper/Embossed							All Embossed							
(L) Length	mm (in.)	3.20 ± 0.40 (0.126 ± 0.016)							3.20 ± 0.40 (0.126 ± 0.016)							4.50 ± 0.30 (0.177 ± 0.012)						
W) Width	mm (in.)	1.60 ± 0.30 (0.063 ± 0.012)							2.50 ± 0.30 (0.098 ± 0.012)							3.20 ± 0.20 (0.126 ± 0.008)						
(t) Terminal	mm (in.)	0.50 ± 0.25 (0.020 ± 0.010)							0.50 ± 0.25 (0.020 ± 0.010)							0.61 ± 0.36 (0.024 ± 0.014)						
Voltage:	4	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50	
Cap (pF)	100	101																				
	150	151																				
	220	221																				
	330	331																				
	470	471																				
	680	681																				
	1000	102																				
	1500	152																				
	2200	222																				
	3300	332																				
	4700	472																				
	6800	682																				
Cap (μF)	0.01	103																				
	0.015	150																				
	0.022	223																				
	0.033	333																				
	0.047	473																				
	0.068	689																				
	0.1	104																				
	0.15	154																				
	0.22	224																				
	0.33	334																				
	0.47	474																				
	0.68	684																				
	1.0	105																				
	1.5	155																				
	2.2	225																				
	3.3	335																				
	4.7	475	X	X	X	X	X	X	X							Z	Z	Z	Z	Z	Z	Z
	10	106	X	X	X	X	X	X	X							X	X	Z	Z	Z	Z	Z
	22	226	X	X	X	X	X									Z	Z	Z	Z	Z	Z	Z
	47	476	X	X	X	X										Z	Z	Z	Z	Z	Z	Z
	100	107	X	X												Z	Z					
Voltage:	4	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50	
Case Size	1206							1210							1812							


Letter	A	B	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.22 (0.009)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER													EMBOSSED	

PAPER and EMBOSSED available for 01005

NOTE: Contact factory for non-specified capacitance values
*EIA 01005

Y5V Dielectric

General Specifications









GENERAL DESCRIPTION

Y5V formulations are for general-purpose use in a limited temperature range. They have a wide temperature characteristic of +22% -82% capacitance change over the operating temperature range of -30°C to +85°C. These characteristics make Y5V ideal for decoupling applications within limited temperature range.




PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)

0805	3	G	104	Z	A	T	2	A
Size (L" x W")	Voltage 6.3V = 6 10V = Z 16V = Y 25V = 3 50V = 5	Dielectric Y5V = G	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance Z = +80 -20%	Failure Rate A = Not Applicable	Terminations T = Plated Ni and Sn	Packaging 2 = 7" Reel 4 = 13" Reel	Special Code A = Std. Product



Y5V Dielectric

Specifications and Test Methods

Parameter/Test	Y5V Specification Limits		Measuring Conditions		
Operating Temperature Range	-30°C to +85°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance				
Dissipation Factor	$\leq 5.0\%$ for $\geq 50V$ DC rating $\leq 7.0\%$ for $25V$ DC rating $\leq 9.0\%$ for $16V$ DC rating $\leq 12.5\%$ for $\leq 10V$ DC rating		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm .2V$ For Cap $> 10 \mu F$, 0.5Vrms @ 120Hz		
Insulation Resistance	10,000MΩ or 500MΩ - μF , whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max)		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	$\leq \pm 30\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	\geq Initial Value $\times 0.1$			
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at $230 \pm 5^\circ C$ for 5.0 ± 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, $<25\%$ leaching of either end terminal		Dip device in eutectic solder at $260^\circ C$ for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	$\leq \pm 20\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: $-30^\circ C \pm 2^\circ$ 30 ± 3 minutes	
	Capacitance Variation	$\leq \pm 20\%$		Step 2: Room Temp ≤ 3 minutes	
	Dissipation Factor	Meets Initial Values (As Above)		Step 3: $+85^\circ C \pm 2^\circ$ 30 ± 3 minutes	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp ≤ 3 minutes	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with twice rated voltage in test chamber set at $85^\circ C \pm 2^\circ C$ for 1000 hours (+48, -0)	
	Capacitance Variation	$\leq \pm 30\%$			
	Dissipation Factor	\leq Initial Value $\times 1.5$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.1$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.	
	Capacitance Variation	$\leq \pm 30\%$			
	Dissipation Factor	\leq Initial Value $\times 1.5$ (See above)			
	Insulation Resistance	\geq Initial Value $\times 0.1$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			

Y5V Dielectric

Capacitance Range

PREFERRED SIZES ARE SHADED

SIZE	0201		0402				0603				0805				1206				1210											
Soldering	Reflow Only		Reflow/Wave				Reflow/Wave				Reflow/Wave				ReflowMfeve				Reflow/Wave											
Packaging	All Paper		All Paper				All Paper				Paper/Embossed				Paper/Embossed				Paper/Embossed											
(L) Length (in.)	mm (0.024 ± 0.004)		1.00 ± 0.10 (0.040 ± 0.004)				1.60 ± 0.15 (0.063 ± 0.006)				2.01 ± 0.20 (0.079 ± 0.008)				3.20 ± 0.20 (0.126 ± 0.008)				3.20 ± 0.20 (0.126 ± 0.008)											
W) Width (in.)	mm (0.011 ± 0.004)		0.50 ± 0.10 (0.020 ± 0.004)				.81 ± 0.15 (0.032 ± 0.006)				1.25 ± 0.20 (0.049 ± 0.008)				1.60 ± 0.20 (0.063 ± 0.008)				2.50 ± 0.20 (0.098 ± 0.008)											
(t) Terminal (in.)	mm (0.006 ± 0.002)		0.15 ± 0.05 (0.010 ± 0.006)				0.35 ± 0.15 (0.014 ± 0.006)				0.50 ± 0.25 (0.020 ± 0.010)				0.50 ± 0.25 (0.020 ± 0.010)				.50 ± 0.25 (0.020 ± 0.010)											
WVDC	6.3		10		6		10		16		25		50		10		16		25		50		10		16		25		50	
Cap (pF)	820																													
1000			A																											
2200			A																											
4700			A																											
Cap (μF)	0.010		A		A																									
0.047	A																													
0.10			C		C												G		G								K			
0.22																	G		G											
0.33					C												G		G											
0.47			C		C												G		G											
1.0					J												N		N				M		M		M		N	
2.2					N												N		N				P		Q		K		Q	
4.7																	N		P				Q		X		Z		X	
10.0																	Q												Z	
22.0																														
47.0																														
WVDC	6.3		10		6		10		16		25		50		10		16		25		50		10		16		25		50	



Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max.	0.33	0.56	0.71	0.90	0.94	1.02	1.27	1.40	1.52	1.78	2.29	2.54	2.79
Thickness	(0.013)	(0.022)	(0.028)	(0.035)	(0.037)	(0.040)	(0.050)	(0.055)	(0.060)	(0.070)	(0.090)	(0.100)	(0.110)


PAPER

EMBOSSED

MLCC Gold Termination – AU Series



General Specifications



AVX Corporation will support those customers for commercial and military Multilayer Ceramic Capacitors with a termination consisting of Gold. This termination is indicated by the use of a "7" or "G" in the 12th position of the AVX Catalog Part Number. This fulfills AVX's commitment to providing a full range of products to our customers. Please contact the factory if you require additional information on our MLCC Gold Termination.

PART NUMBER

AU03	Y	G	104	K	A	7	2	A
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
AU02 - 0402	6.3V = 6	COG (NP0) = A	2 Sig. Digits +	B = ± 10 pF (<10 pF)	A = Not Applicable	G* = 1.9μ to 7.87 μ "	2 = 7" Reel	A = Std. Product
AU03 - 0603	10V = Z	X7R = C	Number of	C = $\pm .25$ pF (<10 pF)			4 = 13" Reel	
AU05 - 0805	16V = Y	X5R = D	Zeros	D = $\pm .50$ pF (<10 pF)			U = 4mm TR (01005)	
AU06 - 1206	25V = 3			F = $\pm 1\%$ (≥ 10 pF)		7 = 100 μ " minimum		
AU10 - 1210	35V = D			G = $\pm 2\%$ (≥ 10 pF)				
AU12 - 1812	50V = 5			J = $\pm 5\%$				
AU13 - 1825	100V = 1			K = $\pm 10\%$				
AU14 - 2225	200V = 2			M = $\pm 20\%$				
AU16 - 0306	500V = 7							
AU17 - 0508								
AU18 - 0612								
								Contact Factory For Multiples*

* Contact factory for availability.

MLCC Gold Termination – AU Series

Capacitance Range (NP0 Dielectric)

PREFERRED SIZES ARE SHADED

SIZE	AU02			AU03			AU05			AU06									
Soldering	Reflow/Epoxy/ Wire Bond*			Reflow/Epoxy/ Wire Bond*			Reflow/Epoxy/ Wire Bond*			Reflow/Epoxy/ Wire Bond*									
Packaging	All Paper			All Paper			Paper/Embossed			Paper/Embossed									
(L) Length (in.)	mm 1.00 ± 0.10 (0.040 ± 0.004)	1.60 ± 0.15 (0.063 ± 0.006)					2.01 ± 0.20 (0.079 ± 0.008)			3.20 ± 0.20 (0.126 ± 0.008)									
W) Width (in.)	mm 0.50 ± 0.10 (0.020 ± 0.004)	0.81 ± 0.15 (0.032 ± 0.006)					1.25 ± 0.20 (0.049 ± 0.008)			1.60 ± 0.20 (0.063 ± 0.008)									
(t) Terminal (in.)	mm 0.25 ± 0.15 (0.010 ± 0.006)	0.35 ± 0.15 (0.014 ± 0.006)					0.50 ± 0.25 (0.020 ± 0.010)			0.50 ± 0.25 (0.020 ± 0.010)									
WVDC	16	25	50	16	25	50	100	16	25	50	100	200	16	25	50	100	200	500	
Cap (pF)	C 0.5	C 1.0	C 1.2	C 1.5	G 1.8	G 2.2	G 2.7	G 3.3	G 3.9	G 4.7	G 5.6	G 6.8	G 8.2	G 10	G 12	G 15	G 18	G 22	G 27
	C 1.0	C 1.2	C 1.5	C 1.8	G 2.2	G 2.7	G 3.3	G 3.9	G 4.7	G 5.6	G 6.8	G 8.2	G 10	G 12	G 15	G 18	G 22	G 27	G 33
	C 1.2	C 1.5	C 1.8	C 2.2	G 2.7	G 3.3	G 3.9	G 4.7	G 5.6	G 6.8	G 8.2	G 10	G 12	G 15	G 18	G 22	G 27	G 33	G 39
	C 1.5	C 1.8	C 2.2	C 2.7	G 3.3	G 3.9	G 4.7	G 5.6	G 6.8	G 8.2	G 10	G 12	G 15	G 18	G 22	G 27	G 33	G 39	G 47
					G 56	G 68	G 82	G 100	G 120	G 150	G 180	G 220	G 270	G 330	G 390	G 470	G 560	G 680	G 820
					G 68	G 82	G 100	G 120	G 150	G 180	G 220	G 270	G 330	G 390	G 470	G 560	G 680	G 820	G 1000
					G 82	G 100	G 120	G 150	G 180	G 220	G 270	G 330	G 390	G 470	G 560	G 680	G 820	G 1000	G 1200
					G 100	G 120	G 150	G 180	G 220	G 270	G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000
					G 120	G 150	G 180	G 220	G 270	G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000
					G 150	G 180	G 220	G 270	G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000
					G 180	G 220	G 270	G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000
					G 220	G 270	G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000
					G 270	G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000
					G 330	G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000
					G 390	G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000
					G 4700	G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000
					G 5600	G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000
					G 6800	G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000
					G 8200	G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000
					G 10000	G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000
					G 12000	G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000
					G 15000	G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000
					G 18000	G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000
					G 22000	G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000
					G 27000	G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000
					G 33000	G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000
					G 39000	G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000
					G 47000	G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000
					G 56000	G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000
					G 68000	G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000
					G 82000	G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000
					G 100000	G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000
					G 120000	G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000
					G 150000	G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000
					G 180000	G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000
					G 220000	G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000
					G 270000	G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000
					G 330000	G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000
					G 390000	G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000
					G 470000	G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000
					G 560000	G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000	G 8200000
					G 680000	G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000	G 8200000	G 10000000
					G 820000	G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000	G 8200000	G 10000000	G 12000000
					G 1000000	G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000	G 8200000	G 10000000	G 12000000	G 15000000
					G 1200000	G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000	G 8200000	G 10000000	G 12000000	G 15000000	G 18000000
					G 1500000	G 1800000	G 2200000	G 2700000	G 3300000	G 3900000	G 4700000	G 5600000	G 6800000	G 8200000	G 10000000	G 12000000	G 15000		

MLCC Gold Termination – AU Series



Capacitance Range (NP0 Dielectric)

PREFERRED SIZES ARE SHADED

SIZE	AU10					AU12					AU13					AU14					
Soldering	Reflow/Epoxy/ Wire Bond*					Reflow/Epoxy/ Wire Bond*					Reflow/Epoxy/ Wire Bond*					Reflow/Epoxy/ Wire Bond*					
Packaging	Paper/Embossed					All Embossed					All Embossed					All Embossed					
(L) Length (in.)	mm	3.20 ± 0.20 (0.126 ± 0.008)				4.50 ± 0.30 (0.177 ± 0.012)				4.50 ± 0.30 (0.177 ± 0.012)				5.72 ± 0.25 (0.225 ± 0.010)							
W) Width (in.)	mm	2.50 ± 0.20 (0.098 ± 0.008)				3.20 ± 0.20 (0.126 ± 0.008)				6.40 ± 0.40 (0.252 ± 0.016)				6.35 ± 0.25 (0.250 ± 0.010)							
(t) Terminal (in.)	mm	0.50 ± 0.25 (0.020 ± 0.010)				0.61 ± 0.36 (0.024 ± 0.014)				0.61 ± 0.36 (0.024 ± 0.014)				0.64 ± 0.39 (0.025 ± 0.015)							
WVDC	25	50	100	200	500	25	50	100	200	500	50	100	200	50	100	200	50	100	200		
Cap (pF)	0.5																				
1.0																					
1.2																					
1.5																					
1.8																					
2.2																					
2.7																					
3.3																					
3.9																					
4.7																					
5.6																					
6.8																					
8.2																					
10																					
12																					
15																					
18																					
22																					
27																					
33																					
39																					
47																					
56																					
68																					
82																					
100																					
120																					
150																					
180																					
220																					
270																					
330																					
390																					
470																					
560	J	J	J	J	M																
680	J	J	J	J	M																
820	J	J	J	J	M																
1000	J	J	J	J	M	M	K	K	K	K	M	M	M	M	M	M	M	P			
1200	J	J	J	J	M	M	K	K	K	K	M	M	M	M	M	M	M	M	P		
1500	J	J	J	J	M	M	K	K	K	K	M	M	M	M	M	M	M	M	P		
1800	J	J	J	M		K	K	K	K	K	M	M	M	M	M	M	M	M	P		
2200	J	J	J	Q		K	K	K	K	K	P	M	M	M	M	M	M	M	P		
2700	J	J	J	Q		K	K	K	K	K	Q	M	M	M	M	M	M	M	P		
3300	J	J	J			K	K	K	K	K	P	Q	M	M	M	M	M	M	P		
3900	J	J	M			K	K	K	K	K	P	Q	M	M	M	M	M	M	P		
4700	J	J	M			K	K	K	K	K	P	Q	M	M	M	M	M	M	P		
5600	J	J				K	K	M	P	X			M	M	M	M	M	M	P		
6800	J	J				K	K	M	X			M	M	M	M	M	M	M	P		
8200	J	J				K	M	M				M	M	M	M	M	M	M	P		
0.010	J	J				K	M	M				M	M	M	M	M	M	M	P		
0.012	J	J				K	M	M				M	M	M	M	M	M	M	P		
0.015						K	M	M				M	M	M	M	M	M	M	Y		
0.018						M	M				P	M				M	M	M	Y		
0.022						M	M				P					M	Y	Y			
0.027						M	M				P					P	Y	Y			
0.033						M	M				P					P					
0.039						M	M				P					P					
0.047						M	M				P					P					
0.068						M	M									P					
0.082						M	M									Q					
0.1																					
WVDC	25	50	100	200	500	25	50	100	200	500	50	100	200	50	100	200	50	100	200		
SIZE	AU10					AU12					AU13					AU14					

* Contact Factory

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
	PAPER					EMBOSSED							



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

MLCC Gold Termination – AU Series



Capacitance Range (X7R Dielectric)

PREFERRED SIZES ARE SHADED

SIZE	AU02				AU03					AU05					AU06							
Soldering	Reflow/Epoxy/ Wire Bond*				Reflow/Epoxy/ Wire Bond*					Reflow/Epoxy/ Wire Bond*					Reflow/Epoxy/ Wire Bond*							
Packaging	All Paper				All Paper					Paper/Embossed					Paper/Embossed							
(L) Length mm (in.)	1.00 ± 0.10 (0.040 ± 0.004)				1.60 ± 0.15 (0.063 ± 0.006)					2.01 ± 0.20 (0.079 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)							
W) Width mm (in.)	0.50 ± 0.10 (0.020 ± 0.004)				0.81 ± 0.15 (0.032 ± 0.006)					1.25 ± 0.20 (0.049 ± 0.008)					1.60 ± 0.20 (0.063 ± 0.008)							
(t) Terminal mm (in.)	0.25 ± 0.15 (0.010 ± 0.006)				0.35 ± 0.15 (0.014 ± 0.006)					0.50 ± 0.25 (0.020 ± 0.010)					0.50 ± 0.25 (0.020 ± 0.010)							
WVDC	10	16	25	50	63	10	16	25	50	100	200	63	10	16	25	50	100	200	500			
Cap (pF)	100																					
150																						
220					C								G									
330						C							G	G	G			J	J	J	J	J
470						C							G	G	G			J	J	J	J	J
680						C							G	G	G			J	J	J	J	J
1000							C						G	G	G			J	J	J	J	J
1500							C						G	G	G			J	J	J	J	J
2200							C						G	G	G			J	J	J	J	J
3300							C	C	C				G	G	G			J	J	J	J	J
4700							C	C	C				G	G	G			J	J	J	J	J
6800							C	C	C				G	G	G			J	J	J	J	J
Cap (μF)	0.010												G	G	G			J	J	J	J	J
0.015													G	G	G			J	J	J	J	J
0.022	C												G	G	G			J	J	J	J	J
0.033	C												G	G	G			J	J	J	J	J
0.047													G	G	G			J	J	J	J	J
0.068													G	G	G			J	J	J	J	J
0.10													G	G	G			J	J	J	J	J
0.15													G	G	G			J	J	J	J	J
0.22													G	G	G			J	J	J	J	J
0.33																	N	N	N	N	N	
0.47																	N	N	N	N	N	
0.68																	N	N	N	N	N	
1.0																	N	N	N	N	N	
1.5																	N	N	N	N	N	
2.2																	N	N	N	N	N	
3.3																	P*					
4.7																						
10																						
22																						
47																						
100																						
WVDC	10	16	25	50	63	10	16	25	50	100	200	63	10	16	25	50	100	200	500			
SIZE	AU02				AU03					AU05					AU06							

* Contact Factory

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER												EMBOSS	



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

MLCC Gold Termination – AU Series




Capacitance Range (X7R Dielectric)

PREFERRED SIZES ARE SHADED

SIZE	AU10						AU12				AU13			AU14	
Soldering	Reflow/Epoxy/ Wire Bond*						Reflow/Epoxy/ Wire Bond*				Reflow/Epoxy/ Wire Bond*			Reflow/Epoxy/ Wire Bond*	
Packaging	Paper/Embossed						All Embossed				All Embossed			All Embossed	
(L) Length mm (in.)	3.20 ± 0.20 (0.126 ± 0.008)						4.50 ± 0.30 (0.177 ± 0.012)				4.50 ± 0.30 (0.177 ± 0.012)			5.72 ± 0.25 (0.225 ± 0.010)	
(W) Width mm (in.)	2.50 ± 0.20 (0.098 ± 0.008)						3.20 ± 0.20 (0.126 ± 0.008)				6.40 ± 0.40 (0.252 ± 0.016)			6.35 ± 0.25 (0.250 ± 0.010)	
(t) Terminal mm (in.)	0.50 ± 0.25 (0.020 ± 0.010)						0.61 ± 0.36 (0.024 ± 0.014)				0.61 ± 0.36 (0.024 ± 0.014)			0.64 ± 0.39 (0.025 ± 0.015)	
WVDC	10	16	25	50	100	200	500	50	100	200	500	50	100	50	100
Cap (pF)	100														
	150														
	220														
	330														
	470														
	680														
	1000														
Cap (pF)	1500	J	J	J	J	J	M								
	2200	J	J	J	J	J	M								
	3300	J	J	J	J	J	M								
	4700	J	J	J	J	J	M								
	6800	J	J	J	J	J	M								
Cap (μF)	0.010	J	J	J	J	J	M	K	K	K	K	M	M	M	P
	0.015	J	J	J	J	J	P	K	K	K	K	M	M	M	P
	0.022	J	J	J	J	J	Q	K	K	K	K	M	M	M	P
	0.033	J	J	J	J	J	Q	K	K	K	X	M	M	M	P
	0.047	J	J	J	J	J		K	K	K	Z	M	M	M	P
	0.068	J	J	J	J	J	M	K	K	K	Z	M	M	M	P
	0.10	J	J	J	J	J	M					M	M	M	P
	0.15	J	J	J	J	M	Z					M	M	M	P
	0.22	J	J	J	J	P	Z					M	M	M	P
	0.33	J	J	J	J	Q						M	M	M	P
	0.47	M	M	M	M	Q						M	M	M	P
	0.68	M	M	P	X	X						M	P	M	P
	1.0	N	N		X	Z						M	P	M	P
	1.5	N	N	Z	Z	Z						Z	M	M	X
	2.2	X	X	Z	Z	Z						Z			
	3.3	X	X	Z	Z	Z									
	4.7	X	X	Z	Z	Z									
	10	Z	Z	Z											
	22														
	47														
	100														
WVDC	10	16	25	50	100	200	500	50	100	200	500	50	100	50	100
SIZE	AU10						AU12				AU13			AU14	

* Contact Factory



Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z				
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)				
PAPER						EMBORESSED											

MLCC Gold Termination – AU Series



Capacitance Range (X5R Dielectric)

PREFERRED SIZES ARE SHADED

SIZE	AU02					AU03					AU05					AU06					AU10					AU12					
Soldering	Reflow/Epoxy Wire Bond*					Reflow/Epoxy Wire Bond*					Reflow/Epoxy Wire Bond*					Reflow/Epoxy Wire Bond*					Reflow/Epoxy Wire Bond*					Reflow/Epoxy Wire Bond*					
Packaging	All Paper					All Paper					Paper/Embossed					Paper/Embossed					Paper/Embossed					All Embossed					
(L) Length	mm (in.)	1.00 ± 0.10 (0.040 ± 0.004)					1.60 ± 0.15 (0.063 ± 0.006)					2.01 ± 0.20 (0.079 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)					4.50 ± 0.30 (0.177 ± 0.012)				
(W) Width	mm (in.)	0.50 ± 0.10 (0.020 ± 0.004)					0.81 ± 0.15 (0.032 ± 0.006)					1.25 ± 0.20 (0.049 ± 0.008)					1.60 ± 0.20 (0.063 ± 0.008)					2.50 ± 0.20 (0.098 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)				
(t) Terminal	mm (in.)	0.25 ± 0.15 (0.010 ± 0.006)					0.35 ± 0.15 (0.014 ± 0.006)					0.50 ± 0.25 (0.020 ± 0.010)					0.50 ± 0.25 (0.020 ± 0.010)					0.50 ± 0.25 (0.020 ± 0.010)					0.61 ± 0.36 (0.024 ± 0.014)				
WVDC	4	6.3	10	16	25	50	4	6.3	10	16	25	35	50	6.3	10	16	25	35	50	6.3	10	16	25	35	50	6.3	10	25	50		
Cap (pF)	100																														
150																															
220																															
330							C																								
470							C																								
680							C																								
1000							C																								
1500							C																								
2200							C																								
3300							C																								
4700							C																								
6800							C																								
Cap (μF)	0.010						C																								
0.015							C																								
0.022							C																								
0.033							C																								
0.047							C																								
0.068							C																								
0.10		C					C																								
0.15							C																								
0.22		C*					C																								
0.33																															
0.47		C*																													
0.68																															
1.0							G	G	G	J*						N	N	N	N	P*					Q	Q					
1.5							G*	G*	J*	J*						N	N	N	N									X	X	X	
2.2	C*						G*	G*	J*	J*						N	N	N	N		Q	Q						Z	X		
3.3							J*	J*	J*	J*						N	N	N*	N*		Q	Q									
4.7							J*	J*	J*	J*						P*	P*	P*	P*		Q	Q									
10							K*																								Z
22																															
47																															
100																															
WVDC	4	6.3	10	16	25	50	4	6.3	10	16	25	35	50	6.3	10	16	25	35	50	6.3	10	16	25	35	50	6.3	10	25	50		
SIZE	AU02					AU03					AU05					AU06					AU10					AU12					

* Contact Factory

= *Optional Specifications – Contact Factory

NOTE: Contact factory for non-specified capacitance values

MLCC Gold Termination – AU Series

AU16/AU17/AU18

SIZE		AU16 (0306)				AU17 (0508)				AU18 (0612)						
Packaging		Embossed				Embossed				Embossed						
Length	mm (in.)	0.81 ± 0.15 (0.032 ± 0.006)				1.27 ± 0.25 (0.050 ± 0.010)				1.60 ± 0.25 (0.063 ± 0.010)						
Width	mm (in.)	1.60 ± 0.15 (0.063 ± 0.006)				2.00 ± 0.25 (0.080 ± 0.010)				3.20 ± 0.25 (0.126 ± 0.010)						
Cap Code	WVDC	4	6.3	10	16	25	6.3	10	16	25	50	6.3	10	16	25	50
102	Cap 0.001	A	A	A	A	S	S	S	S	V	S	S	S	S	V	
222	(μF) 0.0022	A	A	A	A	S	S	S	S	V	S	S	S	S	V	
332	0.0033	A	A	A	A	S	S	S	S	V	S	S	S	S	V	
472	0.0047	A	A	A	A	S	S	S	S	V	S	S	S	S	V	
682	0.0068	A	A	A	A	S	S	S	S	V	S	S	S	S	V	
103	0.01	A	A	A	A	S	S	S	S	V	S	S	S	S	V	
153	0.015	A	A	A	A	S	S	S	S	V	S	S	S	S	W	
223	0.022	A	A	A	A	S	S	S	S	V	S	S	S	S	W	
333	0.033	A	A	A		S	S	S	V	V	S	S	S	S	W	
473	0.047	A	A	A		S	S	S	V	A	S	S	S	S	W	
683	0.068	A	A	A		S	S	S	A	A	S	S	S	V	W	
104	0.1	A	A	A		S	S	V	A	A	S	S	S	V	W	
154	0.15	A	A			S	S	V			S	S	S	W	W	
224	0.22	A	A			S	S	A			S	S	V	W		
334	0.33					V	V	A			S	S	V			
474	0.47					V	V	A			S	S	V			
684	0.68					A	A				V	V	W			
105	1	A				A	A				V	V	A			
155	1.5					A					W	W				
225	2.2										A	A				
335	3.3										A					
475	4.7															
685	6.8															
106	10															

Solid = X7R

= X5R

= X7S

mm (in.)

AU16 (0306)	
Code	Thickness
A	0.56 (0.022)


mm (in.)

AU16 (0508)	
Code	Thickness
S	0.56 (0.022)
V	0.76 (0.030)
A	1.02 (0.040)

mm (in.)

AU16 (0612)	
Code	Thickness
S	0.56 (0.022)
V	0.76 (0.030)
W	1.02 (0.040)
A	1.27 (0.050)

PHYSICAL DIMENSIONS AND PAD LAYOUT



PHYSICAL DIMENSIONS

MM (IN.)


	L	W	t
AU16 (0306)	0.81 ± 0.15 (0.032 ± 0.006)	1.60 ± 0.15 (0.063 ± 0.006)	0.13 min. (0.005 min.)
AU17 (0508)	1.27 ± 0.25 (0.050 ± 0.010)	2.00 ± 0.25 (0.080 ± 0.010)	0.13 min. (0.005 min.)
AU18 (0612)	1.60 ± 0.25 (0.063 ± 0.010)	3.20 ± 0.25 (0.126 ± 0.010)	0.13 min. (0.005 min.)

T - See Range Chart for Thickness and Codes

PAD LAYOUT DIMENSIONS


MM (IN.)

	A	B	C
AU16 (0306)	0.31 (0.012)	1.52 (0.060)	0.51 (0.020)
AU17 (0508)	0.51 (0.020)	2.03 (0.080)	0.51 (0.020)
AU18 (0612)	0.76 (0.030)	3.05 (0.120)	0.635 (0.025)



MLCC Tin/Lead Termination "B" (LD Series)

COG (NP0) – General Specifications



AVX Corporation will support those customers for commercial and military Multilayer Ceramic Capacitors with a termination consisting of 5% minimum lead. This termination is indicated by the use of a "B" in the 12th position of the AVX Catalog Part Number. This fulfills AVX's commitment to providing a full range of products to our customers. AVX has provided in the following pages a full range of values that we are currently offering in this special "B" termination. Please contact the factory if you require additional information on our MLCC Tin/Lead Termination "B" products.

Not RoHS Compliant







PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)

LD05	5	A	101	J	A	B	2	A
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
LD02 - 0402	6.3V = 6	COG (NP0) = A	2 Sig. Digits + Number of Zeros	B = ± 10 pF (< 10 pF) C = ± 25 pF (< 10 pF) D = ± 50 pF (< 10 pF) F = $\pm 1\%$ (≥ 10 pF) G = $\pm 2\%$ (≥ 10 pF) J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$	A = Not Applicable 4 = Automotive	B = 5% min lead X = FLEXITERM® with 5% min lead**	2 = 7" Reel 4 = 13" Reel	A = Std. Product
LD03 - 0603	10V = Z	X7R = C						
LD04 - 0504*	16V = Y	X5R = D						
LD05 - 0805	25V = 3	X8R = F						
LD06 - 1206	35V = D							
LD10 - 1210	35V = D							
LD12 - 1812	50V = 5							
LD13 - 1825	100V = 1							
LD14 - 2225	200V = 2							
LD20 - 2220	500V = 7							

*LD04 has the same CV ranges as LD03.

See FLEXITERM® section for CV options


NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers.
Contact factory for non-specified capacitance values.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

MLCC Tin/Lead Termination "B"

COG (NP0) – Specifications and Test Methods


Parameter/Test	NP0 Specification Limits		Measuring Conditions		
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance		Freq.: 1.0 MHz \pm 10% for cap \leq 1000 pF 1.0 kHz \pm 10% for cap $>$ 1000 pF Voltage: 1.0Vrms \pm .2V		
Q	<30 pF: $Q \geq 400 + 20 \times \text{Cap Value}$ ≥ 30 pF: $Q \geq 1000$				
Insulation Resistance	100,000MΩ or 1000MΩ - μ F, whichever is less		Charge device with rated voltage for 60 \pm 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	$\pm 5\%$ or $\pm .5$ pF, whichever is greater			
	Q	Meets Initial Values (As Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$			
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at 230 \pm 5°C for 5.0 \pm 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, $<25\%$ leaching of either end terminal		Dip device in eutectic solder at 260°C for 60 seconds. Store at room temperature for 24 \pm 2 hours before measuring electrical properties.	
	Capacitance Variation	$\leq \pm 2.5\%$ or $\pm .25$ pF, whichever is greater			
	Q	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: -55°C \pm 2° 30 \pm 3 minutes	
	Capacitance Variation	$\leq \pm 2.5\%$ or $\pm .25$ pF, whichever is greater		Step 2: Room Temp \leq 3 minutes	
	Q	Meets Initial Values (As Above)		Step 3: +125°C \pm 2° 30 \pm 3 minutes	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp \leq 3 minutes	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with twice rated voltage in test chamber set at 125°C \pm 2°C for 1000 hours (+48, -0).	
	Capacitance Variation	$\leq \pm 3.0\%$ or $\pm .3$ pF, whichever is greater			
	Q	≥ 30 pF: $Q \geq 350$ ≥ 10 pF, <30 pF: $Q \geq 275 + 5C/2$ <10 pF: $Q \geq 200 + 10C$			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Remove from test chamber and stabilize at room temperature for 24 hours before measuring.	
	Capacitance Variation	$\leq \pm 5.0\%$ or $\pm .5$ pF, whichever is greater			
	Q	≥ 30 pF: $Q \geq 350$ ≥ 10 pF, <30 pF: $Q \geq 275 + 5C/2$ <10 pF: $Q \geq 200 + 10C$			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			

MLCC Tin/Lead Termination "B"

COG (NP0) – Capacitance Range

PREFERRED SIZES ARE SHADED

SIZE	LD02			LD03			LD05			LD06			
	Reflow/Wave			Reflow/Wave			Reflow/Wave			Reflow/Wave			
	All Paper			All Paper			Paper/Embossed			Paper/Embossed			
(L) Length (in.)	1.00 ± 0.10 (0.040 ± 0.004)	1.60 ± 0.15 (0.063 ± 0.006)		2.01 ± 0.20 (0.079 ± 0.008)			3.20 ± 0.20 (0.126 ± 0.008)						
W) Width (in.)	0.50 ± 0.10 (0.020 ± 0.004)	0.81 ± 0.15 (0.032 ± 0.006)		1.25 ± 0.20 (0.049 ± 0.008)			1.60 ± 0.20 (0.063 ± 0.008)						
(t) Terminal (in.)	0.25 ± 0.15 (0.010 ± 0.006)	0.35 ± 0.15 (0.014 ± 0.006)		0.50 ± 0.25 (0.020 ± 0.010)			0.50 ± 0.25 (0.020 ± 0.010)						
WVDC	16	25	50	16	25	50	100	16	25	50	100	200	500
Cap (pF)													
0.5	C	C	C	G	G	G	J	J	J	J	J	J	J
1.0	C	C	C	G	G	G	J	J	J	J	J	J	J
1.2	C	C	C	G	G	G	J	J	J	J	J	J	J
1.5	C	C	C	G	G	G	J	J	J	J	J	J	J
1.8	C	C	C	G	G	G	J	J	J	J	J	J	J
2.2	C	C	C	G	G	G	J	J	J	J	J	J	J
2.7	C	C	C	G	G	G	J	J	J	J	J	J	J
3.3	C	C	C	G	G	G	J	J	J	J	J	J	J
3.9	C	C	C	G	G	G	J	J	J	J	J	J	J
4.7	C	C	C	G	G	G	J	J	J	J	J	J	J
5.6	C	C	C	G	G	G	J	J	J	J	J	J	J
6.8	C	C	C	G	G	G	J	J	J	J	J	J	J
8.2	C	C	C	G	G	G	J	J	J	J	J	J	J
10	C	C	C	G	G	G	J	J	J	J	J	J	J
12	C	C	C	G	G	G	J	J	J	J	J	J	J
15	C	C	C	G	G	G	J	J	J	J	J	J	J
18	C	C	C	G	G	G	J	J	J	J	J	J	J
22	C	C	C	G	G	G	J	J	J	J	J	J	J
27	C	C	C	G	G	G	J	J	J	J	J	J	J
33	C	C	C	G	G	G	J	J	J	J	J	J	J
39	C	C	C	G	G	G	J	J	J	J	J	J	J
47	C	C	C	G	G	G	J	J	J	J	J	J	J
56	C	C	C	G	G	G	J	J	J	J	J	J	J
68	C	C	C	G	G	G	J	J	J	J	J	J	J
82	C	C	C	G	G	G	J	J	J	J	J	J	J
100	C	C	C	G	G	G	J	J	J	J	J	J	J
120	C	C	C	G	G	G	J	J	J	J	J	J	J
150	C	C	C	G	G	G	J	J	J	J	J	J	J
180	C	C	C	G	G	G	J	J	J	J	J	J	J
220	C	C	C	G	G	G	J	J	J	J	J	J	M
270	C	C	C	G	G	G	J	J	J	J	J	J	M
330	C	C	C	G	G	G	J	J	J	M	J	J	M
390	C	C	C	G	G	G	J	J	J	M	J	J	M
470	C	C	C	G	G	G	J	J	J	M	J	J	M
560				G	G	G	J	J	J	M	J	J	M
680				G	G	G	J	J	J	M	J	J	P
820				G	G	G	J	J	J	M	J	J	M
1000				G	G	G	J	J	J	M	J	J	Q
1200				G	G	G	J	J	J	M	J	J	Q
1500				G	G	G	J	J	J	M	J	J	M
1800							J	J	J		J	J	M
2200							J	J	J	N	J	J	M
2700							J	J	J	N	J	J	P
3300							J	J	J		J	J	P
3900							J	J	J		J	J	P
4700							J	J	J		J	J	P
5600										M	J	M	
6800										M	J	M	
8200										M	J	M	
Cap (pF)	0.010												
0.012													
0.015													
0.018													
0.022													
0.027													
0.033													
0.039													
0.047													
0.068													
0.082													
0.1													
WVDC	16	25	50	16	25	50	100	16	25	50	100	200	500
SIZE	LD02			LD03			LD05			LD06			



Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER													
EMBOSSLED													

MLCC Tin/Lead Termination "B"




COG (NP0) – Capacitance Range

PREFERRED SIZES ARE SHADED




SIZE	LD10				LD12				LD13				LD14			
Soldering	Reflow Only				Reflow Only				Reflow Only				Reflow Only			
Packaging	Paper/Embossed				All Embossed				All Embossed				All Embossed			
(L) Length mm (in.)	3.20 ± 0.20 (0.126 ± 0.008)				4.50 ± 0.30 (0.177 ± 0.012)				4.50 ± 0.30 (0.177 ± 0.012)				5.72 ± 0.25 (0.225 ± 0.010)			
W) Width mm (in.)	2.50 ± 0.20 (0.098 ± 0.008)				3.20 ± 0.20 (0.126 ± 0.008)				6.40 ± 0.40 (0.252 ± 0.016)				6.35 ± 0.25 (0.250 ± 0.010)			
(t) Terminal mm (in.)	0.50 ± 0.25 (0.020 ± 0.010)				0.61 ± 0.36 (0.024 ± 0.014)				0.61 ± 0.36 (0.024 ± 0.014)				0.64 ± 0.39 (0.025 ± 0.015)			
WVDC	25	50	100	200	500	25	50	100	200	500	50	100	200	50	100	200
Cap (pF)	0.5															
	1.0															
	1.2															
	1.5															
	1.8															
	2.2															
	2.7															
	3.3															
	3.9															
	4.7															
	5.6															
	6.8															
	8.2															
	10															
	12															
	15															
	18															
	22															
	27															
	33															
	39															
	47															
	56															
	68															
	82															
	100															
	120															
	150															
	180															
	220															
	270															
	330															
	390															
	470															
	560	J	J	J	J	M										
	680	J	J	J	J	M										
	820	J	J	J	J	M										
	1000	J	J	J	J	M	K	K	K	K	M	M	M	M	M	P
	1200	J	J	J	M	M	K	K	K	K	M	M	M	M	M	P
	1500	J	J	J	M	M	K	K	K	K	M	M	M	M	M	P
	1800	J	J	M	M	K	K	K	K	M	M	M	M	M	M	P
	2200	J	J	Q	Q	K	K	K	K	P	M	M	M	M	M	P
	2700	J	J	Q	Q	K	K	K	K	P	M	M	M	M	M	P
	3300	J	J	M	M	K	K	K	P	Q	M	M	M	M	M	P
	3900	J	J	M	M	K	K	K	P	Q	M	M	M	M	M	P
	4700	J	J	M	M	K	K	K	P	Q	M	M	M	M	M	P
	5600	J	J			K	K	M	P	X	M	M	M	M	M	P
	6800	J	J			K	M	M	X		M	M	M	M	M	P
	8200	J	J			K	M	M			M	M	M	M	M	P
Cap (pF)	0.010	J	J			K	M	M			M	M		M	M	P
	0.012	J	J			K	M	M			M	M		M	M	P
	0.015					M	M	M			M	M		M	M	Y
	0.018					M	M				P	M		M	M	Y
	0.022					M	M				P	M		M	Y	Y
	0.027					M	M				P			P	Y	Y
	0.033					M	M				P			P		
	0.039					M	M				P			P		
	0.047					M	M				P			P		
	0.068					M	M							P		
	0.082					M	M							Q		
	0.1					M	M							Q		
WVDC	25	50	100	200	500	25	50	100	200	500	50	100	200	50	100	200
SIZE	LD10				LD12				LD13				LD14			



MLCC Tin/Lead Termination "B"

X8R – General Specifications



AVX Corporation will support those customers for commercial and military Multilayer Ceramic Capacitors with a termination consisting of 5% minimum lead. This termination is indicated by the use of a "B" in the 12th position of the AVX Catalog Part Number. This fulfills AVX's commitment to providing a full range of products to our customers. AVX has provided in the following pages a full range of values that we are currently offering in this special "B" termination. Please contact the factory if you require additional information on our MLCC Tin/Lead Termination "B" products.

Not RoHS Compliant

PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)

LD05	5	F	101	J	A	B	2	A
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
LD02 - 0402	6.3V = 6	X8R = F	2 Sig. Digits + Number of Zeros	B = $\pm .10$ pF (<10 pF)	A = Not Applicable	B = 5% min lead X = FLEXITERM® with 5% min lead**	2 = 7" Reel 4 = 13" Reel	A = Std. Product
LD03 - 0603	10V = Z			C = $\pm .25$ pF (<10 pF)				
LD04 - 0504*	16V = Y			D = $\pm .50$ pF (<10 pF)				
LD05 - 0805	25V = 3			F = $\pm 1\%$ (≥ 10 pF)				
LD06 - 1206	35V = D			G = $\pm 2\%$ (≥ 10 pF)				
LD10 - 1210	50V = 5			J = $\pm 5\%$				
LD12 - 1812	100V = 1			K = $\pm 10\%$				
LD13 - 1825	200V = 2			M = $\pm 20\%$				
LD20 - 2220	500V = 7							

LD04 has the same CV ranges as LD03.

See FLEXITERM® section for CV options


NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers.
Contact factory for non-specified capacitance values.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

MLCC Tin/Lead Termination "B"

X8R – Specifications and Test Methods

Parameter/Test	X8R Specification Limits		Measuring Conditions		
Operating Temperature Range	-55°C to +150°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance		Freq.: 1.0 kHz ± 10% Voltage: 1.0Vrms ± .2V		
Dissipation Factor	≤ 2.5% for ≥ 50V DC rating ≤ 3.5% for 25V DC and 16V DC rating				
Insulation Resistance	100,000MΩ or 1000MΩ - µF, whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	≤ ±12%			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	≥ Initial Value x 0.3			
Solderability	≥ 95% of each terminal should be covered with fresh solder		Dip device in eutectic solder at 230 ± 5°C for 5.0 ± 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal		Dip device in eutectic solder at 260°C for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	≤ ±7.5%			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: -55°C ± 2°	
	Capacitance Variation	≤ ±7.5%		Step 2: Room Temp	
	Dissipation Factor	Meets Initial Values (As Above)		Step 3: +125°C ± 2°	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with 1.5 rated voltage (≤ 10V) in test chamber set at 150°C ± 2°C for 1000 hours (+48, -0) Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.	
	Capacitance Variation	≤ ±12.5%			
	Dissipation Factor	≤ Initial Value x 2.0 (See Above)			
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Store in a test chamber set at 85°C ± 2°C/ 85% ± 5% relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature and humidity for 24 ± 2 hours before measuring.	
	Capacitance Variation	≤ ±12.5%			
	Dissipation Factor	≤ Initial Value x 2.0 (See Above)			
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			

MLCC Tin/Lead Termination "B"

X8R – Capacitance Range



SIZE		LD03		LD05		LD06	
	WVDC	25V	50V	25V	50V	25V	50V
271	Cap 270	G	G				
331	(pF) 330	G	G	J	J		
471	470	G	G	J	J		
681	680	G	G	J	J		
102	1000	G	G	J	J	J	J
152	1500	G	G	J	J	J	J
182	1800	G	G	J	J	J	J
222	2200	G	G	J	J	J	J
272	2700	G	G	J	J	J	J
332	3300	G	G	J	J	J	J
392	3900	G	G	J	J	J	J
472	4700	G	G	J	J	J	J
562	5600	G	G	J	J	J	J
682	6800	G	G	J	J	J	J
822	Cap 8200	G	G	J	J	J	J
103	(μF) 0.01	G	G	J	J	J	J
123	0.012	G	G	J	J	J	J
153	0.015	G	G	J	J	J	J
183	0.018	G	G	J	J	J	J
223	0.022	G	G	J	J	J	J
273	0.027	G	G	J	J	J	J
333	0.033	G	G	J	J	J	J
393	0.039	G	G	J	J	J	J
473	0.047	G	G	J	J	J	J
563	0.056	G		N	N	M	M
683	0.068	G		N	N	M	M
823	0.082			N	N	M	M
104	0.1			N	N	M	M
124	0.12			N	N	M	M
154	0.15			N	N	M	M
184	0.18			N		M	M
224	0.22			N		M	M
274	0.27					M	M
334	0.33					M	M
394	0.39					M	
474	0.47					M	
684	0.68						
824	0.82						
105	1						
	WVDC	25V	50V	25V	50V	25V	50V
	SIZE	LD03		LD05		LD06	


Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER					EMBOSSED								



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

MLCC Tin/Lead Termination "B"

X7R – General Specifications



AVX Corporation will support those customers for commercial and military Multilayer Ceramic Capacitors with a termination consisting of 5% minimum lead. This termination is indicated by the use of a "B" in the 12th position of the AVX Catalog Part Number. This fulfills AVX's commitment to providing a full range of products to our customers. AVX has provided in the following pages a full range of values that we are currently offering in this special "B" termination. Please contact the factory if you require additional information on our MLCC Tin/Lead Termination "B" products.

Not RoHS Compliant







PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)

LD05	5	C	101	J	A	B	2	A
Size LD03 - 0603	Voltage 6.3V = 6	Dielectric X7R = C	Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	Capacitance Tolerance B = $\pm 10\text{ pF}$ ($< 10\text{ pF}$) C = $\pm 25\text{ pF}$ ($< 10\text{ pF}$) D = $\pm 50\text{ pF}$ ($< 10\text{ pF}$) F = $\pm 1\%$ ($\geq 10\text{ pF}$) G = $\pm 2\%$ ($\geq 10\text{ pF}$) J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$	Failure Rate A = Not Applicable	Terminations B = 5% min lead X = FLEXITERM® with 5% min lead** **X7R only	Packaging 2 = 7" Reel 4 = 13" Reel	Special Code A = Std. Product
LD04 - 0504*	10V = Z							
LD05 - 0805	16V = Y							
LD06 - 1206	25V = 3							
LD10 - 1210	35V = D							
LD12 - 1812	50V = 5							
LD13 - 1825	100V = 1							
LD14 - 2225	200V = 2							
LD20 - 2220	500V = 7							

*LD04 has the same CV ranges as LD03.


See FLEXITERM® section for CV options

NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers.
Contact factory for non-specified capacitance values.



MLCC Tin/Lead Termination "B"

X7R – Specifications and Test Methods

Parameter/Test	X7R Specification Limits		Measuring Conditions
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber
Capacitance	Within specified tolerance		
Dissipation Factor	$\leq 10\%$ for $\geq 50V$ DC rating $\leq 12.5\%$ for $25V$ DC rating $\leq 12.5\%$ for $25V$ and $16V$ DC rating $\leq 12.5\%$ for $\leq 10V$ DC rating		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm .2V$
Insulation Resistance	100,000MΩ or 1000MΩ - μF, whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.
Resistance to Flexure Stresses	Appearance	No defects	
	Capacitance Variation	$\leq \pm 12\%$	
	Dissipation Factor	Meets Initial Values (As Above)	
	Insulation Resistance	\geq Initial Value $\times 0.3$	
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at $230 \pm 5^\circ C$ for 5.0 ± 0.5 seconds
Resistance to Solder Heat	Appearance	No defects, $<25\%$ leaching of either end terminal	Dip device in eutectic solder at $260^\circ C$ for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.
	Capacitance Variation	$\leq \pm 7.5\%$	
	Dissipation Factor	Meets Initial Values (As Above)	
	Insulation Resistance	Meets Initial Values (As Above)	
	Dielectric Strength	Meets Initial Values (As Above)	
Thermal Shock	Appearance	No visual defects	Step 1: $-55^\circ C \pm 2^\circ$ 30 ± 3 minutes
	Capacitance Variation	$\leq \pm 7.5\%$	Step 2: Room Temp ≤ 3 minutes
	Dissipation Factor	Meets Initial Values (As Above)	Step 3: $+125^\circ C \pm 2^\circ$ 30 ± 3 minutes
	Insulation Resistance	Meets Initial Values (As Above)	Step 4: Room Temp ≤ 3 minutes
	Dielectric Strength	Meets Initial Values (As Above)	Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature
Load Life	Appearance	No visual defects	Charge device with 1.5 rated voltage ($\leq 10V$) in test chamber set at $125^\circ C \pm 2^\circ C$ for 1000 hours (+48, -0) Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.
	Capacitance Variation	$\leq \pm 12.5\%$	
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)	
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)	
	Dielectric Strength	Meets Initial Values (As Above)	
Load Humidity	Appearance	No visual defects	Store in a test chamber set at $85^\circ C \pm 2^\circ C$ / $85\% \pm 5\%$ relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature and humidity for 24 ± 2 hours before measuring.
	Capacitance Variation	$\leq \pm 12.5\%$	
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)	
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)	
	Dielectric Strength	Meets Initial Values (As Above)	

MLCC Tin/Lead Termination "B"

X7R – Capacitance Range



PREFERRED SIZES ARE SHADED

SIZE	LD02					LD03					LD05					LD06												
	Soldering		Reflow/Wave			Soldering		Reflow/Wave			Soldering		Reflow/Wave			Soldering		Reflow/Wave										
Packaging	All Paper		All Paper			Paper		Paper/Embossed			Paper		Paper/Embossed			Paper		Paper/Embossed										
(L) Length	mm (in.)	1.00 ± 0.10 (0.040 ± 0.004)		1.60 ± 0.15 (0.063 ± 0.006)				2.01 ± 0.20 (0.079 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)															
W) Width	mm (in.)	0.50 ± 0.10 (0.020 ± 0.004)		0.81 ± 0.15 (0.032 ± 0.006)				1.25 ± 0.20 (0.049 ± 0.008)					1.60 ± 0.20 (0.063 ± 0.008)															
(t) Terminal	mm (in.)	0.25 ± 0.15 (0.010 ± 0.006)		0.35 ± 0.15 (0.014 ± 0.006)				0.50 ± 0.25 (0.020 ± 0.010)					0.50 ± 0.25 (0.020 ± 0.010)															
WVDC		16	25	50	6.3	10	16	25	50	100	200	6.3	10	16	25	50	100	200	6.3	10	16	25	50	100	200	500		
Cap (pF)	100																											
	150																											
	220		C																									
	330		C					G	G	G			J	J	J	J	J	J								K		
	470		C					G	G	G			J	J	J	J	J	J								K		
	680		C					G	G	G			J	J	J	J	J	J								K		
	1000		C					G	G	G			J	J	J	J	J	J								K		
	1500		C					G	G	G			J	J	J	J	J	J								M		
	2200		C					G	G	G			J	J	J	J	J	J								M		
	3300		C	C				G	G	G			J	J	J	J	J	J								M		
	4700		C	C	C			G	G	G			J	J	J	J	J	J								M		
	6800		C	C				G	G	G			J	J	J	J	J	J								P		
Cap (μF)	0.010	C	C					G	G				J	J	J	J	J	J								J		
	0.015	C						G	G				J	J	J	J	J	J								M		
	0.022	C						G	G				J	J	J	J	J	J								M		
	0.033	C						G	G				J	J	J	J	N									M		
	0.047							G	G				J	J	J	J	N									M		
	0.068							G	G				J	J	J	J	N									P		
	0.10	C*						G	G	G			J	J	J	J	N									P		
	0.15							G	G	G			J	J	J	J	N									Q		
	0.22							G	G	G			J	J	J	J	N									Q		
	0.33												N	N	N	N	N									P		
	0.47												N	N	N	N	N									Q		
	0.68												N	N	N	N	N									Q		
	1.0												N	N	N*												Q	
	1.5															P*												Q
	2.2																											Q
	3.3																											Q
	4.7																											Q
	10																											Q
	22																											Q
	47																											Q
	100																											Q
WVDC	16	25	50	6.3	10	16	25	50	100	200	6.3	10	16	25	50	100	200	6.3	10	16	25	50	100	200	500			
SIZE	LD02					LD03					LD05					LD06												

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
	PAPER												EMBOSSED


= Under Development

MLCC Tin/Lead Termination "B"

X7R – Capacitance Range

PREFERRED SIZES ARE SHADED


SIZE	LD10						LD12						LD13			LD20			LD14	
Soldering	Reflow Only						Reflow Only						Reflow Only			Reflow Only			Reflow Only	
Packaging	Paper/Embossed						All Embossed						All Embossed			All Embossed			All Embossed	
(L) Length (in.)	mm 3.20 ± 0.20 (0.126 ± 0.008)						mm 4.50 ± 0.30 (0.177 ± 0.012)						mm 4.50 ± 0.30 (0.177 ± 0.012)			mm 5.70 ± 0.50 (0.224 ± 0.020)			mm 5.72 ± 0.25 (0.225 ± 0.010)	
W) Width (in.)	mm 2.50 ± 0.20 (0.098 ± 0.008)						mm 3.20 ± 0.20 (0.126 ± 0.008)						mm 6.40 ± 0.40 (0.252 ± 0.016)			mm 5.00 ± 0.40 (0.197 ± 0.016)			mm 6.35 ± 0.25 (0.250 ± 0.010)	
(t) Terminal (in.)	mm 0.50 ± 0.25 (0.020 ± 0.010)						mm 0.61 ± 0.36 (0.024 ± 0.014)						mm 0.61 ± 0.36 (0.024 ± 0.014)			mm 0.64 ± 0.39 (0.025 ± 0.015)			mm 0.64 ± 0.39 (0.025 ± 0.015)	
WVDC	10	16	25	50	100	200	500	50	100	200	500	50	50	100	25	50	100	200	50	100
Cap (pF)	100																			
	150																			
	220																			
	330																			
	470																			
	680																			
	1000																			
	1500	J	J	J	J	J	J	M												
	2200	J	J	J	J	J	J	M												
	3300	J	J	J	J	J	J	M												
	4700	J	J	J	J	J	J	M												
	6800	J	J	J	J	J	J	M												
Cap (μF)	0.010	J	J	J	J	J	J	M	K	K	K	K	M	M		X	X	X	M	P
	0.015	J	J	J	J	J	J	P	K	K	K	K	P	M	M	X	X	X	M	P
	0.022	J	J	J	J	J	J	Q	K	K	K	K	P	M	M	X	X	X	M	P
	0.033	J	J	J	J	J	J	K	K	K	K	X	M	M		X	X	X	M	P
	0.047	J	J	J	J	J	J	K	K	K	K	Z	M	M		X	X	X	M	P
	0.068	J	J	J	J	J	M	K	K	K	K	Z	M	M		X	X	X	M	P
	0.10	J	J	J	J	J	M	K	K	K	K	Z	M	M		X	X	X	M	P
	0.15	J	J	J	J	M	Z	K	K	P	P	M	M	M		X	X	X	M	P
	0.22	J	J	J	J	P	Z	K	K	P	P	M	M	M		X	X	X	M	P
	0.33	J	J	J	J	Q		K	M	X		M	M			X	X	X	M	P
	0.47	M	M	M	M	Q		K	P			M	M			X	X	X	M	P
	0.68	M	M	P	X	X		M	Q			M	P			X	X	X	M	P
	1.0	N	N	P	X	Z		M	X			M	P			X	X		M	P
	1.5	N	N	Z	Z	Z		Z	Z			M				X	X		M	P
	2.2	X	X	Z	Z	Z		Z	Z							X	X		M	P
	3.3	X	X	Z	Z			Z								X	Z			
	4.7	X	X	Z	Z			Z								X	Z			
	10	Z	Z	Z	Z											Z	Z			
	22	Z	Z																	
	47																			
	100																			
WVDC	10	16	25	50	100	200	500	50	100	200	500	50	50	100	25	50	100	200	50	100
SIZE	LD10						LD12						LD13			LD20			LD14	



Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER													
EMBOSSED													

MLCC Tin/Lead Termination "B"

X5R – General Specifications



AVX Corporation will support those customers for commercial and military Multilayer Ceramic Capacitors with a termination consisting of 5% minimum lead. This termination is indicated by the use of a "B" in the 12th position of the AVX Catalog Part Number. This fulfills AVX's commitment to providing a full range of products to our customers. AVX has provided in the following pages a full range of values that we are currently offering in this special "B" termination. Please contact the factory if you require additional information on our MLCC Tin/Lead Termination "B" products.

Not RoHS Compliant

PART NUMBER (SEE PAGE 4 FOR COMPLETE PART NUMBER EXPLANATION)



LD05	5	D	101	J	A	B	2	A
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
LD02 - 0402	6.3V = 6	X5R = D	2 Sig. Digits + Number of Zeros	B = $\pm 10\text{ pF}$ ($<10\text{ pF}$) C = $\pm 25\text{ pF}$ ($<10\text{ pF}$) D = $\pm 50\text{ pF}$ ($<10\text{ pF}$) F = $\pm 1\%$ ($\geq 10\text{ pF}$) G = $\pm 2\%$ ($\geq 10\text{ pF}$) J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$	A = Not Applicable	B = 5% min lead X = FLEXITERM® with 5% min lead**	2 = 7" Reel 4 = 13" Reel	A = Std. Product
LD03 - 0603	10V = Z							
LD04 - 0504*	16V = Y							
LD05 - 0805	25V = 3							
LD06 - 1206	35V = D							
LD10 - 1210	35V = D							
LD12 - 1812	50V = 5							
LD13 - 1825	100V = 1							
LD14 - 2225	200V = 2							
LD20 - 2220	500V = 7							

*LD04 has the same CV ranges as LD03.

See FLEXITERM® section for CV options


NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers.
Contact factory for non-specified capacitance values.

TYPICAL ELECTRICAL CHARACTERISTICS



MLCC Tin/Lead Termination "B"

X5R – Specifications and Test Methods

Parameter/Test	X5R Specification Limits		Measuring Conditions			
Operating Temperature Range	-55°C to +85°C		Temperature Cycle Chamber			
Capacitance	Within specified tolerance					
Dissipation Factor	$\leq 2.5\%$ for $\geq 50V$ DC rating $\leq 3.0\%$ for 25V, 35V DC rating $\leq 12.5\%$ Max. for 16V DC rating and lower Contact Factory for DF by PN		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm .2V$ For Cap $> 10 \mu F$, 0.5Vrms @ 120Hz			
Insulation Resistance	10,000MΩ or 500MΩ - μF , whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity			
Dielectric Strength	No breakdown or visual defects		Charge device with 250% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max)			
Resistance to Flexure Stresses	Appearance	No defects				
	Capacitance Variation	$\leq \pm 12\%$				
	Dissipation Factor	Meets Initial Values (As Above)				
	Insulation Resistance	\geq Initial Value $\times 0.3$				
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at $230 \pm 5^\circ C$ for 5.0 ± 0.5 seconds			
Resistance to Solder Heat	Appearance	No defects, $<25\%$ leaching of either end terminal		Dip device in eutectic solder at $260^\circ C$ for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.		
	Capacitance Variation	$\leq \pm 7.5\%$				
	Dissipation Factor	Meets Initial Values (As Above)				
	Insulation Resistance	Meets Initial Values (As Above)				
	Dielectric Strength	Meets Initial Values (As Above)				
Thermal Shock	Appearance	No visual defects	Step 1: $-55^\circ C \pm 2^\circ$	30 ± 3 minutes		
	Capacitance Variation	$\leq \pm 7.5\%$	Step 2: Room Temp	≤ 3 minutes		
	Dissipation Factor	Meets Initial Values (As Above)	Step 3: $+85^\circ C \pm 2^\circ$	30 ± 3 minutes		
	Insulation Resistance	Meets Initial Values (As Above)	Step 4: Room Temp	≤ 3 minutes		
	Dielectric Strength	Meets Initial Values (As Above)	Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature			
Load Life	Appearance	No visual defects	Charge device with 1.5X rated voltage in test chamber set at $85^\circ C \pm 2^\circ C$ for 1000 hours (+48, -0). Note: Contact factory for *optional specification part numbers that are tested at $< 1.5X$ rated voltage.			
	Capacitance Variation	$\leq \pm 12.5\%$				
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)				
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)				
	Dielectric Strength	Meets Initial Values (As Above)				
Load Humidity	Appearance	No visual defects	Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.			
	Capacitance Variation	$\leq \pm 12.5\%$				
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)				
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)				
	Dielectric Strength	Meets Initial Values (As Above)				


MLCC Tin/Lead Termination "B"



X5R – Capacitance Range

PREFERRED SIZES ARE SHADED

SIZE	LD02					LD03					LD05					LD06					LD10									
Soldering	Reflow/Wave					Reflow/Wave					Reflow/Wave					Reflow/Wave					Reflow/Wave									
Packaging	All Paper					All Paper					Paper/Embossed					Paper/Embossed					Paper/Embossed									
(L) Length (in.)	1.00 ± 0.10 (0.040 ± 0.004)					1.60 ± 0.15 (0.063 ± 0.006)					2.01 ± 0.20 (0.079 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)					3.20 ± 0.20 (0.126 ± 0.008)									
(W) Width (in.)	0.50 ± 0.10 (0.020 ± 0.004)					0.81 ± 0.15 (0.032 ± 0.006)					1.25 ± 0.20 (0.049 ± 0.008)					1.60 ± 0.20 (0.063 ± 0.008)					2.50 ± 0.20 (0.098 ± 0.008)									
(t) Terminal (in.)	0.25 ± 0.15 (0.010 ± 0.006)					0.35 ± 0.15 (0.014 ± 0.006)					0.50 ± 0.25 (0.020 ± 0.010)					0.50 ± 0.25 (0.020 ± 0.010)					0.50 ± 0.25 (0.020 ± 0.010)									
WVDC	4	6.3	10	16	25	50	4	6.3	10	16	25	35	50	6.3	10	16	25	35	50	4	6.3	10	16	25	35	50	6.3	10	25	50
Cap (pF)	100																													
150																														
220							C																							
330							C																							
470							C																							
680							C																							
1000							C																							
1500							C																							
2200							C																							
3300							C																							
4700							C																							
6800							C																							
Cap (μ F)	0.010																													
0.015																														
0.022							C	C																						
0.033							C																							
0.047							C	C																						
0.068							C	C																						
0.10							C	C	C																					
0.15																														
0.22							C*																							
0.33																														
0.47							C*	C*																						
0.68																														
1.0							C*	C*	C*																					
1.5																														
2.2							C*																							
3.3																														
4.7																														
10																														
22																														
47																														
100																														
WVDC	4	6.3	10	16	25	50	4	6.3	10	16	25	35	50	6.3	10	16	25	35	50	6.3	10	16	25	35	50	6.3	10	25	50	
SIZE	LD02					LD03					LD05					LD06					LD10					LD12				




***Optional Specifications – Contact factory**

NOTE: Contact factory for non-specified capacitance values

Automotive MLCC

General Specifications



GENERAL DESCRIPTION

AVX Corporation has supported the Automotive Industry requirements for Multilayer Ceramic Capacitors consistently for more than 25 years. Products have been developed and tested specifically for automotive applications and all manufacturing facilities are QS9000 and VDA 6.4 approved.

AVX is using AECQ200 as the qualification vehicle for this transition. A detailed qualification package is available on request and contains results on a range of part numbers.

HOW TO ORDER

Contact factory for availability of Tolerance Options for Specific Part Numbers.

NOTE: Contact factory for non-specified capacitance values
0402 case size available in T termination only.

COMMERCIAL VS AUTOMOTIVE MLCC PROCESS COMPARISON


	Commercial	Automotive
Administrative	Standard Part Numbers. No restriction on who purchases these parts.	Specific Automotive Part Number. set to control supply of product to Automotive customers.
Design	Minimum ceramic thickness of 0.020"	Minimum Ceramic thickness of 0.029" (0.74mm) on all X7R product.
Dicing	Side & End Margins = 0.003" min	Side & End Margins = 0.004" min Cover Layers = 0.003" min
Lot Qualification (Destructive Physical Analysis - DPA)	As per EIA RS469	Increased sample plan stricter criteria.
Visual/Cosmetic Quality	Standard process and inspection	100% inspection
Application Robustness	Standard sampling for accelerated wave solder on X7R dielectrics	Increased sampling for accelerated wave solder on X7R and NP0 followed by lot by lot reliability testing.

All Tests have Accept/Reject Criteria 0/1

FLEXITERM FEATURES

a) Bend Test

The capacitor is soldered to the PC Board as shown:



Typical bend test results are shown below:

Style	Conventional	Soft Term
0603	>2mm	>5
0805	>2mm	>5
1206	>2mm	>5

a) Temperature Cycle testing

FLEXITERM® has the ability to withstand at least 1000 cycles between -55°C and +125°C

Automotive MLCC-NP0



Capacitance Range

SIZE	0402		0603				0805					1206					
Soldering	Reflow/Wave		Reflow/Wave				Reflow/Wave					Reflow/Wave					
WVDC	25V	50V	25V	50V	100V	200V	25V	50V	100V	200V	250V	25V	50V	100V	200V	250V	500V
0R5	0.5	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
1R0	1.0	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
1R2	1.2	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
1R5	1.5	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
1R8	1.8	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
2R2	2.2	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
2R7	2.7	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
3R3	3.3	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
3R9	3.9	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
4R7	4.7	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
5R6	5.6	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
6R8	6.8	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
8R2	8.2	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
100	10.0	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
120	12	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
150	15	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
180	18	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
220	22	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
270	27	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
330	33	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
390	39	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
470	47	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	J
510	51	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	
560	56	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	
680	68	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	
820	82	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	
101	100	C	C	G	G	G	J	J	J	N	N	J	J	J	J	J	
121	120			G	G	G	J	J	J	N	N	J	J	J	J	J	
151	150			G	G	G	J	J	J	N	N	J	J	J	J	J	
181	180			G	G	G	J	J	J	N	N	J	J	J	J	J	
221	220			G	G	G	J	J	J	N	N	J	J	J	J	J	
271	270			G	G	G	J	J	J	N	N	J	J	J	J	J	
331	330			G	G	G	J	J	J	N	N	J	J	J	J	J	
391	390			G	G		J	J	J			J	J	J	J	J	
471	470			G	G		J	J	J			J	J	J	J	J	
561	560			G	G		J	J	J			J	J	J	J	J	
681	680			G	G		J	J	J			J	J	J	J	J	
821	820						J	J	J			J	J	J	J	J	
102	1000						J	J	J			J	J	J	J	J	
122	1200																
152	1500																
182	1800																
222	2200																
272	2700																
332	3300																
392	3900																
472	4700																
103	10nF																
WVDC	25V	50V	25V	50V	100V	200V	25V	50V	100V	200V	250V	25V	50V	100V	200V	250V	500V
Size	0402		0603				0805					1206					

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER												EMBOSSED	



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

Automotive MLCC - X7R

Capacitance Range



SIZE	0402			0603						0805						1206						1210			1812			2220							
Soldering	Reflow/Wave			Reflow/Wave						Reflow/Wave						Reflow/Wave						Reflow Only			Reflow Only			Reflow Only							
WVDC	16V	25V	50V	10V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	500V	16V	25V	50V	100V	50V	100V	25V	50V	100V			
221	Cap 220	C	C	C													C																		
271	(pF) 270	C	C	C																															
331	330	C	C	C																															
391	390	C	C	C																															
471	470	C	C	C																															
561	560	C	C	C																															
681	680	C	C	C																															
821	820	C	C	C																															
102	1000	C	C	C	G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
182	1800	C	C	C	G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
222	2200	C	C	C	G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
332	3300	C	C	C	G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
472	4700	C	C	C	G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
103	Cap 0.01	C	C	C	G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
123 (F)	0.012	C			G	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
153	0.015	C			G	G	G	G	G	G	G	J	J	J	N	N	N	J	J	J	J	J	J	J	K	K	K	K	K	K					
183	0.018	C			G	G	G	G	G	G	G	J	J	J	N	N	N	J	J	J	J	J	J	J	K	K	K	K	K	K					
223	0.022	C			G	G	G	G	G	G	G	J	J	J	N	N	N	J	J	J	J	J	J	J	K	K	K	K	K	K					
273	0.027	C			G	G	G	G	J			J	J	J	N	N	N	J	J	J	J	J	J	J	K	K	K	K	K	K					
333	0.033	C			G	G	G	G	J			J	J	J	N	N	N	J	J	J	J	J	J	J	K	K	K	K	K	K					
473	0.047				G	G	G	G	J			J	J	J	N	N	N	J	J	M	M	M	M	M	K	K	K	K	K	K					
563	0.056				G	G	G	G	J			J	J	J	N	N	N	J	J	M	M	M	M	M	K	K	M	K	K	K					
683	0.068				G	G	G	G	J			J	J	J	N	N	N	J	J	M	M	M	M	M	K	K	M	K	K	K					
823	0.082				G	G	G	G	J			J	J	J	N	N	N	J	J	M	M	M	M	M	K	K	K	M	K	K					
104	0.1				G	G	G	G	J			J	J	J	N	N	N	J	J	M	P	P	P	P	K	K	K	M	K	K					
124	0.12				G							J	J	N	N	N	N	J	J	M	M	Q	Q	Q	K	K	K	P	K	K					
154	0.15				G							M	N	N	N	N	N	J	J	M	M	Q	Q	Q	K	K	K	P	K	K					
224	0.22				G							M	N	N	N	N	N	J	M	M	Q	Q	Q	Q	M	M	M	P	M	M					
334	0.33											N	N	N	N	N	N	J	M	P	Q			P	P	P	Q	X	X						
474	0.47											N	N	N	N	N	N	M	M	P	Q			P	P	P	Q	X	X						
684	0.68											N	N	N	N	N	N	M	Q	Q	Q			P	P	Q	X	X	X						
105	1											N	N	N	N	N	N	M	Q	Q	Q			P	Q	Q	Z	X	X	Z	Z				
155	1.5											N	N	N	N	N	N	Q	Q	Q	Q			P	Q	Z	Z	X	X	Z	Z				
225	2.2											N	N	N	N	N	N	Q	Q	Q	Q			Z	Z	Z	Z	Z	Z	Z	Z				
335	3.3																	Q	Q	Q	Q			X	Z	Z	Z	Z	Z	Z	Z				
475	4.7																	Q	Q	Q	Q			X	Z	Z	Z	Z	Z	Z	Z				
106	10																								Z	Z	Z	Z	Z	Z	Z	Z			
226	22																																		
WVDC		16V	25V	50V	10V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	500V	16V	25V	50V	100V	50V	100V	25V	50V	100V		
Size		0402			0603							0805						1206							1210						1812			2220	

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER													EMBOSSED

Automotive MLCC - X8R

Capacitance Range



SIZE		0603		0805		1206	
Soldering		Reflow/Wave		Reflow/Wave		Reflow/Wave	
WVDC	WVDC	25V	50V	25V	50V	25V	50V
271	Cap 270	G	G				
331	(pF) 330	G	G	J	J		
471	470	G	G	J	J		
681	680	G	G	J	J		
102	1000	G	G	J	J	J	J
152	1500	G	G	J	J	J	J
182	1800	G	G	J	J	J	J
222	2200	G	G	J	J	J	J
272	2700	G	G	J	J	J	J
332	3300	G	G	J	J	J	J
392	3900	G	G	J	J	J	J
472	4700	G	G	J	J	J	J
562	5600	G	G	J	J	J	J
682	6800	G	G	J	J	J	J
822	8200	G	G	J	J	J	J
103	Cap 0.01	G	G	J	J	J	J
123	(F) 0.012	G	G	J	J	J	J
153	0.015	G	G	J	J	J	J
183	0.018	G	G	J	J	J	J
223	0.022	G	G	J	J	J	J
273	0.027	G	G	J	J	J	J
333	0.033	G	G	J	J	J	J
393	0.039	G	G	J	J	J	J
473	0.047	G	G	J	J	J	J
563	0.056	G		N	N	M	M
683	0.068	G		N	N	M	M
823	0.082			N	N	M	M
104	0.1			N	N	M	M
124	0.12			N	N	M	M
154	0.15			N	N	M	M
184	0.18			N		M	M
224	0.22			N		M	M
274	0.27					M	M
334	0.33					M	M
394	0.39					M	
474	0.47					M	
684	0.68						
824	0.82						
105	1						
WVDC	WVDC	25V	50V	25V	50V	25V	50V
SIZE	WVDC	0603	0805	0805	1206		

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER							EMBOSSED						



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

APS for COTS+ High Reliability Applications

General Specifications Surface Mount NP0, X7R and X8R/L MLCCs



AVX's APS COTS+ series of multilayer ceramic capacitors offers the customer a high reliability solution with an ultralow failure rate, <1ppb, in a variety of case sizes and voltages. The APS range encompasses a wide range of dielectric types to meet the customer's requirements from low temperature/voltage capacitance change dielectric, NP0, to high performing capacitance voltage X7R to high temperature reliability dielectrics, X8R/L.

APS capacitors have a wider capacitance range than MIL spec parts that satisfies the need for higher CV demands and board space saving requirements. Each production lot is extensively tested and removes the requirement for customer specific drawings. The testing regime uses many of the MIL-STD test methods as per MIL-PRF-55681 and has a field failure rate of less than 1 ppb. The APS testing series uses AVX's unique in-house maverick testing detection system that eliminates infant mortality failures.

Applications suitable for APS include Industrial, Telecommunications, Aviation, and Military. The APS is available with a range of different termination finishes, Flexiterm®, Nickel / Tin and Tin with Pb1. Flexiterm® technology delivers improved thermo-mechanical stress resistance.

AVX'S APS RELIABILITY TEST SUMMARY

- 100% Visual Inspection
- DPA
- IR, DF, Cap, DWV
- Maverick Lot Review
- Thermal Shock
- 85/85 Testing
- Additional Life Testing
- C of C with every Order
- Quarterly Data Package

FEATURES

- The APS range has been extensively reliability tested as standard resulting in an ultralow failure rate, $\leq 1\text{ppb}$
- The APS range is available with Flexiterm® that deliver's high thermo-mechanical stress resistance.
- High CV range enabling board space saving requirements.

Dielectric	Temperature/Percentage Cap Change
NP0	-30ppm +30ppm from -55°C + 125°C
X7R	-15% +15% from -55°C to + 125°C
X8R	-15% +15% from -55°C to + 150°C
X8L	-15% +40% from -55°C to + 150°C

HOW TO ORDER

AP03	5	A	104	K	Q	T	2	A
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
AP03=0603	10V = Z	NP0 = A	2 Sig. Digits + Number of Zeros e.g. 10 F = 106	J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$	Q = APS	T = Plated Ni and Sn Z = FLEXITERM®** B = 10% min lead X = FLEXITERM® with 10% min lead	2 = 7" Reel 4 = 13" Reel	A = Std.Product
AP05=0805	16V = Y	X7R = C				Z, X for X7R only		
AP06=1206	25V = 3	X8R = F				**RoHS compliant		
AP10=1210	50V = 5	X8L = L						
AP12=1812	100V = 1							
AP20=2220	200V = 2							
	250V = V							
	500V = 7							

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Number.

APS COTS+ NP0 Series

Capacitance Range

Size	AP03 = 0603			AP05 = 0805			AP06 = 1206					AP10 = 1210				
	WVDC	25V	50V	100V	25V	50V	100V	25V	50V	100V	200V	500V	25V	50V	100V	200V
100 10pF	G	G	G	J	J	J	J	J	J	J	J	J				
120 12	G	G	G	J	J	J	J	J	J	J	J	J				
150 15	G	G	G	J	J	J	J	J	J	J	J	J				
180 18	G	G	G	J	J	J	J	J	J	J	J	J				
220 22	G	G	G	J	J	J	J	J	J	J	J	J				
270 27	G	G	G	J	J	J	J	J	J	J	J	J				
330 33	G	G	G	J	J	J	J	J	J	J	J	J				
390 39	G	G	G	J	J	J	J	J	J	J	J	J				
470 47	G	G	G	J	J	J	J	J	J	J	J	J				
510 51	G	G	G	J	J	J	J	J	J	J	J	J				
560 56	G	G	G	J	J	J	J	J	J	J	J	J				
680 68	G	G	G	J	J	J	J	J	J	J	J	J				
820 82	G	G	G	J	J	J	J	J	J	J	J	J				
101 100	G	G	G	J	J	J	J	J	J	J	J	J				
121 120	G	G	G	J	J	J	J	J	J	J	J	J				
151 150	G	G	G	J	J	J	J	J	J	J	J	J				
181 180	G	G	G	J	J	J	J	J	J	J	J	J				
221 220	G	G	G	J	J	J	J	J	J	J	J	J				
271 270	G	G	G	J	J	J	J	J	J	J	J	J				
331 330	G	G	G	J	J	J	J	J	J	J	J	J				
391 390	G	G		J	J	J	J	J	J	J	J	J				
471 470	G	G		J	J	J	J	J	J	J	J	J				
561 560				J	J	J	J	J	J	J	J	J				
681 680				J	J	J	J	J	J	J	J	J				
821 820				J	J	J	J	J	J	J	J	J				
102 1000				J	J	J	J	J	J	J	J	J	J	J	J	J
122 1200													J	J	M	M
152 1500													J	J	M	M
182 1800													J	J	M	M
222 2200													J	J	M	M
272 2700																
332 3300																
392 3900																
472 4700																
103 10nF																
WVDC	25V	50V	100V	25V	50V	100V	25V	50V	100V	200V	500V	25V	50V	100V	200V	
Size	AP03 = 0603			AP05 = 0805			AP06 = 1206					AP10 = 1210				



TS 16949, ISO 9001 Certified

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER					EMBOSSED								

APS COTS+ X7R Series



Capacitance Range

Size	AP03 = 0603					AP05 = 0805					AP06 = 1206					AP10 = 1210				AP12 = 1812		AP20 = 2220				
WVDC	16V	25V	50V	100V	200V	16V	25V	50V	100V	200V	16V	25V	50V	100V	200V	500V	16V	25V	50V	100V	50V	100V	25V	50V	100V	
102 Cap 1000	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
182 (pF) 1800	G	G	G	G		J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
222 2200	G	G	G	G		J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
332 3300	G	G	G	G		J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
472 4700	G	G	G	G		J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
103 0.01	G	G	G	G		J	J	J	J	J	J	J	J	J	J	K	K	K	K	K	K					
123 0.012	G	G	G			J	J	J	M		J	J	J	J	J	K	K	K	K	K	K					
153 0.015	G	G	G			J	J	J	M		J	J	J	J	J	K	K	K	K	K	K					
183 0.018	G	G	G			J	J	J	M		J	J	J	J	J	K	K	K	K	K	K					
223 0.022	G	G	G			J	J	J	M		J	J	J	J	J	K	K	K	K	K	K					
273 0.027	G	G	G			J	J	J	M		J	J	J	J	J	K	K	K	K	K	K					
333 0.033	G	G	G			J	J	J	M		J	J	J	J	J	K	K	K	K	K	K					
473 0.047	G	G	G			J	J	J	M		J	J	J	M	J	K	K	K	K	K	K					
563 0.056	G	G	G			J	J	J	M		J	J	J	M	J	K	K	K	M	K	K					
683 0.068	G	G	G			J	J	J	M		J	J	J	M	J	K	K	K	M	K	K					
823 0.082	G	G	G			J	J	J	M		J	J	J	M	J	K	K	K	M	K	K					
104 0.1	G	G	G			J	J	M	M		J	J	J	M	J	K	K	K	M	K	K					
124 0.12						J	J	M	N		J	J	M	M		K	K	K	P	K	K					
154 0.15						M	N	M	N		J	J	M	M		K	K	K	P	K	K					
224 0.22						M	N	M	N		J	M	M	Q		M	M	M	P	M	M					
334 0.33						N	N	M	N		J	M	P	Q		P	P	P	Q	X	X					
474 0.47						N	N	M	N		M	M	P	Q		P	P	P	Q	X	X					
684 0.68						N	N	N			M	Q	Q	Q		P	P	Q	X	X	X					
105 Cap 1.0						N	N	N	N*		M	Q	Q	Q*		P	Q	Q	Z*	X	X					
155 (μF) 1.5											Q	Q	Q			P	Q	Z	Z	X	X					
225 2.2											Q	Q	Q			Z	Z	Z	Z*	Z	Z					
335 3.3											Q					X	Z	Z	Z	Z	Z					
475 4.7											Q					X	Z	Z	Z	Z	Z					
106 10															Z	Z*						Z	Z*			
226 22																							Z	Z*		
WVDC	16V	25V	50V	100V	200V	16V	25V	50V	100V	200V	16V	25V	50V	100V	200V	500V	16V	25V	50V	100V	50V	100V	25V	50V	100V	
Size	AP03 = 0603					AP05 = 0805					AP06 = 1206					AP10 = 1210				AP12 = 1812		AP20 = 2220				

*Not currently available with lead plating finish, contact plant for further information.

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER												EMBOSSED	

TS 16949, ISO 9001 Certified

APS COTS+ X8R/L Series

Capacitance Range

X8R

SIZE		AP03 = 0603		AP05 = 0805		AP06 = 1206	
WVDC		25V	50V	25V	50V	25V	50V
331	Cap 330	G	G	J	J		
471	(pF) 470	G	G	J	J		
681	680	G	G	J	J		
102	1000	G	G	J	J	J	J
152	1500	G	G	J	J	J	J
222	2200	G	G	J	J	J	J
332	3300	G	G	J	J	J	J
472	4700	G	G	J	J	J	J
682	6800	G	G	J	J	J	J
103	Cap 0.01	G	G	J	J	J	J
153	(μF) 0.015	G	G	J	J	J	J
223	0.022	G	G	J	J	J	J
333	0.033	G	G	J	J	J	J
473	0.047	G	G	J	J	J	J
683	0.068	G		N	N	M	M
104	0.1			N	N	M	M
154	0.15			N	N	M	M
224	0.22			N		M	M
334	0.33					M	M
474	0.47					M	
684	0.68						
105	1						
WVDC		25V	50V	25V	50V	25V	50V
SIZE		0603		0805		1206	

X8L


SIZE		AP03 = 0603			AP05 = 0805			AP06 = 1206			
WVDC		25V	50V	100V	25V	50V	100V	16V	25V	50V	100V
331	Cap 330		G	G		J	J				
471	(pF) 470		G	G		J	J				
681	680	G	G		J	J					
102	1000	G	G		J	J					
152	1500	G	G		J	J		J	J		
222	2200	G	G		J	J		J	J		
332	3300	G	G		J	J		J	J		
472	4700	G	G		J	J		J	J		
682	6800	G	G		J	J		J	J		
103	Cap 0.01	G	G		J	J		J	J		
153	(μF) 0.015	G	G		J	J	J	J	J	J	
223	0.022	G	G		J	J		J	J	J	
333	0.033	G	G		J	J	N	J	J	J	
473	0.047	G	G		J	J	N	J	J	J	
683	0.068	G	G		J	J		J	J	J	
104	0.1	G	G		J	J		J	J	M	
154	0.15				J	N		J	J	J	Q
224	0.22				N	N		J	J	J	Q
334	0.33				N			J	M	P	Q
474	0.47				N			M	M	P	
684	0.68						M				
105	1						M				
WVDC		25V	50V	100V	25V	50V	100V	16V	25V	50V	100V
SIZE		0603		0805		1206					



Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER					EMBORESSED								

TS 16949, ISO 9001 Certified

General Specifications



GENERAL DESCRIPTION

With increased requirements from the automotive industry for additional component robustness, AVX recognized the need to produce a MLCC with enhanced mechanical strength. It was noted that many components may be subject to severe flexing and vibration when used in various under the hood automotive and other harsh environment applications.

To satisfy the requirement for enhanced mechanical strength, AVX had to find a way of ensuring electrical integrity is maintained whilst external forces are being applied to the component. It was found that the structure of the termination needed to be flexible and after much research and development, AVX launched FLEXITERM®. FLEXITERM® is designed to enhance the mechanical flexure and temperature cycling performance of a standard ceramic capacitor with an X7R dielectric. The industry standard for flexure is 2mm minimum. Using FLEXITERM®, AVX provides up to 5mm of flexure without internal cracks. Beyond 5mm, the capacitor will generally fail "open".

As well as for automotive applications FLEXITERM® will provide Design Engineers with a satisfactory solution when designing PCB's which may be subject to high levels of board flexure.

PRODUCT ADVANTAGES

- High mechanical performance able to withstand, 5mm bend test guaranteed
- Increased temperature cycling performance, 3000 cycles and beyond
- Flexible termination system
- Reduction in circuit board flex failures
- Base metal electrode system
- Automotive or commercial grade products available
- AECQ200 Qualified
- Approved to VW 80808 Specification

APPLICATIONS

High Flexure Stress Circuit Boards

- e.g. Depanelization: Components near edges of board.


Variable Temperature Applications

- Soft termination offers improved reliability performance in applications where there is temperature variation.
- e.g. All kind of engine sensors: Direct connection to battery rail.

Automotive Applications

- Improved reliability.
- Excellent mechanical performance and thermo mechanical performance.

HOW TO ORDER



NOTE: Contact factory for availability of Tolerance Options for Specific Part Numbers

PERFORMANCE TESTING

AEC-Q200 Qualification:

- Created by the Automotive Electronics Council
- Specification defining stress test qualification for passive components



Testing:

Key tests used to compare soft termination to AEC-Q200 qualification:

- Bend Test
- Temperature Cycle Test

BOARD BEND TEST RESULTS

AEC-Q200 Vrs AVX FLEXITERM® Bend Test







TABLE SUMMARY

Typical bend test results are shown below:


Style	Conventional Termination	FLEXITERM®
0603	>2mm	>5mm
0805	>2mm	>5mm
1206	>2mm	>5mm

TEMPERATURE CYCLE TEST PROCEDURE

Test Procedure as per AEC-Q200:

The test is conducted to determine the resistance of the component when it is exposed to extremes of alternating high and low temperatures.

- Sample lot size quantity 77 pieces
- TC chamber cycle from -55°C to +125°C for 1000 cycles
- Interim electrical measurements at 250, 500, 1000 cycles
- Measure parameter capacitance dissipation factor, insulation resistance



BOARD BEND TEST PROCEDURE

According to AEC-Q200

Test Procedure as per AEC-Q200:
Sample size: 20 components
Span: 90mm Minimum deflection spec: 2 mm

- Components soldered onto FR4 PCB (Figure 1)
- Board connected electrically to the test equipment (Figure 2)




Fig 1 - PCB layout with electrical connections





Fig 2 - Board Bend test equipment

AVX ENHANCED SOFT TERMINATION BEND TEST PROCEDURE

Bend Test

The capacitor is soldered to the printed circuit board as shown and is bent up to 10mm at 1mm per second:







- The board is placed on 2 supports 90mm apart (capacitor side down)
- The row of capacitors is aligned with the load stressing knife



- The load is applied and the deflection where the part starts to crack is recorded (Note: Equipment detects the start of the crack using a highly sensitive current detection circuit)
- The maximum deflection capability is 10mm

BEYOND 1000 CYCLES: TEMPERATURE CYCLE TEST RESULTS



Green = Soft Term MLCC (Flexiterm)
Red = Standard MLCC

Soft Term - No Defects up to 3000 cycles


AEC-Q200 specification states 1000 cycles compared to AVX 3000 temperature cycles.

FLEXITERM® TEST SUMMARY

- Qualified to AEC-Q200 test/specification with the exception of using AVX 3000 temperature cycles (up to +150°C bend test guaranteed greater than 5mm).
- FLEXITERM® provides improved performance compared to standard termination systems.


- Board bend test improvement by a factor of 2 to 4 times.
- Temperature Cycling:
 - 0% Failure up to 3000 cycles
 - No ESR change up to 3000 cycle

WITHOUT SOFT TERMINATION



Major fear is of latent board flex failures.

WITH SOFT TERMINATION



Far superior mechanical performance.
Generally open failure mode beyond
5mm flexure

MLCC with FLEXITERM®

Capacitance Range X8R Dielectric



SIZE		0603		0805		1206	
Soldering		Reflow/Wave		Reflow/Wave		Reflow/Wave	
WVDC	25V	50V	25V	50V	25V	50V	
271	Cap 270	G	G				
331	(pF) 330	G	G	J	J		
471	470	G	G	J	J		
681	680	G	G	J	J		
102	1000	G	G	J	J	J	J
152	1500	G	G	J	J	J	J
182	1800	G	G	J	J	J	J
222	2200	G	G	J	J	J	J
272	2700	G	G	J	J	J	J
332	3300	G	G	J	J	J	J
392	3900	G	G	J	J	J	J
472	4700	G	G	J	J	J	J
562	5600	G	G	J	J	J	J
682	6800	G	G	J	J	J	J
822	8200	G	G	J	J	J	J
103	Cap 0.01	G	G	J	J	J	J
123	(μF) 0.012	G	G	J	J	J	J
153	0.015	G	G	J	J	J	J
183	0.018	G	G	J	J	J	J
223	0.022	G	G	J	J	J	J
273	0.027	G	G	J	J	J	J
333	0.033	G	G	J	J	J	J
393	0.039	G	G	J	J	J	J
473	0.047	G	G	J	J	J	J
563	0.056	G		N	N	M	M
683	0.068	G		N	N	M	M
823	0.082			N	N	M	M
104	0.1			N	N	M	M
124	0.12			N	N	M	M
154	0.15			N	N	M	M
184	0.18			N		M	M
224	0.22			N		M	M
274	0.27					M	M
334	0.33					M	M
394	0.39					M	
474	0.47					M	
684	0.68						
824	0.82						
105	1						
WVDC		25V	50V	25V	50V	25V	50V
SIZE		0603		0805		1206	

Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)
PAPER												EMBOSSED	

TS 16949, ISO 9001 Certified



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

MLCC with FLEXITERM®

Capacitance Range X7R Dielectric



Size		0402			0603					0805					1206					1210			1812			2220							
Soldering		Reflow/ Wave			Reflow/Wave					Reflow/Wave					Reflow/Wave					Reflow Only			Reflow Only			Reflow Only							
WVDC		16V	25V	50V	10V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	500V	16V	25V	50V	100V	50V	100V	25V	50V	100V
221	Cap	220	C	C	C														C														
271	(pF)	270	C	C	C																												
331		330	C	C	C																												
391		390	C	C	C																												
471		470	C	C	C																												
561		560	C	C	C																												
681		680	C	C	C																												
821		820	C	C	C																												
102		1000	C	C	C	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	N	N			
182		1800	C	C	C	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	N	N			
222		2200	C	C	C	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	N	N	N			
332		3300	C	C	C	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	N	N			
472		4700	C	C	C	G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	N	N			
103	Cap	0.01	C			G	G	G	G	G	G	J	J	J	J	J	J	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
123	(pF)	0.012	C			G	G	G				J	J	J	N	N	N	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
153		0.015	C			G	G	G				J	J	J	N	N	N	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
183		0.018	C			G	G	G				J	J	J	N	N	N	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
223		0.022	C			G	G	G				J	J	J	N	N	N	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
273		0.027	C			G	G	G				J	J	J	N	N	N	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
333		0.033	C			G	G	G				J	J	J	N	N	N	J	J	J	J	J	J	J	J	K	K	K	K	N	N		
473		0.047				G	G	G				J	J	J	N	N	N	J	J	J	M	J	J	J	J	K	K	K	K	N	N		
563		0.056				G	G	G				J	J	J	N	N	N	J	J	J	M	J	J	J	J	K	K	M	N	N	N		
683		0.068				G	G	G				J	J	J	N	N	N	J	J	J	M	J	J	J	J	K	K	K	M	N	N		
823		0.082				G	G	G				J	J	J	N	N	N	J	J	J	M	J	J	J	J	K	K	K	M	N	N		
104		0.1	C			G	G	G				J	J	J	N	N	N	J	J	J	M	J	J	J	J	K	K	K	M	N	N		
124		0.12										J	J	J	N	N	N	J	J	M	M	M	M	M	M	K	K	K	P	N	N		
154		0.15										M	N	N	N	N	N	J	J	M	M	M	M	M	M	K	K	K	P	N	N		
224		0.22				G	J	J	J	J	J	M	N	N	N	N	N	J	M	M	Q	M	M	M	M	P	N	N	N	N	N		
334		0.33										N	N	N	N	N	N	J	M	P	Q	P	P	P	P	Q	X	X	X	X	X	X	
474		0.47				J	J	J	J	J	J	N	N	N	N	N	N	M	P	Q	P	P	P	P	P	Q	X	X	X	X	X		
684		0.68										N	N	N	N	N	N	M	Q	Q	Q	P	P	P	P	Q	X	X	X	X	X		
105		1										N	N	N	N	N	N	M	Q	Q	Q	P	Q	Q	Z	Z	X	X	X	X	X		
155		1.5										N	N	N	N	N	N	Q	Q	Q	Q	P	Q	Z	Z	Z	Z	Z	Z	Z	Z		
225		2.2										N	N	N	N	N	N	Q	Q	Q	Q	X	Z	Z	Z	Z	Z	Z	Z	Z	Z		
335		3.3																Q	Q	Q	Q	X	Z	Z	Z	Z	Z	Z	Z	Z	Z	Z	
475		4.7																Q	Q	Q	Q	X	Z	Z	Z	Z	Z	Z	Z	Z	Z	Z	
106		10																				Z	Z	Z	Z	Z	Z	Z	Z	Z	Z		
226		22																															
WVDC		16V	25V	50V	10V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	16V	25V	50V	100V	200V	250V	500V	16V	25V	50V	100V	50V	100V	25V	50V	100V
Size		0402			0603					0805					1206					1210			1812			2220							


Letter	A	C	E	G	J	K	M	N	P	Q	X	Y	Z
Max. Thickness	0.33 (0.013)	0.56 (0.022)	0.71 (0.028)	0.90 (0.035)	0.94 (0.037)	1.02 (0.040)	1.27 (0.050)	1.40 (0.055)	1.52 (0.060)	1.78 (0.070)	2.29 (0.090)	2.54 (0.100)	2.79 (0.110)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

FLEXISAFE MLC Chips

General Specifications and Capacitance Range For Ultra Safety Critical Applications



AVX have developed a range of components specifically for safety critical applications.

Utilizing the award-winning FLEXITERM™ layer in conjunction with the cascade design previously used for high voltage MLCCs, a range of ceramic capacitors is now available for customers who require components designed with an industry leading set of safety features.

The FLEXITERM™ layer protects the component from any damage to the ceramic resulting from mechanical stress during PCB assembly or use with end customers. Board flexure type mechanical damage accounts for the majority of MLCC failures. The addition of the cascade structure protects the component from low insulation resistance failure resulting from other common causes for failure; thermal stress damage, repetitive strike ESD damage and placement damage. With the inclusion of the cascade design structure to complement the FLEXITERM™ layer, the FLEXISAFE range of capacitors has unbeatable safety features.

HOW TO ORDER

FS05	5	C	104	K	Q	Z	2	A
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
FS03 = 0603	16V = Y	X7R = C	2 Sig. Digits + Number of Zeros e.g. 10µF = 106	J = ±5% K = ±10% M = ±20%	A = Commercial 4 = Automotive Q = APS	Z = FLEXITERM™ *X = FLEXITERM™ with 5% min lead *Not RoHS Compliant	2 = 7" Reel 4 = 13" Reel	A = Std. Product
FS05 = 0805	25V = 3							
FS06 = 1206	50V = 5							
FS10 = 1210	100V = 1							

CAPACITANCE RANGE FLEXISAFE X7R

SIZE	FS03 = 0603				FS05 = 0805				FS06 = 1206			FS10 = 1210			
	WVDC	16	25	50	100	16	25	50	100	16	25	50	16	25	50
102 1000	G	G	G	G	J	J	J	J	J	J	J	J			
182 1800	G	G	G	G	J	J	J	J	J	J	J	J			
222 2200	G	G	G	G	J	J	J	J	J	J	J	J			
332 3300	G	G	G	G	J	J	J	J	J	J	J	J			
472 4700	G	G	G	G	J	J	J	J	J	J	J	J			
682 6800	G	G	G	G	J	J	J	J	J	J	J	J			
103 0.01	G	G	G	G	J	J	J	J	J	J	J	J			
123 0.012	G	G	G		J	J	J	J	J	J	J	J			
153 0.015	G	G	G		J	J	J	J	J	J	J	J			
183 0.018	G	G	G		J	J	J	J	J	J	J	J			
223 0.022	G	G	G		N	N	N	N	J	J	J	J			
273 0.027					N	N	N	N	J	J	J	J			
333 0.033					N	N	N	N	J	J	J	J			
473 0.047					N	N	N	N	M	M	M	M			
563 0.056					N	N	N	N	M	M	M	M			
683 0.068					N	N	N	N	M	M	M	M			
823 0.082					N	N	N	N	M	M	M	M			
104 0.1					N	N	N	N	M	M	M	M			
124 0.12									M	M	M	M			
154 0.15									M	M	M	Q	Q	Q	
224 0.22												Q	Q	Q	
334 0.33												Q	Q	Q	
474 0.47												Q	Q	Q	

Letter	G	J	M	N	Q
Max. Thickness	0.90 (0.035)	0.94 (0.037)	1.27 (0.050)	1.40 (0.055)	1.78 (0.070)
	PAPER				EMBOSS



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

BENEFITS OF USING CAPACITOR ARRAYS

AVX capacitor arrays offer designers the opportunity to lower placement costs, increase assembly line output through lower component count per board and to reduce real estate requirements.

Reduced Costs

Placement costs are greatly reduced by effectively placing one device instead of four or two. This results in increased throughput and translates into savings on machine time. Inventory levels are lowered and further savings are made on solder materials, etc.

Space Saving

Space savings can be quite dramatic when compared to the use of discrete chip capacitors. As an example, the 0508 4-element array offers a space reduction of >40% vs. 4 x 0402 discrete capacitors and of >70% vs. 4 x 0603 discrete capacitors. (This calculation is dependent on the spacing of the discrete components.)

Increased Throughput

Assuming that there are 220 passive components placed in a mobile phone:

A reduction in the passive count to 200 (by replacing discrete components with arrays) results in an increase in throughput of approximately 9%.

A reduction of 40 placements increases throughput by 18%.


For high volume users of cap arrays using the very latest placement equipment capable of placing 10 components per second, the increase in throughput can be very significant and can have the overall effect of reducing the number of placement machines required to mount components:

If 120 million 2-element arrays or 40 million 4-element arrays were placed in a year, the requirement for placement equipment would be reduced by one machine.

During a 20Hr operational day a machine places 720K components. Over a working year of 167 days the machine can place approximately 120 million. If 2-element arrays are mounted instead of discrete components, then the number of placements is reduced by a factor of two and in the scenario where 120 million 2-element arrays are placed there is a saving of one pick and place machine.


Smaller volume users can also benefit from replacing discrete components with arrays. The total number of placements is reduced thus creating spare capacity on placement machines. This in turn generates the opportunity to increase overall production output without further investment in new equipment.

W2A (0508) Capacitor Arrays



The 0508 4-element capacitor array gives a PCB space saving of over 40% vs four 0402 discretes and over 70% vs four 0603 discrete capacitors.

W3A (0612) Capacitor Arrays



The 0612 4-element capacitor array gives a PCB space saving of over 50% vs four 0603 discretes and over 70% vs four 0805 discrete capacitors.

Capacitor Array

Capacitor Array (IPC)



0508 - 2 Element



0508 - 4 Element




0612 - 4 Element

GENERAL DESCRIPTION

AVX is the market leader in the development and manufacture of capacitor arrays. The array family of products also includes the 0612 4-element device as well as 0508 2-element and 4-element series, all of which have received widespread acceptance in the marketplace.

AVX capacitor arrays are available in X5R, X7R and NPO (C0G) ceramic dielectrics to cover a broad range of capacitance values. Voltage ratings from 6.3 Volts up to 100 Volts are offered. AVX also now offers a range of automotive capacitor arrays qualified to AEC-Q200 (see separate table).

Key markets for capacitor arrays are Mobile and Cordless Phones, Digital Set Top Boxes, Computer Motherboards and Peripherals as well as Automotive applications, RF Modems, Networking Products, etc.



HOW TO ORDER

W	2	A	4	3	C	103	M	A	T	2A
Style W = RoHS L = SnPb	Case Size 2 = 0508 3 = 0612	Array 2 = 2 Element 4 = 4 Element	Number of Caps	Voltage 6 = 6V Z = 10V Y = 16V 3 = 25V 5 = 50V 1 = 100V	Dielectric A = NPO C = X7R D = X5R	Capacitance Code 2 Sig. Digits + Number of Zeros	Capacitance Tolerance J = ±5% K = ±10% M = ±20%	Failure Rate A = Commercial 4 = Automotive	Termination Code *T = Plated Ni and Sn *Z = FLEXITERM® *B = 5% min lead *X = FLEXITERM® with 5% min lead	Packaging & Quantity Code 2A = 7" Reel (4000) 4A = 13" Reel (10000) 2F = 7" Reel (1000)

*RoHS Compliant

*Not RoHS Compliant



RoHS
COMPLIANT

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

Capacitor Array

Capacitance Range – NP0/C0G



SIZE	W2 = 0508			W3 = 0612		
# Elements	4			4		
Soldering	Reflow/Wave			Reflow/Wave		
Packaging	Paper/Embossed			Paper/Embossed		
Length	mm (in.)	1.30 ± 0.15 (0.051 ± 0.006)		1.60 ± 0.150 (0.063 ± 0.006)		
Width	mm (in.)	2.10 ± 0.15 (0.083 ± 0.006)		3.20 ± 0.20 (0.126 ± 0.008)		
Max. Thickness	mm (in.)	0.94 (0.037)		1.35 (0.053)		
	WVDC	16	25	50	16	25
1R0	Cap	1.0				
1R2	(pF)	1.2				
1R5		1.5				
1R8		1.8				
2R2		2.2				
2R7		2.7				
3R3		3.3				
3R9		3.9				
4R7		4.7				
5R6		5.6				
6R8		6.8				
8R2		8.2				
100		10				
120		12				
150		15				
180		18				
220		22				
270		27				
330		33				
390		39				
470		47				
560		56				
680		68				
820		82				
101		100				
121		120				
151		150				
181		180				
221		220				
271		270				
331		330				
391		390				
471		470				
561		560				
681		680				
821		820				
102		1000				
122		1200				
152		1500				
182		1800				
222		2200				
272		2700				
332		3300				
392		3900				
472		4700				
562		5600				
682		6800				
822		8200				

 = Supported Values

Capacitor Array


Capacitance Range – X7R

SIZE	W2 = 0508					W2 = 0508					W3 = 0612							
# Elements	2					4					4							
Soldering	Reflow/Wave					Reflow/Wave					Reflow/Wave							
Packaging	All Paper					Paper/Embossed					Paper/Embossed							
Length mm (in.)	1.30 ± 0.15 (0.051 ± 0.006)					1.30 ± 0.15 (0.051 ± 0.006)					1.60 ± 0.150 (0.063 ± 0.006)							
Width mm (in.)	2.10 ± 0.15 (0.083 ± 0.006)					2.10 ± 0.15 (0.083 ± 0.006)					3.20 ± 0.20 (0.126 ± 0.008)							
Max. Thickness mm (in.)	0.94 (0.037)					0.94 (0.037)					1.35 (0.053)							
WVDC	6	10	16	25	50	100	6	10	16	25	50	100	6	10	16	25	50	100
101 Cap	100																	
121 (PF)	120																	
151	150																	
181	180																	
221	220																	
271	270																	
331	330																	
391	390																	
471	470																	
561	560																	
681	680																	
821	820																	
102	1000																	
122	1200																	
152	1500																	
182	1800																	
222	2200																	
272	2700																	
332	3300																	
392	3900																	
472	4700																	
562	5600																	
682	6800																	
822	8200																	
103 Cap	0.010																	
123 (μF)	0.012																	
153	0.015																	
183	0.018																	
223	0.022																	
273	0.027																	
333	0.033																	
393	0.039																	
473	0.047																	
563	0.056																	
683	0.068																	
823	0.082																	
104	0.10																	
124	0.12																	
154	0.15																	
184	0.18																	
224	0.22																	
274	0.27																	
334	0.33																	
474	0.47																	
564	0.56																	
684	0.68																	
824	0.82																	
105	1.0																	
125	1.2																	
155	1.5																	
185	1.8																	
225	2.2																	
335	3.3																	
475	4.7																	
106	10																	
226	22																	
476	47																	
107	100																	

Capacitor Array



Automotive Capacitor Array (IPC)



As the market leader in the development and manufacture of capacitor arrays AVX is pleased to offer a range of AEC-Q200 qualified arrays to compliment our product offering to the Automotive industry. Both the AVX 0612 and 0508 4-element capacitor array styles are qualified to the AEC-Q200 automotive specifications.

AEC-Q200 is the Automotive Industry qualification standard and a detailed qualification package is available on request. All AVX automotive capacitor array production facilities are certified to ISO/TS 16949:2002.

HOW TO ORDER

W	3	A	4	Y	C	104	K	4	T	2A
Style	Case Size	Array	Number of Caps	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging & Quantity Code
W = RoHS	2 = 0508			Z = 10V	A = NPO	Significant Digits + Number of Zeros	*J = ±5%	4 = Automotive	*T = Plated Ni and Sn	2A = 7" Reel (4000)
L = SnPb	3 = 0612			Y = 16V	C = X7R	e.g. 10μF=106	*K = ±10%		*Z = FLEXITERM®	4A = 13" Reel (10000)
				3 = 25V	F = X8R		*M = ±20%		B = 5% min lead	2F = 7" Reel (1000)
				5 = 50V					X = FLEXITERM® with 5% min lead	
				1 = 100V						

*RoHS Compliant

*Contact factory for availability by part number for K = ±10% and J = ±5% tolerance.

NP0/COG

SIZE		W3 = 0612		
No. of Elements	Reflow/Wave	16	25	50
WVDC				
1R0	Cap 1.0 (pF)	1.0		
1R2		1.2		
1R5		1.5		
1R8		1.8		
2R2		2.2		
2R7		2.7		
3R3		3.3		
3R9		3.9		
4R7		4.7		
5R6		5.6		
6R8		6.8		
8R2		8.2		
100	10			
120	12			
150	15			
180	18			
220	22			
270	27			
330	33			
390	39			
470	47			
560	56			
680	68			
820	82			
101	100			
121	120			
151	150			
181	180			
221	220			
271	270			
331	330			
391	390			
471	470			
561	560			
681	680			
821	820			
102	1000			
122	1200			
152	1500			
182	1800			
222	2200			
272	2700			
332	3300			
392	3900			
472	4700			
562	5600			
682	6800			
822	8200			

= NPO/COG

SIZE		W2 = 0508				W2 = 0508				W3 = 0612				
No. of Elements	Reflow/Wave	2				4				4				
WVDC		16	25	50	100	16	25	50	100	10	16	25	50	100
101	Cap 100 (pF)	100												
121		120												
151		150												
181		180												
221		220												
271		270												
331		330												
391		390												
471		470												
561		560												
681		680												
821		820												
102		1000												
122		1200												
152		1500												
182		1800												
222		2200												
272		2700												
332		3300												
392		3900												
472		4700												
562		5600												
682		6800												
822		8200												

= X7R

*Not RoHS Compliant



LEAD-FREE
LEAD-FREE COMPATIBLE
COMPONENT



RoHS
COMPLIANT

For RoHS compliant products,
please select correct termination style.




The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or
available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

Capacitor Array

Part & Pad Layout Dimensions

PART & PAD LAYOUT DIMENSIONS

millimeters (inches)



PART DIMENSIONS

0508 - 2 Element

L	W	T	BW	BL	P	S
1.30 ± 0.15 (0.051 ± 0.006)	2.10 ± 0.15 (0.083 ± 0.006)	0.94 MAX (0.037 MAX)	0.43 ± 0.10 (0.017 ± 0.004)	0.33 ± 0.08 (0.013 ± 0.003)	1.00 REF (0.039 REF)	0.50 ± 0.10 (0.020 ± 0.004)

0508 - 4 Element

L	W	T	BW	BL	P	X	S
1.30 ± 0.15 (0.051 ± 0.006)	2.10 ± 0.15 (0.083 ± 0.006)	0.94 MAX (0.037 MAX)	0.25 ± 0.06 (0.010 ± 0.003)	0.20 ± 0.08 (0.008 ± 0.003)	0.50 REF (0.020 REF)	0.75 ± 0.10 (0.030 ± 0.004)	0.25 ± 0.10 (0.010 ± 0.004)

0612 - 4 Element

L	W	T	BW	BL	P	X	S
1.60 ± 0.20 (0.063 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	1.35 MAX (0.053 MAX)	0.41 ± 0.10 (0.016 ± 0.004)	$0.18^{+0.25}_{-0.08}$ ($0.007^{+0.010}_{-0.003}$)	0.76 REF (0.030 REF)	1.14 ± 0.10 (0.045 ± 0.004)	0.38 ± 0.10 (0.015 ± 0.004)

PAD LAYOUT DIMENSIONS

0508 - 2 Element

A	B	C	D	E
0.68 (0.027)	1.32 (0.052)	2.00 (0.079)	0.46 (0.018)	1.00 (0.039)

0508 - 4 Element

A	B	C	D	E
0.56 (0.022)	1.32 (0.052)	1.88 (0.074)	0.30 (0.012)	0.50 (0.020)

0612 - 4 Element

A	B	C	D	E
0.89 (0.035)	1.65 (0.065)	2.54 (0.100)	0.46 (0.018)	0.76 (0.030)

Low Inductance Capacitors

Introduction

The signal integrity characteristics of a Power Delivery Network (PDN) are becoming critical aspects of board level and semiconductor package designs due to higher operating frequencies, larger power demands, and the ever shrinking lower and upper voltage limits around low operating voltages. These power system challenges are coming from mainstream designs with operating frequencies of 300MHz or greater, modest ICs with power demand of 15 watts or more, and operating voltages below 3 volts.

The classic PDN topology is comprised of a series of capacitor stages. Figure 1 is an example of this architecture with multiple capacitor stages.

An ideal capacitor can transfer all its stored energy to a load instantly. A real capacitor has parasitics that prevent instantaneous transfer of a capacitor's stored energy. The true nature of a capacitor can be modeled as an RLC equivalent circuit. For most simulation purposes, it is possible to model the characteristics of a real capacitor with one capacitor, one resistor, and one inductor. The RLC values in this model are commonly referred to as equivalent series capacitance (ESC), equivalent series resistance (ESR), and equivalent series inductance (ESL).

The ESL of a capacitor determines the speed of energy transfer to a load. The lower the ESL of a capacitor, the faster that energy can be transferred to a load. Historically, there has been a tradeoff between energy storage (capacitance) and inductance (speed of energy delivery). Low ESL devices typically have low capacitance. Likewise, higher capacitance devices typically have higher ESLs. This tradeoff between ESL (speed of energy delivery) and capacitance (energy storage) drives the PDN design topology that places the fastest low ESL capacitors as close to the load as possible. Low Inductance MLCCs are found on semiconductor packages and on boards as close as possible to the load.




Figure 1 Classic Power Delivery Network (PDN) Architecture

LOW INDUCTANCE CHIP CAPACITORS

The key physical characteristic determining equivalent series inductance (ESL) of a capacitor is the size of the current loop it creates. The smaller the current loop, the lower the ESL. A standard surface mount MLCC is rectangular in shape with electrical terminations on its shorter sides. A Low Inductance Chip Capacitor (LICC) sometimes referred to as Reverse Geometry Capacitor (RGC) has its terminations on the longer side of its rectangular shape.

When the distance between terminations is reduced, the size of the current loop is reduced. Since the size of the current loop is the primary driver of inductance, an 0306 with a smaller current loop has significantly lower ESL than an 0603. The reduction in ESL varies by EIA size, however, ESL is typically reduced 60% or more with an LICC versus a standard MLCC.

INTERDIGITATED CAPACITORS

The size of a current loop has the greatest impact on the ESL characteristics of a surface mount capacitor. There is a secondary method for decreasing the ESL of a capacitor. This secondary method uses adjacent opposing current loops to reduce ESL. The InterDigitated Capacitor (IDC) utilizes both primary and secondary methods of reducing inductance. The IDC architecture shrinks the distance between terminations to minimize the current loop size, then further reduces inductance by creating adjacent opposing current loops.

An IDC is one single capacitor with an internal structure that has been optimized for low ESL. Similar to standard MLCC versus LICCs, the reduction in ESL varies by EIA case size. Typically, for the same EIA size, an IDC delivers an ESL that is at least 80% lower than an MLCC.

Low Inductance Capacitors

Introduction

LAND GRID ARRAY (LGA) CAPACITORS

Land Grid Array (LGA) capacitors are based on the first Low ESL MLCC technology created to specifically address the design needs of current day Power Delivery Networks (PDNs). This is the 3rd low inductance capacitor technology developed by AVX. LGA technology provides engineers with new options. The LGA internal structure and manufacturing technology eliminates the historic need for a device to be physically small to create small current loops to minimize inductance.

The first family of LGA products are 2 terminal devices. A 2 terminal 0306 LGA delivers ESL performance that is equal to or better than an 0306 8 terminal IDC. The 2 terminal 0805 LGA delivers ESL performance that approaches the 0508 8 terminal IDC. New designs that would have used 8 terminal IDCs are moving to 2 terminal LGAs because the layout is easier for a 2 terminal device and manufacturing yield is better for a 2 terminal LGA versus an 8 terminal IDC.

LGA technology is also used in a 4 terminal family of products that AVX is sampling and will formerly introduce in 2008. Beyond 2008, there are new multi-terminal LGA product families that will provide even more attractive options for PDN designers.

LOW INDUCTANCE CHIP ARRAYS (LICA®)

The LICA® product family is the result of a joint development effort between AVX and IBM to develop a high performance MLCC family of decoupling capacitors. LICA was introduced in the 1980s and remains the leading choice of designers in high performance semiconductor packages and high reliability board level decoupling applications.

LICA® products are used in 99.999% uptime semiconductor package applications on both ceramic and organic substrates. The C4 solder ball termination option is the perfect compliment to flip-chip packaging technology. Mainframe class CPUs, ultimate performance multi-chip modules, and communications systems that must have the reliability of 5 9's use LICA®.

LICA® products with either Sn/Pb or Pb-free solder balls are used for decoupling in high reliability military and aerospace applications. These LICA® devices are used for decoupling of large pin count FPGAs, ASICs, CPUs, and other high power ICs with low operating voltages.

When high reliability decoupling applications require the very lowest ESL capacitors, LICA® products are the best option.

470 nF 0306 Impedance Comparison




Figure 2 MLCC, LICC, IDC, and LGA technologies deliver different levels of equivalent series inductance (ESL).

Low Inductance Ceramic Capacitors

LICC (Low Inductance Chip Capacitors) 0306/0508/0612 RoHS Compliant




GENERAL DESCRIPTION

The key physical characteristic determining equivalent series inductance (ESL) of a capacitor is the size of the current loop it creates. The smaller the current loop, the lower the ESL.

A standard surface mount MLCC is rectangular in shape with electrical terminations on its shorter sides. A Low Inductance Chip Capacitor (LICC) sometimes referred to as Reverse Geometry Capacitor (RGC) has its terminations on the longer sides of its rectangular shape. The image on the right shows the termination differences between an MLCC and an LICC.

When the distance between terminations is reduced, the size of the current loop is reduced. Since the size of the current loop is the primary driver of inductance, an 0306 with a smaller current loop has significantly lower ESL than an 0603. The reduction in ESL varies by EIA size, however, ESL is typically reduced 60% or more with an LICC versus a standard MLCC.

AVX LICC products are available with a lead-free finish of plated Nickel/Tin.



PERFORMANCE CHARACTERISTICS

Capacitance Tolerances	K = $\pm 10\%$, M = $\pm 20\%$
Operation Temperature Range	X7R = -55°C to +125°C X5R = -55°C to +85°C X7S = -55°C to +125°C
Temperature Coefficient	X7R, X5R = $\pm 15\%$; X7S = $\pm 22\%$
Voltage Ratings	4, 6.3, 10, 16, 25 VDC
Dissipation Factor	4V, 6.3V = 6.5% max; 10V = 5.0% max; 16V = 3.5% max; 25V = 3.0% max
Insulation Resistance (@+25°C, RVDC)	100,000MΩ min, or 1,000MΩ per μ F min., whichever is less

HOW TO ORDER



0612	Z	D	105	M	A	T	2	A*
Size								
0306								
0508								
0612								
	Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging Available
	0306	4 = 4V	C = X7R	2 Sig. Digits + Number of Zeros	K = $\pm 10\%$ M = $\pm 20\%$	A = N/A 4 = Automotive**	Plated Ni and Sn	2 = 7" Reel 4 = 13" Reel
	0508	6 = 6.3V	D = X5R					
	0612	Z = 10V	W = X6S					
		Y = 16V	Z = X7S					
		3 = 25V						
		5 = 50V						
								Thickness Thickness
								mm (in)
								0.56 (0.022)
								0.76 (0.030)
								1.02 (0.040)
								1.27 (0.050)

*See the thickness tables on the next page.

**Select voltages for Automotive version, contact factory

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

TYPICAL IMPEDANCE CHARACTERISTICS



Low Inductance Ceramic Capacitors

LICC (Low Inductance Chip Capacitors) 0306/0508/0612 RoHS Compliant



SIZE		0306					0508					0612				
Packaging		Embossed					Embossed					Embossed				
Length		mm (in.)					0.81 ± 0.15 (0.032 ± 0.006)					1.27 ± 0.25 (0.050 ± 0.010)				
Width		mm (in.)					1.60 ± 0.15 (0.063 ± 0.006)					3.20 ± 0.25 (0.126 ± 0.010)				
Cap Code	WVDC	4	6.3	10	16	25	6.3	10	16	25	50	6.3	10	16	25	50
102	Cap 0.001	A	A	A	A	A	S	S	S	S	V	S	S	S	S	V
222	(μF) .0022	A	A	A	A	A	S	S	S	S	V	S	S	S	S	V
332	0.0033	A	A	A	A	A	S	S	S	S	V	S	S	S	S	V
472	0.0047	A	A	A	A	A	S	S	S	S	V	S	S	S	S	V
682	0.0068	A	A	A	A	A	S	S	S	S	V	S	S	S	S	V
103	0.01	A	A	A	A	A	S	S	S	S	V	S	S	S	S	V
153	0.015	A	A	A	A	A	S	S	S	S	V	S	S	S	S	W
223	0.022	A	A	A	A	A	S	S	S	S	V	S	S	S	S	W
333	0.033	A	A	A			S	S	S	V	V	S	S	S	S	W
473	0.047	A	A	A			S	S	S	V	A	S	S	S	S	W
683	0.068	A	A				S	S	S	A	A	S	S	S	V	W
104	0.1	A	A	A			S	S	V	A	A	S	S	S	V	W
154	0.15	A	A				S	S	V			S	S	S	W	W
224	0.22	A	A				S	S		A		S	S	V	W	
334	0.33						V	V				S	S	V		
474	0.47						V	V	A			S	S	V		
684	0.68						A	A				V	V	W		
105	1	A					A					V	V	A		
155	1.5						A					W	W			
225	2.2											A	A			
335	3.3											A				
475	4.7															
685	6.8															
106	10															

Solid = X7R

= X5R

= X7S

= X6S

mm (in.)

0306	
Code	Thickness
A	0.56 (0.022)


mm (in.)

0508	
Code	Thickness
S	0.56 (0.022)
V	0.76 (0.030)
A	1.02 (0.040)

mm (in.)

0612	
Code	Thickness
S	0.56 (0.022)
V	0.76 (0.030)
W	1.02 (0.040)
A	1.27 (0.050)

PHYSICAL DIMENSIONS AND PAD LAYOUT



PHYSICAL DIMENSIONS

mm (in.)


Size	L	W	t
0306	0.81 ± 0.15 (0.032 ± 0.006)	1.60 ± 0.15 (0.063 ± 0.006)	0.13 min. (0.005 min.)
0508	1.27 ± 0.25 (0.050 ± 0.010)	2.00 ± 0.25 (0.080 ± 0.010)	0.13 min. (0.005 min.)
0612	1.60 ± 0.25 (0.063 ± 0.010)	3.20 ± 0.25 (0.126 ± 0.010)	0.13 min. (0.005 min.)

T - See Range Chart for Thickness and Codes

PAD LAYOUT DIMENSIONS

mm (in.)

Size	A	B	C
0306	0.31 (0.012)	1.52 (0.060)	0.51 (0.020)
0508	0.51 (0.020)	2.03 (0.080)	0.76 (0.030)
0612	0.76 (0.030)	3.05 (0.120)	0.635 (0.025)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

Low Inductance Capacitors with SnPb Terminations



LD16/LD17/LD18 Tin-Lead Termination "B"


GENERAL DESCRIPTION

The key physical characteristic determining equivalent series inductance (ESL) of a capacitor is the size of the current loop it creates. The smaller the current loop, the lower the ESL.

A standard surface mount MLCC is rectangular in shape with electrical terminations on its shorter sides. A Low Inductance Chip Capacitor (LICC) sometimes referred to as Reverse Geometry Capacitor (RGC) has its terminations on the longer sides of its rectangular shape. The image on the right shows the termination differences between an MLCC and an LICC.

When the distance between terminations is reduced, the size of the current loop is reduced. Since the size of the current loop is the primary driver of inductance, an 0306 with a smaller current loop has significantly lower ESL than an 0603. The reduction in ESL varies by EIA size, however, ESL is typically reduced 60% or more with an LICC versus a standard MLCC.

AVX LICC products are available with a lead termination for high reliability military and aerospace applications that must avoid tin whisker reliability issues.



***Not RoHS Compliant**

PERFORMANCE CHARACTERISTICS

Capacitance Tolerances	K = $\pm 10\%$; M = $\pm 20\%$
Operation Temperature Range	X7R = -55°C to +125°C X5R = -55°C to +85°C X7S = -55°C to +125°C
Temperature Coefficient	X7R, X5R = $\pm 15\%$; X7S = $\pm 22\%$
Voltage Ratings	4, 6.3, 10, 16, 25 VDC
Dissipation Factor	4V, 6.3V = 6.5% max; 10V = 5.0% max; 16V = 3.5% max; 25V = 3.0% max
Insulation Resistance (@+25°C, RVDC)	100,000MΩ min, or 1,000MΩ per μF min., whichever is less



HOW TO ORDER

LD18	Z	D	105	M	A	B	2	A*
Size	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Terminations	Packaging Available	Thickness Thickness
LD16 = 0306	4 = 4V	C = X7R	2 Sig. Digits + Number of Zeros	K = $\pm 10\%$	A = N/A	B = 5% min lead	2 = 7" Reel	mm (in)
LD17 = 0508	6 = 6.3V	D = X5R		M = $\pm 20\%$			4 = 13" Reel	0.56 (0.022)
LD18 = 0612	Z = 10V	W = X6S						0.76 (0.030)
	Y = 16V	Z = X7S						1.02 (0.040)
	3 = 25V							1.27 (0.050)
	5 = 50V							

*See the thickness tables on the next page.

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

TYPICAL IMPEDANCE CHARACTERISTICS



Low Inductance Capacitors with SnPb Terminations



LD16/LD17/LD18 Tin-Lead Termination "B"

SIZE		LD16 (0306)				LD17 (0508)				LD18 (0612)			
Packaging		Embossed				Embossed				Embossed			
Length	mm (in.)	0.81 ± 0.15 (0.032 ± 0.006)				1.27 ± 0.25 (0.050 ± 0.010)				1.60 ± 0.25 (0.063 ± 0.010)			
Width	mm (in.)	1.60 ± 0.15 (0.063 ± 0.006)				2.00 ± 0.25 (0.080 ± 0.010)				3.20 ± 0.25 (0.126 ± 0.010)			
Cap Code	WVDC	6.3	10	16	25	6.3	10	16	25	6.3	10	16	25
102	Cap 0.001	A	A	A	A	S	S	S	S	V	S	S	S
222	(μF).0022	A	A	A	A	S	S	S	S	V	S	S	S
332	0.0033	A	A	A	A	S	S	S	S	V	S	S	S
472	0.0047	A	A	A	A	S	S	S	S	V	S	S	S
682	0.0068	A	A	A	A	S	S	S	S	V	S	S	S
103	0.01	A	A	A	A	S	S	S	S	V	S	S	S
153	0.015	A	A	A	A	S	S	S	S	V	S	S	S
223	0.022	A	A	A	A	S	S	S	S	V	S	S	S
333	0.033	A	A	A		S	S	S	V	V	S	S	S
473	0.047	A	A	A		S	S	S	V	A	S	S	S
683	0.068	A	A	A		S	S	S	A	A	S	S	S
104	0.1	A	A	A		S	S	V	A	A	S	S	S
154	0.15	A	A			S	S	V			S	S	S
224	0.22	A	A			S	S	A			S	S	V
334	0.33					V	V	A			S	S	V
474	0.47					V	V	A			S	S	V
684	0.68					A	A				V	V	W
105	1					A	A				V	V	A
155	1.5					A	A				W	W	
225	2.2										A	A	
335	3.3										A	A	
475	4.7												
685	6.8												
106	10												

Solid = X7R

= X5R

= X6S

mm (in.)

LD16 (0306)	
Code	Thickness
A	0.56 (0.022)


mm (in.)

LD17 (0508)	
Code	Thickness
S	0.56 (0.022)
V	0.76 (0.030)

mm (in.)

LD18 (0612)	
Code	Thickness
S	0.56 (0.022)
V	0.76 (0.030)
W	1.02 (0.040)
A	1.27 (0.050)

PHYSICAL DIMENSIONS AND PAD LAYOUT



PHYSICAL DIMENSIONS

mm (in.)


Size	L	W	t
LD16 (0306)	0.81 ± 0.15 (0.032 ± 0.006)	1.60 ± 0.15 (0.063 ± 0.010)	0.13 min. (0.005 min.)
LD17 (0508)	1.27 ± 0.25 (0.050 ± 0.010)	2.00 ± 0.25 (0.080 ± 0.010)	0.13 min. (0.005 min.)
LD18 (0612)	1.60 ± 0.25 (0.063 ± 0.010)	3.20 ± 0.25 (0.126 ± 0.010)	0.13 min. (0.005 min.)

T - See Range Chart for Thickness and Codes

PAD LAYOUT DIMENSIONS

mm (in.)

Size	A	B	C
LD16 (0306)	0.31 (0.012)	1.52 (0.060)	0.51 (0.020)
LD17 (0508)	0.51 (0.020)	2.03 (0.080)	0.76 (0.030)
LD18 (0612)	0.76 (0.030)	3.05 (0.120)	0.635 (0.025)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

IDC Low Inductance Capacitors (RoHS)

IDC (InterDigitated Capacitors) 0306/0612/0508



GENERAL DESCRIPTION


Inter-Digitated Capacitors (IDCs) are used for both semiconductor package and board level decoupling. The equivalent series inductance (ESL) of a single capacitor or an array of capacitors in parallel determines the response time of a Power Delivery Network (PDN). The lower the ESL of a PDN, the faster the response time. A designer can use many standard MLCCs in parallel to reduce ESL or a low ESL Inter-Digitated Capacitor (IDC) device. These IDC devices are available in versions with a maximum height of 0.95mm or 0.55mm.

IDCs are typically used on packages of semiconductor products with power levels of 15 watts or greater. Inter-Digitated Capacitors are used on CPU, GPU, ASIC, and ASSP devices produced on 0.13 μ , 90nm, 65nm, and 45nm processes. IDC devices are used on both ceramic and organic package substrates. These low ESL surface mount capacitors can be placed on the bottom side or the top side of a package substrate. The low profile 0.55mm maximum height IDCs can easily be used on the bottom side of BGA packages or on the die side of packages under a heat spreader.


IDCs are used for board level decoupling of systems with speeds of 300MHz or greater. Low ESL IDCs free up valuable board space by reducing the number of capacitors required versus standard MLCCs. There are additional benefits to reducing the number of capacitors beyond saving board space including higher reliability from a reduction in the number of components and lower placement costs based on the need for fewer capacitors.

The Inter-Digitated Capacitor (IDC) technology was developed by AVX. This is the second family of Low Inductance MLCC products created by AVX. IDCs are a cost effective alternative to AVX's first generation low ESL family for high-reliability applications known as LICA (Low Inductance Chip Array).

AVX IDC products are available with a lead-free finish of plated Nickel/Tin.



TYPICAL IMPEDANCE



HOW TO ORDER

W	3	L	1	6	D	225	M	A	T	3	A
Style	IDC Case Size	Low Inductance	Number of Terminals	Voltage	Dielectric	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Termination	Packaging Available	Thickness Max. Thickness
	2 = 0508		1 = 8 Terminals	4 = 4V	C = X7R	2 Sig. Digits + Number of Zeros	M = $\pm 20\%$	A = N/A	T = Plated Ni and Sn	1 = 7" Reel	mm (in)
	3 = 0612		6 = 6.3V	D = X5R						3 = 13" Reel	A = Standard
	4 = 0306		Z = 10V	Z = X7S							S = 0.55 (0.022)
			Y = 16V								
			3 = 25V								

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.



PERFORMANCE CHARACTERISTICS

Capacitance Tolerance	$\pm 20\%$ Preferred
Operation Temperature Range	X7R = -55°C to +125°C X5R = -55°C to +85°C X7S = -55°C to +125°C
Temperature Coefficient	$\pm 15\%$ (0VDC), $\pm 22\%$ (X7S)
Voltage Ratings	4, 6.3, 10, 16, 25 VDC
Dissipation Factor	$\leq 6.3V = 6.5\%$ max; 10V = 5.0% max; $\geq 16V = 3.5\%$ max
Insulation Resistance (@+25°C, RVDC)	100,000M Ω min, or 1,000M Ω per μ F min., whichever is less

Dissipation Factor	No problems observed after 2.5 x RVDC for 5 seconds at 50mA max current
CTE (ppm/C)	12.0
Thermal Conductivity	4-5W/M K
Terminations Available	Plated Nickel and Solder

IDC Low Inductance Capacitors (RoHS)

IDC (InterDigitated Capacitors) 0306/0612/0508




SIZE	W4 = 0306		W2 = Thin 0508				W2 = 0508				W3= Thin 0612				W3 = 0612				W3 = THICK 0612						
Max. Thickness (mm) (in.)	0.55 (0.022)		0.55. (0.022)				0.95 (0.037)				0.55 (0.022)				0.95 (0.037)				1.22 (0.048)						
WVDC	4	6.3	4	6.3	10	16	25	4	6.3	10	16	25	4	6.3	10	16	4	6.3	10	16	25	4	6.3	10	16
Cap (μF)	0.010																								
	0.022																								
	0.033																								
	0.047																								
	0.068																								
	0.10																								
	0.22																								
	0.33																								
	0.47																								
	0.68																								
	1.0																								
	1.5																								
	2.2																								
	3.3																								

PHYSICAL DIMENSIONS AND PAD LAYOUT

Consult factory for additional requirements

- = X7R
- = X5R
- = X7S



PHYSICAL CHIP DIMENSIONS MILLIMETERS (INCHES)

SIZE	W	L	BW	BL	P
0306	1.60 ± 0.20 (0.063 ± 0.008)	0.82 ± 0.10 (0.032 ± 0.006)	0.25 ± 0.10 (0.010 ± 0.004)	0.20 ± 0.10 (0.008 ± 0.004)	0.40 ± 0.05 (0.015 ± 0.002)
0508	2.03 ± 0.20 (0.080 ± 0.008)	1.27 ± 0.20 (0.050 ± 0.008)	0.30 ± 0.10 (0.012 ± 0.004)	0.25 ± 0.15 (0.010 ± 0.006)	0.50 ± 0.05 (0.020 ± 0.002)
0612	3.20 ± 0.20 (0.126 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	0.50 ± 0.10 (0.020 ± 0.004)	0.25 ± 0.15 (0.010 ± 0.006)	0.80 ± 0.10 (0.031 ± 0.004)

PAD LAYOUT DIMENSIONS

SIZE	A	B	C	D	E
0306	0.38 (0.015)	0.89 (0.035)	1.27 (0.050)	0.20 (0.008)	0.40 (0.015)
0508	0.64 (0.025)	1.27 (0.050)	1.91 (0.075)	0.28 (0.011)	0.50 (0.020)
0612	0.89 (0.035)	1.65 (0.065)	2.54 (0.010)	0.45 (0.018)	0.80 (0.031)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

IDC Low Inductance Capacitors (SnPb)

IDC (InterDigitated Capacitors) 0306/0612/0508



GENERAL DESCRIPTION


Inter-Digitated Capacitors (IDCs) are used for both semiconductor package and board level decoupling. The equivalent series inductance (ESL) of a single capacitor or an array of capacitors in parallel determines the response time of a Power Delivery Network (PDN). The lower the ESL of a PDN, the faster the response time. A designer can use many standard MLCCs in parallel to reduce ESL or a low ESL Inter-Digitated Capacitor (IDC) device. These IDC devices are available in versions with a maximum height of 0.95mm or 0.55mm.

IDCs are typically used on packages of semiconductor products with power levels of 15 watts or greater. Inter-Digitated Capacitors are used on CPU, GPU, ASIC, and ASSP devices produced on 0.13 μ , 90nm, 65nm, and 45nm processes. IDC devices are used on both ceramic and organic package substrates. These low ESL surface mount capacitors can be placed on the bottom side or the top side of a package substrate. The low profile 0.55mm maximum height IDCs can easily be used on the bottom side of BGA packages or on the die side of packages under a heat spreader.


IDCs are used for board level decoupling of systems with speeds of 300MHz or greater. Low ESL IDCs free up valuable board space by reducing the number of capacitors required versus standard MLCCs. There are additional benefits to reducing the number of capacitors beyond saving board space including higher reliability from a reduction in the number of components and lower placement costs based on the need for fewer capacitors.

The Inter-Digitated Capacitor (IDC) technology was developed by AVX. This is the second family of Low Inductance MLCC products created by AVX. IDCs are a cost effective alternative to AVX's first generation low ESL family for high-reliability applications known as LICA (Low Inductance Chip Array).

AVX IDC products are available with a lead termination for high reliability military and aerospace applications that must avoid tin whisker reliability issues.



TYPICAL IMPEDANCE



HOW TO ORDER

L Style	3 IDC Case Size	L Low Inductance	1 Number of Terminals	6 Voltage 4 = 4V 6 = 6.3V Z = 10V Y = 16V 3 = 25V	D Dielectric C = X7R D = X5R Z = X7S	225 Capacitance Code (In pF) 2 Sig. Digits + Number of Zeros	M Capacitance Tolerance M = $\pm 20\%$	A Failure Rate A = N/A	B Termination B = 5% min. Lead	3 Packaging Available 1=7" Reel 3=13" Reel	A Thickness Max. Thickness mm (in) A=Standard S=0.55 (0.022)
	2 = 0508		1 = 8 Termi- nals								

NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

***Not RoHS Compliant**

PERFORMANCE CHARACTERISTICS

Capacitance Tolerance	$\pm 20\%$ Preferred
Operation Temperature Range	X7R = -55°C to +125°C X5R = -55°C to +85°C X7S = -55°C to +125°C
Temperature Coefficient	$\pm 15\%$ (0VDC), $\pm 22\%$ (X7S)
Voltage Ratings	4, 6.3, 10, 16, 25 VDC
Dissipation Factor	$\leq 6.3V = 6.5\% \text{ max};$ $10V = 5.0\% \text{ max};$ $\geq 16V = 3.5\% \text{ max}$
Insulation Resistance (@+25°C, RVDC)	100,000M Ω min, or 1,000M Ω per μF min., whichever is less

Dissipation Factor	No problems observed after 2.5 x RVDC for 5 seconds at 50mA max current
CTE (ppm/C)	12.0
Thermal Conductivity	4-5W/M K
Terminations Available	Plated Nickel and Solder


IDC Low Inductance Capacitors (SnPb)

IDC (InterDigitated Capacitors) with Sn/Pb Termination 0306/0612/0508

SIZE	W4 = 0306		W2 = Thin 0508				W2 = 0508				W3= Thin 0612				W3 = 0612				W3 = THICK 0612						
Max. Thickness mm (in.)	0.55 (0.022)		0.55 (0.022)				0.95 (0.037)				0.55 (0.022)				0.95 (0.037)				1.22 (0.048)						
WVDC	4	6.3	4	6.3	10	16	25	4	6.3	10	16	25	4	6.3	10	16	4	6.3	10	16	25	4	6.3	10	16
Cap (μF)	0.010																								
	0.022																								
	0.033																								
	0.047																								
	0.068																								
	0.10																								
	0.22																								
	0.33																								
	0.47																								
	0.68																								
	1.0																								
	1.5																								
	2.2																								
	3.3																								

PHYSICAL DIMENSIONS AND PAD LAYOUT

Consult factory for additional requirements



 = X7R
 = X5R
 = X7S

PHYSICAL CHIP DIMENSIONS MILLIMETERS (INCHES)

SIZE	W	L	BW	BL	P
0306	1.60 ± 0.20 (0.063 ± 0.008)	0.82 ± 0.10 (0.032 ± 0.006)	0.25 ± 0.10 (0.010 ± 0.004)	0.20 ± 0.10 (0.008 ± 0.004)	0.40 ± 0.05 (0.015 ± 0.002)
0508	2.03 ± 0.20 (0.080 ± 0.008)	1.27 ± 0.20 (0.050 ± 0.008)	0.30 ± 0.10 (0.012 ± 0.004)	0.25 ± 0.15 (0.010 ± 0.006)	0.50 ± 0.05 (0.020 ± 0.002)
0612	3.20 ± 0.20 (0.126 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	0.50 ± 0.10 (0.020 ± 0.004)	0.25 ± 0.15 (0.010 ± 0.006)	0.80 ± 0.10 (0.031 ± 0.004)

PAD LAYOUT DIMENSIONS

SIZE	A	B	C	D	E
0306	0.38 (0.015)	0.89 (0.035)	1.27 (0.050)	0.20 (0.008)	0.40 (0.015)
0508	0.64 (0.025)	1.27 (0.050)	1.91 (0.075)	0.28 (0.011)	0.50 (0.020)
0612	0.89 (0.035)	1.65 (0.065)	2.54 (0.010)	0.45 (0.018)	0.80 (0.031)

LGA Low Inductance Capacitors

0204/0306 Land Grid Array



Land Grid Array (LGA) capacitors are the latest family of low inductance MLCCs from AVX. These new LGA products are the third low inductance family developed by AVX. The innovative LGA technology sets a new standard for low inductance MLCC performance.

Our initial 2 terminal versions of LGA technology deliver the performance of an 8 terminal IDC low inductance MLCC with a number of advantages including:

- Simplified layout of 2 large solder pads compared to 8 small pads for IDCs
- Opportunity to reduce PCB or substrate contribution to system ESL by using multiple parallel vias in solder pads
- Advanced FCT manufacturing process used to create uniformly flat terminations on the capacitor that resist "tombstoning"
- Better solder joint reliability

APPLICATIONS


Semiconductor Packages

- Microprocessors/CPUs
- Graphics Processors/GPUs
- Chipsets
- FPGAs
- ASICs

Board Level Device Decoupling

- Frequencies of 300 MHz or more
- ICs drawing 15W or more
- Low voltages
- High speed buses

0306 2 TERMINAL LGA COMPARISON WITH 0306 8 TERMINAL IDC



LGA Low Inductance Capacitors

0204/0306 Land Grid Array




SIZE	LG12 (0204)					LG22 (0306)							
Length mm (in.)	0.50 (0.020)					0.76 (0.030)							
Width mm (in.)	1.00 (0.039)					1.60 (0.063)							
Temp. Char.	X5R (D)	X7S (Z)	X6S (W)	X7R (C)	X5R (D)	X7S (Z)	X6S (W)						
Working Voltage	6.3 (6)	4 (4)	6.3 (6)	4 (4)	6.3 (6)	4 (4)	6.3 (6)	4 (4)	6.3 (6)	4 (4)	6.3 (6)	4 (4)	
Cap (μF)	0.010 (103)												
	0.022 (223)												
	0.047 (473)												
	0.100 (104)												
	0.220 (224)												
	0.330 (334)												
	0.470 (474)												
	1.000 (105)												
	2.200 (225)												

= X7R = X5R = X7S = X6S

HOW TO ORDER

LG	1	2	6	Z	104	M	A	T	2	S	1
Style	Case Size	Number of Terminals	Working Voltage	Temperature Characteristic	Coded Cap	Cap Tolerance	Termination Style	Termination			
	1 = 0204 2 = 0306	2	4=4V 6=6.3V Z=10V	C = X7R D = X5R Z = X7S W = X6S	M = ±20%	A = "U" Land	100% Sn*				
								*Contact factory for other termination finishes			
									Packaging Tape & Reel	Thickness	Number of Capacitors
									2 = 7" Reel 4 = 13" Reel	S = 0.55mm max	1




PART DIMENSIONS

MM (INCHES)

Series	L	W	T	BW	BL
LG12 (0204)	0.5 ± 0.05 (0.020 ± 0.002)	1.00 ± 0.10 (0.039 ± 0.004)	0.50 ± 0.05 (0.020 ± 0.002)	0.8 ± 0.10 (0.031 ± 0.004)	0.13 ± 0.08 (0.005 ± 0.003)
LG22 (0306)	0.76 ± 0.10 (0.030 ± 0.004)	1.60 ± 0.10 (0.063 ± 0.004)	0.50 ± 0.05 (0.020 ± 0.002)	1.50 ± 0.10 (0.059 ± 0.004)	0.28 ± 0.08 (0.011 ± 0.003)



RECOMMENDED SOLDER PAD DIMENSIONS MM (INCHES)



Series	PL	PW1	G
LG12 (0204)	0.50 (0.020)	1.00 (0.039)	0.20 (0.008)
LG22 (0306)	0.65 (0.026)	1.50 (0.059)	0.20 (0.008)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

LGA Low Inductance Capacitors

0204/0306 Land Grid Array – Tin/Lead Termination “B”


SIZE	PG12 (0204)				PG22 (0306)							
Length mm (in.)	0.50 (0.020)				0.76 (0.030)							
Width mm (in.)	1.00 (0.039)				1.60 (0.063)							
Temp. Char.	X5R (D)	X7S (Z)	X6S (W)		X7R (C)	X5R (D)	X7S (Z)	X6S (W)				
Working Voltage	6.3 (6) (4)	4 (6) (4)	6.3 (6) (4)	4 (6) (4)	10 (Z) (6) (4)	6.3 (6) (4)	4 (6) (4)	6.3 (6) (4)	4 (6) (4)	6.3 (6) (4)	4 (6) (4)	
Cap (μF)	0.010 (103)											
	0.022 (223)											
	0.047 (473)											
	0.100 (104)											
	0.220 (224)											
	0.330 (334)											
	0.470 (474)											
	1.000 (105)											
	2.200 (225)											

 = X7R  = X5R  = X7S  = X6S

HOW TO ORDER

PG	1	2	6	Z	104	M	A	B	2	S	1
Style	Case Size	Number of Terminals	Working Voltage	Temperature Characteristic	Coded Cap	Cap Tolerance	Termination Style	Termination	Packaging	Thickness	Number of Capacitors
	1 = 0204 2 = 0306	2	4=4V 6=6.3V Z=10V	C = X7R D = X5R Z = X7S W = X6S	M = ±20%	A = "U" Land	5% Min Lead	5% Min Lead	2 = 7" Reel 4 = 13" Reel	S = 0.55mm max	

***Not RoHS Compliant**



PART DIMENSIONS

MM (INCHES)

Series	L	W	T	BW	BL
PG12 (0204)	0.5 ± 0.05 (0.020 ± 0.002)	1.00 ± 0.10 (0.039 ± 0.004)	0.50 ± 0.05 (0.020 ± 0.002)	0.8 ± 0.10 (0.031 ± 0.004)	0.13 ± 0.08 (0.005 ± 0.003)
PG22 (0306)	0.76 ± 0.10 (0.030 ± 0.004)	1.60 ± 0.10 (0.063 ± 0.004)	0.50 ± 0.05 (0.020 ± 0.002)	1.50 ± 0.10 (0.059 ± 0.004)	0.28 ± 0.08 (0.011 ± 0.003)


RECOMMENDED SOLDER PAD DIMENSIONS

MM (INCHES)

Series	PL	PW1	G
PG12 (0204)	0.50 (0.020)	1.00 (0.039)	0.20 (0.008)
PG22 (0306)	0.65 (0.026)	1.50 (0.059)	0.20 (0.008)

High Temperature MLCCs

AT Series – 200°C & 250°C Rated



Present military specifications, as well as a majority of commercial applications, require a maximum operating temperature of 125°C. However, the emerging market for high temperature electronics demands capacitors operating reliably at temperatures beyond 125°C. AVX's high temperature chip capacitor product line, has been extended with the BME COG chip. All AT chips have verified capabilities of long term operation up to 250°C for applications in both military and commercial businesses. These capacitors demonstrate high volumetric efficiency, high insulation resistance and low ESR/ESL for the most demanding applications, such as "down-hole" oil exploration and aerospace programs.

HOW TO ORDER

AT10	3	T	104	K	A	T	2	A
AVX Style	Voltage Code	Temperature Coefficient	Capacitance Code	Capacitance Tolerance	Test Level	Termination	Packaging	Special Code
AT03 = 0603	16V = Y	PME	(2 significant digits + no. of zeros)	J = ±5%	1 = Standard	1 = Pd/Ag	2 = 7" Reel	A = Standard
AT05 = 0805	25V = 3	COG 250°C = A	101 = 100pF	K = ±10%	T = 100% Sn Plated (RoHS Compliant)	4 = 13" Reel		
AT06 = 1206	50V = 5	COG 200°C = 2	102 = 1nF	M = ±20%	7 = Ni/Au Plated (For 250°C BME COG Only)	9 = Bulk		
AT10 = 1210		VHT 250°C = T	103 = 10nF					
AT12 = 1812		VHT 200°C = 4	104 = 100nF					
AT14 = 2225		BME	105 = 1μF					
		COG 250°C = 5						
		COG 200°C = 3						

ELECTRICAL SPECIFICATIONS

Temperature Coefficient

PME COG 0±30ppm/°C, -55C to 250°C
BME COG 0±30ppm/°C, -55C to 200°C

See TCC Plot for +250°C

VHT: T ±15%, -55°C to +150°C
See TCC Plot for +250°C

Capacitance Test (MIL-STD-202, Method 305)
25°C, 1.0 ± 0.2 Vrms (open circuit voltage) @ 1kHz

Dissipation factor 25°C
COG: 0.15% Max at 1.0 ± 0.2 Vrms (open circuit voltage) @ 1kHz
VHT: 2.5% Max at 1.0 ± 0.2 Vrms (open circuit voltage) @ 1kHz

Insulation Resistance 25°C (MIL-STD-202, Method 302)
100GΩ or 1000MΩ-μF (whichever is less)


Insulation Resistance 125°C (MIL-STD-202, Method 302)
10GΩ or 100MΩ-μF (whichever is less)

Insulation Resistance 200°C (MIL-STD-202, Method 302)
1GΩ or 10MΩ-μF (whichever is less)

Insulation Resistance 250°C (MIL-STD-202, Method 302)
100MΩ or 1MΩ-μF (whichever is less)

Direct Withstanding Voltage 25°C (Flash Test)
250% rated voltage for 5 seconds with 50mA max charging current

DIMENSIONS:



Size	AT03 = 0603	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225
(L) Length	1.60 ± 0.15 (0.063 ± 0.006)	2.01 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	4.50 ± 0.30 (0.177 ± 0.012)	5.72 ± 0.25 (0.225 ± 0.010)
(W) Width	0.81 ± 0.15 (0.032 ± 0.006)	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	2.50 ± 0.20 (0.098 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	6.35 ± 0.25 (0.250 ± 0.010)
(T) Thickness Max.	1.02 (0.040)	1.30 (0.051)	1.52 (0.060)	1.70 (0.067)	2.54 (0.100)	2.54 (0.100)
(t) terminal	min. 0.25 (0.010)	0.25 (0.010)	0.25 (0.010)	0.25 (0.010)	0.25 (0.010)	0.25 (0.010)
max.	0.75 (0.030)	0.75 (0.030)	0.75 (0.030)	0.75 (0.030)	1.02 (0.040)	1.02 (0.040)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.


High Temperature MLCC

AT Series – 200°C & 250°C Rated




PERFORMANCE CHARACTERISTICS


Typical Temperature Coefficient of Capacitance (VHT Dielectric)




Typical Temperature Coefficient of Capacitance (COG Dielectric)




Typical Voltage Coefficient of Capacitance (VHT Dielectric)




Typical Voltage Coefficient of Capacitance (COG Dielectric)



Typical RC vs Temperature (VHT Dielectric)



Typical RC vs Temperature (COG Dielectric)




High Temperature MLCC


AT Series – 200°C & 250°C Rated

RELIABILITY

250°C Life Test @ 2x Rated Voltage (VHT Dielectric)



250°C Life Test @ 2x Rated Voltage (C0G Dielectric)



VHT - Failure Rate @ 90% Confidence Level (%/1000 hours)

Temperature (°C)	50% Rated Voltage	100% Rated Voltage
200	0.002	0.017
250	0.026	0.210

*Typical 1210, 1812, 2225 Failure Rate Analysis based on 250°C testing and voltage ratings specified on the following page.


COG - Failure Rate @ 90% Confidence Level (%/1000 hours)

Temperature (°C)	50% Rated Voltage	100% Rated Voltage
200	0.006	0.047
250	0.074	0.590


*Typical 1812 and 2225 Failure Rate Analysis based on 250°C testing and voltage ratings specified on the following page.

FREQUENCY RESPONSE


Impedance Frequency Response (VHT Dielectric)




Impedance Frequency Response (C0G Dielectric)



ESR Frequency Response (VHT Dielectric)



ESR Frequency Response (C0G Dielectric)



High Temperature MLCC

AT Series – 200°C & 250°C Rated



CAPACITANCE RANGE

PREFERRED SIZES ARE SHADED

VHT

Temp. Coefficient: 4 200°C Rated

Case Size	AT03 = 0603	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225
Soldering	Reflow/Wave	Reflow/Wave	Reflow/Wave	Reflow Only	Reflow Only	Reflow Only
(L) Length	mm 1.60±0.15 (in.) (0.063±0.006)	2.01±0.20 (0.079±0.008)	3.20±0.20 (0.126±0.008)	4.50±0.30 (0.177±0.012)	5.72±0.25 (0.225±0.010)	
(W) Width	mm 0.81±0.15 (in.) (0.032±0.006)	1.25±0.20 (0.049±0.008)	2.50±0.20 (0.063±0.008)	3.20±0.20 (0.098±0.008)	6.35±0.25 (0.126±0.008)	6.35±0.25 (0.250±0.010)
(T) Thickness	mm 1.02 (in.) (0.040)	1.30 (0.051)	1.52 (0.060)	1.70 (0.100)	2.54 (0.100)	2.54
(t) Terminal	min 0.25(0.010)	0.25(0.010)	0.25(0.010)	0.25(0.010)	0.25(0.010)	0.25(0.010)
max	0.75(0.030)	0.75(0.030)	0.75(0.030)	0.75(0.030)	1.02(0.040)	1.02(0.040)
Rated Temp. (°C)	200	200	200	200	200	200
Temp. Coefficient	4	4	4	4	4	4
Voltage (V)	25	25	50	25	50	50
Cap (pF)	1000 102					
	1200 122					
	1500 152					
	1800 182					
	2200 222					
	2700 272					
Cap (pF)	3300 332					
	3900 392					
	4700 472					
	5600 562					
	6800 682					
	8200 822					
Cap (pF)	0.010 103					
	0.012 123					
	0.015 153					
	0.018 183					
	0.022 223					
	0.027 273					
Cap (pF)	0.033 333					
	0.039 393					
	0.047 473					
	0.056 563					
Cap (pF)	0.068 683					
	0.082 823					
	0.100 104					
	0.120 124					
	0.150 154					
	0.180 184					
	0.220 224					
	0.270 274					
	0.330 334					
	0.390 394					
	0.470 474					
	0.560 564					
	0.680 684					
	0.820 824					
	1.000 105					
Voltage (V)	25	25	50	25	50	50
Rated Temp. (°C)	200	200	200	200	200	200
Case Size	AT03 = 0603	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225

VHT

Temp. Coefficient: T 250°C Rated

Case Size	AT03 = 0603	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225
Soldering	Reflow/Wave	Reflow/Wave	Reflow/Wave	Reflow Only	Reflow Only	Reflow Only
(L) Length	mm 1.60±0.15 (in.) (0.063±0.006)	2.01±0.20 (0.079±0.008)	3.20±0.20 (0.126±0.008)	3.20±0.20 (0.126±0.008)	4.50±0.30 (0.177±0.012)	5.72±0.25 (0.225±0.010)
(W) Width	mm 0.81±0.15 (in.) (0.032±0.006)	1.25±0.20 (0.049±0.008)	2.50±0.20 (0.063±0.008)	3.20±0.20 (0.098±0.008)	6.35±0.25 (0.126±0.008)	6.35±0.25 (0.250±0.010)
(T) Thickness	mm 1.02 (in.) (0.040)	1.30 (0.051)	1.52 (0.060)	1.70 (0.100)	2.54 (0.100)	2.54
(t) Terminal	min 0.25(0.010)	0.25(0.010)	0.25(0.010)	0.25(0.010)	0.25(0.010)	0.25(0.010)
max	0.75(0.030)	0.75(0.030)	0.75(0.030)	1.02(0.040)	1.02(0.040)	1.02(0.040)
Rated Temp. (°C)	250	250	250	250	250	250
Temp. Coefficient	T	T	T	T	T	T
Voltage (V)	16	16	25	16	25	25
Cap (pF)	1000 102					
	1200 122					
	1500 152					
	1800 182					
	2200 222					
	2700 272					
Cap (pF)	3300 332					
	3900 392					
	4700 472					
	5600 562					
	6800 682					
	8200 822					
Cap (pF)	0.010 103					
	0.012 123					
	0.015 153					
	0.018 183					
	0.022 223					
	0.027 273					
Cap (pF)	0.033 333					
	0.039 393					
	0.047 473					
	0.056 563					
Cap (pF)	0.068 683					
	0.082 823					
	0.100 104					
	0.120 124					
	0.150 154					
	0.180 184					
	0.220 224					
	0.270 274					
	0.330 334					
	0.390 394					
	0.470 474					
	0.560 564					
	0.680 684					
	0.820 824					
	1.000 105					
Voltage (V)	16	16	25	16	25	25
Rated Temp. (°C)	250	250	250	250	250	250
Case Size	AT03 = 0603	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225

Voltage rating per table. Capacitance values specified at 25°C, derate capacitance value based on TCC and VCC Plots on page 107.

NOTE: Contact factory for non-specified capacitance values.

High Temperature MLCC

AT Series – 200°C & 250°C Rated

CAPACITANCE RANGE

PREFERRED SIZES ARE SHADED

BME COG

Temp. Coefficient: 4 200°C Rated

Case Size	AT03=0603	AT05=0805	AT06=1206	
Soldering				
(L) Length (mm)	Reflow/Wave	Reflow/Wave	Reflow/Wave	
(L) Length (in.)	1.60±0.15 (0.063±0.006)	2.01±0.20 (0.079±0.008)	3.20±0.20 (0.126±0.008)	
(W) Width (mm)	0.81±0.15 (0.032±0.006)	1.25±0.20 (0.049±0.008)	1.60±0.20 (0.063±0.008)	
(T) Thickness (mm)	1.02 (0.040)	1.30 (0.051)	1.52 (0.060)	
(t) Terminal min	0.25(0.010)	0.25(0.010)	0.25(0.010)	
(t) Terminal max	0.75(0.030)	0.75(0.030)	0.75(0.030)	
Rated Temp. (°C)	200	200	200	
Temp. Coefficeint	3	3	3	
Voltage (V)	25	50	25	50
Cap (pF)	39 390			
	47 470			
	56 560			
	68 680			
	82 820			
	100 101			
	120 121			
	150 151			
	180 181			
	220 221			
	270 271			
	330 331			
	390 391			
	470 471			
	560 561			
	680 681			
	820 821			
	1000 102			
	1200 122			
	1500 152			
	1800 182			
	2200 222			
	2700 272			
	3300 332			
	3900 392			
	4700 472			
	5600 562			
	6800 682			
	8200 822			
Cap (μF)	0.010 103			
	0.012 123			
	0.015 153			
	0.018 183			
	0.022 223			
	0.027 273			
	0.033 333			
	0.039 393			
	0.047 473			
	0.056 563			
	0.068 683			
	0.082 823			
	0.100 104			
Voltage (V)	25	50	25	50
Rated Temp. (°C)	200	200	200	200
Case Size	AT03=0603	AT05=0805	AT06=1206	

Voltage rating per table. Capacitance values specified at 25°C, derate capacitance value based on TCC and VCC Plots on page 107.

NOTE: Contact factory for non-specified capacitance values.

BME COG (Ni/Au)

Temp. Coefficient: 5 250°C Rated

Case Size	AT03=0603	AT05=0805	AT06 = 1206
Soldering			
(L) Length (mm)	Reflow/Wave	Reflow/Wave	Reflow/Wave
(L) Length (in.)	1.60±0.15 (0.063±0.006)	2.01±0.20 (0.079±0.008)	3.20±0.20 (0.126±0.008)
(W) Width (mm)	0.81±0.15 (0.032±0.006)	1.25±0.20 (0.049±0.008)	1.60±0.20 (0.063±0.008)
(T) Thickness (mm)	1.02 (0.040)	1.30 (0.051)	1.52 (0.060)
(t) Terminal min	0.25(0.010)	0.25(0.010)	0.25(0.010)
(t) Terminal max	0.75(0.030)	0.75(0.030)	0.75(0.030)
Rated Temp. (°C)	250	250	250
Temp. Coefficeint	5	5	5
Voltage (V)	25	25	25
Cap (pF)	39 390		
	47 470		
	56 560		
	68 680		
	82 820		
	100 101		
	120 121		
	150 151		
	180 181		
	220 221		
	270 271		
	330 331		
	390 391		
	470 471		
	560 561		
	680 681		
	820 821		
	1000 102		
	1200 122		
	1500 152		
	1800 182		
	2200 222		
	2700 272		
	3300 332		
	3900 392		
	4700 472		
	5600 562		
	6800 682		
	8200 822		
Cap (μF)	0.010 103		
	0.012 123		
	0.015 153		
	0.018 183		
	0.022 223		
	0.027 273		
	0.033 333		
	0.039 393		
	0.047 473		
	0.056 563		
	0.068 683		
	0.082 823		
	0.100 104		
Voltage (V)	25	25	25
Rated Temp. (°C)	250	250	250
Case Size	AT03=0603	AT05=0805	AT06=1206

High Temperature MLCC

AT Series – 200°C & 250°C Rated



CAPACITANCE RANGE

PREFERRED SIZES ARE SHADED

PME COG

Temp. Coefficient: 2 200°C Rated

Case Size	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225
Soldering	Reflow/Wave	Reflow/Wave	Reflow Only	Reflow Only	Reflow Only
(L) Length	mm (in.)	2.01 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	4.50 ± 0.30 (0.177 ± 0.012)
(W) Width	mm (in.)	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	2.50 ± 0.20 (0.098 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)
(T) Thickness	mm (in.)	1.30 (0.051)	1.52 (0.060)	1.70 (0.067)	2.54 (0.100)
(t) Terminal	min max	0.25 (0.010) 0.75 (0.030)	0.25 (0.010) 0.75 (0.030)	0.25 (0.010) 0.75 (0.030)	0.25 (0.010) 0.75 (0.040)
Rated Temp. (°C)	200	200	200	200	200
Temp. Coefficeint	2	2	2	2	2
Voltage (V)	50	50	50	50	50
100	101				
120	121				
150	151				
180	181				
220	221				
270	271				
330	331				
390	391				
470	471				
560	561				
680	681				
820	821				
1000	102				
1200	122				
1500	152				
1800	182				
2200	222				
2700	272				
3300	332				
3900	392				
4700	472				
5600	562				
6800	682				
8200	822				
0.010	103				
0.012	123				
0.015	153				
0.018	183				
0.022	223				
0.027	273				
0.033	333				
0.039	393				
0.047	473				
0.056	563				
0.068	683				
0.082	823				
0.100	104				
Voltage (V)	50	50	50	50	50
Rated Temp. (°C)	200	200	200	200	200
Case Size	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225

PME COG

Temp. Coefficient: A 250°C Rated


Case Size	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225
Soldering	Reflow/Wave	Reflow/Wave	Reflow Only	Reflow Only	Reflow Only
(L) Length	mm (in.)	2.01 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	4.50 ± 0.30 (0.177 ± 0.012)
(W) Width	mm (in.)	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	2.50 ± 0.20 (0.098 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)
(T) Thickness	mm (in.)	1.30 (0.051)	1.52 (0.060)	1.70 (0.067)	2.54 (0.100)
(t) Terminal	min max	0.25 (0.010) 0.75 (0.030)	0.25 (0.010) 0.75 (0.030)	0.25 (0.010) 0.75 (0.040)	0.25 (0.010) 0.75 (0.040)
Rated Temp. (°C)	250	250	250	250	250
Temp. Coefficeint	A	A	A	A	A
Voltage (V)	25	25	25	25	25
100	101				
120	121				
150	151				
180	181				
220	221				
270	271				
330	331				
390	391				
470	471				
560	561				
680	681				
820	821				
1000	102				
1200	122				
1500	152				
1800	182				
2200	222				
2700	272				
3300	332				
3900	392				
4700	472				
5600	562				
6800	682				
8200	822				
0.010	103				
0.012	123				
0.015	153				
0.018	183				
0.022	223				
0.027	273				
0.033	333				
0.039	393				
0.047	473				
0.056	563				
0.068	683				
0.082	823				
0.100	104				
Voltage (V)	25	25	25	25	25
Rated Temp. (°C)	250	250	250	250	250
Case Size	AT05 = 0805	AT06 = 1206	AT10 = 1210	AT12 = 1812	AT14 = 2225

Voltage rating per table. Capacitance values specified at 25°C, derate capacitance value based on TCC and VCC Plots on page 107.

NOTE: Contact factory for non-specified capacitance values.

High Voltage MLC Chips

For 600V to 5000V Applications



High value, low leakage and small size are difficult parameters to obtain in capacitors for high voltage systems. AVX special high voltage MLC chip capacitors meet these performance characteristics and are designed for applications such as snubbers in high frequency power converters, resonators in SMPS, and high voltage coupling/dc blocking. These high voltage chip designs exhibit low ESRs at high frequencies.

Larger physical sizes than normally encountered chips are used to make high voltage MLC chip products. Special precautions must be taken in applying these chips in surface mount assemblies. The temperature gradient during heating or cooling cycles should not exceed 4°C per second. The preheat temperature must be within 50°C of the peak temperature reached by the ceramic bodies through the soldering process. Chip sizes 1210 and larger should be reflow soldered only. Capacitors may require protective surface coating to prevent external arcing.

For 1825, 2225 and 3640 sizes, AVX offers leaded version in either thru-hole or SMT configurations (for details see section on high voltage leaded MLC chips)

NEW 630V RANGE

HOW TO ORDER


1808	A	A	271	M	A	1	2	A
AVX Style	Voltage	Temperature Coefficient	Capacitance Code	Capacitance Tolerance	Test Level	Termination*	Packaging**	Special Code
0805	600V/630V = C	NPO (COG) = A	(2 significant digits + no. of zeros)	COG: J = ±5%	A = Standard	1 = Pd/Ag	1 or 2 = 7" Reel	A = Standard
1206	1000V = A	X7R = C	Examples:	K = ±10%		T = Plated	3 or 4 = 13" Reel	
1210	1500V = S		10 pF = 100	M = ±20%		Ni and Sn (RoHS Compliant)		
1808	2000V = G		100 pF = 101	X7R: K = ±10%				
1812	2500V = W		1,000 pF = 102	M = ±20%				
1825	3000V = H		22,000 pF = 223	Z = +80%, -20%				
2220	4000V = J		220,000 pF = 224					
2225	5000V = K		1 μF = 105					
3640								

Notes:

1. Capacitors with X7R dielectrics are not intended for applications across AC supply mains or AC line filtering with polarity reversal. Contact plant for recommendations. Contact factory for availability of Termination and Tolerance options for Specific Part Numbers.
2. *Terminations with 5% minimum lead (Pb) is available, see pages 100 and 101 for LD style. Leaded terminations are available, see pages 102-106.

**The 3640 Style is not available on 7" Reels.

*** AVX offers nonstandard chip sizes. Contact factory for details.



DIMENSIONS

millimeters (inches)

SIZE	0805	1206	1210*	1808*	1812*	1825*	2220*	2225*	3640*
(L) Length	2.10 ± 0.20 (0.083 ± 0.008)	3.30 ± 0.30 (0.130 ± 0.012)	3.30 ± 0.40 (0.130 ± 0.016)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	5.70 ± 0.50 (0.224 ± 0.020)	5.72 ± 0.25 (0.225 ± 0.010)	9.14 ± 0.25 (0.360 ± 0.010)
(W) Width	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	2.50 ± 0.30 (0.098 ± 0.012)	2.00 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.30 (0.126 ± 0.012)	6.30 ± 0.40 (0.248 ± 0.016)	5.00 ± 0.40 (0.197 ± 0.016)	6.35 ± 0.25 (0.250 ± 0.010)	10.2 ± 0.25 (0.400 ± 0.010)
(T) Thickness Max.	1.35 (0.053)	1.80 (0.071)	2.80 (0.110)	2.20 (0.087)	2.80 (0.110)	3.40 (0.134)	3.40 (0.134)	2.54 (0.100)	2.54 (0.100)
(t) terminal min. max.	0.50 ± 0.20 (0.020 ± 0.008)	0.60 ± 0.20 (0.024 ± 0.008)	0.75 ± 0.35 (0.030 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.76 (0.030) 1.52 (0.060)			

*Reflow Soldering Only



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

For 600V to 5000V Applications



NPO (COG) DIELECTRIC – PERFORMANCE CHARACTERISTICS

Capacitance Range	10 pF to 0.100 μ F (25°C, 1.0 ± 0.2 Vrms at 1kHz, for ≤ 1000 pF use 1 MHz)
Capacitance Tolerances	±5%, ±10%, ±20%
Dissipation Factor	0.1% max. (+25°C, 1.0 ± 0.2 Vrms, 1kHz, for ≤ 1000 pF use 1 MHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	0 ±30 ppm/C (0 VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K MΩ min. or 1000 MΩ - μ F min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K MΩ min. or 100 MΩ - μ F min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

NPO (COG) CAPACITANCE RANGE – PREFERRED SIZES ARE SHADED

Letter	A	C	E	F	G	X	7
Max. Thickness	0.813 (0.032)	1.448 (0.057)	1.8034 (0.071)	2.2098 (0.087)	2.794 (0.110)	0.940 (0.037)	3.30 (0.130)

NOTE: Contact factory for non-specified capacitance values

High Voltage MLC Chips

For 600V to 5000V Applications



NPO (COG) CAPACITANCE RANGE – PREFERRED SIZES ARE SHADED

Case Size	1825						2220						2225						3640								
Soldering	Reflow Only						Reflow Only						Reflow Only						Reflow Only								
(L) Length mm (in.)	4.60 ± 0.50 (0.181 ± 0.020)						5.70 ± 0.50 (0.224 ± 0.020)						5.70 ± 0.50 (0.225 ± 0.010)						9.14 ± 0.25 (0.360 ± 0.010)								
W) Width mm (in.)	6.30 ± 0.40 (0.248 ± 0.016)						5.00 ± 0.40 (0.197 ± 0.016)						6.30 ± 0.40 (0.250 ± 0.010)						10.2 ± 0.25 (0.400 ± 0.010)								
(T) Thickness mm (in.)	3.40 (0.134)						3.40 (0.134)						3.40 (0.100)						2.54 (0.100)								
(t) Terminal mm max	0.75 ± 0.35 (0.030 ± 0.014)						0.85 ± 0.35 (0.033 ± 0.014)						0.85 ± 0.35 (0.033 ± 0.014)						0.76 (0.030) 1.52 (0.060)								
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000	
Cap(μF)	1.5	1R5																									
18	1R8																										
22	2R2																										
27	2R7																										
33	3R3																										
39	3R9																										
47	4R7																										
56	5R6																										
68	6R8																										
82	8R2																										
10	100	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
12	120	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
15	150	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
18	180	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
22	220	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
27	270	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
33	330	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
39	390	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	F					
47	470	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	G					
56	560	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	G					
68	680	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	G					
82	820	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	F	G					
100	101	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
120	121	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
150	151	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
180	181	E	E	G	E	F	E	F	E	E	E	E	E	E	F	E	E	E	E	E	G	G					
220	221	E	E	G	E	F	E	F	E	E	E	E	E	F	E	E	E	E	E	E	G	G					
270	271	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
330	331	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
390	391	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
470	471	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
560	561	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	G	G					
680	681	E	E	G	E	F	F	G	E	E	E	E	F	F	E	E	E	E	E	E	G	G					
750	751	E	E	G	E	F	F	G	E	E	E	E	F	F	E	E	E	E	E	E	G	G					
820	821	E	E	G	E	F	F	G	E	E	E	E	F	F	E	E	E	E	E	E	G	G					
1000	102	E	E	G	E	F	F	G	E	E	E	E	F	F	E	E	E	E	E	E	G	G					
1200	122	E	E	G	E	F	F	G	E	E	E	E	G	G	E	E	E	E	E	E	G	G					
1500	152	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	G	G					
1800	182	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	G	G					
2200	222	E	E	G	G	G	G	G	E	E	E	G	G	G	G	E	E	E	E	E	G	G					
2700	272	E	E	G	G	G	G	G	E	E	E	G	G	G	G	E	E	E	E	E	G	G					
3300	332	E	E	G	G	G	G	G	E	E	E	G	G	G	G	E	E	E	F	F	G	G					
3900	392	E	E	G	G	G	G	G	E	E	E	G	G	G	G	E	E	E	G	G	G	G					
4700	472	E	E	G	G	G	G	G	E	E	E	G	G	G	G	F	F	F	G	G	G	G					
5600	562	F	F	G	G	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G					
6800	682	F	F	G	G	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G					
8200	822	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G	G					
Cap(μF)	0.010	103	F	E	G				7	7	7					G	G	G						G	G	G	G
0.012	123	E	G													G	G							G	G	G	G
0.015	153	E														G	G							G	G	G	G
0.018	183	E														G	G							G	G	G	G
0.022	223	E														G	G							G	G	G	G
0.027	273	F																									
0.033	333	F															G	G									
0.039	393	G																									
0.047	473	G															G	G									
0.056	563	G															G	G									
0.068	683	G															G	G									
0.100	104																										
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000	
Case Size	1825						2220						2225						3640								

Letter	A	C	E	F	G	X	7
Max.	0.813	1.448	1.8034	2.2098	2.794	0.940	3.30
Thickness	(0.032)	(0.057)	(0.071)	(0.087)	(0.110)	(0.037)	(0.130)

NOTE: Contact factory for non-specified capacitance values



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer/ by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

For 600V to 5000V Applications



X7R Dielectric Performance Characteristics

Capacitance Range	10 pF to 0.82 µF (25°C, 1.0 ± 0.2 Vrms at 1kHz)
Capacitance Tolerances	±10%; ±20%; +80%, -20%
Dissipation Factor	2.5% max. (+25°C, 1.0 ± 0.2 Vrms, 1kHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	±15% (0 VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K MΩ min. or 1000 MΩ - µF min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K MΩ min. or 100 MΩ - µF min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

X7R CAPACITANCE RANGE – PREFERRED SIZES ARE SHADED

Case Size	0805			1206			1210			1808			1812		
Soldering	Reflow/Wave			Reflow/Wave			Reflow Only			Reflow Only			Reflow Only		
(L) Length (mm)	2.10 ± 0.20 (0.085 ± 0.008)			3.30 ± 0.30 (0.130 ± 0.012)			3.30 ± 0.40 (0.130 ± 0.016)			4.60 ± 0.50 (0.181 ± 0.020)			4.60 ± 0.50 (0.177 ± 0.012)		
(W) Width (mm)	1.25 ± 0.20 (0.049 ± 0.008)			1.60 ± 0.30/-0.10 (0.063 ± 0.012/-0.004)			2.50 ± 0.30 (0.098 ± 0.012)			2.00 ± 0.20 (0.079 ± 0.008)			3.20 ± 0.30 (0.126 ± 0.008)		
(T) Thickness (mm)	1.35 (0.053)			1.80 (0.071)			2.80 (0.110)			2.20 (0.087)			2.80 (0.100)		
(t) Terminal max	0.50 ± 0.20 (0.020 ± 0.008)			0.60 ± 0.20 (0.024 ± 0.008)			0.75 ± 0.35 (0.030 ± 0.014)			0.75 ± 0.35 (0.030 ± 0.014)			0.75 ± 0.35 (0.030 ± 0.014)		
Voltage (V)	600 630 1000	600 630 1000 1500	2000	600 630 1000 1500	2000	600 630 1000 1500	2000	600 630 1000 1500 2000	2500 3000 4000	600 630 1000 1500 2000	2500 3000 4000	600 630 1000 1500 2000	2500 3000 4000	600 630 1000 1500 2000	2500 3000 4000
Cap (pF)	100 101	X X C C C E E E E E E													
	120 121	X X C C C E E E E E E													
	150 151	X X C C C E E E E E E													
	180 181	X X C C C E E E E E E													
	220 221	X X C C C E E E E E E													
	270 271	X X C C C E E E E E E											E E E E E		
	330 331	X X C C C E E E E E E											E E E E E		
	390 391	X X C C C E E E E E E											E E E E E		
	470 471	X X C C C E E E E E E											E E E E E E		
	560 561	X X C C C E E E E E E											E E E E E E		
	680 681	X X C C C E E E E E E											E E E E E F		
	750 751	X X C C C E E E E E E											E E E E F F		
	820 821	X X C C C E E E E E E											E E E E F F		
	1000 102	X X X C C E E E E E E											E E E E F F		
	1200 122	X X X C C E E E E E E											F F F F F F		
	1500 152	X X X C C E E E E E E											F F F F F G G		
	1800 182	X X X C C E E E E E E											F F F F F G G		
	2200 222	X X X C C E E E E F E											F F F F F G G		
	2700 272	C C C C E E E E F E											F F F F F G G		
	3300 332	C C C C E E E E F E											F F F F F G G		
	3900 392	C C C C E E E E F E											F F F F F G G		
	4700 472	C C C C E E E E F E											F F F F F G G		
	5600 562	C C C C E E E E F E											F F F F G G G		
	6800 682	C C C C E E E E F E											F F F F G G G		
	8200 822	C C C C E E E E F E											F F F F G G G		
	Cap (pF)	0.010 103	C C C C E E E E F E										F F F F G G G		
	0.015 153	C C E E E											F F F G		
	0.018 183	C C E E E											F F G		
	0.022 223	C C E E E											F F G		
	0.027 273	E E E											F F G		
	0.033 333	E E E											F F G		
	0.039 393	E E E											F F G		
	0.047 473	E E E											F F G		
	0.056 563	F F F											F F G		
	0.068 683	F F F											F F G		
	0.082 823	F F F											F F G		
	0.100 104	F F F											F F G		
	0.150 154												G G		
	0.220 224												G G		
	0.270 274														
	0.330 334														
	0.390 394														
	0.470 474														
	0.560 564														
	0.680 684														
	0.820 824														
	1.000 105														
Voltage (V)	600 630 1000	600 630 1000 1500	2000	600 630 1000 1500	2000	600 630 1000 1500	2000	600 630 1000 1500 2000	2500 3000 4000	600 630 1000 1500 2000	2500 3000 4000	600 630 1000 1500 2000	2500 3000 4000	600 630 1000 1500 2000	2500 3000 4000
Case Size	0805			1206			1210			1808			1812		

Letter	A	C	E	F	G	X	7
Max. Thickness	0.813 (0.032)	1.448 (0.057)	1.8034 (0.071)	2.2098 (0.087)	2.794 (0.110)	0.940 (0.037)	3.30 (0.130)

NOTE: Contact factory for non-specified capacitance values

High Voltage MLC Chips

For 600V to 5000V Applications



X7R CAPACITANCE RANGE PREFERRED SIZES ARE SHADED

Letter	A	C	E	F	G	X	7
Max.	0.813	1.448	1.8034	2.2098	2.794	0.940	3.30
Thickness	(0.032)	(0.057)	(0.071)	(0.087)	(0.110)	(0.037)	(0.130)


NOTE: Contact factory for non-specified capacitance values



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer/ by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

Tin/Lead Termination "B" - 600V to 5000V Applications



AVX Corporation will support those customers for commercial and military Multilayer Ceramic Capacitors with a termination consisting of 5% minimum lead. This termination is indicated by the use of a "B" in the 12th position of the AVX Catalog Part Number. This fulfills AVX's commitment to providing a full range of products to our customers. AVX has provided in the following pages, a full range of values that we are offering in this "B" termination.

Larger physical sizes than normally encountered chips are used to make high voltage MLC chip product. Special precautions must be taken in applying these chips in surface mount assemblies. The temperature gradient during heating or cooling cycles should not exceed 4°C per second.

The preheat temperature must be within 50°C of the peak temperature reached by the ceramic bodies through the soldering process. Chip sizes 1210 and larger should be reflow soldered only. Capacitors may require protective surface coating to prevent external arcing.

For 1825, 2225 and 3640 sizes, AVX offers leaded version in either thru-hole or SMT configurations (for details see section on high voltage leaded MLC chips).

NEW 630V RANGE

HOW TO ORDER

LD08	A	A	271	K	A	B	1	A
AVX Style	Voltage	Temperature Coefficient	Capacitance Code	Capacitance Tolerance	Test Level	Termination*	Packaging	Special Code
LD05 - 0805	600V/630V = C	COG = A	(2 significant digits + no. of zeros)	COG: J = ±5% K = ±10% M = ±20%	A = Standard 4 = Automotive*	B = 5% Min Pb X = FLEXITERM® 5% min. Pb*	2 = 7" Reel** 4 = 13" Reel	A = Standard
LD06 - 1206	1000V = A							
LD06 - 1206	1500V = S	X7R = C						
LD10 - 1210	2000V = G							
LD08 - 1808	2500V = W							
LD12 - 1812	3000V = H							
LD13 - 1825	4000V = J							
LD20 - 2220	5000V = K							
LD14 - 2225								
LD40 - 3640								

Notes: Capacitors with X7R dielectrics are not intended for applications across AC supply mains or AC line filtering with polarity reversal. Contact plant for recommendations. Contact factory for availability of Termination and Tolerance options for Specific Part Numbers.


NOT RoHS Compliant

* FLEXITERM is not available in the LD40 Style

** The LD40 Style is not available on 7" Reels.

*** AVX offers nonstandard chip sizes. Contact factory for details.

* Not all values are supported in Automotive grade. Please contact factory for availability.



millimeters (inches)

DIMENSIONS

SIZE	LD05 (0805)	LD06 (1206)	LD10* (1210)	LD08* (1808)	LD12* (1812)	LD13* (1825)	LD20* (2220)	LD14* (2225)	LD40* (3640)
(L) Length	2.10 ± 0.20 (0.083 ± 0.008)	3.30 ± 0.30 (0.130 ± 0.012)	3.30 ± 0.40 (0.130 ± 0.016)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	5.70 ± 0.50 (0.224 ± 0.020)	5.70 ± 0.50 (0.224 ± 0.020)	9.14 ± 0.25 (0.360 ± 0.010)
(W) Width	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ± 0.20 (0.063 ± 0.008)	2.50 ± 0.30 (0.098 ± 0.012)	2.00 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.30 (0.126 ± 0.012)	6.30 ± 0.40 (0.248 ± 0.016)	5.00 ± 0.40 (0.197 ± 0.016)	6.30 ± 0.40 (0.248 ± 0.016)	10.2 ± 0.25 (0.400 ± 0.010)
(T) Thickness Max.	1.35 (0.053)	1.80 (0.071)	2.80 (0.110)	2.20 (0.087)	2.80 (0.110)	3.40 (0.134)	3.40 (0.134)	3.40 (0.134)	2.54 (0.100)
(t) terminal min.	0.50 ± 0.20 (0.020 ± 0.008)	0.60 ± 0.20 (0.024 ± 0.008)	0.75 ± 0.35 (0.030 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.76 (0.030)			
terminal max.									1.52 (0.060)

*Reflow Soldering Only

Performance of ceramic capacitors can be simulated by using the online SpiMLCC software program - <http://spicat.avx.com/mlcc>
Custom values, ratings and configurations are also available.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

Tin/Lead Termination "B" - 600V to 5000V Applications



NPO (COG) Dielectric Performance Characteristics

Capacitance Range	10 pF to 0.047 μ F (25°C, 1.0 \pm 0.2 Vrms at 1kHz, for \leq 1000 pF use 1 MHz)
Capacitance Tolerances	\pm 5%, \pm 10%, \pm 20%
Dissipation Factor	0.1% max. (+25°C, 1.0 \pm 0.2 Vrms, 1kHz, for \leq 1000 pF use 1 MHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	0 \pm 30 ppm/ $^{\circ}$ C (0 VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K M Ω min. or 1000 M Ω - μ F min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K M Ω min. or 100 M Ω - μ F min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

HIGH VOLTAGE COG CAPACITANCE VALUES

VOLTAGE	LD05 (0805)	LD06 (1206)	LD10 (1210)	LD08 (1808)	LD12 (1812)	LD13 (1825)	LD20 (2220)	LD14 (2225)	LD40 (3640)
600/630	min. max.	10 pF 330 pF	10 pF 1200 pF	100 pF 2700 pF	100 pF 3300 pF	100 pF 5600 pF	1000 pF 0.012 μ F	1000 pF 0.012 pF	1000 pF 0.018 μ F
	min. max.	10 pF 180 pF	10 pF 560 pF	10 pF 1500 pF	100 pF 2200 pF	100 pF 3300 pF	1000 pF 8200 pF	1000 pF 0.010 pF	1000 pF 0.022 μ F
1500	min. max.	— —	10 pF 270 pF	10 pF 680 pF	10 pF 820 pF	10 pF 1800 pF	100 pF 4700 pF	100 pF 4700 pF	100 pF 5600 pF
	min. max.	— —	10 pF 120 pF	10 pF 270 pF	10 pF 330 pF	10 pF 1000 pF	100 pF 1800 pF	100 pF 2200 pF	100 pF 2700 pF
2500	min. max.	— —	— —	10 pF 180 pF	10 pF 470 pF	10 pF 1200 pF	100 pF 1500 pF	100 pF 1800 pF	100 pF 3900 pF
	min. max.	— —	— —	10 pF 120 pF	10 pF 330 pF	10 pF 820 pF	10 pF 1000 pF	10 pF 1200 pF	100 pF 2700 pF
3000	min. max.	— —	— —	10 pF 120 pF	10 pF 330 pF	10 pF 820 pF	10 pF 1000 pF	10 pF 1200 pF	100 pF 2700 pF
	min. max.	— —	— —	10 pF 47 pF	10 pF 150 pF	10 pF 330 pF	10 pF 470 pF	10 pF 560 pF	100 pF 1200 pF
4000	min. max.	— —	— —	— —	— —	— —	— —	— —	100 pF 1200 pF
	min. max.	— —	— —	— —	— —	— —	10 pF 220 pF	10 pF 270 pF	10 pF 820 pF

X7R Dielectric Performance Characteristics


Capacitance Range	10 pF to 0.56 μ F (25°C, 1.0 \pm 0.2 Vrms at 1kHz)
Capacitance Tolerances	\pm 10%; \pm 20%; +80%, -20%
Dissipation Factor	2.5% max. (+25°C, 1.0 \pm 0.2 Vrms, 1kHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	\pm 15% (0 VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K M Ω min. or 1000 M Ω - μ F min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K M Ω min. or 100 M Ω - μ F min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

HIGH VOLTAGE X7R MAXIMUM CAPACITANCE VALUES

VOLTAGE	0805	1206	1210	1808	1812	1825	2220	2225	3640
600/630	min. max.	100 pF 6800 pF	1000 pF 0.022 μ F	1000 pF 0.056 μ F	1000 pF 0.068 μ F	0.010 μ F 0.390 μ F	0.010 μ F 0.270 μ F	0.010 μ F 0.330 μ F	0.010 μ F 0.560 μ F
	min. max.	100 pF 1500 pF	100 pF 6800 pF	1000 pF 0.015 μ F	1000 pF 0.018 μ F	1000 pF 0.039 μ F	1000 pF 0.100 μ F	1000 pF 0.120 μ F	1000 pF 0.150 μ F
1500	min. max.	— —	100 pF 2700 pF	100 pF 5600 pF	100 pF 6800 pF	100 pF 0.015 μ F	1000 pF 0.056 μ F	1000 pF 0.068 μ F	1000 pF 0.100 μ F
	min. max.	— —	10 pF 1500 pF	100 pF 3300 pF	100 pF 3300 pF	100 pF 8200 pF	100 pF 0.022 μ F	1000 pF 0.027 μ F	1000 pF 0.033 μ F
2500	min. max.	— —	— —	10 pF 2200 pF	10 pF 5600 pF	100 pF 0.015 μ F	100 pF 0.018 μ F	100 pF 0.022 μ F	1000 pF 0.022 μ F
	min. max.	— —	— —	10 pF 1800 pF	10 pF 3900 pF	100 pF 0.010 μ F	100 pF 0.012 μ F	100 pF 0.015 μ F	1000 pF 0.018 μ F
4000	min. max.	— —	— —	— —	— —	— —	— —	— —	100 pF 6800 pF
	min. max.	— —	— —	— —	— —	— —	— —	— —	100 pF 3300 pF
5000	min. max.	— —	— —	— —	— —	— —	— —	— —	— —

High Voltage MLC Chips

FLEXITERM® - 600V to 5000V Applications



High value, low leakage and small size are difficult parameters to obtain in capacitors for high voltage systems. AVX special high voltage MLC chips capacitors meet these performance characteristics and are designed for applications such as snubbers in high frequency power converters, resonators in SMPS, and high voltage coupling/DC blocking. These high voltage chip designs exhibit low ESRs at high frequencies.

To make high voltage chips, larger physical sizes than are normally encountered are necessary. These larger sizes require that special precautions be taken in applying these chips in surface mount assemblies. In response to this, and to follow from the success of the FLEXITERM® range of low voltage parts, AVX is delighted to offer a FLEXITERM® high voltage range of capacitors, FLEXITERM®.


The FLEXITERM® layer is designed to enhance the mechanical flexure and temperature cycling performance of a standard ceramic capacitor, giving customers a solution where board flexure or temperature cycle damage are concerns.

HOW TO ORDER

1808	A	C	272	K	A	Z	1	A
AVX Style	Voltage	Temperature Coefficient	Capacitance Code (2 significant digits + no. of zeros)	Capacitance Tolerance	Test Level	Termination*	Packaging	Special Code
0805	600V/630V = C	COG = A	Examples: 10 pF = 100	COG: J = ±5%	Z=FLEXITERM®	2 = 7" Reel		
1206	1000V = A	X7R = C	100 pF = 101	K = ±10%	100% Tin (RoHS Compliant)	4 = 13" Reel		
1210	1500V = S		1,000 pF = 102	M = ±20%				
1808	2000V = G		22,000 pF = 223	X7R: K = ±10%				
1812	2500V = W		220,000 pF = 224	M = ±20%				
1825	3000V = H		1 µF = 105	Z = +80%, -20%				
2220	4000V = J							
2225	5000V = K							

Notes: Capacitors with X7R dielectrics are not intended for applications across AC supply mains or AC line filtering with polarity reversal. Contact plant for recommendations. Contact factory for availability of Termination and Tolerance options for Specific Part Numbers.

*** AVX offers nonstandard chip sizes. Contact factory for details.



DIMENSIONS

MILLIMETERS (INCHES)

SIZE	0805	1206	1210*	1808*	1812*	1825*	2220*	2225*
(L) Length	2.10 ± 0.20 (0.083 ± 0.008)	3.30 ± 0.30 (0.130 ± 0.012)	3.30 ± 0.40 (0.130 ± 0.016)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	5.70 ± 0.50 (0.224 ± 0.020)	5.70 ± 0.50 (0.224 ± 0.020)
(W) Width	1.25 ± 0.20 (0.049 ± 0.008)	$1.60^{+0.30}_{-0.10}$ ($0.063^{+0.012}_{-0.004}$)	2.50 ± 0.30 (0.098 ± 0.012)	2.00 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.30 (0.126 ± 0.012)	6.30 ± 0.40 (0.248 ± 0.016)	5.00 ± 0.40 (0.197 ± 0.016)	6.30 ± 0.40 (0.248 ± 0.016)
(T) Thickness Max.	1.35 (0.053)	1.80 (0.071)	2.80 (0.110)	2.20 (0.087)	2.80 (0.110)	3.40 (0.134)	3.40 (0.134)	3.40 (0.134)
(t) terminal	min. 0.50 ± 0.20 (0.020 ± 0.008)	max. 0.60 ± 0.20 (0.024 ± 0.008)		0.75 ± 0.35 (0.030 ± 0.014)	0.75 ± 0.35 (0.030 ± 0.014)	0.75 ± 0.35 (0.030 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)

*Reflow Soldering Only

Performance of SMPS capacitors can be simulated by downloading SpiCalci software program - <http://www.avx.com/SpiApps/default.asp#spicalci>
Custom values, ratings and configurations are also available.



High Voltage MLC Chips

FLEXITERM® - 600V to 5000V Applications



NP0 (C0G) Dielectric

Performance Characteristics

Capacitance Range	10 pF to 0.100 μ F (+25°C, 1.0 \pm 0.2 Vrms, 1kHz)
Capacitance Tolerances	\pm 5%, \pm 10%, \pm 20%
Dissipation Factor	0.1% max. (+25°C, 1.0 \pm 0.2 Vrms, 1kHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	0 \pm 30 ppm/°C (0 VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K M Ω min. or 1000 M Ω - μ F min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K M Ω min. or 100 M Ω - μ F min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

NPO (COG) CAPACITANCE RANGE

PREFERRED SIZES ARE SHADED

Case Size Soldering	0805			1206			1210			1808			1812			
	Reflow/Wave			Reflow/Wave			Reflow Only			Reflow Only			Reflow Only			
(L) Length mm (in.)	2.10 ± 0.20 (0.083 ± 0.008)			3.30 ± 0.30 (0.130 ± 0.012)			3.30 ± 0.40 (0.130 ± 0.016)			4.60 ± 0.50 (0.181 ± 0.020)			4.60 ± 0.50 (0.181 ± 0.020)			
W) Width mm (in.)	1.25 ± 0.20 (0.049 ± 0.008)			1.60 ± 0.30/-0.10 (0.063 ± 0.012/-0.004)			2.50 ± 0.30 (0.098 ± 0.012)			2.00 ± 0.20 (0.079 ± 0.008)			3.20 ± 0.30 (0.126 ± 0.012)			
(T) Thickness mm (in.)	1.35 (0.053)			1.80 (0.071)			2.80 (0.110)			2.20 (0.087)			2.80 (0.110)			
(t) Terminal mm max	0.50 ± 0.20 (0.020 ± 0.008)			0.60 ± 0.20 (0.024 ± 0.008)			0.75 ± 0.35 (0.030 ± 0.014)			0.75 ± 0.35 (0.030 ± 0.014)			0.75 ± 0.35 (0.030 ± 0.014)			
Voltage (V)	600	630	1000	600	630	1000	1500	2000	600	630	1000	1500	2000	2500	3000	4000
Cap (pF)	1.5	1R5	A A	X X X X X X												
	1.8	1R8	A A	X X X X X X												
	2.2	2R2	A A	X X X X X X												
	2.7	2R7	A A	X X X X X X												
	3.3	3R3	A A	X X X X X X												
	3.9	3R9	A A	X X X X X X												
	4.7	4R7	A A	X X X X X X												
	5.6	5R6	A A	X X X X X X												
	6.8	6R8	A A	X X X X X X												
	8.2	8R2	A A	X X X X X X												
	10	100	A A	A X X X X X	C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	12	120	A A	A X X X X X	C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	15	150	A A	A X X X X X	C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	18	180	A A	A X X X X X	C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	22	220	A A	A X X X X X	C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	27	270	A A	A X X X X X	C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	33	330	A A	A X X X X D	D C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	39	390	A A	A X X X X D	D C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	47	470	A A	A X X X M	D C C	D D	D	C C	C C	C C	C C	C C	C C	C C	C C	C E
	56	560	A A	A X X X M	C C	C C	C	D C C	C C	C C	C C	C C	C C	C C	C C	C F
	68	680	A A	A X X X M	C C	C C	C	D C C	C C	C C	C C	C C	C C	C C	C C	C F
	82	820	X X	X X X C	C C	C C	C	D C C	C C	C C	C C	C C	C C	C C	C C	C F
	100	101	X X	X X X C	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	120	121	C C	C X X C E	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C G
	150	151	C C	C X X C E	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C G
	180	181	C C	C X E E	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	220	221	C C	X X E E	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	270	271	C C	C E E	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	330	331	C C	C E E	C C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	390	391	C C	C E E	E C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	470	471	C C	C E E	E C	C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	560	561	C C	C C E		C C	C	C C	C C	C C	C C	C C	C C	C C	C C	C F
	680	681	C C	C C E		C C	C	C C	F F	C C	C C	F F	F F	C C	C C	F G G
	750	751	C C	E E		C C	C	E G G	C C	F F	F F	F F	F F	C C	C C	F G G
	820	821	C C	E E E		C C	C	E G G	C C	C C	F F	E E	E E	C C	C C	F G G
	1000	102		E E E		C C	C	E G G		C C	F F	E E	E E	C C	C C	F F G G
	1200	122		E E		C C	C	E		E E	F F	E E	E E	C C	C C	F E E
	1500	152		E E		C C	C	G		E E	F F			C C	C C	F F F
	1800	182		E E		C C	C	G		E E	F F			C C	C C	F F F
	2200	222		E E		E E				E E	E E			C C	C C	E G G
	2700	272		E E		E E				E E	E E			C C	C C	E G G
	3300	332		E E		E E				E E	E E			C C	C C	F
	3900	392				E E				E E	E E			C C	C C	F
	4700	472				E E				E E	E E			C C	C C	G
	5600	562				E E				E E	E E			C C	C C	
	6800	682				E E				E F	F F			C C	C C	
	8200	822												E E	E E	
Cap (μF)	0.010	103												E E	E E	
	0.012	123												F F	F F	
	0.015	153												G G	G G	
	0.018	183												G G	G G	
	0.022	223														
	0.033	333														
	0.047	473														
	0.056	563														
	0.068	683														
	0.100	104														
Voltage (V)	600	630	1000	600	630	1000	1500	2000	600	630	1000	1500	2000	2500	3000	4000
Case Size	0805			1206			1210			1808			1812			



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer/ by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

FLEXITERM® - 600V to 5000V Applications



NP0 (COG) CAPACITANCE RANGE

PREFERRED SIZES ARE SHADED

Case Size	1825								2220								2225															
Soldering	Reflow Only								Reflow Only								Reflow Only															
(L) Length mm (in.)																																
(W) Width mm (in.)																																
(T) Thickness mm (in.)																																
(t) Terminal max mm (in.)																																
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000						
Cap (pF)	1.5 1R5								600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000						
	1.8 1R8																															
	2.2 2R2																															
	2.7 2R7																															
	3.3 3R3																															
	3.9 3R9																															
	4.7 4R7																															
	5.6 5R6																															
	6.8 6R8																															
	8.2 8R2																															
10 100	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
12 120	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
15 150	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
18 180	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
22 220	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
27 270	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
33 330	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
39 390	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F							
47 470	E	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	G							
56 560	E	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	G							
68 680	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	G							
82 820	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	G							
100 101	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	G	G							
120 121	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	G	G							
150 151	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	G	G							
180 181	E	E	E	E	E	E	F	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	G	G							
220 221	E	E	E	E	E	E	F	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	G	G							
270 271	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E									G	G						
330 331	E	E	E	E	E	E	F	E	E	E	E	E	E	E	E	E										G	G					
390 391	E	E	E	E	E	E	E		E	E	E	E	E	E	E	E											G	G				
470 471	E	E	E	E	E	E	E		E	E	E	E	E	E	E	E												G	G			
560 561	E	E	E	E	E	E	E		E	E	E	E	E	E	E	E												G	G			
680 681	E	E	E	E	E	F	F		E	E	E	E	F	F	F	F												G	G			
750 751	E	E	E	E	E	F	F		E	E	E	E	F	F	F	F												G	G			
820 821	E	E	E	E	E	F	F		E	E	E	E	F	F	F	F												G	G			
1000 102	E	E	E	E	F	F			E	E	E	E	F	F	F	F												G	G			
1200 122	E	E	E	E	G	G			E	E	E	E	G	G	G	G												G	G			
1500 152	E	E	E	F	F	G	G		E	E	E	F	F	G	G	G												G	G			
1800 182	E	E	F	F	G	G			E	E	E	F	F	G	G	G												G	G			
2200 222	E	E	E	G	G				E	E	E	G	G																G	G		
2700 272	E	E	E	G	G				E	E	E	G	G																G	G		
3300 332	E	E	E	G	G				E	E	E	G	G																G	G		
3900 392	E	E	E	G	G				E	E	E	G	G																G	G		
4700 472	E	E	E	G	G				E	E	E	G	G																G	G		
5600 562	F	F	F	G	G				F	F	F																			G	G	
6800 682	F	F	F						F	F	F																			G	G	
8200 822	G	G	G						G	G	G																			G	G	
Cap (μF)	0.010 103																														G	G
	0.012 123																														G	G
	0.015 153																														G	G
	0.018 183																														G	G
	0.022 223																														G	G
	0.033 333																														G	G
	0.047 473																														G	G
	0.056 563																														G	G
	0.068 683																														G	G
	0.100 104																														G	G
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000						
Case Size	1825								2220								2225															

NOTE: Contact factory for non-specified capacitance

Letter	A	C	E	F	G	X
Max.	0.813	1448	1.803	2210	2.794	0.940
Thickness	(0.032)	(0.057)	(0.071)	(0.087)	(0.110)	(0.037)



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

FLEXITERM® - 600V to 5000V Applications



X7R Dielectric

Performance Characteristics

Capacitance Range	10 pF to 0.82 µF (25°C, 1.0 ±0.2 Vrms at 1kHz)
Capacitance Tolerances	±10%; ±20%; +80%, -20%
Dissipation Factor	2.5% max. (+25°C, 1.0 ±0.2 Vrms, 1kHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	±15% (0 VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K MΩ min. or 1000 MΩ - µF min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K MΩ min. or 100 MΩ - µF min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

X7R CAPACITANCE RANGE

PREFERRED SIZES ARE SHADED

Case Size	0805			1206			1210			1808			1812		
	Soldering			Reflow/Wave			Reflow Only			Reflow Only			Reflow Only		
(L) Length (mm) (in.)	2.10 ±0.20 (0.083 ±0.008)			3.30 ±0.30 (0.130 ±0.012)			3.30 ±0.40 (0.130 ±0.016)			4.60 ±0.50 (0.181 ±0.020)			4.60 ±0.50 (0.181 ±0.020)		
(W) Width (mm) (in.)	1.25 ±0.20 (0.049 ±0.008)			1.60 ±0.30/-0.10 (0.063 ±0.012/-0.004)			2.50 ±0.30 (0.098 ±0.012)			2.00 ±0.20 (0.079 ±0.008)			3.20 ±0.30 (0.126 ±0.012)		
(T) Thickness (mm) (in.)	1.35 (0.053)			1.80 (0.071)			2.80 (0.110)			2.20 (0.087)			2.80 (0.110)		
(t) Terminal max	0.50 ±0.20 (0.020 ±0.008)			0.60 ±0.20 (0.024 ±0.008)			0.75 ±0.35 (0.030 ±0.014)			0.75 ±0.35 (0.030 ±0.014)			0.75 ±0.35 (0.030 ±0.014)		
Voltage (V)	600 630 1000 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000
Cap (pF)	100 101	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	120 121	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	150 151	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	180 181	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	220 221	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	270 271	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	330 331	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	390 391	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	470 471	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	560 561	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	680 681	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	750 751	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	820 821	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	1000 102	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E
	1200 122	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	F F F F	F F F F
	1500 152	X X C C	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	F F F F	F F F F	G G
	1800 182	X X	C C E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E E E	E E F F	F F F F	F F F F	F F F F	F F F F	F G G
	2200 222	X X	C C E E	E E E E	E E E F	E E E F	E E E F	E E F F	F F F F	F F F F	F F F F	F F F F	F F F F	F F F F	F G G
	2700 272	X X	C C E E	E E E E	E E F F	E E F F	E E F F	E E F F	F F F F	F F F F	F F F F	F F F F	F F F F	F G G	
	3300 332	X X	C C E		E E E F	E E E F	E E E F	E E E F	F F F F	F F F F	F F F F	F F F F	F F F F	F F F F	G G
	3900 392	X X	C C E		E E E G	E E E G	E E E G	E E E F	F F F F	F F F F	F F F F	F F F F	F F F F	F F F F	G G
	4700 472	X X	C C E		E E E G	E E E G	E E E G	E E E F	F F F F	F F F F	F F F F	F F F F	F F F F	F F F F	G G
	5600 562	X X	C C E		E E E G	E E E G	E E E G	E E E F	F F F F	F F F F	F F F F	F F F F	F F F F	F F F F	G G
	6800 682	X X	C C E		E E E E	E E E E	E E E E	E E E F	F F F F	F F F F	F F F F	F F F F	F F F F	F F F F	G G
	8200 822	X X	C C E		E E E E	E E E E	E E E E	E E E E	F F F F	F F F F	F F F F	F F F F	F F F F	F F E G	G G
Cap (pF)	0.010 103	C C	C C E	E E E	E E E	E E E	E E E	F F F	F F F	F F F	F F F	F F F	F F F	F F F	G G
	0.015 153	C C	C E E	E E E	E E E	E E E	F F F	F F F	F F F	F F F	F F F	F F F	F F F	F F F	G G
	0.018 183	C C	E E E		E E E	E E E	F F F	F F F	F F F	F F F	F F F	F F F	F F F	F F G	
	0.022 223	C C	E E		E E E	E E E	F F F	F F F	F F F	F F F	F F F	F F F	F F F	F F G	
	0.027 273		E E		E E	E E	F F	F F	F F	F F	F F	F F	F F	F F G	
	0.033 333		E E		E E	E E	F F	F F	F F	F F	F F	F F	F F	F F G	
	0.039 393				E E	E E	F F	F F	F F	F F	F F	F F	F F	F F G	
	0.047 473				E E	E E	F F	F F	F F	F F	F F	F F	F F	F F G	
	0.056 563				F F	F F	F F	F F	F F	F F	F F	F F	F F		
	0.068 683				F F	F F	F F	F F	F F	F F	F F	F F	F F		
	0.082 823				F F	F F									
	0.100 104				F F	F F									
	0.150 154													G G	
	0.220 224													G G	
	0.270 274														
	0.330 334														
	0.390 394														
	0.470 474														
	0.560 564														
	0.680 684														
	0.820 824														
	1.000 105														
Voltage (V)	600 630 1000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000	600 630 1000 1500 2000
Case Size	0805	1206	1210	1808										1812	



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

High Voltage MLC Chips

AVX
A KYOCERA GROUP COMPANY

FLEXITERM® - 600V to 5000V Applications


X7R CAPACITANCE RANGE PREFERRED SIZES ARE SHADED

Letter	A	C	E	F	G	P	X
Max. Thickness	0.813 (0.032)	1.448 (0.057)	1.8034 (0.071)	2.2098 (0.087)	2.794 (0.110)	3.048 (0.120)	0.940 (0.037)

NOTE: Contact factory for non-specified capacitance values

High Voltage MLC Chip Capacitors

For 600V to 3000V Automotive Applications - AEC-Q200



Modern automotive electronics could require components capable to work with high voltage (e.g. xenon lamp circuits or power converters in hybrid cards). AVX offers high voltage ceramic capacitors qualified according to AEC-Q200 standard.

High value, low leakage and small size are difficult parameters to obtain in capacitors for high voltage systems. AVX special high voltage MLC chip capacitors meet these performance characteristics and are designed for applications such as snubbers in high frequency power converters, resonators in SMPS, and high voltage coupling/dc blocking. These high voltage chip designs exhibit low ESRs at high frequencies.

Due to high voltage nature, larger physical dimensions are necessary. These larger sizes require special precautions to be taken in applying of MLC chips. The temperature gradient during heating or cooling cycles should not exceed 4°C per second. The preheat temperature must be within 50°C of the peak temperature reached by the ceramic bodies through the soldering process. Chip sizes 1210 and larger should be reflow soldered only. Capacitors may require protective surface coating to prevent external arcing.

To improve mechanical and thermal resistance, AVX recommend to use flexible terminations system - FLEXITERM®.

HOW TO ORDER


1210	C	C	223	K	4	T	1	A
Size	Voltage	Dielectric	Capacitance Code	Capacitance Tolerance	Failure Rate	Terminations	Packaging	Special Code
1206	C = 630V	X7R = C	2 Sig. Digits + Number of Zeros e.g. 103 = 10nF (223 = 22nF)	K = ±10% M = ±20%	4=Automotive	T = Plated Ni and Sn Z = FLEXITERM®	1 or 2 = 7" Reel 3 or 4 = 13" Reel	A = Std. Product
1210	A = 1000V							
1808	S = 1500V							
1812	G = 2000V							
2220	W = 2500V							
	H = 3000V							

*AVX offers nonstandard case size. Contact factory for details.

Notes: Capacitors with X7R dielectrics are not intended for applications across AC supply mains or AC line filtering with polarity reversal.
Please contact AVX for recommendations

CHIP DIMENSIONS DESCRIPTION

(See capacitance range chart on page 128)



L = Length
W = Width
T = Thickness
t = Terminal

X7R DIELECTRIC PERFORMANCE CHARACTERISTICS

Parameter/Test	Specification Limits	Measuring Conditions
Operating Temperature Range	-55°C to +125°C	Temperature Cycle Chamber
Capacitance Dissipation Factor Capacitance Tolerance	within specified tolerance 2.5% max. ±5% (J), ±10% (K), ±20% (M)	Freq.: 1kHz ±10% Voltage: 1.0Vrms s ±0.2Vrms T = +25°C, V = 0Vdc
Temperature Characteristics	X7R = ±15%	Vdc = 0V, T = (-55°C to +125°C)
Insulation Resistance	100GΩ min. or 1000MΩ • μF min. (whichever is less) 10GΩ min. or 100MΩ • μF min. (whichever is less)	T = +25°C, V = 500Vdc T = +125°C, V = 500Vdc (t ≥ 120 sec, I ≤ 50mA)
Dielectric Strength	No breakdown or visual defect	120% of rated voltage t ≤ 5 sec, I ≤ 50mA



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

X7R CAPACITANCE RANGE PREFERRED SIZES ARE SHADED


Case Size Soldering	1206					1210					1808					1812					2220						
	Reflow/Wave					ReflowOnly					ReflowOnly					ReflowOnly					ReflowOnly						
(L) Length mm (in.)		3.20 ± 0.20 (0.126 ± 0.008)				3.30 ± 0.40 (0.130 ± 0.016)					4.57 ± 0.25 (0.180 ± 0.010)					4.50 ± 0.30 (0.177 ± 0.012)					5.70 ± 0.50 (0.224 ± 0.020)						
W) Width mm (in.)		1.60 ± 0.20 (0.063 ± 0.008)				2.50 ± 0.30 (0.098 ± 0.012)					2.03 ± 0.25 (0.080 ± 0.010)					3.20 ± 0.20 (0.126 ± 0.008)					5.00 ± 0.40 (0.197 ± 0.016)						
(T) Thickness mm (in.)		1.52 (0.060)				1.70 (0.067)					2.03					2.54					3.30						
(t) Terminal mm max		0.25 (0.010)				0.25 (0.010)					0.25 (0.010)					0.25 (0.010)					0.25 (0.010)						
Voltage (V)	630	1000	1500	2000	2500	630	1000	1500	2000	630	1000	1500	2000	2500	3000	630	1000	1500	2000	2500	3000	4000	630	1000	1500	2000	3000
Cap (pF)	100 101																										
	120 121																										
	150 151																										
	180 181																										
	220 221																										
	270 271																										
	330 331																										
	390 391																										
	470 471																										
	560 561																										
	680 681																										
	820 821																										
	1000 102																										
	1200 122																										
	1500 152																										
	1800 182																										
	2200 222																										
	2700 272																										
	3300 332																										
	3900 392																										
	4700 472																										
	5600 562																										
	6800 682																										
	8200 822																										
Cap (μF)	0.01 103																										
	0.012 123																										
	0.015 153																										
	0.018 183																										
	0.022 223																										
	0.027 273																										
	0.033 333																										
	0.039 393																										
	0.047 473																										
	0.056 563																										
	0.068 683																										
	0.082 823																										
	0.100 104																										
	0.120 124																										
	0.150 154																										
Voltage (V)	630	1000	1500	2000	2500	630	1000	1500	2000	630	1000	1500	2000	2500	3000	630	1000	1500	2000	2500	3000	4000	630	1000	1500	2000	3000
Case Size	1206					1210					1808					1812					2220						

NOTE: Contact factory for non-specified capacitance values

MIL-PRF-55681/Chips


Part Number Example

CDR01 thru CDR06



MILITARY DESIGNATION PER MIL-PRF-55681

Part Number Example



NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

MIL Style: CDR01, CDR02, CDR03, CDR04, CDR05, CDR06

Voltage Temperature Limits:

BP = $0 \pm 30 \text{ ppm}/^\circ\text{C}$ without voltage; $0 \pm 30 \text{ ppm}/^\circ\text{C}$ with rated voltage from -55°C to $+125^\circ\text{C}$

BX = $\pm 15\%$ without voltage; $+15 - 25\%$ with rated voltage from -55°C to $+125^\circ\text{C}$

Capacitance: Two digit figures followed by multiplier (number of zeros to be added) e.g., 101 = 100 pF

Rated Voltage: A = 50V, B = 100V

Capacitance Tolerance: J $\pm 5\%$, K $\pm 10\%$, M $\pm 20\%$

Termination Finish:

M = Palladium silver

N = Silver-nickel-gold

S = Solder coated final with a minimum of 4 percent lead

T = Silver

U = Base metallization-barrier metal-solder coated (tin/lead alloy, with a minimum of 4 percent lead)

W = Base metallization-barrier metal-tinned (tin or tin/lead alloy)

Y = Base metallization-barrier metal-tin (100 percent)

Z = Base metallization-barrier metal-tinned (tin/lead alloy, with a minimum of 4 percent lead)

*See MIL-PRF-55681 Specification for more details

Failure Rate Level: M = 1.0%, P = .1%, R = .01%, S = .001%

Packaging: Bulk is standard packaging. Tape and reel per RS481 is available upon request.

***Not RoHS Compliant**

CROSS REFERENCE: AVX/MIL-PRF-55681/CDR01 THRU CDR06*

Per MIL-PRF-55681	AVX Style	Length (L)	Width (W)	Thickness (T)		D		Termination Band (t)	
				Min.	Max.	Min.	Max.	Min.	Max.
CDR01	0805	.080 $\pm .015$.050 $\pm .015$.022	.055	.030	—	.010	—
CDR02	1805	.180 $\pm .015$.050 $\pm .015$.022	.055	—	—	.010	.030
CDR03	1808	.180 $\pm .015$.080 $\pm .018$.022	.080	—	—	.010	.030
CDR04	1812	.180 $\pm .015$.125 $\pm .015$.022	.080	—	—	.010	.030
CDR05	1825	.180 $^{+.020}_{-.015}$.250 $^{+.020}_{-.015}$.020	.080	—	—	.010	.030
CDR06	2225	.225 $\pm .020$.250 $\pm .020$.020	.080	—	—	.010	.030

*For CDR11, 12, 13, and 14 see AVX Microwave Chip Capacitor Catalog



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

CDR01 thru CDR06 to MIL-PRF-55681

Military Type Designation	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 0805/CDR01				
CDR01BP100B--	10	J,K	BP	100
CDR01BP120B--	12	J	BP	100
CDR01BP150B--	15	J,K	BP	100
CDR01BP180B--	18	J	BP	100
CDR01BP220B--	22	J,K	BP	100
CDR01BP270B--	27	J	BP	100
CDR01BP330B--	33	J,K	BP	100
CDR01BP390B--	39	J	BP	100
CDR01BP470B--	47	J,K	BP	100
CDR01BP560B--	56	J	BP	100
CDR01BP680B--	68	J,K	BP	100
CDR01BP820B--	82	J	BP	100
CDR01BP101B--	100	J,K	BP	100
CDR01B-121B--	120	J,K	BP,BX	100
CDR01B-151B--	150	J,K	BP,BX	100
CDR01B-181B--	180	J,K	BP,BX	100
CDR01BX221B--	220	K,M	BX	100
CDR01BX271B--	270	K	BX	100
CDR01BX331B--	330	K,M	BX	100
CDR01BX391B--	390	K	BX	100
CDR01BX471B--	470	K,M	BX	100
CDR01BX561B--	560	K	BX	100
CDR01BX681B--	680	K,M	BX	100
CDR01BX821B--	820	K	BX	100
CDR01BX102B--	1000	K,M	BX	100
CDR01BX122B--	1200	K	BX	100
CDR01BX152B--	1500	K,M	BX	100
CDR01BX182B--	1800	K	BX	100
CDR01BX222B--	2200	K,M	BX	100
CDR01BX272B--	2700	K	BX	100
CDR01BX332B--	3300	K,M	BX	100
CDR01BX392A--	3900	K	BX	50
CDR01BX472A--	4700	K,M	BX	50
AVX Style 1805/CDR02				
CDR02BP221B--	220	J,K	BP	100
CDR02BP271B--	270	J	BP	100
CDR02BX392B--	3900	K	BX	100
CDR02BX472B--	4700	K,M	BX	100
CDR02BX562B--	5600	K	BX	100
CDR02BX682B--	6800	K,M	BX	100
CDR02BX822B--	8200	K	BX	100
CDR02BX103B--	10,000	K,M	BX	100
CDR02BX123A--	12,000	K	BX	50
CDR02BX153A--	15,000	K,M	BX	50
CDR02BX183A--	18,000	K	BX	50
CDR02BX223A--	22,000	K,M	BX	50

- └ Add appropriate failure rate
- └ Add appropriate termination finish
- └ Capacitance Tolerance


Military Type Designation/	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1808/CDR03				
CDR03BP331B--	330	J,K	BP	100
CDR03BP391B--	390	J	BP	100
CDR03BP471B--	470	J,K	BP	100
CDR03BP561B--	560	J	BP	100
CDR03BP681B--	680	J,K	BP	100
CDR03BP821B--	820	J	BP	100
CDR03BP102B--	1000	J,K	BP	100
CDR03BX123B--	12,000	K	BX	100
CDR03BX153B--	15,000	K,M	BX	100
CDR03BX183B--	18,000	K	BX	100
CDR03BX223B--	22,000	K,M	BX	100
CDR03BX273B--	27,000	K	BX	100
CDR03BX333B--	33,000	K,M	BX	100
CDR03BX393A--	39,000	K	BX	50
CDR03BX473A--	47,000	K,M	BX	50
CDR03BX563A--	56,000	K	BX	50
CDR03BX683A--	68,000	K,M	BX	50
AVX Style 1812/CDR04				
CDR04BP122B--	1200	J	BP	100
CDR04BP152B--	1500	J,K	BP	100
CDR04BP182B--	1800	J	BP	100
CDR04BP222B--	2200	J,K	BP	100
CDR04BP272B--	2700	J	BP	100
CDR04BP332B--	3300	J,K	BP	100
CDR04BX393B--	39,000	K	BX	100
CDR04BX473B--	47,000	K,M	BX	100
CDR04BX563B--	56,000	K	BX	100
CDR04BX823A--	82,000	K	BX	50
CDR04BX104A--	100,000	K,M	BX	50
CDR04BX124A--	120,000	K	BX	50
CDR04BX154A--	150,000	K,M	BX	50
CDR04BX184A--	180,000	K	BX	50
AVX Style 1825/CDR05				
CDR05BP392B--	3900	J,K	BP	100
CDR05BP472B--	4700	J,K	BP	100
CDR05BP562B--	5600	J,K	BP	100
CDR05BX683B--	68,000	K,M	BX	100
CDR05BX823B--	82,000	K	BX	100
CDR05BX104B--	100,000	K,M	BX	100
CDR05BX124B--	120,000	K	BX	100
CDR05BX154B--	150,000	K,M	BX	100
CDR05BX224A--	220,000	K,M	BX	50
CDR05BX274A--	270,000	K	BX	50
CDR05BX334A--	330,000	K,M	BX	50
AVX Style 2225/CDR06				
CDR06BP682B--	6800	J,K	BP	100
CDR06BP822B--	8200	J,K	BP	100
CDR06BP103B--	10,000	J,K	BP	100
CDR06BX394A--	390,000	K	BX	50
CDR06BX474A--	470,000	K,M	BX	50

- └ Add appropriate failure rate
- └ Add appropriate termination finish
- └ Capacitance Tolerance

MIL-PRF-55681/Chips


Part Number Example

CDR31 thru CDR35



MILITARY DESIGNATION PER MIL-PRF-55681

Part Number Example



NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

Termination Finish:

M = Palladium silver

N = Silver-nickel-gold

S = Solder coated final with a minimum of 4 percent lead

T = Silver

U = Base metallization-barrier metal-solder coated
(tin/lead alloy, with a minimum of 4 percent lead)

W = Base metallization-barrier metal-tinned
(tin or tin/lead alloy)

Y = Base metallization-barrier metal-tin (100 percent)

Z = Base metallization-barrier metal-tinned
(tin/lead alloy, with a minimum of 4 percent lead)

*See MIL-PRF-55681 Specification for more details

Failure Rate Level: M = 1.0%, P = .1%, R = .01%,
S = .001%

Packaging: Bulk is standard packaging. Tape and reel per RS481 is available upon request.

***Not RoHS Compliant**

CROSS REFERENCE: AVX/MIL-PRF-55681/CDR31 THRU CDR35

Per MIL-PRF-55681	AVX Style	Length (L) (mm)	Width (W) (mm)	Termination Band (t)			
				Max. (mm)	Max. (mm)	Min. (mm)	Max. (mm)
CDR31	0805	2.00	1.25	1.3	.50	.70	.30
CDR32	1206	3.20	1.60	1.3	—	.70	.30
CDR33	1210	3.20	2.50	1.5	—	.70	.30
CDR34	1812	4.50	3.20	1.5	—	.70	.30
CDR35	1825	4.50	6.40	1.5	—	.70	.30



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

CDR31 to MIL-PRF-55681/7

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 0805/CDR31 (BP)				
CDR31BP1R0B--	1.0	B,C	BP	100
CDR31BP1R1B--	1.1	B,C	BP	100
CDR31BP1R2B--	1.2	B,C	BP	100
CDR31BP1R3B--	1.3	B,C	BP	100
CDR31BP1R5B--	1.5	B,C	BP	100
CDR31BP1R6B--	1.6	B,C	BP	100
CDR31BP1R8B--	1.8	B,C	BP	100
CDR31BP2R0B--	2.0	B,C	BP	100
CDR31BP2R2B--	2.2	B,C	BP	100
CDR31BP2R4B--	2.4	B,C	BP	100
CDR31BP2R7B--	2.7	B,C,D	BP	100
CDR31BP3R0B--	3.0	B,C,D	BP	100
CDR31BP3R3B--	3.3	B,C,D	BP	100
CDR31BP3R6B--	3.6	B,C,D	BP	100
CDR31BP3R9B--	3.9	B,C,D	BP	100
CDR31BP4R3B--	4.3	B,C,D	BP	100
CDR31BP4R7B--	4.7	B,C,D	BP	100
CDR31BP5R1B--	5.1	B,C,D	BP	100
CDR31BP5R6B--	5.6	B,C,D	BP	100
CDR31BP6R2B--	6.2	B,C,D	BP	100
CDR31BP6R8B--	6.8	B,C,D	BP	100
CDR31BP7R5B--	7.5	B,C,D	BP	100
CDR31BP8R2B--	8.2	B,C,D	BP	100
CDR31BP9R1B--	9.1	B,C,D	BP	100
CDR31BP100B--	10	F,J,K	BP	100
CDR31BP110B--	11	F,J,K	BP	100
CDR31BP120B--	12	F,J,K	BP	100
CDR31BP130B--	13	F,J,K	BP	100
CDR31BP150B--	15	F,J,K	BP	100
CDR31BP160B--	16	F,J,K	BP	100
CDR31BP180B--	18	F,J,K	BP	100
CDR31BP200B--	20	F,J,K	BP	100
CDR31BP220B--	22	F,J,K	BP	100
CDR31BP240B--	24	F,J,K	BP	100
CDR31BP270B--	27	F,J,K	BP	100
CDR31BP300B--	30	F,J,K	BP	100
CDR31BP330B--	33	F,J,K	BP	100
CDR31BP360B--	36	F,J,K	BP	100
CDR31BP390B--	39	F,J,K	BP	100
CDR31BP430B--	43	F,J,K	BP	100
CDR31BP470B--	47	F,J,K	BP	100
CDR31BP510B--	51	F,J,K	BP	100
CDR31BP560B--	56	F,J,K	BP	100
CDR31BP620B--	62	F,J,K	BP	100
CDR31BP680B--	68	F,J,K	BP	100
CDR31BP750B--	75	F,J,K	BP	100
CDR31BP820B--	82	F,J,K	BP	100
CDR31BP910B--	91	F,J,K	BP	100

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 0805/CDR31 (BP) cont'd				
CDR31BP101B--	100	F,J,K	BP	100
CDR31BP111B--	110	F,J,K	BP	100
CDR31BP121B--	120	F,J,K	BP	100
CDR31BP131B--	130	F,J,K	BP	100
CDR31BP151B--	150	F,J,K	BP	100
CDR31BP161B--	160	F,J,K	BP	100
CDR31BP181B--	180	F,J,K	BP	100
CDR31BP201B--	200	F,J,K	BP	100
CDR31BP221B--	220	F,J,K	BP	100
CDR31BP241B--	240	F,J,K	BP	100
CDR31BP271B--	270	F,J,K	BP	100
CDR31BP301B--	300	F,J,K	BP	100
CDR31BP331B--	330	F,J,K	BP	100
CDR31BP361B--	360	F,J,K	BP	100
CDR31BP391B--	390	F,J,K	BP	100
CDR31BP431B--	430	F,J,K	BP	100
CDR31BP471B--	470	F,J,K	BP	100
CDR31BP511A--	510	F,J,K	BP	50
CDR31BP561A--	560	F,J,K	BP	50
CDR31BP621A--	620	F,J,K	BP	50
CDR31BP681A--	680	F,J,K	BP	50

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 0805/CDR31 (BX)				
CDR31BX471B--	470	K,M	BX	100
CDR31BX561B--	560	K,M	BX	100
CDR31BX681B--	680	K,M	BX	100
CDR31BX821B--	820	K,M	BX	100
CDR31BX102B--	1,000	K,M	BX	100
CDR31BX122B--	1,200	K,M	BX	100
CDR31BX152B--	1,500	K,M	BX	100
CDR31BX182B--	1,800	K,M	BX	100
CDR31BX222B--	2,200	K,M	BX	100
CDR31BX272B--	2,700	K,M	BX	100
CDR31BX332B--	3,300	K,M	BX	100
CDR31BX392B--	3,900	K,M	BX	100
CDR31BX472B--	4,700	K,M	BX	100
CDR31BX562A--	5,600	K,M	BX	50
CDR31BX682A--	6,800	K,M	BX	50
CDR31BX822A--	8,200	K,M	BX	50
CDR31BX103A--	10,000	K,M	BX	50
CDR31BX123A--	12,000	K,M	BX	50
CDR31BX153A--	15,000	K,M	BX	50
CDR31BX183A--	18,000	K,M	BX	50

-  Add appropriate failure rate
-  Add appropriate termination finish
-  Capacitance Tolerance

1/ The complete part number will include additional symbols to indicate capacitance tolerance, termination and failure rate level.

-  Add appropriate failure rate
-  Add appropriate termination finish
-  Capacitance Tolerance

CDR32 to MIL-PRF-55681/8

Military Type Designation 1 /	Capacitance in pF	Capacitance Tolerance	Rated temperature and Voltage-Temperature Limits	WVDC
AVX Style 1206/CDR32 (BP)				
CDR32BP1R0B--	1.0	B,C	BP	100
CDR32BP1R1B--	1.1	B,C	BP	100
CDR32BP1R2B--	1.2	B,C	BP	100
CDR32BP1R3B--	1.3	B,C	BP	100
CDR32BP1R5B--	1.5	B,C	BP	100
CDR32BP1R6B--	1.6	B,C	BP	100
CDR32BP1R8B--	1.8	B,C	BP	100
CDR32BP2R0B--	2.0	B,C	BP	100
CDR32BP2R2B--	2.2	B,C	BP	100
CDR32BP2R4B--	2.4	B,C	BP	100
CDR32BP2R7B--	2.7	B,C,D	BP	100
CDR32BP3R0B--	3.0	B,C,D	BP	100
CDR32BP3R3B--	3.3	B,C,D	BP	100
CDR32BP3R6B--	3.6	B,C,D	BP	100
CDR32BP3R9B--	3.9	B,C,D	BP	100
CDR32BP4R3B--	4.3	B,C,D	BP	100
CDR32BP4R7B--	4.7	B,C,D	BP	100
CDR32BP5R1B--	5.1	B,C,D	BP	100
CDR32BP5R6B--	5.6	B,C,D	BP	100
CDR32BP6R2B--	6.2	B,C,D	BP	100
CDR32BP6R8B--	6.8	B,C,D	BP	100
CDR32BP7R5B--	7.5	B,C,D	BP	100
CDR32BP8R2B--	8.2	B,C,D	BP	100
CDR32BP9R1B--	9.1	B,C,D	BP	100
CDR32BP100B--	10	F,J,K	BP	100
CDR32BP110B--	11	F,J,K	BP	100
CDR32BP120B--	12	F,J,K	BP	100
CDR32BP130B--	13	F,J,K	BP	100
CDR32BP150B--	15	F,J,K	BP	100
CDR32BP160B--	16	F,J,K	BP	100
CDR32BP180B--	18	F,J,K	BP	100
CDR32BP200B--	20	F,J,K	BP	100
CDR32BP220B--	22	F,J,K	BP	100
CDR32BP240B--	24	F,J,K	BP	100
CDR32BP270B--	27	F,J,K	BP	100
CDR32BP300B--	30	F,J,K	BP	100
CDR32BP330B--	33	F,J,K	BP	100
CDR32BP360B--	36	F,J,K	BP	100
CDR32BP390B--	39	F,J,K	BP	100
CDR32BP430B--	43	F,J,K	BP	100
CDR32BP470B--	47	F,J,K	BP	100
CDR32BP510B--	51	F,J,K	BP	100
CDR32BP560B--	56	F,J,K	BP	100
CDR32BP620B--	62	F,J,K	BP	100
CDR32BP680B--	68	F,J,K	BP	100
CDR32BP750B--	75	F,J,K	BP	100
CDR32BP820B--	82	F,J,K	BP	100
CDR32BP910B--	91	F,J,K	BP	100

- └ Add appropriate failure rate
- └ Add appropriate termination finish
- └ Capacitance Tolerance

Military Type Designation 1 /	Capacitance in pF	Capacitance Tolerance	Rated Temperature and Voltage-Temperature Limits	WVDC
AVX Style 0805/CDR31 (BP) cont'd				
CDR32BP101B--	100	F,J,K	BP	100
CDR32BP111B--	110	F,J,K	BP	100
CDR32BP121B--	120	F,J,K	BP	100
CDR32BP131B--	130	F,J,K	BP	100
CDR32BP151B--	150	F,J,K	BP	100
CDR32BP161B--	160	F,J,K	BP	100
CDR32BP181B--	180	F,J,K	BP	100
CDR32BP201B--	200	F,J,K	BP	100
CDR32BP221B--	220	F,J,K	BP	100
CDR32BP241B--	240	F,J,K	BP	100
CDR32BP271B--	270	F,J,K	BP	100
CDR32BP301B--	300	F,J,K	BP	100
CDR32BP331B--	330	F,J,K	BP	100
CDR32BP361B--	360	F,J,K	BP	100
CDR32BP391B--	390	F,J,K	BP	100
CDR32BP431B--	430	F,J,K	BP	100
CDR32BP471B--	470	F,J,K	BP	100
CDR32BP511B--	510	F,J,K	BP	100
CDR32BP561B--	560	F,J,K	BP	100
CDR32BP621B--	620	F,J,K	BP	100
CDR32BP681B--	680	F,J,K	BP	100
CDR32BP751B--	750	F,J,K	BP	100
CDR32BP821B--	820	F,J,K	BP	100
CDR32BP911B--	910	F,J,K	BP	100
CDR32BP102B--	1,000	F,J,K	BP	100
CDR32BP112A--	1,100	F,J,K	BP	50
CDR32BP122A--	1,200	F,J,K	BP	50
CDR32BP132A--	1,300	F,J,K	BP	50
CDR32BP152A--	1,500	F,J,K	BP	50
CDR32BP162A--	1,600	F,J,K	BP	50
CDR32BP182A--	1,800	F,J,K	BP	50
CDR32BP202A--	2,000	F,J,K	BP	50
CDR32BP222A--	2,200	F,J,K	BP	50

Military Type Designation 1 /	Capacitance in pF	Capacitance Tolerance	Rated Temperature and Voltage-Temperature Limits	WVDC
AVX Style 1206/CDR32 (BX)				
CDR32BX472B--	4,700	K,M	BX	100
CDR32BX562B--	5,600	K,M	BX	100
CDR32BX682B--	6,800	K,M	BX	100
CDR32BX822B--	8,200	K,M	BX	100
CDR32BX103B--	10,000	K,M	BX	100
CDR32BX123B--	12,000	K,M	BX	100
CDR32BX153B--	15,000	K,M	BX	100
CDR32BX183A--	18,000	K,M	BX	50
CDR32BX223A--	22,000	K,M	BX	50
CDR32BX273A--	27,000	K,M	BX	50
CDR32BX333A--	33,000	K,M	BX	50
CDR32BX393A--	39,000	K,M	BX	50

- └ Add appropriate failure rate
- └ Add appropriate termination finish
- └ Capacitance Tolerance

1/ The complete part number will include additional symbols to indicate capacitance tolerance, termination and failure rate level.

CDR33/34/35 to MIL-PRF-55681/9/10/11

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1210/CDR33 (BP)				
CDR33BP102B--	1,000	F,J,K	BP	100
CDR33BP112B--	1,100	F,J,K	BP	100
CDR33BP122B--	1,200	F,J,K	BP	100
CDR33BP132B--	1,300	F,J,K	BP	100
CDR33BP152B--	1,500	F,J,K	BP	100
CDR33BP162B--	1,600	F,J,K	BP	100
CDR33BP182B--	1,800	F,J,K	BP	100
CDR33BP202B--	2,000	F,J,K	BP	100
CDR33BP222B--	2,200	F,J,K	BP	100
CDR33BP242A--	2,400	F,J,K	BP	50
CDR33BP272A--	2,700	F,J,K	BP	50
CDR33BP302A--	3,000	F,J,K	BP	50
CDR33BP332A--	3,300	F,J,K	BP	50

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1210/CDR33 (BX)				
CDR33BX153B--	15,000	K,M	BX	100
CDR33BX183B--	18,000	K,M	BX	100
CDR33BX223B--	22,000	K,M	BX	100
CDR33BX273B--	27,000	K,M	BX	100
CDR33BX393A--	39,000	K,M	BX	50
CDR33BX473A--	47,000	K,M	BX	50
CDR33BX563A--	56,000	K,M	BX	50
CDR33BX683A--	68,000	K,M	BX	50
CDR33BX823A--	82,000	K,M	BX	50
CDR33BX104A--	100,000	K,M	BX	50

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1812/CDR34 (BP)				
CDR34BP222B--	2,200	F,J,K	BP	100
CDR34BP242B--	2,400	F,J,K	BP	100
CDR34BP272B--	2,700	F,J,K	BP	100
CDR34BP302B--	3,000	F,J,K	BP	100
CDR34BP332B--	3,300	F,J,K	BP	100
CDR34BP362B--	3,600	F,J,K	BP	100
CDR34BP392B--	3,900	F,J,K	BP	100
CDR34BP432B--	4,300	F,J,K	BP	100
CDR34BP472B--	4,700	F,J,K	BP	100
CDR34BP512A--	5,100	F,J,K	BP	50
CDR34BP562A--	5,600	F,J,K	BP	50
CDR34BP622A--	6,200	F,J,K	BP	50
CDR34BP682A--	6,800	F,J,K	BP	50
CDR34BP752A--	7,500	F,J,K	BP	100
CDR34BP822B--	8,200	F,J,K	BP	100
CDR34BP823A--	8,600	F,J,K	BP	50
CDR34BP822A--	8,200	F,J,K	BP	50
CDR34BP912A--	9,100	F,J,K	BP	50
CDR34BP103A--	10,000	F,J,K	BP	50

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1812/CDR34 (BX)				
CDR34BX273B--	27,000	K,M	BX	100
CDR34BX333B--	33,000	K,M	BX	100
CDR34BX393B--	39,000	K,M	BX	100
CDR34BX473B--	47,000	K,M	BX	100
CDR34BX563B--	56,000	K,M	BX	100
CDR34BX104A--	100,000	K,M	BX	50
CDR34BX124A--	120,000	K,M	BX	50
CDR34BX154A--	150,000	K,M	BX	50
CDR34BX184A--	180,000	K,M	BX	50

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1825/CDR35 (BP)				
CDR35BP472B--	4,700	F,J,K	BP	100
CDR35BP512B--	5,100	F,J,K	BP	100
CDR35BP562B--	5,600	F,J,K	BP	100
CDR35BP622B--	6,200	F,J,K	BP	100
CDR35BP682B--	6,800	F,J,K	BP	100
CDR35BP752B--	7,500	F,J,K	BP	100
CDR35BP822B--	8,200	F,J,K	BP	100
CDR35BP912B--	9,100	F,J,K	BP	100
CDR35BP103B--	10,000	F,J,K	BP	100
CDR35BP113A--	11,000	F,J,K	BP	50
CDR35BP123A--	12,000	F,J,K	BP	50
CDR35BP133A--	13,000	F,J,K	BP	50
CDR35BP153A--	15,000	F,J,K	BP	50
CDR35BP163A--	16,000	F,J,K	BP	50
CDR35BP183A--	18,000	F,J,K	BP	50
CDR35BP203A--	20,000	F,J,K	BP	50
CDR35BP223A--	22,000	F,J,K	BP	50

Military Type Designation 1 /	Capacitance in pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	WVDC
AVX Style 1825/CDR35 (BX)				
CDR35BX563B--	56,000	K,M	BX	100
CDR35BX683B--	68,000	K,M	BX	100
CDR35BX823B--	82,000	K,M	BX	100
CDR35BX104B--	100,000	K,M	BX	100
CDR35BX124B--	120,000	K,M	BX	100
CDR35BX154B--	150,000	K,M	BX	100
CDR35BX184A--	180,000	K,M	BX	50
CDR35BX224A--	220,000	K,M	BX	50
CDR35BX274A--	270,000	K,M	BX	50
CDR35BX334A--	330,000	K,M	BX	50
CDR35BX394A--	390,000	K,M	BX	50
CDR35BX474A--	470,000	K,M	BX	50


- Add appropriate failure rate
- Add appropriate termination finish
- Capacitance Tolerance

- Add appropriate failure rate
- Add appropriate termination finish
- Capacitance Tolerance

1/ The complete part number will include additional symbols to indicate capacitance tolerance, termination and failure rate level.

MLCC Medical Applications – MM Series

General Specifications



The AVX MM series is a multi-layer ceramic capacitor designed for use in medical applications other than implantable/life support. These components have the design & change control expected for medical devices and also offer enhanced LAT including reliability testing and 100% inspection.

APPLICATIONS

Implantable, Non-Life Supporting Medical Devices

- e.g. implanted temporary cardiac monitor, insulin pumps

External, Life Supporting Medical Devices


- e.g. heart pump external controller

External Devices

- e.g. patient monitoring, diagnostic equipment

HOW TO ORDER

MM02	Z	A	100	J	G	T	3	A
Size	Rated Voltage	Dielectric Code	Capacitance Code (In pF)	Capacitance Tolerance	Failure Rate	Termination Finish	Packaging	Special Code
MM02 = 0402	Z = 10V	A = NP0 (C0G)	(2 significant digits + number of zeros)	B = $\pm 0.1\text{pF}$	C = Standard Range	T = Plated Ni & Sn (NP0 only)	2 = 7" Reel	A = Standard
MM03 = 0603	Y = 16V	C = X7R	for values $<10\text{pF}$:	C = $\pm 0.25\text{pF}$	Contact AVX for others	Z = Flexiterm (X7R only)	4 = 13" Reel	Contact AVX for others
MM05 = 0805	3 = 25V		letter R denotes decimal point.	D = $\pm 0.5\text{pF}$				
MM06 = 1206	5 = 50V		Example:	F = $\pm 1\% (\geq 10\text{pF})$				
MM10 = 1210	1 = 100V		68pF = 680	G = $\pm 2\% (\geq 10\text{pF})$				
MM08 = 1808	2 = 200V		8.2pF = 8R2	J = $\pm 5\%$				
MM12 = 1812	V = 250V			K = $\pm 10\%$				
MM20 = 2220	7 = 500V			M = $\pm 20\%$				



COMMERCIAL VS MM SERIES PROCESS COMPARISON

	Commercial	MM Series
Administrative	Standard part numbers; no restriction on who purchases these parts	Specific series part number, used to control supply of product
Design	Minimum ceramic thickness of 0.020" on all X7R product	Minimum ceramic thickness of 0.029" (0.74mm)
Dicing	Side & end margins = 0.003" min	Side & end margins = 0.004" min Cover layers = 0.003" min
Lot Qualification Destructive Physical Analysis (DPA)	As per EIA RS469	Increased sample plan – stricter criteria
Visual/Cosmetic Quality	Standard process and inspection	100% inspection
Application Robustness	Standard sampling for accelerated wave solder on X7R dielectrics	Increased sampling for accelerated wave solder on X7R and NP0 followed by lot by lot reliability testing
Design/Change Control	Required to inform customer of changes in: <ul style="list-style-type: none"> • form • fit • function 	AVX will qualify and notify customers before making any change to the following materials or processes: <ul style="list-style-type: none"> • Dielectric formulation, type, or supplier • Metal formulation, type, or supplier • Termination material formulation, type, or supplier • Manufacturing equipment type • Quality testing regime including sample size and accept/ reject criteria

MM Series – MLCC for Medical Applications



NP0 (C0G) – Specifications & Test Methods

Parameter/Test	NP0 Specification Limits		Measuring Conditions	
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber	
Capacitance	Within specified tolerance		Freq.: 1.0 MHz \pm 10% for cap \leq 1000 pF 1.0 kHz \pm 10% for cap $>$ 1000 pF Voltage: 1.0Vrms \pm .2V	
Q	<30 pF: Q \geq 400+20 x Cap Value ≥30 pF: Q \geq 1000			
Insulation Resistance	100,000MΩ or 1000MΩ - μF, whichever is less		Charge device with rated voltage for 60 \pm 5 secs @ room temp/humidity	
Dielectric Strength	No breakdown or visual defects		Charge device with 300% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.	
Resistance to Flexure Stresses	Appearance	No defects		
	Capacitance Variation	±5% or ±.5 pF, whichever is greater		
	Q	Meets Initial Values (As Above)		
	Insulation Resistance	≥ Initial Value x 0.3		
Solderability	≥ 95% of each terminal should be covered with fresh solder		Dip device in eutectic solder at 230 \pm 5°C for 5.0 \pm 0.5 seconds	
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal		
	Capacitance Variation	≤ ±2.5% or ±.25 pF, whichever is greater		
	Q	Meets Initial Values (As Above)		
	Insulation Resistance	Meets Initial Values (As Above)		
	Dielectric Strength	Meets Initial Values (As Above)		
Thermal Shock	Appearance	No visual defects	Step 1: -55°C \pm 2° 30 \pm 3 minutes	
	Capacitance Variation	≤ ±2.5% or ±.25 pF, whichever is greater	Step 2: Room Temp ≤ 3 minutes	
	Q	Meets Initial Values (As Above)	Step 3: +125°C \pm 2° 30 \pm 3 minutes	
	Insulation Resistance	Meets Initial Values (As Above)	Step 4: Room Temp ≤ 3 minutes	
	Dielectric Strength	Meets Initial Values (As Above)	Repeat for 5 cycles and measure after 24 hours at room temperature	
Load Life	Appearance	No visual defects	Charge device with twice rated voltage in test chamber set at 125°C \pm 2°C for 1000 hours (+48, -0). Remove from test chamber and stabilize at room temperature for 24 hours before measuring.	
	Capacitance Variation	≤ ±3.0% or ± .3 pF, whichever is greater		
	Q	≥ 30 pF: Q \geq 350 ≥10 pF, <30 pF: Q \geq 275 +5C/2 <10 pF: Q \geq 200 +10C		
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)		
	Dielectric Strength	Meets Initial Values (As Above)		
Load Humidity	Appearance	No visual defects	Store in a test chamber set at 85°C \pm 2°C/ 85% ± 5% relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature for 24 \pm 2 hours before measuring.	
	Capacitance Variation	≤ ±5.0% or ± .5 pF, whichever is greater		
	Q	≥ 30 pF: Q \geq 350 ≥10 pF, <30 pF: Q \geq 275 +5C/2 <10 pF: Q \geq 200 +10C		
	Insulation Resistance	≥ Initial Value x 0.3 (See Above)		
	Dielectric Strength	Meets Initial Values (As Above)		

MM Series – MLCC for Medical Applications

NP0/C0G Capacitance Range




PREFERRED SIZES ARE SHADED

SIZE	0603				0805				1206				
	WVDC	16	25	50	100	16	25	50	100	16	25	50	100
Cap (pF)	0.5	0R5											
	1.0	1R0											
	1.2	1R2											
	1.5	1R5											
	1.8	1R8											
	2.2	2R2											
	2.7	2R7											
	3.3	3R3											
	3.9	3R9											
	4.7	4R7											
	5.6	5R6											
	6.8	6R8											
	8.2	8R2											
	10	100											
	12	120											
	15	150											
	18	180											
	22	220											
	27	270											
	33	330											
	39	390											
	47	470											
	56	560											
	68	680											
	82	820											
	100	101											
	120	121											
	150	151											
	180	181											
	220	221											
	270	271											
	330	331											
	390	391											
	470	471											
	560	561											
	680	681											
	820	821											
	1000	102											
	1200	122											
	1500	152											
WVDC	16	25	50	100	16	25	50	100	16	25	50	100	
SIZE	0603				0805				1206				

MM Series – MLCC for Medical Applications



X7R Specifications and Test Methods

Parameter/Test	X7R Specification Limits		Measuring Conditions		
Operating Temperature Range	-55°C to +125°C		Temperature Cycle Chamber		
Capacitance	Within specified tolerance				
Q	$\leq 10\%$ for $\geq 50V$ DC rating $\leq 12.5\%$ for $25V$ DC rating $\leq 12.5\%$ for $25V$ and $16V$ DC rating $\leq 12.5\%$ for $\leq 10V$ DC rating		Freq.: 1.0 kHz $\pm 10\%$ Voltage: 1.0Vrms $\pm .2V$		
Insulation Resistance	100,000MΩ or 1000MΩ - μ F, whichever is less		Charge device with rated voltage for 120 ± 5 secs @ room temp/humidity		
Dielectric Strength	No breakdown or visual defects		Charge device with 300% of rated voltage for 1-5 seconds, w/charge and discharge current limited to 50 mA (max) Note: Charge device with 150% of rated voltage for 500V devices.		
Resistance to Flexure Stresses	Appearance	No defects			
	Capacitance Variation	$\leq \pm 12\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$			
Solderability	$\geq 95\%$ of each terminal should be covered with fresh solder		Dip device in eutectic solder at $230 \pm 5^\circ C$ for 5.0 ± 0.5 seconds		
Resistance to Solder Heat	Appearance	No defects, <25% leaching of either end terminal		Dip device in eutectic solder at $260^\circ C$ for 60 seconds. Store at room temperature for 24 ± 2 hours before measuring electrical properties.	
	Capacitance Variation	$\leq \pm 7.5\%$			
	Dissipation Factor	Meets Initial Values (As Above)			
	Insulation Resistance	Meets Initial Values (As Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Thermal Shock	Appearance	No visual defects		Step 1: $-55^\circ C \pm 2^\circ$ 30 ± 3 minutes	
	Capacitance Variation	$\leq \pm 7.5\%$		Step 2: Room Temp ≤ 3 minutes	
	Dissipation Factor	Meets Initial Values (As Above)		Step 3: $+125^\circ C \pm 2^\circ$ 30 ± 3 minutes	
	Insulation Resistance	Meets Initial Values (As Above)		Step 4: Room Temp ≤ 3 minutes	
	Dielectric Strength	Meets Initial Values (As Above)		Repeat for 5 cycles and measure after 24 ± 2 hours at room temperature	
Load Life	Appearance	No visual defects		Charge device with 1.5 rated voltage ($\leq 10V$) in test chamber set at $125^\circ C \pm 2^\circ C$ for 1000 hours (+48, -0) Remove from test chamber and stabilize at room temperature for 24 ± 2 hours before measuring.	
	Capacitance Variation	$\leq \pm 12.5\%$			
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			
Load Humidity	Appearance	No visual defects		Store in a test chamber set at $85^\circ C \pm 2^\circ C/ 85\% \pm 5\%$ relative humidity for 1000 hours (+48, -0) with rated voltage applied. Remove from chamber and stabilize at room temperature and humidity for 24 ± 2 hours before measuring.	
	Capacitance Variation	$\leq \pm 12.5\%$			
	Dissipation Factor	\leq Initial Value $\times 2.0$ (See Above)			
	Insulation Resistance	\geq Initial Value $\times 0.3$ (See Above)			
	Dielectric Strength	Meets Initial Values (As Above)			

MM Series – MLCC for Medical Applications



X7R Capacitance Range

PREFERRED SIZES ARE SHADED

SIZE	0402		0603		0805		1206		1210		1808		1812		2220														
	WVDC	16	25	50	10	16	25	50	100	200	250	10	16	25	50	100	200	250	500	50	100	200	50	100	200	250	25	50	100
Cap (pF)	220	221																											
	270	271																											
	330	331																											
	390	391																											
	470	471																											
	560	561																											
	680	681																											
	820	821																											
	1000	102																											
	1200	122																											
	1500	152																											
	1800	182																											
	2200	222																											
	2700	272																											
	3300	332																											
	3900	392																											
	4700	472																											
	5600	562																											
	6800	682																											
	8200	822																											
cap	0.010	103																											
uF	0.012	123																											
	0.015	153																											
	0.018	183																											
	0.022	223																											
	0.027	273																											
	0.033	333																											
	0.039	393																											
	0.047	473																											
	0.056	563																											
	0.068	683																											
	0.082	823																											
	0.10	104																											
	0.12	124																											
	0.15	154																											
	0.22	224																											
	0.33	334																											
	0.47	474																											
	0.56	564																											
	0.68	684																											
	0.82	824																											
	1.0	105																											
	1.2	125																											
	1.5	155																											
WVDC	16	25	50	10	16	25	50	100	200	10	16	25	50	100	200	250	500	10	16	25	50	100	200	250	500	50	100	200	
SIZE	0402	0603	0805	1206	1210	1808	1812	2220																					



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer by reference and should be reviewed in full before placing any order.

Packaging of Chip Components


Automatic Insertion Packaging

TAPE & REEL QUANTITIES

All tape and reel specifications are in compliance with RS481.

	4mm	8mm	12mm	
Paper or Embossed Carrier		0612, 0508, 0805, 1206, 1210		
Embossed Only	0101		1808	1812, 1825 2220, 2225
Paper Only		0101, 0201, 0306, 0402, 0603		
Qty. per Reel/7" Reel	4,000	1,000, 2,000, 3,000 or 4,000, 10,000, 15,000, 20,000 Contact factory for exact quantity	3,000	500, 1,000 Contact factory for exact quantity
Qty. per Reel/13" Reel		5,000, 10,000, 50,000 Contact factory for exact quantity	10,000	4,000

REEL DIMENSIONS



Tape Size ⁽¹⁾	A Max.	B* Min.	C	D* Min.	N Min.	W ₁	W ₂ Max.	W ₃
4mm	1.80 (7.087)	1.5 (0.059)	13.0 ^{±0.5} (0.522 ^{±0.020})	20.2 (0.795)	60.0 (2.362)	4.35 ^{±0.3} (0.171 ^{±0.011})	7.95 (0.312)	
8mm	330 (12.992)	1.5 (0.059)	13.0 ^{+0.50} -0.20 ^{+0.020} _{-0.008}	20.2 (0.795)	50.0 (1.969)	8.40 ^{+1.5} -0.0 ^{+0.059} _{-0.0}	14.4 (0.567)	7.90 Min. (0.311) 10.9 Max. (0.429)
						12.4 ^{+2.0} -0.0 ^{+0.079} _{-0.0}	18.4 (0.724)	11.9 Min. (0.469) 15.4 Max. (0.607)


Metric dimensions will govern.

English measurements rounded and for reference only.


(1) For tape sizes 16mm and 24mm (used with chip size 3640) consult EIA RS-481 latest revision.

Embossed Carrier Configuration

4, 8 & 12mm Tape Only



Chip Orientation



4, 8 & 12mm Embossed Tape Metric Dimensions Will Govern

CONSTANT DIMENSIONS

Tape Size	D ₀	E ₁	P ₀	P ₂	S ₁ Min.	T Max.	T ₁ Max.
4mm	0.80±0.04 (0.031±0.001)	0.90±0.05 (0.035±0.001)	2.0±0.04 (0.078±0.001)	1.00±0.02 (0.039±0.0007)	1.075 (0.042)	0.26 (0.010)	0.06 (0.002)
8mm & 12mm	1.50 ^{+0.10} (0.059 ^{+0.004})	1.75 ± 0.10 (0.069 ± 0.004)	4.0 ± 0.10 (0.157 ± 0.004)	2.0 ± 0.05 (0.079 ± 0.002)	0.60 (0.024)	0.60 (0.024)	0.10 (0.004)

VARIABLE DIMENSIONS

Tape Size	B ₁ Max.	D ₁ Min.	E ₂ Min.	F	P ₁ See Note 5	R Min. See Note 2	T ₂	W Max.	A ₀ B ₀ K ₀
8mm	4.35 (0.171)	1.00 (0.039)	6.25 (0.246)	3.50 ± 0.05 (0.138 ± 0.002)	4.00 ± 0.10 (0.157 ± 0.004)	25.0 (0.984)	2.50 Max. (0.098)	8.30 (0.327)	See Note 1
12mm	8.20 (0.323)	1.50 (0.059)	10.25 (0.404)	5.50 ± 0.05 (0.217 ± 0.002)	4.00 ± 0.10 (0.157 ± 0.004)	30.0 (1.181)	6.50 Max. (0.256)	12.3 (0.484)	See Note 1
8mm 1/2 Pitch	4.35 (0.171)	1.00 (0.039)	6.25 (0.246)	3.50 ± 0.05 (0.138 ± 0.002)	2.00 ± 0.10 (0.079 ± 0.004)	25.0 (0.984)	2.50 Max. (0.098)	8.30 (0.327)	See Note 1
12mm Double Pitch	8.20 (0.323)	1.50 (0.059)	10.25 (0.404)	5.50 ± 0.05 (0.217 ± 0.002)	8.00 ± 0.10 (0.315 ± 0.004)	30.0 (1.181)	6.50 Max. (0.256)	12.3 (0.484)	See Note 1




NOTES:

1. The cavity defined by A₀, B₀, and K₀ shall be configured to provide the following:
Surround the component with sufficient clearance such that:
b) the component does not protrude beyond the sealing plane of the cover tape.
c) the component can be removed from the cavity in a vertical direction without mechanical restriction, after the cover tape has been removed.
d) rotation of the component is limited to 20° maximum (see Sketches D & E).
e) lateral movement of the component is restricted to 0.5mm maximum (see Sketch F).
2. Tape with or without components shall pass around radius "R" without damage.

3. Bar code labeling (if required) shall be on the side of the reel opposite the round sprocket holes. Refer to EIA-556.


4. B₁ dimension is a reference dimension for tape feeder clearance only.

5. If P₁ = 2.0mm, the tape may not properly index in all tape feeders.



Paper Carrier Configuration

8 & 12mm Tape Only



4, 8 & 12mm Embossed Tape Metric Dimensions Will Govern

CONSTANT DIMENSIONS




Tape Size	D ₀	E	P ₀	P ₂	T ₁	G. Min.	R Min.
8mm and 12mm	1.50 ^{+0.10} (0.059 ^{+0.004})	1.75 ± 0.10 (0.069 ± 0.004)	4.00 ± 0.10 (0.157 ± 0.004)	2.00 ± 0.05 (0.079 ± 0.002)	0.10 (0.004) Max.	0.75 (0.030) Min.	25.0 (0.984) See Note 2 Min.

VARIABLE DIMENSIONS

Tape Size	P ₁ See Note 4	E ₂ Min.	F	W	A ₀ B ₀	T
8mm	4.00 ± 0.10 (0.157 ± 0.004)	6.25 (0.246)	3.50 ± 0.05 (0.138 ± 0.002)	8.00 ^{+0.30} (0.315 ^{+0.012})	See Note 1	1.10mm (0.043) Max. for Paper Base Tape and 1.60mm (0.063) Max. for Non-Paper Base Compositions
12mm	4.00 ± 0.10 (0.157 ± 0.004)	10.25 (0.404)	5.50 ± 0.05 (0.217 ± 0.002)	12.0 ± 0.30 (0.472 ± 0.012)		
8mm 1/2 Pitch	2.00 ± 0.05 (0.079 ± 0.002)	6.25 (0.246)	3.50 ± 0.05 (0.138 ± 0.002)	8.00 ^{+0.30} (0.315 ^{+0.012})		
12mm Double Pitch	8.00 ± 0.10 (0.315 ± 0.004)	10.25 (0.404)	5.50 ± 0.05 (0.217 ± 0.002)	12.0 ± 0.30 (0.472 ± 0.012)		

NOTES:

- The cavity defined by A₀, B₀, and T shall be configured to provide sufficient clearance surrounding the component so that:
 - the component does not protrude beyond either surface of the carrier tape;
 - the component can be removed from the cavity in a vertical direction without mechanical restriction after the top cover tape has been removed;
 - rotation of the component is limited to 20° maximum (see Sketches A & B);
 - lateral movement of the component is restricted to 0.5mm maximum (see Sketch C).
- Tape with or without components shall pass around radius "R" without damage.
- Bar code labeling (if required) shall be on the side of the reel opposite the sprocket holes. Refer to EIA-556.
- If P₁ = 2.0mm, the tape may not properly index in all tape feeders.



Bar Code Labeling Standard

AVX bar code labeling is available and follows latest version of EIA-556

Basic Capacitor Formulas

I. Capacitance (farads)

$$\text{English: } C = \frac{.224 \text{ K A}}{T_D}$$

$$\text{Metric: } C = \frac{.0884 \text{ K A}}{T_D}$$

II. Energy stored in capacitors (Joules, watt - sec)

$$E = \frac{1}{2} CV^2$$

III. Linear charge of a capacitor (Amperes)

$$I = C \frac{dV}{dt}$$

IV. Total Impedance of a capacitor (ohms)

$$Z = \sqrt{R_S^2 + (X_C - X_L)^2}$$

V. Capacitive Reactance (ohms)

$$X_C = \frac{1}{2 \pi f C}$$

VI. Inductive Reactance (ohms)

$$X_L = 2 \pi f L$$

VII. Phase Angles:

Ideal Capacitors: Current leads voltage 90°

Ideal Inductors: Current lags voltage 90°

Ideal Resistors: Current in phase with voltage

VIII. Dissipation Factor (%)

$$D.F. = \tan \delta \text{ (loss angle)} = \frac{E.S.R.}{X_C} = (2 \pi f C) (E.S.R.)$$

IX. Power Factor (%)

P.F. = Sine (loss angle) = Cos φ (phase angle)

P.F. = (when less than 10%) = DF

X. Quality Factor (dimensionless)

$$Q = \text{Cotan } \delta \text{ (loss angle)} = \frac{1}{D.F.}$$

XI. Equivalent Series Resistance (ohms)

$$E.S.R. = (D.F.) (X_C) = (D.F.) / (2 \pi f C)$$

XII. Power Loss (watts)

$$\text{Power Loss} = (2 \pi f C V^2) (D.F.)$$

XIII. KVA (Kilowatts)

$$KVA = 2 \pi f C V^2 \times 10^{-3}$$

XIV. Temperature Characteristic (ppm/°C)

$$T.C. = \frac{C_t - C_{25}}{C_{25} (T_t - 25)} \times 10^6$$

XV. Cap Drift (%)

$$C.D. = \frac{C_1 - C_2}{C_1} \times 100$$

XVI. Reliability of Ceramic Capacitors

$$L_0 = \left(\frac{V_t}{V_o} \right)^X \left(\frac{T_t}{T_o} \right)^Y$$

XVII. Capacitors in Series (current the same)

$$\text{Any Number: } \frac{1}{C_T} = \frac{1}{C_1} + \frac{1}{C_2} + \dots + \frac{1}{C_N}$$

$$\text{Two: } C_T = \frac{C_1 C_2}{C_1 + C_2}$$

XVIII. Capacitors in Parallel (voltage the same)

$$C_T = C_1 + C_2 + \dots + C_N$$

XIX. Aging Rate

$$A.R. = \% \Delta C / \text{decade of time}$$

XX. Decibels

$$db = 20 \log \frac{V_1}{V_2}$$

METRIC PREFIXES

Pico	$\times 10^{-12}$
Nano	$\times 10^{-9}$
Micro	$\times 10^{-6}$
Milli	$\times 10^{-3}$
Deci	$\times 10^{-1}$
Deca	$\times 10^{+1}$
Kilo	$\times 10^{+3}$
Mega	$\times 10^{+6}$
Giga	$\times 10^{+9}$
Tera	$\times 10^{+12}$


SYMBOLS

K = Dielectric Constant	f = frequency	L_t = Test life
A = Area	L = Inductance	V_t = Test voltage
T_D = Dielectric thickness	δ = Loss angle	V_o = Operating voltage
V = Voltage	φ = Phase angle	T_t = Test temperature
t = time	$X \& Y$ = exponent effect of voltage and temp.	T_o = Operating temperature
R_S = Series Resistance	L_o = Operating life	

General Description

Basic Construction – A multilayer ceramic (MLC) capacitor is a monolithic block of ceramic containing two sets of offset, interleaved planar electrodes that extend to two opposite surfaces of the ceramic dielectric. This simple structure requires a considerable amount of sophistication, both in material and manufacture, to produce it in the quality and quantities needed in

today's electronic equipment.



Formulations – Multilayer ceramic capacitors are available in both Class 1 and Class 2 formulations. Temperature compensating formulation are Class 1 and temperature stable and general application formulations are classified as Class 2.

Class 1 – Class 1 capacitors or temperature compensating capacitors are usually made from mixtures of titanates where barium titanate is normally not a major part of the mix. They have predictable temperature coefficients and in general, do not have an aging characteristic. Thus they are the most stable capacitor available. The most popular Class 1 multilayer ceramic capacitors are COG (NPO) temperature compensating capacitors (negative-positive 0 ppm/°C).

Class 2 – EIA Class 2 capacitors typically are based on the chemistry of barium titanate and provide a wide range of capacitance values and temperature stability. The most commonly used Class 2 dielectrics are X7R and Y5V. The X7R provides intermediate capacitance values which vary only $\pm 15\%$ over the temperature range of -55°C to 125°C. It finds applications where stability over a wide temperature range is required.

The Y5V provides the highest capacitance values and is used in applications where limited temperature changes are expected. The capacitance value for Y5V can vary from 22% to -82% over the -30°C to 85°C temperature range.

All Class 2 capacitors vary in capacitance value under the influence of temperature, operating voltage (both AC and DC), and frequency. For additional information on performance changes with operating conditions, consult AVX's software, SpiCap.

General Description

Table 1: EIA and MIL Temperature Stable and General Application Codes

EIA CODE	
Percent Capacity Change Over Temperature Range	
RS198	Temperature Range
X7	-55°C to +125°C
X6	-55°C to +105°C
X5	-55°C to +85°C
Y5	-30°C to +85°C
Z5	+10°C to +85°C
Code	Percent Capacity Change
D	±3.3%
E	±4.7%
F	±7.5%
P	±10%
R	±15%
S	±22%
T	+22%, -33%
U	+22%, -56%
V	+22%, -82%

EXAMPLE – A capacitor is desired with the capacitance value at 25°C to increase no more than 7.5% or decrease no more than 7.5% from -30°C to +85°C. EIA Code will be Y5F.

MIL CODE		
Symbol	Temperature Range	
A	-55°C to +85°C	
B	-55°C to +125°C	
C	-55°C to +150°C	
Symbol	Cap. Change Zero Volts	Cap. Change Rated Volts
R	+15%, -15%	+15%, -40%
S	+22%, -22%	+22%, -56%
W	+22%, -56%	+22%, -66%
X	+15%, -15%	+15%, -25%
Y	+30%, -70%	+30%, -80%
Z	+20%, -20%	+20%, -30%

Temperature characteristic is specified by combining range and change symbols, for example BR or AW. Specification slash sheets indicate the characteristic applicable to a given style of capacitor.

In specifying capacitance change with temperature for Class 2 materials, EIA expresses the capacitance change over an operating temperature range by a 3 symbol code. The first symbol represents the cold temperature end of the temperature range, the second represents the upper limit of the operating temperature range and the third symbol represents the capacitance change allowed over the operating temperature range. Table 1 provides a detailed explanation of the EIA system.

Effects of Voltage – Variations in voltage have little effect on Class 1 dielectric but does affect the capacitance and dissipation factor of Class 2 dielectrics. The application of DC voltage reduces both the capacitance and dissipation factor while the application of an AC voltage within a reasonable range tends to increase both capacitance and dissipation factor readings. If a high enough AC voltage is applied, eventually it will reduce capacitance just as a DC voltage will. Figure 2 shows the effects of AC voltage.

Cap. Change vs. A.C. Volts

X7R




Figure 2

Capacitor specifications specify the AC voltage at which to measure (normally 0.5 or 1 VAC) and application of the wrong voltage can cause spurious readings. Figure 3 gives the voltage coefficient of dissipation factor for various AC voltages at 1 kilohertz. Applications of different frequencies will affect the percentage changes versus voltages.

D.F. vs. A.C. Measurement Volts

X7R




Figure 3

Typical effect of the application of DC voltage is shown in Figure 4. The voltage coefficient is more pronounced for higher K dielectrics. These figures are shown for room temperature conditions. The combination characteristic known as voltage temperature limits which shows the effects of rated voltage over the operating temperature range is shown in Figure 5 for the military BX characteristic.

General Description

Example Change vs. D.C. Volts
X7R




Figure 4

Example Cap. Change vs. Temperature
X7R





Figure 5

Effects of Time – Class 2 ceramic capacitors change capacitance and dissipation factor with time as well as temperature, voltage and frequency. This change with time is known as aging. Aging is caused by a gradual re-alignment of the crystalline structure of the ceramic and produces an exponential loss in capacitance and decrease in dissipation factor versus time. A typical curve of aging rate for semistable ceramics is shown in Figure 6.

If a Class 2 ceramic capacitor that has been sitting on the shelf for a period of time, is heated above its curie point, (125°C for 4 hours or 150°C for 1/2 hour will suffice) the part will de-age and return to its initial capacitance and dissipation factor readings. Because the capacitance changes rapidly, immediately after de-aging, the basic capacitance measurements are normally referred to a time period sometime after the de-aging process. Various manufacturers use different time bases but the most popular one is one day or twenty-four hours after "last heat." Change in the aging curve can be caused by the application of voltage and other stresses. The possible changes in capacitance due to de-aging by heating the unit explain why capacitance changes are allowed after test, such as temperature cycling, moisture resistance, etc., in MIL specs. The application of high voltages such as dielectric withstanding voltages also tends to de-age capacitors and is why re-reading of capacitance after 12 or 24 hours is allowed in military specifications after dielectric strength tests have been performed.

Example Curve of Aging Rate
X7R



Characteristic	Max. Aging Rate %/Decade
C0G (NP0)	None
X7R, X5R	2
Y5V	7

Figure 6

Effects of Frequency – Frequency affects capacitance and impedance characteristics of capacitors. This effect is much more pronounced in high dielectric constant ceramic formulation than in low K formulations. AVX's SpiCap software generates impedance, ESR, series inductance, series resonant frequency and capacitance all as functions of frequency, temperature and DC bias for standard chip sizes and styles. It is available free from AVX and can be downloaded for free from AVX website: www.avx.com.



General Description

Effects of Mechanical Stress – High "K" dielectric ceramic capacitors exhibit some low level piezoelectric reactions under mechanical stress. As a general statement, the piezoelectric output is higher, the higher the dielectric constant of the ceramic. It is desirable to investigate this effect before using high "K" dielectrics as coupling capacitors in extremely low level applications.

Reliability – Historically ceramic capacitors have been one of the most reliable types of capacitors in use today. The approximate formula for the reliability of a ceramic capacitor is:

$$\frac{L_o}{L_t} = \left(\frac{V_t}{V_o} \right)^X \left(\frac{T_t}{T_o} \right)^Y$$

where

L_o = operating life	T_t = test temperature and
L_t = test life	T_o = operating temperature
V_t = test voltage	in °C
V_o = operating voltage	X, Y = see text

Historically for ceramic capacitors exponent X has been considered as 3. The exponent Y for temperature effects typically tends to run about 8.

A capacitor is a component which is capable of storing electrical energy. It consists of two conductive plates (electrodes) separated by insulating material which is called the dielectric. A typical formula for determining capacitance is:

$$C = \frac{.224 \text{ KA}}{t}$$

C = capacitance (picofarads)
 K = dielectric constant (Vacuum = 1)
 A = area in square inches
 t = separation between the plates in inches (thickness of dielectric)
 .224 = conversion constant (.0884 for metric system in cm)

Capacitance – The standard unit of capacitance is the farad. A capacitor has a capacitance of 1 farad when 1 coulomb charges it to 1 volt. One farad is a very large unit and most capacitors have values in the micro (10^{-6}), nano (10^{-9}) or pico (10^{-12}) farad level.

Dielectric Constant – In the formula for capacitance given above the dielectric constant of a vacuum is arbitrarily chosen as the number 1. Dielectric constants of other materials are then compared to the dielectric constant of a vacuum.

Dielectric Thickness – Capacitance is indirectly proportional to the separation between electrodes. Lower voltage requirements mean thinner dielectrics and greater capacitance per volume.

Area – Capacitance is directly proportional to the area of the electrodes. Since the other variables in the equation are usually set by the performance desired, area is the easiest parameter to modify to obtain a specific capacitance within a material group.

Energy Stored – The energy which can be stored in a capacitor is given by the formula:

$$E = \frac{1}{2}CV^2$$

E = energy in joules (watts-sec)
 V = applied voltage
 C = capacitance in farads

Potential Change – A capacitor is a reactive component which reacts against a change in potential across it. This is shown by the equation for the linear charge of a capacitor:

$$I_{\text{ideal}} = C \frac{dV}{dt}$$


where

I = Current
 C = Capacitance
 dV/dt = Slope of voltage transition across capacitor

Thus an infinite current would be required to instantly change the potential across a capacitor. The amount of current a capacitor can "sink" is determined by the above equation.

Equivalent Circuit – A capacitor, as a practical device, exhibits not only capacitance but also resistance and inductance. A simplified schematic for the equivalent circuit is:

C = Capacitance	L = Inductance
R_s = Series Resistance	R_p = Parallel Resistance



Reactance – Since the insulation resistance (R_p) is normally very high, the total impedance of a capacitor is:

$$Z = \sqrt{R_s^2 + (X_C - X_L)^2}$$


where

Z = Total Impedance	
R_s = Series Resistance	
X_C = Capacitive Reactance	$= \frac{1}{2\pi fC}$
X_L = Inductive Reactance	$= 2\pi fL$

The variation of a capacitor's impedance with frequency determines its effectiveness in many applications.

Phase Angle – Power Factor and Dissipation Factor are often confused since they are both measures of the loss in a capacitor under AC application and are often almost identical in value. In a "perfect" capacitor the current in the capacitor will lead the voltage by 90°.

General Description



In practice the current leads the voltage by some other phase angle due to the series resistance R_S . The complement of this angle is called the loss angle and:

$$\begin{aligned} \text{Power Factor (P.F.)} &= \cos \phi \text{ or } \sin \delta \\ \text{Dissipation Factor (D.F.)} &= \tan \delta \end{aligned}$$

for small values of the tan and sine are essentially equal which has led to the common interchangeability of the two terms in the industry.

Equivalent Series Resistance – The term E.S.R. or Equivalent Series Resistance combines all losses both series and parallel in a capacitor at a given frequency so that the equivalent circuit is reduced to a simple R-C series connection.

Dissipation Factor – The DF/PF of a capacitor tells what percent of the apparent power input will turn to heat in the capacitor.

The $\frac{di}{dt}$ seen in current microprocessors can be as high as 0.3 A/ns, and up to 10A/ns. At 0.3 A/ns, 100pH of parasitic inductance can cause a voltage spike of 30mV. While this does not sound very drastic, with the V_{CC} for microprocessors decreasing at the current rate, this can be a fairly large percentage.

Another important, often overlooked, reason for knowing the parasitic inductance is the calculation of the resonant frequency. This can be important for high frequency, bypass capacitors, as the resonant point will give the most signal attenuation. The resonant frequency is calculated from the simple equation:

$$f_{res} = \frac{1}{2\pi\sqrt{LC}}$$

Insulation Resistance – Insulation Resistance is the resistance measured across the terminals of a capacitor and consists principally of the parallel resistance R_P shown in the equivalent circuit. As capacitance values and hence the area of dielectric increases, the I.R. decreases and hence the product ($C \times IR$ or RC) is often specified in ohm farads or more commonly megohm-microfarads. Leakage current is determined by dividing the rated voltage by IR (Ohm's Law).

Dielectric Strength – Dielectric Strength is an expression of the ability of a material to withstand an electrical stress. Although dielectric strength is ordinarily expressed in volts, it is actually dependent on the thickness of the dielectric and thus is also more generically a function of volts/mil.

Dielectric Absorption – A capacitor does not discharge instantaneously upon application of a short circuit, but drains gradually after the capacitance proper has been discharged. It is common practice to measure the dielectric absorption by determining the "reappearing voltage" which appears across a capacitor at some point in time after it has been fully discharged under short circuit conditions.

Corona – Corona is the ionization of air or other vapors which causes them to conduct current. It is especially prevalent in high voltage units but can occur with low voltages as well where high voltage gradients occur. The energy discharged degrades the performance of the capacitor and can in time cause catastrophic failures.

$$\text{Dissipation Factor} = \frac{\text{E.S.R.}}{X_C} = (2\pi fC) (\text{E.S.R.})$$

The watts loss are:

$$\text{Watts loss} = (2\pi fCV^2) (\text{D.F.})$$

Very low values of dissipation factor are expressed as their reciprocal for convenience. These are called the "Q" or Quality factor of capacitors.


Parasitic Inductance – The parasitic inductance of capacitors is becoming more and more important in the decoupling of today's high speed digital systems. The relationship between the inductance and the ripple voltage induced on the DC voltage line can be seen from the simple inductance equation:

$$V = L \frac{di}{dt}$$

Surface Mounting Guide

MLC Chip Capacitors

REFLOW SOLDERING



Case Size	D1	D2	D3	D4	D5
0201	0.85 (0.033)	0.30 (0.012)	0.25 (0.010)	0.30 (0.012)	0.35 (0.014)
0402	1.70 (0.067)	0.60 (0.024)	0.50 (0.020)	0.60 (0.024)	0.50 (0.020)
0603	2.30 (0.091)	0.80 (0.031)	0.70 (0.028)	0.80 (0.031)	0.75 (0.030)
0805	3.00 (0.118)	1.00 (0.039)	1.00 (0.039)	1.00 (0.039)	1.25 (0.049)
1206	4.00 (0.157)	1.00 (0.039)	2.00 (0.079)	1.00 (0.039)	1.60 (0.063)
1210	4.00 (0.157)	1.00 (0.039)	2.00 (0.079)	1.00 (0.039)	2.50 (0.098)
1808	5.60 (0.220)	1.00 (0.039)	3.60 (0.142)	1.00 (0.039)	2.00 (0.079)
1812	5.60 (0.220)	1.00 (0.039)	3.60 (0.142)	1.00 (0.039)	3.00 (0.118)
1825	5.60 (0.220)	1.00 (0.039)	3.60 (0.142)	1.00 (0.039)	6.35 (0.250)
2220	6.60 (0.260)	1.00 (0.039)	4.60 (0.181)	1.00 (0.039)	5.00 (0.197)
2225	6.60 (0.260)	1.00 (0.039)	4.60 (0.181)	1.00 (0.039)	6.35 (0.250)

Dimensions in millimeters (inches)

Component Pad Design


Component pads should be designed to achieve good solder fillets and minimize component movement during reflow soldering. Pad designs are given below for the most common sizes of multilayer ceramic capacitors for both wave and reflow soldering. The basis of these designs is:

- Pad width equal to component width. It is permissible to

decrease this to as low as 85% of component width but it is not advisable to go below this.

- Pad overlap 0.5mm beneath component.
- Pad extension 0.5mm beyond components for reflow and 1.0mm for wave soldering.

WAVE SOLDERING



Case Size	D1	D2	D3	D4	D5
0603	3.10 (0.12)	1.20 (0.05)	0.70 (0.03)	1.20 (0.05)	0.75 (0.03)
0805	4.00 (0.15)	1.50 (0.06)	1.00 (0.04)	1.50 (0.06)	1.25 (0.05)
1206	5.00 (0.19)	1.50 (0.06)	2.00 (0.09)	1.50 (0.06)	1.60 (0.06)

Dimensions in millimeters (inches)

Component Spacing

For wave soldering components must be spaced sufficiently far apart to avoid bridging or shadowing (inability of solder to penetrate properly into small spaces). This is less important for reflow soldering but sufficient space must be allowed to enable rework should it be required.

Preheat & Soldering

The rate of preheat should not exceed 4°C/second to prevent thermal shock. A better maximum figure is about 2°C/second.


For capacitors size 1206 and below, with a maximum thickness of 1.25mm, it is generally permissible to allow a temperature differential from preheat to soldering of 150°C. In all other cases this differential should not exceed 100°C.

For further specific application or process advice, please consult AVX.

Cleaning

Care should be taken to ensure that the capacitors are thoroughly cleaned of flux residues especially the space beneath the capacitor. Such residues may otherwise become conductive and effectively offer a low resistance bypass to the capacitor.

Ultrasonic cleaning is permissible, the recommended conditions being 8 Watts/litre at 20-45 kHz, with a process cycle of 2 minutes vapor rinse, 2 minutes immersion in the ultrasonic solvent bath and finally 2 minutes vapor rinse.



Surface Mounting Guide

Recommended Soldering Profiles

REFLOW SOLDER PROFILES

AVX RoHS compliant products utilize termination finishes (e.g. Sn or SnAg) that are compatible with all Pb-Free soldering systems and are fully reverse compatible with SnPb soldering systems. A recommended SnPb profile is shown for comparison; for Pb-Free soldering, IPC/JEDECJ- STD-020C may be referenced. The upper line in the chart shows the maximum envelope to which products are qualified (typically 3x reflow cycles at 260°C max). The center line gives the recommended profile for optimum wettability and soldering in Pb-Free Systems.

Preheat:

The pre-heat stabilizes the part and reduces the temperature differential prior to reflow. The initial ramp to 125°C may be rapid, but from that point (2-3)°C/sec is recommended to allow ceramic parts to heat uniformly and plastic encapsulated parts to stabilize through the glass transition temperature of the body (~ 180°C).

Reflow:

In the reflow phase, the maximum recommended time > 230°C is 40secs. Time at peak reflow is 10secs max.; optimum reflow is achieved at 250°C, (see wetting balance chart opposite) but products are qualified to 260°C max. Please reference individual product datasheets for maximum limits

Cool Down:

Cool down should not be forced and 6°C/sec is recommended. A slow cool down will result in a finer grain structure of the reflow solder in the solder fillet.

WAVE SOLDER PROFILES

For wave solder, there is no change in the recommended wave profile; all standard Pb-Free (SnCu/SnCuAg) systems operate at the same 260°C max recommended for SnPb systems.

Preheat:



This is more important for wave solder; a higher temperature preheat will reduce the thermal shock to SMD parts that are immersed (please consult individual product data sheets for SMD parts that are suited to wave solder). SMD parts should ideally be heated from the bottom-Side prior to wave. PTH (Pin through hole) parts on the topside should not be separately heated.

Wave:


250°C – 260°C recommended for optimum solderability.

Cool Down:

As with reflow solder, cool down should not be forced and 6°C/sec is recommended. Any air knives at the end of the 2nd wave should be heated.



IMPORTANT NOTE: Typical Pb-Free reflow solders have a more dull and grainy appearance compared to traditional SnPb. Elevating the reflow temperature will not change this, but extending the cool down can help improve the visual appearance of the joint.



Surface Mounting Guide

MLC Chip Capacitors



APPLICATION NOTES

Storage

The components should be stored in their "as received packaging" where possible. If the components are removed from their original packaging then they should be stored in an airtight container (e.g. a heat sealed plastic bag) with desiccant (e.g. silica gel). Storage area temperature should be kept between +5 degrees C and +30 degrees C with humidity < 70% RH. Storage atmosphere must be free of gas containing sulfur and chlorine. Avoid exposing the product to saline moisture or to temperature changes that might result in the formation of condensation. To assure good solderability performance we recommend that the product be used within 6 months from our shipping date, but can be used for up to 12 months. Chip capacitors may crack if exposed to hydrogen (H₂) gas while sealed or if coated with silicon, which generates hydrogen gas.

Solderability

Terminations to be well soldered after immersion in a 60/40 tin/lead solder bath at 245°C +/- 5°C for 5 +0/-0.5 seconds.

Leaching

Terminations will resist leaching for at least the immersion times and conditions shown below.

Termination Type	Solder Tin/Lead/Silver	Solder Temp °C	Immersion Time Seconds
Nickel Barrier	60/40/0	260 ± 5	30 ± 1

Lead-Free Wave Soldering

The recommended peak temperature for lead-free wave soldering is 250°C-260°C for 3-5 seconds. The other parameters of the profile remains the same as above.

The following should be noted by customers changing from lead based systems to the new lead free pastes.

- A. The visual standards used for evaluation of solder joints will need to be modified as lead free joints are not as bright as with tin-lead pastes and the fillet may not be as large.
- B. Lead-free solder pastes do not allow the same self alignment as lead containing systems. Standard mounting pads are acceptable, but machine set up may need to be modified.

General

Surface mounting chip multilayer ceramic capacitors are designed for soldering to printed circuit boards or other substrates. The construction of the components is such that they will withstand the time/temperature profiles used in both wave and reflow soldering methods.

Handling

Chip multilayer ceramic capacitors should be handled with care to avoid damage or contamination from perspiration and skin oils. The use of tweezers or vacuum pick ups is strongly recommended for individual components. Bulk handling should ensure that abrasion and mechanical shock are minimized. Taped and reeled components provides the ideal medium for direct presentation to the placement machine. Any mechanical shock should be minimized during handling chip multilayer ceramic capacitors.

Preheat

It is important to avoid the possibility of thermal shock during soldering and carefully controlled preheat is therefore required. The rate of preheat should not exceed 4°C/second and a target figure 2°C/second is recommended. Although an 80°C to 120°C temperature differential is preferred, recent developments allow a temperature differential between the component surface and the soldering temperature of 150°C (Maximum) for capacitors of 1210 size and below with a maximum thickness of 1.25mm. The user is cautioned that the risk of thermal shock increases as chip size or temperature differential increases.

Soldering

Mildly activated rosin fluxes are preferred. The minimum amount of solder to give a good joint should be used. Excessive solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. AVX terminations are suitable for all wave and reflow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

Cooling

Natural cooling in air is preferred, as this minimizes stresses within the soldered joint. When forced air cooling is used, cooling rate should not exceed 4°C/second. Quenching is not recommended but if used, maximum temperature differentials should be observed according to the preheat conditions above.

Cleaning

Flux residues may be hygroscopic or acidic and must be removed. AVX MLC capacitors are acceptable for use with all of the solvents described in the specifications MIL-STD-202 and EIA-RS-198. Alcohol based solvents are acceptable and properly controlled water cleaning systems are also acceptable. Many other solvents have been proven successful, and most solvents that are acceptable to other components on circuit assemblies are equally acceptable for use with ceramic capacitors.

Prevention of Metallic Migration

Note that when components with Sn plating on the end terminations are to be used in applications that are likely to experience conditions of high humidity under bias voltage, we strongly recommend that the circuit boards be conformally coated to protect the Sn from moisture that might lead to migration and eventual current leakage.

When using Capacitor Arrays we recommend that there is no differential in applied voltage between adjacent elements.

Surface Mounting Guide

MLC Chip Capacitors

POST SOLDER HANDLING

Once SMP components are soldered to the board, any bending or flexure of the PCB applies stresses to the soldered joints of the components. For leaded devices, the stresses are absorbed by the compliancy of the metal leads and generally don't result in problems unless the stress is large enough to fracture the soldered connection.

Ceramic capacitors are more susceptible to such stress because they don't have compliant leads and are brittle in nature. The most frequent failure mode is low DC resistance or short circuit. The second failure mode is significant loss of capacitance due to severing of contact between sets of the internal electrodes.

Cracks caused by mechanical flexure are very easily identified and generally take one of the following two general forms:


Mechanical cracks are often hidden underneath the termination and are difficult to see externally. However, if one end termination falls off during the removal process from PCB, this is one indication that the cause of failure was excessive mechanical stress due to board warping.

COMMON CAUSES OF MECHANICAL CRACKING


The most common source for mechanical stress is board depanelization equipment, such as manual breakapart, v-cutters and shear presses. Improperly aligned or dull cutters may cause torquing of the PCB resulting in flex stresses being transmitted to components near the board edge. Another common source of flexural stress is contact during parametric testing when test points are probed. If the PCB is allowed to flex during the test cycle, nearby ceramic capacitors may be broken.

A third common source is board to board connections at vertical connectors where cables or other PCBs are connected to the PCB. If the board is not supported during the plug/unplug cycle, it may flex and cause damage to nearby components.

Special care should also be taken when handling large ($>6"$ on a side) PCBs since they more easily flex or warp than smaller boards.



Type A:
Angled crack between bottom of device to top of solder joint.




Type B:
Fracture from top of device to bottom of device.


REWORKING OF MLCS

Thermal shock is common in MLCS that are manually attached or reworked with a soldering iron. AVX strongly recommends that any reworking of MLCS be done with hot air reflow rather than soldering irons. It is practically impossible to cause any thermal shock in ceramic capacitors when using hot air reflow.

However direct contact by the soldering iron tip often causes thermal cracks that may fail at a later date. If rework by soldering iron is absolutely necessary, it is recommended that the wattage of the iron be less than 30 watts and the tip temperature be $<300^{\circ}\text{C}$. Rework should be performed by applying the solder iron tip to the pad and not directly contacting any part of the ceramic capacitor.




Preferred Method - No Direct Part Contact




Poor Method - Direct Contact with Part

PCB BOARD DESIGN

To avoid many of the handling problems, AVX recommends that MLCS be located at least $.2"$ away from nearest edge of board. However when this is not possible, AVX recommends that the panel be routed along the cut line, adjacent to where the MLC is located.



No Stress Relief for MLCS



Routed Cut Line Relieves Stress on MLC



FOLLOW US:

VISIT US AT WWW.AVX.COM

North America
Tel: +1 864-967-2150

Europe
Tel: +44 1276-697000

Asia
Tel: +65 6286-7555

Central America
Tel: +55 11-46881960

Japan
Tel: +81 740-321250