

4		3		2		1													
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS											
© COPYRIGHT — By —		ALL RIGHTS RESERVED.		G		—		P		LTR		DESCRIPTION		DATE		DWN		APVD	
										H1		REDRAW PER ECO-11-020548		02FEB12		KH		DR	

D

C

B

A

1

FOR 2.67[.105] TO 5.08[.200] WIRE INSULATION DIA

SERRATIONS

SLEEVE

AMP

AMP

AMP

AMP

SPLICE

29.46
[1.160]
MAX

500	LOOSE PIECE	INSULATION: PVC COLOR: YELLOW BODY: COPPER PER ASTM B152 ANNEALED TIN PLATED PER ASTM B545		34069
QTY	PACKAGE TYPE	MATERIAL & FINISH		PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

MATERIAL
—

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ± —
1 PLC ± —
2 PLC ± —
3 PLC ± 0.203[.008]
4 PLC ± —
ANGLES ± 5°
FINISH —

DWN
KIRAN HOLAL
CHK
ROHDE DANIEL
APVD
ROHDE DANIEL
PRODUCT SPEC
—
APPLICATION SPEC
—
WEIGHT
—

02FEB12
02FEB12
02FEB12

TE Connectivity

NAME
—
WIRE SPLICE BUTT-PLASTI-GRIP WIRE SIZE 12-10

SIZE
A3

CAGE CODE
00779

DRAWING NO
C-34069

RESTRICTED TO
—

CUSTOMER DRAWING

SCALE
8:1

SHEET
1 OF 1

REV
H1

1470-19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[34069](#)