






REVISIONS					
#	LYR	DESCRIPTION	DATE	DWN	APVD
	D	REVISED PER ECO-16-009784	20JUN16	RS	GJ



POS.	DIM. A
3*5	33.70
3*4	27.70
3*3	21.70



- 1

MATERIAL:
LEVEL 1:PBT,STANDARD TEMPERATURE 105°C
KEY A:NATURAL; KEY B:PURPLE; KEY C:BLUE; KEY D:YELLOW

LEVEL 2:NYLON,HIGH TEMPERATURE 150°C
KEY A:LIGHT GREY; KEY B:RED; KEY C:BLACK; KEY D:NATURAL
- 2

MATERIAL MARK:
LEVEL 1:PBT,LEVEL 2:HDT
- 3







APPLICABLE CONTACT P/N
RECEPTACLE CONTACT:1971237/1971779/81/83/85/87-*, 2238066-*
- 4

MATING CONN. P/N
CAP HSG:*-1971874/5-*,
DOUBLE ROW LOCK PLATE:*-1971778-*;SINGLE ROW LOCK PLATE:*-1971777-*

5 This product has not completed validation testing.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN TOMMY WU 09JUL2012	TE TE Connectivity PLUG HOUSING,TRIPLE ROW POWER TRIPLE LOCK			
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ±0.35 2 PLC ±0.25 3 PLC ± 4 PLC ± ANGLES ± FINISH	CHK HAPYE WU 09JUL2012				
		APVD YUZHONG MAO 09JUL2012				
		PRODUCT SPEC 108-106118				
		APPLICATION SPEC 114-106118				
MATERIAL 1	-	WEIGHT -	SIZE A1	CAGE CODE 00779	DRAWING NO 1971876	RESTRICTED TO -
Customer Drawing			SCALE 3:1	SHEET 1	OF 2	REV D

REVISIONS				
P	LYR	DESCRIPTION	DATE	APVD
	-	SEE SHEET 1	-	-




3*5	LEVEL 1	KEY A	1-1971876-7
		KEY B	2-1971876-7
		KEY C	3-1971876-7
		KEY D	4-1971876-7
3*4	LEVEL 2	KEY A	5-1971876-7
		KEY B	6-1971876-7
		KEY C	7-1971876-7
		KEY D	8-1971876-7
3*3	LEVEL 1	KEY A	1-1971876-4
		KEY B	2-1971876-4
		KEY C	3-1971876-4
		KEY D	4-1971876-4
3*4	LEVEL 2	KEY A	5-1971876-4
		KEY B	6-1971876-4
		KEY C	7-1971876-4
		KEY D	8-1971876-4
3*3	LEVEL 1	KEY A	1-1971876-3
		KEY B	2-1971876-3
		KEY C	3-1971876-3
		KEY D	4-1971876-3
3*3	LEVEL 2	KEY A	5-1971876-3
		KEY B	6-1971876-3
		KEY C	7-1971876-3
		KEY D	8-1971876-3
POS.	MATERIAL	KEY	P/N


3*3 POSITIONS

3*4 POSITIONS


3*5 POSITIONS




KEYING FOR 3*3 POS.



KEYING FOR 3*4 POS.



KEYING FOR 3*5 POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN TOMMY WU 09JUL2012		 TE Connectivity			
DIMENSIONS: mm		CHK HAPYE WU 09JUL2012					
		APVD YUZHONG MAO 09JUL2012					
		PRODUCT SPEC					
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME PLUG HOUSING,TRIPLE ROW POWER TRIPLE LOCK					
0 PLC ±		108-106118					
1 PLC ±0.35		APPLICATION SPEC					
2 PLC ±0.25		114-106118					
3 PLC ±		SIZE					
4 PLC ±		CAGE CODE					
ANGLES		DRAWING NO					
FINISH		RESTRICTED TO					
MATERIAL	-	WEIGHT	-	A1	100779	1971876	-
-	-	Customer Drawing	-	SCALE	-	SHEET	2 OF 2
-	-					REV	D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[8-1971876-3](#)