

4


3

2


1

THIS DRAWING IS UNPUBLISHED.
RELEASED FOR PUBLICATION DEC , 1996.
© COPYRIGHT 1996 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST	REVISIONS			
		P	LTR	DESCRIPTION	DATE
J			B	REVISED FJB0-0300-03	08MAY03





A-A



B-B



C-C



- 1 MATERIAL : 銅合金
- 2 仕上げ : 全面ニッケル下地めっきの上に
接触部 : 金めっき
圧着部 : 半田めっき
- 3 仕上げ : 全面錫めっき
- 4 仕上げ : 材料めっき
全面ニッケル下地めっきの上に
接触部 : 金めっき
圧着部 : 錫めっき
- 5 使用コネクタ型番 : X-353575-X
- 6 一般公差
10以下 : ±0.2
10を越え 30以下 : ±0.25
30を越え 100以下 : ±0.3
角度 : ±3°

- 1 MATERIAL : COPPER ALLOY.
- 2 FINISH : NICKEL PL ALL OVER
CONTACT AREA : GOLD PL.
BAREL AREA : TIN-LEAD PL.
- 3 FINISH : TIN PL ALL OVER.
- 4 FINISH : PRE-PLATED
NICKEL PL ALL OVER
CONTACT AREA : GOLD PL.
BAREL AREA : TIN PL.
- 5 USED CONNECTOR P/N : X-353575-X
- 6 GENERAL TOLERANCE
10 ≥ : ±0.2
30 ≥ >10 : ±0.25
100 ≥ >30 : ±0.3
ANGLES : ±3°

AVAILABLE	4	353581-3
NOT AVAILABLE	3	1-353581-2
AVAILABLE	2	353581-2
TOOLING STATUS	仕上げ FINISH	P/N

WIRE RANGE 適合電線断面積 0.85~1.25mm ² (AWG#18~#16)		INSULATION DIA 被覆外径 ø2.73~3.43 mm	
DWN T.FUMIKURA 25DEC96		Tyco Electronics AMP K.K. Kawasaki, Japan	
CHK T.YAMADA 26DEC96		NAME 名称	
APVD T.YAMADA 26DEC96		PLUG TAB CONTACT HYBRID MINI DRAWER CONNECTOR	
PRODUCT SPEC 製品規格		SIZE A3	
APPLICATION SPEC 取付適用規格 114-5238		CAGE CODE 00779	
WEIGHT		DRAWING NO 番号 C-353581	
CUSTOMER DRAWING		RESTRICTED TO —	
SCALE 尺度 NTS		SHEET 1 OF 1	
		REV B	

THIS DRAWING IS A CONTROLLED DOCUMENT.	
DIMENSIONS: 単位 : 概 MM	TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差
	0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±
MATERIAL 材料	FINISH 仕上

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-353581-2](#)