

Base strip - STB 3/3-G-5,08 - 1751031

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 16 A, Number of positions: 3, Pitch: 5.08 mm, Color: green, Contact surface: Tin, Mounting: Wave soldering



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| GTIN |  4 017918 028305 |
| Weight per Piece (excluding packing) | 2.23 g |
| Custom tariff number | 85369010 |
| Country of origin | Poland |

Technical data

Dimensions

| | |
|----------------|------------|
| Pitch | 5.08 mm |
| Pin dimensions | 1 x 0,8 mm |
| Hole diameter | 1.3 mm |

General

| | |
|----------------------------------|--------|
| Range of articles | STB |
| Rated voltage (III/3) | 250 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 16 A |
| Color | green |
| Stripping length | 8 mm |
| Number of positions | 3 |

Standards and Regulations

| | |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
| | CSA |

Base strip - STB 3/3-G-5,08 - 1751031

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440490 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002637 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals

Approvals

Approvals

CSA / UL Recognized / EAC / EAC


Ex Approvals


Approvals submitted

Approval details

Base strip - STB 3/3-G-5,08 - 1751031

Approvals

| | |
|---|-------|
| CSA  | |
| | |
| Nominal current I _N | 10 A |
| Nominal voltage U _N | 300 V |

| | |
|---|-------|
| UL Recognized  | |
| | |
| Nominal current I _N | 10 A |
| Nominal voltage U _N | 300 V |

| |
|-----|
| EAC |
|-----|

| |
|-----|
| EAC |
|-----|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1751031](#)