



1. MATERIALS:
CASE AND ACTUATOR: THERMOPLASTIC, UL94-V0.
FRAME: STEEL, TIN PLATED.
BUSHING AND ACTUATOR LEVER: BRASS, NICKEL PLATED
ROCKER CONTACT: SILVER/BRASS, LAMINATED.
PLUNGER: STAINLESS STEEL, PASSIVATED
SPRING: MUSICAL WIRE.
TERMINALS: SILVER/BRASS, LAMINATED, SILVER PLATED.
TERMINAL SEAL: SP EPOXY
DP EPOXY OPTIONAL
2. ELECTRICAL:
CURRENT RATING: 3A @ 125V AC OR 28V DC (2 POSITION)
2A @ 125V AC (3 POSITION)
INITIAL CONTACT RESISTANCE: 20 MLLIOHMS MAX
INSULATION RESISTANCE: 1,000 MEGAOHMS AT 500V DC MIN
DIELECTRIC STRENGTH: 1,000 VOLTS RMS AT SEA LEVEL
LIFE EXPECTANCY: 80,000 CYCLES (2 POSITION)
60,000 CYCLES (3 POSITION)
3. ENVIRONMENTAL:
OPERATING TEMPERATURE: -22°F TO +185°F (-30°C TO +85°C)
STORAGE TEMPERATURE: -67°F TO +185°F (-55°C TO +85°C)
4. TT13A2T04 HAS TERMINALS 1, 3, 4 & 6
HARDWARE INCLUDED: 1 HEX NUT AND 1 LOCKWASHER.

| | | | | | |
|---|--|---|--|---|--------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN RAGHAVENDRA 26AUG10 | |  TE Connectivity | |
| | | CHK EPPLEY NAZ 26AUG10 | | | |
| DIMENSIONS: mm [INCHES] | | TOLERANCES UNLESS OTHERWISE SPECIFIED: | | NAME | |
|  | | APVD EPPLEY NAZ 26AUG10 | | SWITCH, TINY TOGGLE SERIES, 1 & 2 POLE | |
| | | PRODUCT SPEC | | | |
| | | APPLICATION SPEC | | | |
| | | SIZE | | | |
| MATERIAL | | FINISH | | WEIGHT | |
| - | | - | | A2 00779 C=1825222-2 | |
| CUSTOMER DRAWING | | | | SCALE | SHEET |
| | | | | 4:1 | 1 OF 1 |
| | | | | REV | B |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[TT13A2T04](#)