



THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		20
© COPYRIGHT 20		BY -		ALL RIGHTS RESERVED.
PART NO.	"A°"	HOUSING	CONTACT	
1-1410353-1	0°	5	6	
1-1410353-2	45°	5	6	
1-1410353-3	90°	5	6	
1-1410353-7	270°	5	6	
1-1410353-8	315°	5	6	
1-1410353-9	7	5	6	

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	RELEASED	04AUG2011	BC	AS

- 1 MATERIAL: HOUSING: ZINC ALLOY DIE CASTING, ZAMAK 3. CONTACT: PHOSPHOR BRONZE
- 2 HOLE FOR POSITIVE RETENTION SCREW.
- 3 DASH NUMBERS INDICATE KEY ORIENTATION (P/N 1-1410353-2 SHOWN ON DRAWING)
- 4 GROUND PAD  $\varnothing 5\text{mm}$  ON BOTH SIDE OF PCB.
- 5 FINISH: SILVER OVER NICKEL OVER COPPER
- 6 CONTACT FINISH: 3.81 $\mu\text{m}$  MINIMUM SILVER IN CONTACT AREA OVER 1.27 $\mu\text{m}$  MINIMUM NICKEL ALL OVER
- 7 GUIDE MODULE W/O KEYING  
GUIDE PIN 1410354 SERIES MUST BE ORIENTED TO PROVIDE PROPER ESD PERFORMANCE

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1410353-3](#)