

KUL Series Latching Panel Plug-in Relay

- Magnetic latching relay
- Single or dual wound DC coils or single wound AC coils
- 1, 2, and 3 pole Form C contact arrangement
- Reset occurs by reversing polarity in a single coil relay or by energizing the reset winding in dual coil relays
- Various mounting and socket styles

Typical applications

Alarm systems, machine tools, battery chargers, process and power controls, pressure washers, paving equipment



Approvals

UL E22575; CSA LR15734

Technical data of approved types on request

Contact Data

Contact arrangement	1 form C (CO), 2 form C (CO), 3 form C (CO)	
Rated voltage	240VAC	
Rated current	10A	
Contact material	Ag	AgCdO
Min. recommended contact load	100mA, 12VDC	300mA, 12VDC
Frequency of operation	360 ops./hour	
Operate/release time max.	25/25ms	

Contact ratings

Type	Load	Cycles
UL 508		
Ag	5A, 240VAC 1/6HP, 120VAC 1/3HP, 240VAC 0.5A, 120VDC 2.5A, 120VAC, tungsten	100x10 ³
AgCdO	10A, 250VAC 1/3HP, 120VAC 1/2HP, 250VAC 5A, 120VAC, tungsten 0.5A, 125VDC 10A, 28VDC 10FLA, 30LRA, 125VAC 5FLA, 15LRA, 250VAC 125VA, pilot duty, 125/250VAC	100x10 ³
Mechanical endurance	10x10 ⁶ ops.	

Coil Data

Coil voltage range	12 to 110VDC (single and dual coil) 24 to 240VAC (single coil) 24 to 120VAC (dual coil)
Coil insulation system according UL	Class B

Coil versions, DC coil 1)

Coil code	Rated voltage VDC	Operate voltage VDC	Coil resistance $\Omega \pm 10\%$	Rated coil power W
Single coil				
12	12	9.0	120	1.2
24	24	18.0	472	1.25
48	48	36.0	1800	1.3
110	110	82.5	10000	1.25
Dual coil 2)				
12	12	9.0	90	1.6
24	24	18.0	350	1.65
48	48	36.0	1400	1.65
110	110	82.5	7400	1.65

1) Latch and reset coil voltages and resistances are the same (unlike coils on request).

2) Dual coil available only with 1 or 2 form C contacts.

All figures are given for coil without preenergization, at ambient temperature +23°C.

Coil versions, AC coil 3)

Coil code	Rated voltage VAC	Operate voltage VAC	Latch coil resistance $\Omega \pm 15\%$	Reset coil resistance $\Omega \pm 15\%$	Reset coil resistor Ω
Single coil					
24	24	20.4	176	—	680
120	120	102.0	3700	—	15000
240	240	204.0	179000	—	68000
Dual coil					
24	24	20.4	100	250	—
120	120	102.0	2525	2200	5600

3) AC coils use diodes. Diodes and resistors included inside relay with 1 and 2 Form C contacts. For 3 Form C relay, the customer must furnish and wire diodes and resistors externally (1N4007 is recommended diode).

All figures are given for coil without preenergization, at ambient temperature +23°C.

Insulation Data

Initial dielectric strength between open contacts	500V _{rms}
between contact and coil	1500V _{rms}
between adjacent contacts	1500V _{rms}
Initial insulation resistance between insulated elements	100M Ω

KUL Series Latching Panel Plug-in Relay (Continued)

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter

Ambient temperature

DC coil Single coil: -45°C to 70°C

Dual coil: -45°C to 50°C

AC coil Single coil: -45°C to 70°C

Category of environmental protection

IEC 61810 RTI - dust protected

Terminal type Quick connects (QC) .187

Weight 96g

Packaging/unit tray/25 pcs., box/150pcs.

Accessories


For details see datasheet

Sockets and Accessories, KUP Relays


Product Code	Description
27E893	DIN socket (use 20C318 clip)
27E121	Track mount socket (use 20C314 clips)
27E043	Chassis mount/solder eyelet socket (use 20C254 clip)
27E046	Chassis mount/PCB socket (use 20C254 clip)
27E067	Chassis mount/quick connect socket (use 20C254 clip)
27E396	Snap-in/quick connect socket (use 20C254 clip)

Dimensions


Plain case



Bracket mount case


Terminal dimensions

4.75mm (.187) quick connect




KUL Series Latching Panel Plug-in Relay (Continued)
Terminal assignment


Bottom view on pins – Contact positions shown in diagrams is with the "RESET" input having been energized last.

Single Coil – DC


1 Form C



2 Form C




3 Form C




Dual Coil – AC or DC

1 Form C



2 Form C




Polarity for DC only.


Polarity for DC only.

Single Coil – AC


1 Form C



2 Form C



3 Form C



1) Do not connect any low impedance loads from terminal B to A.

2) Resistor and diodes connected by customer. See Coil Data Chart for resistor value. Recommended using 1N4007 diode.

Product code structure

Typical product code

KUL

-11

D

1

D

-12

Type

KUL Enclosed magnetic latching relay

Contact arrangement and rating

5 1 form C (1 CO)

11 2 form C (2 CO)

14 3 form C (3 CO)

Coil Input

A AC

D DC

Mounting and options

1 Socket mount (plain) case

5 Bracket mount case

Terminal and contact material

1 4.75mm (.187in) quick connect/solder; Ag, 5A

5 4.75mm (.187in) quick connect/solder; AgCdO, 10A

Note: 5.21mm (.205) QC and PCB terminals available on request

Number of coils

S Single coil

D Dual coil

Coil voltage

Coil code: please refer to coil versions table

Product Code	Arrangement	Material	Coil	Case Style	Terminals	Part Number
KUL-5A15S-120	1 Form C, 1 CO	AgCdO	120 VAC	Plain case	Plug-in	1393116-4
KUL-11A15S-24	2 Form C, 2 CO		24 VAC			2-1393115-7
KUL-11A15S-120			120 VAC			2-1393115-6
KUL-11D15D-12			12 VDC			3-1393115-1
KUL-11D15D-24			24 VDC			3-1393115-2
KUL-11D15D-48			48 VDC			3-1393115-3
KUL-11D15S-12			12 VDC			3-1393115-4
KUL-11D15S-24			24 VDC			3-1393115-5

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[KUL-11D15D-110](#)