


			1				
REVISIONS							
DESC	RIPTION			DATE	DWN	APVD	
5				18MAY2016	WL	SY	
				I		I	
							D
ST, UL94V-O; COLOR: NATURAL.							
HOSPHOR BRONZE.							
E TABLE) LD FLASH ON ENTIRE CONTACT.							
0 μ " MIN. MATTE-TIN ON ENTIRE CONTACT.							
DNTACT UNDERPLATED 50 μ " MIN. NICKEL.) N. TIN OR MATTE-TIN OVER 50 μ " MIN. NICKEL.							
'							
DF MATING RECEPTACLE: X-1775013-X CAPABLE TO 260°C AS PER							
CONDITION B.							
TIONS FOR LOW HALOGEN (BY WEIGHT):							
900 PPM (0.09%)							
900 PPM (0.09%) FION OF (CI) + (Br) \leq 1500 PPM (0.15%)							\sim
							0
							В
	1		1				
6.25	5.6	4.0	12	5-177			
11.05		8.8	24		5014		
6.25	5.6	4.0	12		5014-	- 1	
C ENSIO		A	NO. OF		NUM	BER	
TE TE Connectivity							
BOARD-TO-BOARD CONNECTOR, 0.8mm PITCH, FINE-STACK							
	0.0111		H. PLUG	STACK			А
AGE CODE DRAWING NO RESTRICTED TO							
00779 C -1775014 -							
		SCAL	- ^e 7:1 ^{she}	et 1 of 2	REV	Ġ.	



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1775014-2</u>