

Exploded view diagram of a mechanical assembly. The diagram shows various components and their assembly sequence, indicated by numbered callouts (1 through 67). Key components include a central motor unit, a terminal support structure, and various mounting brackets and fasteners. A detail view of the terminal support location shows a dimension of 3.56 ± 0.5 [1.40 ± .020] and labels 8 REF and 34 REF.

- | | | | | | | | | | | |
|---|----------------------|-----|-----|-----|----|----|----|---------|-------------|---------|
| <p>* WARNING</p> <p>ON INSTALLATION, SET WIRE DISC TO LARGEST WIRE SIZE SETTING. USE OF SETTINGS BELOW MIN. REQUIRED CRIMP HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.</p> | | | | | | | | | | |
|  | PRE-FEED 40mm STROKE | | | | | | | | | |
| | - | - | - | - | - | - | - | - | 84 | |
| | - | - | - | - | - | - | - | - | 83 | |
| | - | - | - | - | - | - | - | - | 82 | |
| | - | - | - | - | - | - | - | - | 81 | |
| | - | - | - | - | - | - | - | - | 80 | |
| | - | - | - | - | - | - | - | - | 79 | |
| | - | - | - | - | - | - | - | - | 78 | |
| | - | - | - | - | - | - | - | - | 77 | |
| | - | - | - | - | - | - | - | - | 76 | |
| | - | - | - | - | - | - | - | - | 75 | |
| | - | - | - | - | - | - | - | - | 74 | |
| | -77 | -76 | -72 | -71 | -6 | -2 | -1 | PART NO | DESCRIPTION | ITEM NO |

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1528603-1](#)