

## 1N4001-G Thru. 1N4007-G

Voltage: 50 to 1000 V

Current: 1.0 A

RoHS Device




### Features

- Low cost construction.
- Fast forward voltage drop.
- Low reverse leakage.
- High forward surge current capability.
- High soldering temperature guarantee: 260 °C/10 seconds, 0.375"(9.5mm) lead length at 5lbs(2.3kg) tension.

### Mechanical data

- Case: transfer molded plastic, DO-41
- Epoxy: UL 94V-0 rate flame retardant
- Polarity: Indicated by cathode band
- Lead: Plated axial lead, solderable per MIL-STD-202E, method 208C
- Mounting position: Any
- Weight: 0.012ounce, 0.33 grams



### Electrical Characteristics (at TA=25°C unless otherwise noted)

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load derate current by 20%.

Parameter	Symbol	1N4001 -G	1N4002 -G	1N4003 -G	1N4004 -G	1N4005 -G	1N4006 -G	1N4007 -G	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current 0.375"(9.5mm) Lead Length @TA=55 °C	$I_{AV}$	1.0							A
Peak Forward Surge Current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	30							A
Maximum Instantaneous Forward Voltage @1.0A	$V_F$	1.1							V
Maximum DC Reverse Current at Rated DC Blocking voltage per element	$I_R$	$T_A=25\text{ }^\circ\text{C}$							$\mu\text{A}$
		$T_A=100\text{ }^\circ\text{C}$							
Maximum Full Load Reverse Current,full cycle average 0.375"(9.5mm)lead length at $T_L=75\text{ }^\circ\text{C}$	$I_{R(AV)}$	30							$\mu\text{A}$
Typical Junction Capacitance (Note 1)	$C_J$	15							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	60							°C/W
Operating Temperature Range	$T_J$	-55 ~ +150							°C
Storage Temperature Range	$T_{STG}$	-55 ~ +150							°C

NOTES:

1. Measured at 1.0MHz and Applied Reverse Voltage of 4.0V DC.
2. Thermal Resistance from junction to terminal 6.0mm<sup>2</sup>copper pads to each terminal.

## Rating and Characteristic Curves ( 1N4001-G Thru. 1N4007-G )

Fig.1 Typical Forward Current Derating Curve




Fig.2 Maximum. Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Reverse Characteristics





Fig.5 Typical Junction Capacitance



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Comchip Technology:

[1N4007T-G](#) [1N4001-G](#) [1N4002-G](#) [1N4003-G](#) [1N4004-G](#) [1N4005-G](#) [1N4006-G](#) [1N4007-G](#) [1N4002T-G](#) [1N4006T-G](#) [1N4005T-G](#) [1N4003T-G](#) [1N4004B-G](#) [1N4006B-G](#) [1N4005B-G](#) [1N4001B-G](#) [1N4007B-G](#) [1N4002B-G](#) [1N4003B-G](#)