

Specification Control Drawing

a) Part as supplied.



b) Part after unrestricted recovery.





DIMENSIONS in millimetres {in inches,for reference}

		,										
Part No.	i Min a	H Max b	Min a	J Ma× b	Р ±10% b	R ±10% Ь	5 ±10% b	T ±10% b	U ±10% b	J0 ±10% b	HW ±20% b	JW ±20% b
202K121-*-01	24 {0.94}	10.4 {0.41}	24 {0.94}	5.6 {0.22}	26 {1.02}	9 {0.35)	3.0 {0.12}	1.0 {0.04}	1	8.5 {0.33}	1.6 {0.06}	0.9 {0.04}
202K132-*-01	30 {1.18}	14.2 {0.56}	30 {1,18}	5.9 {0.23}	43 {1.69}	20 {0.79}	3.0 {0.12}	1.0 {0.04}	1	11.5 {0.45}	1.8 {0.07}	1.0 {0.04}
202K142-*-01	31 (1,22)	18.0 {0.71}	31 {1,22}	7.1 {0.28}	47 {1.85}	15 {0.59}	3.0 {0.12}].0 {0.04}	1	17.0 {0.67}	1.8 {0.07}	1.0 {0.04}
202K153-*-01	36 {1.42}	22.4 {0.88}	36 {1.42}	8.4 {0.33}	60 (2.36)	22 {0.87}	3.0 {0.12}	1.0 {0.04}	1	19.5 {0.77}	2.0 {0.08}	1.0 {0.04}
202K163-*-01	43 (1.69)	28.2 {1.11}	43 {1.69)	9.9 0.39}	79 {3.11}	41 {1.61	3.0 (0.12)].7 {0.07}	20 {0.79}	21.0 (0.83)	2.2 {0.09}	1.0 {0.04}
202K174-*-01	60 {2.36}	35.1 {1.38}	60 {2,36}	15.7 {0.62}	110 {4.33}	52 {2.05}	3.0 {0.12}	1.7 {0.07}	20 {0,79}	39.0 {1.54}	3.2 {0.13}	1.5 {0.06}
202K185-*-01	66 {2.60}	44.5 {1.75}	66 (2.60)	16.8 {0.66}	150 {5.91}	70 {2.76}	3.0 {0.12}	2.0 {0.08}	20 {0.79}	51.5 {2.03}	3.8 {0.15}	2.0 {0.08}
					#	#						

This is a trimmed variant

Modified dimensions are shown thus:- #

Drawn A.LILLEY. C

Checked

MKTG.

Date April 2007

Conforms to ISO Recommendations 3rd Angle Projection Not to Scale

Approval Design

Q.A.

Issue 5

202K1**-*-01

	TE Conne	Specificat ectivity Control Dr	202K1**-*-01 Issue 5
Iss.	Date	E.C.R. No.	Details of Change
2 3 4	October 2001 October 2002 April 2007	**** CR02-HM-0001 CR07-HM-010	Redrawn 202K121, JW was 0.5 Document title was 202K121 thru 185-*-01

(Ordering Information)



COMPATIBILITY CHART)

Material Dash Number	Material Description	SPEC Number	Coating Slash Number
-3	POLYOLEFIN, SEMI-RIGID	RT-301, RK-6703	/42,/86, /180
-4	POLYOLEFIN, FLEXIBLE	RT-1304 RT-1050	/42,/86, /180
-6	SILICON	RT-602, RK-6706	NZA
-25	ELASTOMER, FLUID RESISTANT	RT-1325, RK-6713	/42, /86, /225
-130	POLYOLEFIN, COMMERCIAL FLEXIBLE	RW-2008	/42

NOTES

(1) Dimension U does not apply on sizes 202K121 thru 202K153.

(2) If eyelet clip (000W212) is required with part then add CS-1858 to description (i.e. 202K132-3-01-CS-1858-0).

(3) As supplied dimensions are for uncoated parts, when coating is added entry diameters will reduce by 1.5mm Max.

TE Connectivity Faraday Road, Swindon, Wiltshire, SN3 5HH England	TE Connectivity 300, Constitution Drive, Menlo Park, CA 94025 USA
Telephone: (01793) 528171 Fax: 572516	Telephone (650) 361-3860 Fax: (650) 361-5579
Cage Code K1010	Cage Code 06090

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 202K121-3-01-0