

y	6	6	6	6	6	6	6	6	6	6		6	6	6	6	6	6	6	6	6	6	6
h	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
g	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
f	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
e	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
d	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
c	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
b	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
a	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
z	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0
P																						
O																						
S																						

Figure 1: Dimensions of the test specimen. The figure includes three views: a side elevation, a top view, and a front view. The side elevation shows a specimen with a total width of $21.40^{+0.50}_{-0}$ and a central section width of 17.70 ± 0.10 . The top view shows a rectangular specimen with a width of 8.00 and a length of 50.0 MAX. The front view shows a specimen with a width of $2.00 \pm 0.05 (24 \times)$ and a length of 48.00. Various dimensions and tolerances are specified throughout the drawings.

Diagram illustrating the dimensions of two probe assemblies relative to a vertical reference line labeled "SEATING PLANE FOR CONNECTOR".

- Assembly 4:** The distance from the left end to the center of the probe is 8.20. The distance from the center of the probe to the right end is 3.70.
- Assembly 6:** The distance from the left end to the center of the probe is 11.2. The distance from the center of the probe to the right end is 3.70.

A diagram of a rectangular field with a width of 48.0 and a height of 8.0. The field is filled with a grid of small circles, representing points. The circles are arranged in 6 rows and 24 columns, with a small gap in the 2nd row from the right side.

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001
CATALOG NO: HM2P95PDH3U5----

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P95PDH3U5N9LF](#)