



DETAIL Z
SCALE 2:1

Specification:

- Electrical Char
Insulation Resistance: 500MΩ min. 500V DC for 1 minute
Contact Resistance: 30mΩ max.
Rating Current: 1.5A max.
Rating Voltage: 150V AC
- Physical Char
Housing(Option): For Waving Soldering Process.
PBT Glass filled (UL 94V-0) Color: Black
Soldering Temperature: 235°C for 5 sec.
Spring Wire: 0.35mm thickness Phosphor Bronze
6u" Gold on contact area over 50u" Nickel
Temperature Range: -40°C to +85°C
Durability: 750 mating cycles min.
- Packing: Tray

RoHS compliant
Unit:mm

Scale	Free							Customer-No.
TOLERANCE								
.XX	±0.25			Drawn	21.07.2017	Winnie		
.XXX	±0.13			Approved	30.08.2018	Amy		
.XXXX	±0.05	②	Update the dimensions					
DIM	TOL	①	Update the tolerance & Rating Voltage	12.07.2018	Segal			ASSMANN WSW-No. A-2004-2-4-LP/S-R
		①	Drawn	21.07.2016	Winnie			Drawing-No. ASS 7322 CO
Angle	+0°30'		Modification					Replace ASS 7322 CO
								rev02
								SHEET



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H