

NLP250-DC Series

Single Output

Data Sheet

Total Power: 250 W
Input Voltage: 38 - 60 Vac
of Outputs: Single

SPECIAL FEATURES

- -48 Vdc input
- 250 W on main channel with forced air
- Low profile fits 1U applications
- U-Channel for maximum thermal performance
- 5 V standby output
- 12 V fan output
- Integrated control and monitoring features
- Overcurrent, overvoltage and overtemperature protection
- Compliance to EN55022-B conducted noise standard
- RoHS compliant
- Two year warranty

SAFETY

- VDE0805/EN60950-1
- IEC950/IEC60950-1
- UL/cUL 60950-1
- CSA-C22.2 60950-1
- CB Certificate
- CE Mark (LVD)



Electrical Specifications

Input		
Input voltage range	-48 Vdc Nominal	38 - 60 Vac
Input surge current	60 Vdc (cold start)	40 A max.
Input voltage protection	Reverse polarity protected	
Input current	-48 Vdc @ 250 W	7 A
Input fuse	UL/IEC127	T6.4 AH, 250 Vac
Output		
Maximum power	200 LFM forced air	250 watts
Total regulation (line and load)	Main output	± 2.0%
	Auxiliary outputs	± 5.0%
Turn-on delay	-48 Vdc input	2.0 s max.
Transient response	Main output	5.0% or 250 mV
	50 - 100% Step at 0.5 A/μs	max. dev., 1 ms max recovery to 1%
Temperature coefficient		±0.04%/°C
Overvoltage protection	Main output	115%, ± 5%
Short circuit protection	Cyclic operation	Continuous
Minimum output current	Singles	0 A
Auxiliary outputs (See Note 8, page 3)	5 Vsb	5 V @ 1.0 A
	12 V (fan)	12 V @ 1.5 A

All specifications are typical at nominal input, full load at 25 °C unless otherwise stated.

EMC Characteristics ⁽⁵⁾		
Conducted emissions	EN55022, FCC part 15 CISPR22, GR-1089 CORE, ETSi 300-386	Level B
ESD air	EN61000-4-2	Level 3
ESD contact	EN61000-4-2	Level 3
Radiated immunity	EN61000-4-3	Level 3
Fast transients	EN61000-4-4	Level 3
Surge	EN61000-4-5	Level 3
Conducted immunity	EN61000-4-6	Level 3
General Specifications		
Hold-up time	-48 Vdc input	4 ms @ 250 W
Efficiency	-48 Vdc @ 250 W	85% typ.
Isolation voltage	Input/output Input/chassis	1500 Vdc 1500 Vdc
Safety approvals (see note 6, page 3)	UL/cUL UL60950-1, VDE EN60950-1, CAN/CSA22.2 No. 60950-1	
Weight		650g (22 oz)
MTBF (@25 °C)	Telcordia SR-332	317,000 hours min.

Environmental Specifications		
Thermal performance	Operating ambient,	-50 °C to +70 °C
	(See derating curve)	
	Non-operating	-40 °C to +85 °C
	0 °C to 50 °C ambient,	250 W
	200 LFM forced air 250 LFM with cover	
	0 °C to 50 °C ambient	175 W
	Convection cooled	
	50 °C to 70 °C ambient,	Derate linearly
	Convection cooled	to 50% load
Relative humidity	Non-condensing	Per GR-63-Core
Altitude	Operating	10,000 feet max.
	Non-operating	30,000 feet max.
Vibration	5-100 Hz	Per GR-63-Core
Shock	Per GR-63-Core	Zone 4


Ordering Information


Output Voltage	Output Current			Ripple ⁽³⁾	Total Regulation	Model Numbers ^(9, 10)
	Min	Max (free air) ^(1, 4)	Max (forced air) ^(2, 4)			
12 V	0 A	14.6 A	21 A	120 mV	± 2.0%	NLP250N-48S12J

Notes

- Free air convection. Maximum continuous output power not to exceed 175 W. Refer to Figure 1 for the derating curve.
- 200 LFM (250 LFM with cover) forced air cooling from the longer side. Maximum continuous output power not to exceed 250 W.
- Figure is peak-to-peak for room temperature rating. Output noise measurements are made across a 20 MHz bandwidth using a 6 inch twisted pair, terminated with a 10 μ F tantalum capacitor and a 0.1 μ F ceramic capacitor.
- CAUTION: Allow a minimum of 1 second after disconnecting line power when making thermal measurements. For optimum reliability no part of the heatsink should exceed 115 °C and no semi-conductor case temperature should exceed 120 °C.
- No external filtering required during conducted emissions testing but some applications may require additional filtering to achieve system compliance. Compliance with radiated EMI specifications may require mounting in a suitable enclosure.
- This product is only for inclusion by professional installers within other equipment and must not be operated as a standalone product.
- 5 V sb (standby) output is available whenever DC input is present, regardless of remote ON/OFF signal status. 12 V (fan) present when main output is present.
- The 'J' suffix indicates that these parts are Pb-free (RoHS 6/6) compliant.
- NOTICE: Please contact your local Emerson representative or visit our website at <http://www.PowerConversion.com>.10 NOTICE: Some models do not support all options. Please contact your local Artesyn Embedded Power representative or use the on-line model number search tool at <http://www.artesyn.com> to find a suitable alternative.

Mechanical Drawing





Pin Connections

J1	
Pin 1	-48 Vdc
Pin 2	Ground
Pin 3	Return
J2	
Pin 1	N/C
Pin 2	-V0 Remote Sense
Pin 3	+V0 Remote Sense; Load compensation for 0.2 V to 0.5 V drop at load (sense point)
Pin 4	5 V Standby
Pin 5	Signal Common (RTN): 5 V standby and 12 V fans
Pin 6	12 V DC Fan Voltage
Pin 7	Signal Common (RTN): 5 V standby and 12 V fans
Pin 8	Inhibit: A closed contact (Low) will shut down PSU main output within 200 ms (typical)
Pin 9	DC Power Good: $V_o > -8\%$ of nominal = Logic High, Out of Regulation = Logic Low
TER1	
TER1	+12 V
TER2	
TER2	GND

Connector and Mating Connector Types

Connector	Type	Mating Connector Type
J1	Molex 10-84-5030 (4202 series)	Molex 50-84-1035 (42021 series) or equivalent with Molex 02-08-1001 (42024 series) or equivalent crimp terminals
J2	Molex	Molex 90142-0010 Molex 90119-2110 crimp terminals
TER1 TER2	Terminal block	Terminal block contains #6-32 screw with clamp washer suitable for wire size 12-22 awg (0.5-2.5 mm ²). Max Torque tp 1.36 Nm (12 in.lb)

WORLDWIDE OFFICES

Americas

2900 South Diablo Way
Suite B100
Tempe, AZ 85282, USA
+1 888 412 7832

Europe (UK)

Ground Floor Offices, Barbary House
4 Harbour Buildings, Waterfront West
Brierley Hill, West Midlands
DY5 1LN, UK
+44 (0) 1384 842 211

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
+852 2176 3333

ARTESYNTM
An Advanced Energy Company

www.artesyn.com

Artesyn Embedded Technologies, Artesyn Embedded Power, Artesyn, and all Artesyn related logos are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. Specifications are subject to change without notice. © 2019 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit www.artesyn.com/legal.

For more information: www.artesyn.com
For support: productsupport.ep@artesyn.com

NLP250-DC DS 16Dec2019

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Artesyn Embedded Technologies:](#)

[NLP250N-48S12J](#)