

Antenna - RAD-ISM-2400-ANT-OMNI-2-1 - 2867461

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Omnidirectional antenna, 2.4 GHz, 2 dBi, linear vertical, 1.5 m cable, MCX (male), IP65, 50 Ω impedance

Product Features

- For mobile or point-to-multipoint applications with a small range



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	84.4 g
Custom tariff number	85177019
Country of origin	Germany

Technical data

Dimensions

Width	7.8 mm
Height	82.5 mm
Fixed cable length	1.50 m

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-30 °C ... 75 °C

General

With connecting cable	yes
Frequency range	2.4 GHz
	2.4 GHz
Horizontal beamwidth	360 °

Antenna - RAD-ISM-2400-ANT-OMNI-2-1 - 2867461

Technical data

General

Vertical beamwidth	75 °
Impedance	50 Ω
Gain	2 dBi
Connection method	MCX (male)
Fixed cable length	1.50 m
Material	Polyurethane (Antenna housing)
	Polycarbonate PC (Antenna foot)
Mounting type	Wall mounting

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	19070102
eCl@ss 5.1	19070102
eCl@ss 6.0	19070102
eCl@ss 7.0	19070102
eCl@ss 8.0	19070105
eCl@ss 9.0	19070105

ETIM

ETIM 2.0	EC000416
ETIM 3.0	EC001698
ETIM 4.0	EC001698
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2867461](#)