

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	- - -
© COPYRIGHT - By -	ALL RIGHTS RESERVED.	

LOC	DIST	REVISIONS				APVD
		P	LTR	DESCRIPTION	DATE	
EH	00			AV REV PER ECO-13-001932	14MAR2013	GG LH


FINISHED CABLE DATA

CONDUCTORS	WIRE AWG	24 AWG SOLID
	MATERIAL	SOLID BARE COPPER
INSULATION	MATERIAL	FLUOROPOLYMER/POLYOLEFIN
JACKET	MATERIAL	FR PVC
ELECTRICAL REQUIREMENTS		
INSULATION RESISTANCE	500 MEGOHMS MIN/1000 FT	
CONDUCTOR RESISTANCE	28.6 OHMS MAX/1000 FT	

COLOR CODE 

PAIR

1	WHT-BLU/BLU
2	WHT-ORG/ORG
3	WHT-GRN/GRN
4	WHT-BRN/BRN




LEGEND TO BE REPEATED EVERY 24"

TE CONNECTIVITY 520 SERIES 4/24 AWG T256 CMP CULUS ETL VERIFIED TIA-568-C.2 CAT 5E PAT 6153826, 6743983 XXXX FT

CATALOG NUMBER	WEIGHT		PACKAGING
	LBS/KFT	KG/KM	
TE520P-XX02	21	31	1,000' REEL
TE520P-XXII	20	30	1,000' REELEX BOX
TE520P-XXRB	22	33	1,000' REEL-IN-A-BOX

THIS DRAWING IS A CONTROLLED DOCUMENT.	DWN M.BOLES CHK C.STEWART APVD M.RUBERA PRODUCT SPEC	26NOV2001 13FEB96 13FEB96	TE Connectivity
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:		
	0 PLC $\pm .1$ 1 PLC $\pm .02$ 2 PLC $\pm .005$ 3 PLC $\pm .0005$ 4 PLC $\pm .0005$	ANGLES	APPLICATION SPEC
MATERIAL	FINISH	WEIGHT	NAME CABLE, 520 SERIES CAT 5e, ENHANCED, 4 UTP, 24AWG, CMP
			SIZE CAGE CODE DRAWING NO A2 00779 C-57825 CUSTOMER DRAWING
		RESTRICTED TO	SCALE NTS SHEET 1 OF 1 REV AV

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity Divested:](#)

[57825-7](#)