



STRIPPING DIMENSIONS

Directive 2002/95/EC RoHS compliant

(b)

NOTES:

1. MATERIAL: COPPER ALLOY
2. PLATING:
 - ITEM 1: SEE TABLE
 - ITEM 2: GOLD FLASH over NICKEL
 - ITEM 3: NICKEL PLATED
3. CRIMPING: USE CRIMP TOOL 360X10409X
WITH TOOL INSERT 360X20029X
SELECTOR SETTINGS: 5 FOR AWG 12
4 FOR AWG 14

(b)

PLATING ITEM 1	PART-NO.
GOLD FLASH over NICKEL	131A11029X
min. 30µin HARD GOLD over min. 50µin NICKEL	131C11029X
min. 50µin HARD GOLD over min. 50µin NICKEL	131J11029X

(b)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: SEE NOTES				tolerance ISO 2768-m		dim. in mm		scale: 5:1	
				date		name		material: SEE NOTES	
				drawn 23.03.98		Barcinski		title: HIGH POWER CONTACT MALE CRIMP VERSION 20A D-SUB COMBINATION	
				appd. 23.03.98		Mickenbecker			
				norm					
				d-old				dwg no:	
4 x b	Ä3854	19.01.11	K.H.			13K11D2A		DIN-A4	
a	Origin							sh: 1	
rev.	description	date	name					part no: SEE TABLE	



title:		scale: 5:1	
material: SEE NOTES		material: SEE NOTES	
dwg no:		DIN-A4	
13K11D2A		sh: 1	
part no: SEE TABLE		part no: SEE TABLE	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[131C11029X](#)