	4	3		2		1	
[THIS DRAWING IS UNPUBLISHED. RELEASED FOR		LOC	DIST	REVISIO	NS	
	C COPYRIGHT – By – ALL R	IGHTS RESERVED.	FT	P LTR	DESCRIPTIC	ON DATE	DWN APVD
)	MATERIAL: HOUSING: THERMOPLASTIC, UL94V-0, BLACK TERMINALS: BRIGHT TIN PLATED COPPER ALLO SCREWS: 8-32, ZINC PLATED STEEL. ELECTRICAL PROPERTIES: CURRENT RATING: 30A VOLTAGE RATING: 600V WIRE RANGE: 10-18 AWG (UL) 10-22 AWG (CSA)	ΟY			REVISED PER ECO-11-0155	01AUG1	HMR SM
	MECHANICAL: RECOMMENDED TORQUE: 20 IN-LB. OPERATING TEMP.: -40°C TO +120°C				8.823 8.385	5 19 8WWV-19-008 1-	1546845-9
				<u>1-1546160-1</u>	7.948		
× /					7.073 6.635 6.198	3 16 8WWV-16-008 1- 5 15 8WWV-15-008 1-	1546845-6 C 1546845-5
]	5.760		796616-5
					5.323 4.885 4.448 4.010	5 11 8WWV-11-008 1- 3 10 8WWV-10-008 1-	1546845-1
3				033 21±.02	3.573 3.135 2.698 2.260 1.823	5 7 8WWV-07-008 8 6 8WWV-06-008 9 5 8WWV-05-008 9- 6 4 8WWV-04-008 1-	1546160-2 B
	.438±.002		► .438 TYP	.2	SEE FIGURE 1.385		1546160 - 1 1546845 - 3
	TYP				.948		796616-9
	.255	.20			DIM L	NO CATALOG	PART NUMBER
	Ø.073±.003 TYP <u>Recommended PCB Lay</u>		DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONS: INCHES O PLC ± -	S SCHLEGEL CHK 1 ⁻ S YODER	1/15/06 1/15/06 NAME		
			1 PLC ± - 2 PLC ± .01	_	W8	WWV-XX-008 ASSEMBLY	A
			3 PLC ± .005 4 PLC ± - ANGLES ± 1'	APPLICATION SPEC	SIZE CAGE CODE DRAW	VING NO	RESTRICTED TO
		MATERIAL		WEIGHT	A3 00779 G ⁼	- 9-1437659-0	_
				CUSTOMER DRAWI	NG	SCALE 1:1 SHEET 1 OF	1 REV D1
-	1470–19 (3/11)						

D

С

В

А

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-1546160-2</u>