

		REVISIONS			
REV	DESCRIPTION		DATE	APPROVED	
03 ₁	UPDATED		11/30/93	BB	

Technical drawing of the OSM Right Angle Plug to Plug Adapter. The drawing shows a side view of the assembly with dimensions in inches and millimeters. Key dimensions include: .438 (11.1mm) for the housing length, .117 (3.0mm) for the plug length, and .312 (7.9mm) for the hex diameter. Two reference planes (REF PLANE) are indicated. The OSM PLUG is shown inserted into the housing. The center contact is captured.

HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°		
DRAWN BY RR DATE 12-13-79		
CHECKED BY R SMITH 12-14-79		
APPD BY PFH 12-14-79		
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		
USE ASS'Y PROCEDURE		
NO. AP. N/A		
TITLE OSM RIGHT ANGLE PLUG TO PLUG ADAPTER		
SIZE B	CODE IDENT NO. 26805	2087-1230-02
SCALE 5:1	REV 03 ₁	
SHEET 1 OF 1		

NOTES:
1. CAPTURED CENTER CONTACT

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2087-1230-02](#)