## XXRK1A3KBM12

# ultrasonic sensor parallelepipedic 16x30x74 - receiver - Sn 0.6m 2NC - M12 con

Product availability: Non-Stock - Not normally stocked in distribution facility



#### Main

| · · · · · · · · · · · · · · · · · · · |  |
|---------------------------------------|--|
| Commercial Status                     | Commercialised                             |
| Range of product                      | OsiSense XX                                |
| Sensor type                           | Ultrasonic sensor receiver                 |
| Series name                           | General purpose                            |
| Sensor name                           | XXR  |
| Sensor design                         | Flat form 74 x 30 x 16                     |
| Detection system                      | Thru beam (need a transmitter XXTK1A3M12)  |
| [Sn] nominal sensing distance         | 2 ft (0.61 m) fixed                        |
| Material                              | Plastic                                    |
| Type of output signal                 | Discrete                                   |
| Discrete output function              | 2 NC                                       |
| Wiring technique                      | 4-wire                                     |
| Discrete output type                  | PNP and NPN                                |
| [Us] rated supply voltage             | 1224 V DC with reverse polarity protection |
| Electrical connection                 | Male connector M12 4 pins                  |
| [Sd] sensing range                    | 02 ft (00.61 m)                            |
| IP degree of protection               | IP67 conforming to IEC 60529               |
|                                       |  |

#### Complementary

| Complementary                   |   |
|---------------------------------|---|
| Enclosure material              | ULTEM   |
| Front material                  | Silicone  |
| Supply voltage limits           | 1028 V DC   |
| [Sa] assured operating distance | 02 ft (00.61 m)                                   |
| Current consumption             | 40 mA   |
| Maximum switching current       | 100 mA with overload and short-circuit protection |
| Voltage drop                    | <1V   |
| Switching frequency             | <= 40 Hz  |
| Delay first up                  | 100 ms  |
| Delay response                  | 10 ms   |
| Delay recovery                  | 10 ms   |
| Marking                         | CE  |
| Height                          | 1.18 in (30 mm)                                   |
| Width                           | 0.67 in (17 mm)                                   |
| Depth                           | 3.35 in (85 mm)                                   |
| Product weight                  | 0.11 lb(US) (0.05 kg)                             |
|                                 |   |

#### Environment

| Standards                             | IEC 60947-5-2  |
|---------------------------------------|--|
| Ambient air temperature for operation | 32140 °F (060 °C)  |
| Ambient air temperature for storage   | -40176 °F (-4080 °C)                                       |
| Vibration resistance                  | +/-1 mm conforming to IEC 60068-2-6 1055 Hz                |
| Shock resistance                      | 30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27 |
| Resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2                   |
| Resistance to electromagnetic fields  | 9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3     |
| Resistance to fast transients         | 1 kV level 3 conforming to IEC 61000-4-4                   |
|                                       |  |

### Ordering and shipping details

| Category              | 22490 - SENSORS-ULTRASONIC (XX5,6)                        |
|-----------------------|---|
| Discount Schedule     | DS2   |
| GTIN                  | 003389119127769   |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 0.20  |
| Product availability  | Non-Stock - Not normally stocked in distribution facility |
| Returnability         | Υ   |
| Country of origin     | US  |

#### Contractual warranty

|         | and the second s |
|---------|--|
| Period  | 18 months  |
| i Cilou | 10 11011(13  |
|         |  |



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XXRK1A3KBM12