





1. MATERIAL (DRAWN PART)
TYPE: C19400
2. FINISH
UNDER PLATE TYPE: NICKEL
UNDER PLATE THICKNESS: 0.0005 - 0.0013

TOP PLATE TYPE: TIN
TOP PLATE THICKNESS: 0.0013 - 0.0025
3. PARTS MUST BE FREE OF EXCESSIVE BURRS,
CRACKS OR OTHER VISUAL IMPERFECTIONS
THAT MAY AFFECT FIT, FORM OR FUNCTION.
4. REFER TO INSTRUCTION SHEET 408-10258 FOR
CRIMP TOOLING AND APPLICATION SPECIFICATION

5 PRELIMINARY PART — NOT RELEASED FOR PRODUCTION

5	-	-	-	APT OUTER FERRULE SIZE E	1587836-5
5	-	-	-	APT OUTER FERRULE SIZE D	1587836-4
5	-	-	-	APT OUTER FERRULE SIZE C	1587836-3
	6.20	1.22	3.00	APT OUTER FERRULE SIZE B	1587836-2
5	-	-	-	APT OUTER FERRULE SIZE A	1587836-1
5N	A	WT (gms)	WIRE SIZE (mm ²)	DESCRIPTION	PART NO.

1587836-2 SHOWN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D SIMPSON 04AUG2011		 TE Connectivity						
		CHK Y SOONAVALA 04AUG2011								
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD A GUANCO 04AUG2011		NAME				
		0 PLC ±.		PRODUCT SPEC		OUTER FERRULE, APT				
		1 PLC ±0.1		-						
		2 PLC ±0.05		APPLICATION SPEC						
		3 PLC ±0.001		-						
4 PLC ±0.0001		ANGLES ±2		SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO		
MATERIAL		FINISH		WEIGHT		A200779		C-1587836	-	
				SEE TABLE						
CUSTOMER DRAWING						SCALE	8.	SHEET	OF	REV
										A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1587836-2](#)