

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311


Phone: (818) 701-4933 Fax: (818) 701-4939

MMBT5401

PNP Plastic Encapsulate Transistor

SOT-23

	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.110	.120	2.80	3.04	
В	.083	.104	2.10	2.64	
С	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
Е	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
Н	.035	.044	.89	1.12	
7	.003	.007	.085	.180	
K	.015	.020	.37	.51	



Features

- Halogen free available upon request by adding suffix "-HF"
- Collector Current: I_{CM}=0.6A
- Collector-Base Voltage: V_{(BR)CBO}=160V
- Operating And Storage Temperatures –55°C to 150°C
- Capable of 0.3Watts of Power Dissipation
- Marking: 2L
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARAC	ETERISTICS			
$V_{(BR)CEO}$	Collector -Emitter Breakdown Voltage (-E=1.0mAdc, I _B =0)	150		Vdc
V _{(BR)CBO}	Collector-Base Breakdown Voltage (I _c =100uAdc, I _E =0)	160		Vdc
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage (I _E =10uAdc, I _C =0)	5.0		Vdc
Сво	Collector Cutoff Current (V _{CB} =120Vdc, I _E =0)		0.1	uAdc
I _{EBO}	Emitter Cutoff Current $(V_{EB}$ =4.0Vdc, I_{C} =0)		0.1	uAdc

ON CHARACTERISTICS

	DOO 10:	00		
h _{FE-1}	DC Current Gain	80		
	(V _{CE} =5.0Vdc, _b =1.0mAdc)			
h _{FE-2}	DC Current Gain	100	300	
	(V _{CE} =5.0Vdc, b=10mAdc)			
h _{FE-3}	DC Current Gain	50		
	(V _{CE} =5.0Vdc, _C =50mAdc)			
V _{CE(sat)}	Collector-Emitter Saturation Voltage			
	(├=50mAdc, I₃=5.0mAdc)		0.5	Vdc
V _{BE(sat)}	Base-Emitter Saturation Voltage			
(3-1)	(-50mAdc, l _B =5.0mAdc)		1.0	Vdc


SMALL-SIGNAL CHARACTERISTICS

f⊤	Current Gain-Bandwidth Product		
	(l_c =10mAdc, V_{ce} =5.0Vdc, f=30MHz)	100	 MHz




MMBT5401


Micro Commercial Components





MMBT5401







Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): MMBT5401-TP