



Product: 6302UE ☑

Security & Sound, #18-4c, BC, CMP

Product Description

Security & Sound Cable, Plenum-CMP 4-18 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material No. of Conductors 18 7x26 BC - Bare Copper 4 Conductor Count: 4 Insulation Material Material Trade Name Nominal Wall Thickness PVC-LS - Polyvinyl Chloride (Low Smoke) Flamarrest® 0.008 in Color Chart Color



Outer Shield Material



Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC-LS - Polyvinyl Chloride (Low Smoke)	Flamarrest®	0.18 in	0.015 in	Yes

Construction and Dimensions

Cabling

Lay Direction	Twists	
Left Hand	3.4 twist/ft	

Electrical Characteristics

Conductor DCR



Capacitance

Nom. Capacitance Conductor to Conductor 34 pF/ft

Current

	Element	Max. Recommended Current [A]
10C Temperature Rise		Per conductor @ 25°C (10C temperature rise): 4 A

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

Installation Temp Range:	0°C To +75°C
Operating Temp Range:	-10°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	33 lbs/1000ft
Max Recommended Pulling Tension:	89.6 lbs
Min Bend Radius/Minor Axis:	1.8 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Suitability

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262 Plenum Flame Test	
CSA Flammability:	FT6	
ISO/IEC Flammability:	IEC 60332-1-2	
UL voltage rating:	300 V RMS	

Plenum/Non-Plenum

		1
Plenum (Y/N):	Yes	

Part Number

Non-Plenum Number:	5302UE

Variants

Item #	Color	UPC	Footnote
6302UE 8771000	Natural	612825340232	С
6302UE 877500	Natural	612825175391	
6302UE 877C250	Natural		
6302UE 877U1000	Natural	612825175377	
6302UE 877U500	Natural	612825175384	

Footnote:	C - CRATE REEL PUT-UP.

History

Update and Revision:

Revision Number: 0.217 Revision Date: 04-02-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.